

Package ‘maaslin3’

January 24, 2025

Title ``Refining and extending generalized multivariate linear models for meta-omic association discovery"

Year 2024

Version 0.99.3

Depends R (>= 4.4)

Description MaAsLin 3 refines and extends generalized multivariate linear models for meta-omic association discovery. It finds abundance and prevalence associations between microbiome meta-omics features and complex metadata in population-scale epidemiological studies. The software includes multiple analysis methods (including support for multiple covariates, repeated measures, and ordered predictors), filtering, normalization, and transform options to customize analysis for your specific study.

License MIT + file LICENSE

Imports dplyr, pbapply, lmerTest, parallel, lme4, optparse, logging, multcomp, ggplot2, RColorBrewer, patchwork, scales, rlang, tibble, ggnewscale, survival, methods, BiocGenerics, SummarizedExperiment, TreeSummarizedExperiment

Suggests knitr, testthat (>= 2.1.0), rmarkdown, markdown, kableExtra

VignetteBuilder knitr

Collate fit.R utility_scripts.R viz.R maaslin3.R

URL <http://huttenhower.sph.harvard.edu/maaslin3>

biocViews Metagenomics, Software, Microbiome, Normalization, MultipleComparison

BugReports <https://github.com/biobakery/maaslin3/issues>

NeedsCompilation no

git_url <https://git.bioconductor.org/packages/maaslin3>

git_branch devel

git_last_commit cc4bab0

git_last_commit_date 2025-01-06

Repository Bioconductor 3.21

Date/Publication 2025-01-24

Author William Nickols [aut, cre] (ORCID:
<https://orcid.org/0000-0001-8214-9746>),
 Jacob Nearing [aut]

Maintainer William Nickols <willnickols@g.harvard.edu>

Contents

maaslin3	2
maaslin_check_arguments	7
maaslin_check_formula	10
maaslin_compute_formula	11
maaslin_contrast_test	14
maaslin_filter	16
maaslin_fit	18
maaslin_log_arguments	22
maaslin_normalize	27
maaslin_plot_results	29
maaslin_plot_results_from_output	33
maaslin_process_metadata	37
maaslin_read_data	39
maaslin_reorder_data	41
maaslin_transform	43
maaslin_write_results	45
maaslin_write_results_lefse_format	47
preprocess_dna_mtx	50

Index	52
--------------	-----------

maaslin3	<i>MaAsLin 3: A multivariable statistical framework for finding abundance and prevalence associations between metadata and high-dimensional microbial multi-omics data.</i>
----------	---

Description

This wrapper for all MaAsLin 3 steps finds abundance and prevalence associations between microbiome meta-omics features and complex metadata in population-scale epidemiological studies. The software includes multiple analysis methods (including support for multiple covariates, repeated measures, and ordered predictors), filtering, normalization, and transform options to customize analysis for your specific study.

Usage

```
maaslin3(input_data,
         input_metadata,
         output,
         formula = NULL,
```

```
fixed_effects = NULL,  
reference = NULL,  
random_effects = NULL,  
group_effects = NULL,  
ordered_effects = NULL,  
strata_effects = NULL,  
feature_specific_covariate = NULL,  
feature_specific_covariate_name = NULL,  
feature_specific_covariate_record = NULL,  
min_abundance = 0,  
min_prevalence = 0,  
zero_threshold = 0,  
min_variance = 0,  
max_significance = 0.1,  
normalization = 'TSS',  
transform = 'LOG',  
correction = 'BH',  
standardize = TRUE,  
unscaled_abundance = NULL,  
median_comparison_abundance = TRUE,  
median_comparison_prevalence = FALSE,  
median_comparison_abundance_threshold = 0,  
median_comparison_prevalence_threshold = 0,  
subtract_median = FALSE,  
warn_prevalence = TRUE,  
augment = TRUE,  
evaluate_only = NULL,  
plot_summary_plot = TRUE,  
summary_plot_first_n = 25,  
coef_plot_vars = NULL,  
heatmap_vars = NULL,  
plot_associations = TRUE,  
max_pngs = 30,  
cores = 1,  
save_models = FALSE,  
save_plots_rds = FALSE,  
verbosity = 'FINEST',  
summary_plot_balanced = FALSE)
```

Arguments

- input_data** A data frame of feature abundances or read counts, a filepath to a tab-delimited file with abundances, or a SummarizedExperiment or TreeSummarizedExperiment object with the taxa table in 'assays' and metadata in 'colData'. If a data frame or a filepath is supplied, the table should be formatted with features as columns and samples as rows (or the transpose). The column and row names should be the feature names and sample names respectively.
- input_metadata** A data frame of per-sample metadata or a filepath to a tab-delimited file with

	metadata. It should be formatted with variables as columns and samples as rows (or the transpose). The column and row names should be the variable names and sample names respectively.
output	The output folder to write results.
formula	A formula in lme4 format. Random effects, interactions, and functions of the metadata can be included (note that these functions will be applied after standardization if <code>standardize=TRUE</code>). Group, ordered, and strata variables can be specified as: <code>group(grouping_variable)</code> , <code>ordered(ordered_variable)</code> and <code>strata(strata_variable)</code> . The other variable options below will not be considered if a formula is set.
fixed_effects	A vector of variable names to be included as fixed effects.
reference	For a variable with more than two levels supplied with <code>fixed_effects</code> , the factor to use as a reference provided as a string of 'variable,reference' semi-colon delimited for multiple variables.
random_effects	A vector of variable names to be included as random intercepts.
group_effects	A factored categorical variable to be included for group testing. An ANOVA-style test will be performed to assess whether any of the variable's levels are significant, and no coefficients or individual p-values will be returned.
ordered_effects	A factored categorical variable to be included. Consecutive levels will be tested for significance against each other, and the resulting associations will correspond to effect sizes, standard errors, and significances of each level versus the previous.
strata_effects	A vector with one variable name to be included as the strata variable in case-control studies. Strata cannot be combined with random effects.
feature_specific_covariate	A table of feature-specific covariates or a filepath to a tab-delimited file with feature-specific covariates. It should be formatted with features as columns and samples as rows (or the transpose). The row names and column names should be the same as those of the <code>input_data</code> : the column and row names should be the feature names and sample names respectively.
feature_specific_covariate_name	The name for the feature-specific covariates when fitting the models.
feature_specific_covariate_record	Whether to keep the feature-specific covariates in the outputs when calculating p-values, writing results, and displaying plots.
min_abundance	Features with abundances more than <code>min_abundance</code> in <code>min_prevalence</code> of the samples will be included for analysis. The threshold is applied after normalization and before transformation.
min_prevalence	See <code>min_abundance</code> .
zero_threshold	Abundances less than or equal to <code>zero_threshold</code> will be treated as zeros. This is primarily to be used when the abundance table has likely low-abundance false positives.
min_variance	Features with abundance variances less than or equal to <code>min_variance</code> will be dropped. This is primarily used for dropping features that are entirely zero.

max_significance	The FDR corrected q-value threshold for significance used in selecting which associations to write as significant and to plot.
normalization	The normalization to apply to the features before transformation and analysis. The option TSS (total sum scaling) is recommended, but CLR (centered log ratio) and NONE can also be used.
transform	The transformation to apply to the features after normalization and before analysis. The option LOG (base 2) is recommended, but PLOG (pseudo-log) and NONE can also be used.
correction	The correction to obtain FDR-corrected q-values from raw p-values. Any valid options for p.adjust can be used.
standardize	Whether to apply z-scores to continuous metadata variables so they are on the same scale. This is recommended in order to compare coefficients across metadata variables, but note that functions of the metadata specified in the formula will apply after standardization.
unscaled_abundance	A data frame with a single column of absolute abundances or a filepath to such a tab-delimited file. The row names should match the names of the samples in input_data and input_metadata. When using spike-ins, the single column should have the same name as one of the features in input_data, and the unscaled_abundance should correspond to the absolute quantity of the spike-in. When using total abundance scaling, the single column should have the name 'total', and the unscaled_abundance should correspond to the total abundance of each sample.
median_comparison_abundance	Test abundance coefficients against a null value corresponding to the median coefficient for a metadata variable across the features. This is recommended for relative abundance data but should not be used for absolute abundance data.
median_comparison_prevalence	Test prevalence coefficients against a null value corresponding to the median coefficient for a metadata variable across the features. This is only recommended if the analyst is interested in how feature prevalence associations compare to each other or if there is likely strong compositionality-induced sparsity.
median_comparison_abundance_threshold	Coefficients within median_comparison_abundance_threshold of the median association will automatically be counted as insignificant (p-value set to 1) since they likely represent compositionality-induced associations. This threshold will be divided by the metadata variable's standard deviation if the metadata is continuous to ensure the threshold applies to the right scale.
median_comparison_prevalence_threshold	Same as median_comparison_abundance_threshold but applied to the prevalence associations.
subtract_median	Subtract the median from the coefficients.
warn_prevalence	Warn when prevalence associations are likely induced by abundance associations. This requires re-fitting the linear models on the TSS log-transformed data.

<code>augment</code>	Add extra lowly-weighted 0s and 1s to avoid linear separability.
<code>evaluate_only</code>	Whether to evaluate just the abundance ("abundance") or prevalence ("prevalence") models
<code>plot_summary_plot</code>	Generate a summary plot of significant associations.
<code>summary_plot_first_n</code>	Include the top <code>summary_plot_first_n</code> features with significant associations.
<code>coef_plot_vars</code>	Vector of variable names to be used in the coefficient plot section of the summary plot. Continuous variables should match the metadata column name, and categorical variables should be of the form "[variable] [level]".
<code>heatmap_vars</code>	Vector of variable names to be used in the heatmap section of the summary plot. Continuous variables should match the metadata column name, and categorical variables should be of the form "[variable] [level]".
<code>plot_associations</code>	Whether to generate plots for significant associations.
<code>max_pngs</code>	The top <code>max_pngs</code> significant associations will be plotted.
<code>cores</code>	How many cores to use when fitting models. (Using multiple cores will likely be faster only for large datasets or complex models.
<code>save_models</code>	Whether to return the fit models and save them to an RData file.
<code>save_plots_rds</code>	Whether to return the fit models and save them to an RData file.
<code>verbosity</code>	The level of verbosity for the logging package.
<code>summary_plot_balanced</code>	If set to TRUE the summary plot will show the top N features of each variable included in <code>coef_plot_vars</code> where N is equal to: <code>ceiling(summary_plot_first_n/length(coef_plot_vars))</code> . Will error if <code>coef_plot_vars = NULL</code>

Value

A list containing the following items:

- (1) `data`: A dataframe of feature abundances with the retained samples for fitting.
- (2) `normalized_data`: A dataframe of normalized feature abundances.
- (3) `filtered_data`: A dataframe of feature abundances on the original scale after normalization and filtering.
- (4) `transformed_data`: A dataframe of feature abundances after filtering, normalization, and transformation.
- (5) `metadata`: A dataframe of metadata with the retained samples for fitting.
- (6) `standardized_metadata`: A dataframe of metadata after scaling (if selected).
- (7) `formula`: Checked or constructed formula(s) specifying the model to be fit.
- (8) `fit_data_abundance`: The results from the fit abundance models (see [maaslin_fit](#)).
- (9) `fit_data_prevalence`: The results from the fit prevalence models (see [maaslin_fit](#)).

Author(s)

William Nickols<willnickols@g.harvard.edu>,
Jacob Nearing<nearing@broadinstitute.org>,
Maintainers: Lauren McIver<lauren.j.mciver@gmail.com>,

Examples

```
# Read features table
taxa_table_name <- system.file("extdata", "HMP2_taxonomy.tsv", package =
"maaslin3")
taxa_table <- read.csv(taxa_table_name, sep = '\t')

# Read metadata table
metadata_name <- system.file("extdata", "HMP2_metadata.tsv", package =
"maaslin3")
metadata <- read.csv(metadata_name, sep = '\t')

metadata$diagnosis <-
  factor(metadata$diagnosis, levels = c('nonIBD', 'UC', 'CD'))
metadata$dysbiosis_state <-
  factor(metadata$dysbiosis_state, levels = c('none', 'dysbiosis_UC',
'dysbiosis_CD'))
metadata$antibiotics <-
  factor(metadata$antibiotics, levels = c('No', 'Yes'))

#Run MaAsLin3
fit_out <- maaslin3::maaslin3(input_data = taxa_table,
                             input_metadata = metadata,
                             output = 'output',
                             formula = '~ diagnosis + dysbiosis_state +
antibiotics + age + reads',
                             plot_summary_plot = FALSE,
                             plot_associations = FALSE)

unlink('output', recursive=TRUE)
logging::logReset()
```

maaslin_check_arguments

Check parameter arguments to ensure a successful MaAsLin 3 run.

Description

Check the arguments provided are valid for further MaAsLin 3 use.

Usage

```
maaslin_check_arguments(feature_specific_covariate = NULL,
                        feature_specific_covariate_name = NULL,
                        feature_specific_covariate_record = NULL,
                        zero_threshold = 0,
                        normalization = 'TSS',
                        transform = 'LOG',
                        correction = 'BH',
                        warn_prevalence = TRUE,
                        evaluate_only = NULL,
                        unscaled_abundance = NULL,
                        median_comparison_abundance = TRUE)
```

Arguments

feature_specific_covariate
A table of feature-specific covariates or a filepath to a tab-delimited file with feature-specific covariates. It should be formatted with features as columns and samples as rows (or the transpose). The row names and column names should be the same as those of the `input_data`: the column and row names should be the feature names and sample names respectively.

feature_specific_covariate_name
The name for the feature-specific covariates when fitting the models.

feature_specific_covariate_record
Whether to keep the feature-specific covariates in the outputs when calculating p-values, writing results, and displaying plots.

zero_threshold Abundances less than or equal to `zero_threshold` will be treated as zeros. This is primarily to be used when the abundance table has likely low-abundance false positives.

normalization The normalization to apply to the features before transformation and analysis. The option TSS (total sum scaling) is recommended, but CLR (centered log ratio) and NONE can also be used.

transform The transformation to apply to the features after normalization and before analysis. The option LOG (base 2) is recommended, but PLOG (pseudo-log) and NONE can also be used.

correction The correction to obtain FDR-corrected q-values from raw p-values. Any valid options for `p.adjust` can be used.

warn_prevalence
Warn when prevalence associations are likely induced by abundance associations. This requires re-fitting the linear models on the TSS log-transformed data.

evaluate_only Whether to evaluate just the abundance ("abundance") or prevalence ("prevalence") models

unscaled_abundance
A data frame with a single column of absolute abundances or a filepath to such a tab-delimited file. The row names should match the names of the samples

in `input_data` and `input_metadata`. When using spike-ins, the single column should have the same name as one of the features in `input_data`, and the `unscaled_abundance` should correspond to the absolute quantity of the spike-in. When using total abundance scaling, the single column should have the name 'total', and the `unscaled_abundance` should correspond to the total abundance of each sample.

`median_comparison_abundance`

Test abundance coefficients against a null value corresponding to the median coefficient for a metadata variable across the features. This is recommended for relative abundance data but should not be used for absolute abundance data.

Value

No value is returned, but incompatible arguments will produce an error.

Author(s)

William Nickols<willnickols@g.harvard.edu>
 Jacob Nearing<nearing@broadinstitute.org>
 Maintainers: Lauren McIver<lauren.j.mciver@gmail.com>

Examples

```
# Read features table
taxa_table_name <- system.file("extdata", "HMP2_taxonomy.tsv", package =
"maaslin3")
taxa_table <- read.csv(taxa_table_name, sep = '\t')

# Read metadata table
metadata_name <- system.file("extdata", "HMP2_metadata.tsv", package =
"maaslin3")
metadata <- read.csv(metadata_name, sep = '\t')

metadata$diagnosis <-
  factor(metadata$diagnosis, levels = c('nonIBD', 'UC', 'CD'))
metadata$dysbiosis_state <-
  factor(metadata$dysbiosis_state, levels = c('none', 'dysbiosis_UC',
'dysbiosis_CD'))
metadata$antibiotics <-
  factor(metadata$antibiotics, levels = c('No', 'Yes'))

# Prepare parameter lists
maaslin3::maaslin_check_arguments(zero_threshold = 0,
normalization = 'TSS',
transform = 'LOG',
correction = 'BH',
median_comparison_abundance = TRUE)

unlink('output', recursive=TRUE)
logging::logReset()
```

maaslin_check_formula *Check a MaAsLin 3 formula to ensure a proper MaAsLin 3 run.*

Description

Ensure that the formula provided is valid. Only one of `maaslin_compute_formula` or `maaslin_check_formula` should be used.

Usage

```
maaslin_check_formula(data,  
                      metadata,  
                      input_formula = NULL,  
                      feature_specific_covariate_name = NULL)
```

Arguments

<code>data</code>	A data frame of feature abundances. It should be formatted with features as columns and samples as rows. The column and row names should be the feature names and sample names respectively.
<code>metadata</code>	A data frame of per-sample metadata. It should be formatted with variables as columns and samples as rows. The column and row names should be the variable names and sample names respectively.
<code>input_formula</code>	A formula in lme4 format. Random effects, interactions, and functions of the metadata can be included (note that these functions will be applied after standardization if <code>standardize=TRUE</code>). Group, ordered, and strata variables can be specified as: <code>group(grouping_variable)</code> , <code>ordered(ordered_variable)</code> and <code>strata(strata_variable)</code> . The other variable options below will not be considered if a formula is set.
<code>feature_specific_covariate_name</code>	The name for the feature-specific covariates when fitting the models.

Value

A list containing the following named items:

- (1) `formula`: The constructed formula.
- (2) `random_effects_formula`: A formula for the random effects.

Author(s)

William Nickols<willnickols@g.harvard.edu>,
Jacob Nearing<nearing@broadinstitute.org>,
Maintainers: Lauren McIver<lauren.j.mciver@gmail.com>,

Examples

```

# Read features table
taxa_table_name <- system.file("extdata", "HMP2_taxonomy.tsv", package =
"maaslin3")
taxa_table <- read.csv(taxa_table_name, sep = '\t')

# Read metadata table
metadata_name <- system.file("extdata", "HMP2_metadata.tsv", package =
"maaslin3")
metadata <- read.csv(metadata_name, sep = '\t')

metadata$diagnosis <-
  factor(metadata$diagnosis, levels = c('nonIBD', 'UC', 'CD'))
metadata$dysbiosis_state <-
  factor(metadata$dysbiosis_state, levels = c('none', 'dysbiosis_UC',
'dysbiosis_CD'))
metadata$antibiotics <-
  factor(metadata$antibiotics, levels = c('No', 'Yes'))

#Run MaAsLin3
maaslin3::maaslin_log_arguments(
  input_data = taxa_table,
  input_metadata = metadata,
  output = 'output',
  formula = '~ diagnosis + dysbiosis_state + antibiotics +
age + reads',
  plot_summary_plot = FALSE,
  plot_associations = FALSE)
read_data_list <- maaslin3::maaslin_read_data(
taxa_table,
metadata)
read_data_list <- maaslin3::maaslin_reorder_data(
read_data_list$data,
read_data_list$metadata)

data <- read_data_list$data
metadata <- read_data_list$metadata

formulas <- maaslin3::maaslin_check_formula(
  data,
  metadata,
  input_formula = '~ diagnosis + dysbiosis_state + antibiotics +
age + reads')

unlink('output', recursive=TRUE)
logging::logReset()

```

maaslin_compute_formula

Compute a formula for a MaAsLin 3 run based on the specified effects.

Description

Compute a formula using variables provided through `fixed_effects`, `random_effects`, `group_effects`, `ordered_effects`, and `strata_effects`. Only one of `maaslin_compute_formula` or `maaslin_check_formula` should be used.

Usage

```
maaslin_compute_formula(data,
                        metadata,
                        fixed_effects = NULL,
                        random_effects = NULL,
                        group_effects = NULL,
                        ordered_effects = NULL,
                        strata_effects = NULL,
                        feature_specific_covariate_name = NULL)
```

Arguments

<code>data</code>	A data frame of feature abundances. It should be formatted with features as columns and samples as rows. The column and row names should be the feature names and sample names respectively.
<code>metadata</code>	A data frame of per-sample metadata. It should be formatted with variables as columns and samples as rows. The column and row names should be the variable names and sample names respectively.
<code>fixed_effects</code>	A vector of variable names to be included as fixed effects.
<code>random_effects</code>	A vector of variable names to be included as random intercepts.
<code>group_effects</code>	A factored categorical variable to be included for group testing. An ANOVA-style test will be performed to assess whether any of the variable's levels are significant, and no coefficients or individual p-values will be returned.
<code>ordered_effects</code>	A factored categorical variable to be included. Consecutive levels will be tested for significance against each other, and the resulting associations will correspond to effect sizes, standard errors, and significances of each level versus the previous.
<code>strata_effects</code>	A vector with one variable name to be included as the strata variable in case-control studies. Strata cannot be combined with random effects.
<code>feature_specific_covariate_name</code>	The name for the feature-specific covariates when fitting the models.

Value

A list containing the following named items:

- (1) `formula`: The constructed formula.
- (2) `random_effects_formula`: A formula for the random effects.

Author(s)

William Nickols<willnickols@g.harvard.edu>
 Jacob Nearing<nearing@broadinstitute.org>
 Maintainers: Lauren McIver<lauren.j.mciver@gmail.com>

Examples

```
# Read features table
taxa_table_name <- system.file("extdata", "HMP2_taxonomy.tsv", package =
"maaslin3")
taxa_table <- read.csv(taxa_table_name, sep = '\t')

# Read metadata table
metadata_name <- system.file("extdata", "HMP2_metadata.tsv", package =
"maaslin3")
metadata <- read.csv(metadata_name, sep = '\t')

metadata$diagnosis <-
  factor(metadata$diagnosis, levels = c('nonIBD', 'UC', 'CD'))
metadata$dysbiosis_state <-
  factor(metadata$dysbiosis_state, levels = c('none', 'dysbiosis_UC',
'dysbiosis_CD'))
metadata$antibiotics <-
  factor(metadata$antibiotics, levels = c('No', 'Yes'))

#Run MaAsLin3
maaslin3::maaslin_log_arguments(
  input_data = taxa_table,
  input_metadata = metadata,
  output = 'output',
  fixed_effects = c('diagnosis', 'dysbiosis_state', 'antibiotics',
'age', 'reads'),
  random_effects = c('participant_id'),
  plot_summary_plot = FALSE,
  plot_associations = FALSE)
read_data_list <- maaslin3::maaslin_read_data(
  taxa_table,
  metadata)
read_data_list <- maaslin3::maaslin_reorder_data(
  read_data_list$data,
  read_data_list$metadata)

data <- read_data_list$data
metadata <- read_data_list$metadata

formulas <- maaslin3::maaslin_compute_formula(
  data,
  metadata,
  fixed_effects = c('diagnosis', 'dysbiosis_state', 'antibiotics',
'age', 'reads'),
  random_effects = c('participant_id'))
```

```
unlink('output', recursive=TRUE)
logging::logReset()
```

maaslin_contrast_test *Perform a contrast from a fit MaAsLin 3 model.*

Description

Perform a contrast test (`lmerTest::contest` for mixed effects linear; `multcomp::glht` for all others) using a named contrast matrix and right hand side. One contrast test is applied per row of the matrix.

Usage

```
maaslin_contrast_test(fits,
                      contrast_mat,
                      rhs = NULL,
                      median_comparison = NULL)
```

Arguments

<code>fits</code>	The list of fits from <code>maaslin_fit</code> with <code>save_models = TRUE</code> .
<code>contrast_mat</code>	A matrix with one row per contrast test to run. The columns will be matched to the coefficients of the model by name. Contrast vector coefficients need not be specified if they would be zero. If row names are provided, they will be used to label the test in the results.
<code>rhs</code>	The right hand size of the contrast test. The length should be the same as the number of rows in the <code>contrast_mat</code> . This will default to 0 or the median comparison if <code>median_comparison=TRUE</code> .
<code>median_comparison</code>	Run a median comparison as though the contrast had been fit directly. The parameter <code>rhs</code> must be <code>NULL</code> if so.

Value

A dataframe with the following columns:

- (1) `feature`: The feature involved in the test.
- (2) `test`: The name of the `contrast_mat` row for the test or the row number of the `contrast_mat` if no row names are specified.
- (3) `coef`: The coefficient used in the hypothesis test: this is the dot product of the contrast vector and the model coefficients.
- (4) `rhs`: The right hand side against which the coefficient is test.
- (5) `stderr`: The standard error of the coefficient.
- (7) `pval_individual`: The (uncorrected) p-value of the test.
- (8) `error`: Any error produced during the testing. NA otherwise.
- (10) `model`: abundance for the abundance models and prevalence for the prevalence models.

Author(s)

William Nickols<willnickols@g.harvard.edu>
 Jacob Nearing<nearing@broadinstitute.org>
 Maintainers: Lauren McIver<lauren.j.mciver@gmail.com>

Examples

```
# Read features table
taxa_table_name <- system.file("extdata", "HMP2_taxonomy.tsv", package =
"maaslin3")
taxa_table <- read.csv(taxa_table_name, sep = '\t')

# Read metadata table
metadata_name <- system.file("extdata", "HMP2_metadata.tsv", package =
"maaslin3")
metadata <- read.csv(metadata_name, sep = '\t')

metadata$diagnosis <-
  factor(metadata$diagnosis, levels = c('nonIBD', 'UC', 'CD'))
metadata$dysbiosis_state <-
  factor(metadata$dysbiosis_state, levels = c('none', 'dysbiosis_UC',
'dysbiosis_CD'))
metadata$antibiotics <-
  factor(metadata$antibiotics, levels = c('No', 'Yes'))

#Run MaAsLin3
fit_out <- maaslin3::maaslin3(input_data = taxa_table,
                             input_metadata = metadata,
                             output = 'output',
                             formula = '~ diagnosis + dysbiosis_state +
antibiotics + age + reads',
                             plot_summary_plot = FALSE,
                             plot_associations = FALSE)

contrast_mat <- matrix(c(1, 1, 0, 0, 0, 0, 1, 1),
                      ncol = 4, nrow = 2, byrow = TRUE)

colnames(contrast_mat) <- c("diagnosisUC",
                           "diagnosisCD",
                           "dysbiosis_statedysbiosis_UC",
                           "dysbiosis_statedysbiosis_CD")

rownames(contrast_mat) <- c("diagnosis_test", "dysbiosis_test")

maaslin_contrast_test(fits = fit_out$fit_data_abundance$fits,
                     contrast_mat = contrast_mat)

unlink('output', recursive=TRUE)
logging::logReset()
```

maaslin_filter *Filter abundance data before MaAsLin 3 model fitting.*

Description

Set abundances below zero_threshold to zero, remove features without abundances more than min_abundance in min_prevalence of the samples, and remove features with variances less than or equal to min_variance.

Usage

```
maaslin_filter(normalized_data,
               output,
               min_abundance = 0,
               min_prevalence = 0,
               zero_threshold = 0,
               min_variance = 0)
```

Arguments

normalized_data	A data frame of normalized feature abundances. It should be formatted with features as columns and samples as rows. The column and row names should be the feature names and sample names respectively.
output	The output folder to write results.
min_abundance	Features with abundances more than min_abundance in min_prevalence of the samples will be included for analysis. The threshold is applied after normalization and before transformation.
min_prevalence	See min_abundance.
zero_threshold	Abundances less than or equal to zero_threshold will be treated as zeros. This is primarily to be used when the abundance table has likely low-abundance false positives.
min_variance	Features with abundance variances less than or equal to min_variance will be dropped. This is primarily used for dropping features that are entirely zero.

Value

A dataframe of filtered features (features are columns; samples are rows).

Author(s)

William Nickols<willnickols@g.harvard.edu>,
Jacob Nearing<nearing@broadinstitute.org>,
Maintainers: Lauren McIver<lauren.j.mciver@gmail.com>,

Examples

```
# Read features table
taxa_table_name <- system.file("extdata", "HMP2_taxonomy.tsv", package =
"maaslin3")
taxa_table <- read.csv(taxa_table_name, sep = '\t')

# Read metadata table
metadata_name <- system.file("extdata", "HMP2_metadata.tsv", package =
"maaslin3")
metadata <- read.csv(metadata_name, sep = '\t')

metadata$diagnosis <-
  factor(metadata$diagnosis, levels = c('nonIBD', 'UC', 'CD'))
metadata$dysbiosis_state <-
  factor(metadata$dysbiosis_state, levels = c('none', 'dysbiosis_UC',
'dysbiosis_CD'))
metadata$antibiotics <-
  factor(metadata$antibiotics, levels = c('No', 'Yes'))

#Run MaAsLin3
maaslin3::maaslin_log_arguments(
  input_data = taxa_table,
  input_metadata = metadata,
  output = 'output',
  formula = '~ diagnosis + dysbiosis_state + antibiotics +
age + reads',
  plot_summary_plot = FALSE,
  plot_associations = FALSE)

read_data_list <- maaslin3::maaslin_read_data(
  taxa_table,
  metadata)
read_data_list <- maaslin3::maaslin_reorder_data(
  read_data_list$data,
  read_data_list$metadata)

data <- read_data_list$data
metadata <- read_data_list$metadata

formulas <- maaslin3::maaslin_check_formula(
  data,
  metadata,
  input_formula = '~ diagnosis + dysbiosis_state + antibiotics +
age + reads')

normalized_data = maaslin3::maaslin_normalize(data,
  output = 'output')

filtered_data = maaslin3::maaslin_filter(normalized_data,
  output = 'output')

unlink('output', recursive=TRUE)
```

```
logging::logReset()
```

```
maaslin_fit          Fit MaAsLin 3 models.
```

Description

Fit the abundance data with abundance and prevalence models to discover feature-metadata associations.

Usage

```
maaslin_fit(filtered_data,
             transformed_data,
             metadata,
             formula,
             random_effects_formula,
             feature_specific_covariate = NULL,
             feature_specific_covariate_name = NULL,
             feature_specific_covariate_record = NULL,
             zero_threshold = 0,
             max_significance = 0.1,
             correction = 'BH',
             median_comparison_abundance = TRUE,
             median_comparison_prevalence = FALSE,
             median_comparison_abundance_threshold = 0,
             median_comparison_prevalence_threshold = 0,
             subtract_median = FALSE,
             warn_prevalence = TRUE,
             augment = TRUE,
             evaluate_only = NULL,
             cores = 1,
             save_models = FALSE,
             data = NULL,
             min_abundance = 0,
             min_prevalence = 0,
             min_variance = 0)
```

Arguments

`filtered_data` A data frame of filtered feature abundances. It should be formatted with features as columns and samples as rows. The column and row names should be the feature names and sample names respectively.

`transformed_data` A data frame of transformed feature abundances. It should be formatted with features as columns and samples as rows. The column and row names should be the feature names and sample names respectively.

metadata	A data frame of per-sample metadata. It should be formatted with variables as columns and samples as rows. The column and row names should be the variable names and sample names respectively.
formula	A formula in lme4 format as from maaslin_check_formula .
random_effects_formula	A formula in lme4 format as from maaslin_check_formula .
feature_specific_covariate	A table of feature-specific covariates or a filepath to a tab-delimited file with feature-specific covariates. It should be formatted with features as columns and samples as rows (or the transpose). The row names and column names should be the same as those of the input_data: the column and row names should be the feature names and sample names respectively.
feature_specific_covariate_name	The name for the feature-specific covariates when fitting the models.
feature_specific_covariate_record	Whether to keep the feature-specific covariates in the outputs when calculating p-values, writing results, and displaying plots.
zero_threshold	Abundances less than or equal to zero_threshold will be treated as zeros. This is primarily to be used when the abundance table has likely low-abundance false positives.
max_significance	The FDR corrected q-value threshold for significance used in selecting which associations to write as significant and to plot.
correction	The correction to obtain FDR-corrected q-values from raw p-values. Any valid options for p.adjust can be used.
median_comparison_abundance	Test abundance coefficients against a null value corresponding to the median coefficient for a metadata variable across the features. This is recommended for relative abundance data but should not be used for absolute abundance data.
median_comparison_prevalence	Test prevalence coefficients against a null value corresponding to the median coefficient for a metadata variable across the features. This is only recommended if the analyst is interested in how feature prevalence associations compare to each other or if there is likely strong compositionality-induced sparsity.
median_comparison_abundance_threshold	Coefficients within median_comparison_abundance_threshold of the median association will automatically be counted as insignificant (p-value set to 1) since they likely represent compositionality-induced associations. This threshold will be divided by the metadata variable's standard deviation if the metadata is continuous to ensure the threshold applies to the right scale.
median_comparison_prevalence_threshold	Same as median_comparison_abundance_threshold but applied to the prevalence associations.
subtract_median	Subtract the median from the coefficients.

warn_prevalence	Warn when prevalence associations are likely induced by abundance associations. This requires re-fitting the linear models on the TSS log-transformed data.
augment	Add extra lowly-weighted 0s and 1s to avoid linear separability.
evaluate_only	Whether to evaluate just the abundance ("abundance") or prevalence ("prevalence") models
cores	How many cores to use when fitting models. (Using multiple cores will likely be faster only for large datasets or complex models.
save_models	Whether to return the fit models and save them to an RData file.
data	The original data (only necessary if warn_prevalence is TRUE).
min_abundance	The original min_abundance parameter (only necessary if warn_prevalence is TRUE).
min_prevalence	The original min_prevalence parameter (only necessary if warn_prevalence is TRUE).
min_variance	The original min_variance parameter (only necessary if min_variance is TRUE).

Value

A list containing the following named items:

- (1) `fit_data_abundance`: The results from the fit abundance models.
- (2) `fit_data_prevalence`: The results from the fit prevalence models.

The `fit_data_abundance` and `fit_data_prevalence` items have the same structure. They are both lists with the following named items:

- (1) `results`: A results table with the modeled associations (see below).
- (2) `residuals`: A features (rows) by samples (columns) dataframe of residuals from the models.
- (3) `fitted`: A features (rows) by samples (columns) dataframe of fitted values from the models.
- (4) `ranef`: A features (rows) by random effect (columns) dataframe of random effects from the models. If multiple random effects are specified, this is a dataframe of dataframes.
- (5) `fits`: If `save_models=TRUE`, this is a list of the fit models.

The results tables contain the following columns for each association (row):

- (1) `feature`: The feature involved in the association.
- (2) `metadata`: The metadata variable involved in the association.
- (3) `value`: The value of the metadata variable: the metadata variable itself if continuous or the level if categorical.
- (4) `name`: The name of the model component involved in the association: the metadata variable itself if continuous or a concatenated version of the metadata variable and level if categorical.
- (5) `coef`: The coefficient of the association: the slope coefficient in the abundance model and the change in log odds in the prevalence model.
- (6) `stderr`: The standard error of the coefficient.

- (7) `pval_individual`: The (uncorrected) p-value of the association.
- (8) `qval_individual`: The FDR corrected q-value of the association. FDR correction is performed over all associations in the abundance and prevalence modeling without errors together.
- (9) `pval_joint`: The p-value of the overall association (combining abundance and prevalence) by taking the minimum of the abundance and logistic p-values and applying the Beta(1,2) CDF. These will be the same in the abundance and prevalence results for an association.
- (10) `qval_joint`: The FDR corrected q-value of the association. FDR correction is performed over all joint p-values without errors.
- (11) `error`: Any error produced by the model during fitting. NA otherwise.
- (12) `model`: `linear` for the abundance models and `logistic` for the prevalence models.
- (13) `N`: The number of data points for the association's feature.
- (14) `N_not_zero`: The number of non-zero data points for the association's feature.

Author(s)

William Nickols<willnickols@g.harvard.edu>
 Jacob Nearing<nearing@broadinstitute.org>
 Maintainers: Lauren McIver<lauren.j.mciver@gmail.com>

Examples

```
# Read features table
taxa_table_name <- system.file("extdata", "HMP2_taxonomy.tsv", package =
"maaslin3")
taxa_table <- read.csv(taxa_table_name, sep = '\t')

# Read metadata table
metadata_name <- system.file("extdata", "HMP2_metadata.tsv", package =
"maaslin3")
metadata <- read.csv(metadata_name, sep = '\t')

metadata$diagnosis <-
  factor(metadata$diagnosis, levels = c('nonIBD', 'UC', 'CD'))
metadata$dysbiosis_state <-
  factor(metadata$dysbiosis_state, levels = c('none', 'dysbiosis_UC',
'dysbiosis_CD'))
metadata$antibiotics <-
  factor(metadata$antibiotics, levels = c('No', 'Yes'))

#Run MaAsLin3
maaslin3::maaslin_log_arguments(
  input_data = taxa_table,
  input_metadata = metadata,
  output = 'output',
  formula = '~ diagnosis + dysbiosis_state + antibiotics +
age + reads',
  plot_summary_plot = FALSE,
  plot_associations = FALSE)
```

```

read_data_list <- maaslin3::maaslin_read_data(
  taxa_table,
  metadata)
read_data_list <- maaslin3::maaslin_reorder_data(
  read_data_list$data,
  read_data_list$metadata)

data <- read_data_list$data
metadata <- read_data_list$metadata

formulas <- maaslin3::maaslin_check_formula(
  data,
  metadata,
  input_formula = '~ diagnosis + dysbiosis_state + antibiotics +
age + reads')

formula <- formulas$formula
random_effects_formula <- formulas$random_effects_formula

normalized_data = maaslin3::maaslin_normalize(data,
  output = 'output')

filtered_data = maaslin3::maaslin_filter(normalized_data,
  output = 'output')

transformed_data = maaslin3::maaslin_transform(filtered_data,
  output = 'output')

standardized_metadata = maaslin3::maaslin_process_metadata(
  metadata,
  formula = formula)

maaslin_results = maaslin3::maaslin_fit(
  filtered_data,
  transformed_data,
  standardized_metadata,
  formula,
  random_effects_formula,
  warn_prevalence = FALSE)

unlink('output', recursive=TRUE)
logging::logReset()

```

maaslin_log_arguments *Log MaAsLin 3 parameters.*

Description

Check that the parameters provided are valid for further MaAsLin 3 use and open a logger to log the parameters.

Usage

```

maaslin_log_arguments(input_data,
                      input_metadata,
                      output,
                      formula = NULL,
                      fixed_effects = NULL,
                      reference = NULL,
                      random_effects = NULL,
                      group_effects = NULL,
                      ordered_effects = NULL,
                      strata_effects = NULL,
                      feature_specific_covariate = NULL,
                      feature_specific_covariate_name = NULL,
                      feature_specific_covariate_record = NULL,
                      min_abundance = 0,
                      min_prevalence = 0,
                      zero_threshold = 0,
                      min_variance = 0,
                      max_significance = 0.1,
                      normalization = 'TSS',
                      transform = 'LOG',
                      correction = 'BH',
                      standardize = TRUE,
                      unscaled_abundance = NULL,
                      median_comparison_abundance = TRUE,
                      median_comparison_prevalence = FALSE,
                      median_comparison_abundance_threshold = 0,
                      median_comparison_prevalence_threshold = 0,
                      subtract_median = FALSE,
                      warn_prevalence = TRUE,
                      augment = TRUE,
                      evaluate_only = NULL,
                      plot_summary_plot = TRUE,
                      summary_plot_first_n = 25,
                      coef_plot_vars = NULL,
                      heatmap_vars = NULL,
                      plot_associations = TRUE,
                      max_pngs = 30,
                      cores = 1,
                      save_models = FALSE,
                      save_plots_rds = FALSE,
                      verbosity = 'FINEST',
                      summary_plot_balanced = FALSE)

```

Arguments

input_data A data frame of feature abundances or read counts or a filepath to a tab-delimited file with abundances. It should be formatted with features as columns and sam-

	ples as rows (or the transpose). The column and row names should be the feature names and sample names respectively.
input_metadata	A data frame of per-sample metadata or a filepath to a tab-delimited file with metadata. It should be formatted with variables as columns and samples as rows (or the transpose). The column and row names should be the variable names and sample names respectively.
output	The output folder to write results.
formula	A formula in lme4 format. Random effects, interactions, and functions of the metadata can be included (note that these functions will be applied after standardization if standardize=TRUE). Group, ordered, and strata variables can be specified as: group(grouping_variable), ordered(ordered_variable) and strata(strata_variable). The other variable options below will not be considered if a formula is set.
fixed_effects	A vector of variable names to be included as fixed effects.
reference	For a variable with more than two levels supplied with fixed_effects, the factor to use as a reference provided as a string of 'variable,reference' semi-colon delimited for multiple variables.
random_effects	A vector of variable names to be included as random intercepts.
group_effects	A factored categorical variable to be included for group testing. An ANOVA-style test will be performed to assess whether any of the variable's levels are significant, and no coefficients or individual p-values will be returned.
ordered_effects	A factored categorical variable to be included. Consecutive levels will be tested for significance against each other, and the resulting associations will correspond to effect sizes, standard errors, and significances of each level versus the previous.
strata_effects	A vector with one variable name to be included as the strata variable in case-control studies. Strata cannot be combined with random effects.
feature_specific_covariate	A table of feature-specific covariates or a filepath to a tab-delimited file with feature-specific covariates. It should be formatted with features as columns and samples as rows (or the transpose). The row names and column names should be the same as those of the input_data: the column and row names should be the feature names and sample names respectively.
feature_specific_covariate_name	The name for the feature-specific covariates when fitting the models.
feature_specific_covariate_record	Whether to keep the feature-specific covariates in the outputs when calculating p-values, writing results, and displaying plots.
min_abundance	Features with abundances more than min_abundance in min_prevalence of the samples will be included for analysis. The threshold is applied after normalization and before transformation.
min_prevalence	See min_abundance.
zero_threshold	Abundances less than or equal to zero_threshold will be treated as zeros. This is primarily to be used when the abundance table has likely low-abundance false positives.

min_variance	Features with abundance variances less than or equal to min_variance will be dropped. This is primarily used for dropping features that are entirely zero.
max_significance	The FDR corrected q-value threshold for significance used in selecting which associations to write as significant and to plot.
normalization	The normalization to apply to the features before transformation and analysis. The option TSS (total sum scaling) is recommended, but CLR (centered log ratio) and NONE can also be used.
transform	The transformation to apply to the features after normalization and before analysis. The option LOG (base 2) is recommended, but PLOG (pseudo-log) and NONE can also be used.
correction	The correction to obtain FDR-corrected q-values from raw p-values. Any valid options for p.adjust can be used.
standardize	Whether to apply z-scores to continuous metadata variables so they are on the same scale. This is recommended in order to compare coefficients across metadata variables, but note that functions of the metadata specified in the formula will apply after standardization.
unscaled_abundance	A data frame with a single column of absolute abundances or a filepath to such a tab-delimited file. The row names should match the names of the samples in input_data and input_metadata. When using spike-ins, the single column should have the same name as one of the features in input_data, and the unscaled_abundance should correspond to the absolute quantity of the spike-in. When using total abundance scaling, the single column should have the name 'total', and the unscaled_abundance should correspond to the total abundance of each sample.
median_comparison_abundance	Test abundance coefficients against a null value corresponding to the median coefficient for a metadata variable across the features. This is recommended for relative abundance data but should not be used for absolute abundance data.
median_comparison_prevalence	Test prevalence coefficients against a null value corresponding to the median coefficient for a metadata variable across the features. This is only recommended if the analyst is interested in how feature prevalence associations compare to each other or if there is likely strong compositionality-induced sparsity.
median_comparison_abundance_threshold	Coefficients within median_comparison_abundance_threshold of the median association will automatically be counted as insignificant (p-value set to 1) since they likely represent compositionality-induced associations. This threshold will be divided by the metadata variable's standard deviation if the metadata is continuous to ensure the threshold applies to the right scale.
median_comparison_prevalence_threshold	Same as median_comparison_abundance_threshold but applied to the prevalence associations.
subtract_median	Subtract the median from the coefficients.

warn_prevalence	Warn when prevalence associations are likely induced by abundance associations. This requires re-fitting the linear models on the TSS log-transformed data.
augment	Add extra lowly-weighted 0s and 1s to avoid linear separability.
evaluate_only	Whether to evaluate just the abundance ("abundance") or prevalence ("prevalence") models
plot_summary_plot	Generate a summary plot of significant associations.
summary_plot_first_n	Include the top summary_plot_first_n features with significant associations.
coef_plot_vars	Vector of variable names to be used in the coefficient plot section of the summary plot. Continuous variables should match the metadata column name, and categorical variables should be of the form "[variable] [level]".
heatmap_vars	Vector of variable names to be used in the heatmap section of the summary plot. Continuous variables should match the metadata column name, and categorical variables should be of the form "[variable] [level]".
plot_associations	Whether to generate plots for significant associations.
max_pngs	The top max_pngs significant associations will be plotted.
cores	How many cores to use when fitting models. (Using multiple cores will likely be faster only for large datasets or complex models.
save_models	Whether to return the fit models and save them to an RData file.
save_plots_rds	Whether to return the plots to an RDS file.
verbosity	The level of verbosity for the logging package.
summary_plot_balanced	If set to TRUE the summary plot will show the top N features of each variable included in coef_plot_vars where N is equal to: ceiling(summary_plot_first_n/length(coef_plot_vars)). Will error if coef_plot_vars = NULL

Value

No value is returned, but a logger is opened with the parameters logged.

Author(s)

William Nickols<willnickols@g.harvard.edu>,
 Jacob Nearing<nearing@broadinstitute.org>,
 Maintainers: Lauren McIver<lauren.j.mciver@gmail.com>,

Examples

```
# Read features table
taxa_table_name <- system.file("extdata", "HMP2_taxonomy.tsv", package =
"maaslin3")
```

```

taxa_table <- read.csv(taxa_table_name, sep = '\t')

# Read metadata table
metadata_name <- system.file("extdata", "HMP2_metadata.tsv", package =
"maaslin3")
metadata <- read.csv(metadata_name, sep = '\t')

metadata$diagnosis <-
  factor(metadata$diagnosis, levels = c('nonIBD', 'UC', 'CD'))
metadata$dysbiosis_state <-
  factor(metadata$dysbiosis_state, levels = c('none', 'dysbiosis_UC',
'dysbiosis_CD'))
metadata$antibiotics <-
  factor(metadata$antibiotics, levels = c('No', 'Yes'))

# Prepare parameter lists
maaslin3::maaslin_log_arguments(input_data = taxa_table,
  input_metadata = metadata,
  output = 'output',
  formula = '~ diagnosis + dysbiosis_state +
  antibiotics + age + reads',
  plot_summary_plot = FALSE,
  plot_associations = FALSE)
unlink('output', recursive=TRUE)
logging::logReset()

```

maaslin_normalize	<i>Normalize abundance data for MaAsLin 3 model fitting.</i>
-------------------	--

Description

Normalize the abundance data according to the normalization parameter. If `unscaled_abundance` is specified, compute the absolute abundances.

Usage

```

maaslin_normalize(data,
  output,
  zero_threshold = 0,
  normalization = 'TSS',
  unscaled_abundance = NULL)

```

Arguments

data	A data frame of feature abundances. It should be formatted with features as columns and samples as rows. The column and row names should be the feature names and sample names respectively.
output	The output folder to write results.

- zero_threshold** Abundances less than or equal to `zero_threshold` will be treated as zeros. This is primarily to be used when the abundance table has likely low-abundance false positives.
- normalization** The normalization to apply to the features before transformation and analysis. The option TSS (total sum scaling) is recommended, but CLR (centered log ratio) and NONE can also be used.
- unscaled_abundance**
A data frame with a single column of absolute abundances. The row names should match the names of the samples in `input_data` and `input_metadata`. When using spike-ins, the single column should have the same name as one of the features in `input_data`, and the `unscaled_abundance` should correspond to the absolute quantity of the spike-in. When using total abundance scaling, the single column should have the name 'total', and the `unscaled_abundance` should correspond to the total abundance of each sample.

Value

A dataframe of normalized features (features are columns; samples are rows).

Author(s)

William Nickols<willnickols@g.harvard.edu>,
Jacob Nearing<nearing@broadinstitute.org>,
Maintainers: Lauren McIver<lauren.j.mciver@gmail.com>,

Examples

```
# Read features table
taxa_table_name <- system.file("extdata", "HMP2_taxonomy.tsv", package =
"maaslin3")
taxa_table <- read.csv(taxa_table_name, sep = '\t')

# Read metadata table
metadata_name <- system.file("extdata", "HMP2_metadata.tsv", package =
"maaslin3")
metadata <- read.csv(metadata_name, sep = '\t')

metadata$diagnosis <-
  factor(metadata$diagnosis, levels = c('nonIBD', 'UC', 'CD'))
metadata$dysbiosis_state <-
  factor(metadata$dysbiosis_state, levels = c('none', 'dysbiosis_UC',
'dysbiosis_CD'))
metadata$antibiotics <-
  factor(metadata$antibiotics, levels = c('No', 'Yes'))

#Run MaAsLin3
maaslin3::maaslin_log_arguments(
  input_data = taxa_table,
  input_metadata = metadata,
  output = 'output',
```

```

    formula = '~ diagnosis + dysbiosis_state + antibiotics +
    age + reads',
    plot_summary_plot = FALSE,
    plot_associations = FALSE)

read_data_list <- maaslin3::maaslin_read_data(
  taxa_table,
  metadata)
read_data_list <- maaslin3::maaslin_reorder_data(
  read_data_list$data,
  read_data_list$metadata)

data <- read_data_list$data
metadata <- read_data_list$metadata

formulas <- maaslin3::maaslin_check_formula(
  data,
  metadata,
  input_formula = '~ diagnosis + dysbiosis_state + antibiotics +
  age + reads')

normalized_data = maaslin3::maaslin_normalize(data,
  output = 'output')

unlink('output', recursive=TRUE)
logging::logReset()

```

maaslin_plot_results *Plot the results from a MaAsLin 3 run.*

Description

Two types of plots are generated. First, the summary plot contains sorted per-feature coefficients plotted with their standard errors for key variables and a heatmap summarizing the remaining variables. Second, for significant features, association plots (scatterplots, boxplots, or tables depending on the association) are generated to visualize and verify the model fits. The data are shown with their transformed values in the association plots since this is the scale on which the models are fit.

Usage

```

maaslin_plot_results(output,
  transformed_data,
  unstandardized_metadata,
  fit_data_abundance,
  fit_data_prevalence,
  normalization,
  transform,
  feature_specific_covariate = NULL,
  feature_specific_covariate_name = NULL,

```

```

feature_specific_covariate_record = NULL,
median_comparison_abundance = TRUE,
median_comparison_prevalence = FALSE,
max_significance = 0.1,
plot_summary_plot = TRUE,
summary_plot_first_n = 25,
coef_plot_vars = NULL,
heatmap_vars = NULL,
plot_associations = TRUE,
max_pngs = 30,
balanced = FALSE,
save_plots_rds = FALSE)

```

Arguments

output	The output folder to write results.
transformed_data	A data frame of transformed feature abundances. It should be formatted with features as columns and samples as rows. The column and row names should be the feature names and sample names respectively.
unstandardized_metadata	A data frame of per-sample metadata. It should be formatted with variables as columns and samples as rows. The column and row names should be the variable names and sample names respectively.
fit_data_abundance	The abundance outputs of maaslin_fit .
fit_data_prevalence	The prevalence outputs of maaslin_fit .
normalization	The normalization to apply to the features before transformation and analysis. The option TSS (total sum scaling) is recommended, but CLR (centered log ratio) and NONE can also be used.
transform	The transformation to apply to the features after normalization and before analysis. The option LOG (base 2) is recommended, but PLOG (pseudo-log) and NONE can also be used.
feature_specific_covariate	A table of feature-specific covariates or a filepath to a tab-delimited file with feature-specific covariates. It should be formatted with features as columns and samples as rows (or the transpose). The row names and column names should be the same as those of the input_data: the column and row names should be the feature names and sample names respectively.
feature_specific_covariate_name	The name for the feature-specific covariates when fitting the models.
feature_specific_covariate_record	Whether to keep the feature-specific covariates in the outputs when calculating p-values, writing results, and displaying plots.

median_comparison_abundance	Test abundance coefficients against a null value corresponding to the median coefficient for a metadata variable across the features. This is recommended for relative abundance data but should not be used for absolute abundance data.
median_comparison_prevalence	Test prevalence coefficients against a null value corresponding to the median coefficient for a metadata variable across the features. This is only recommended if the analyst is interested in how feature prevalence associations compare to each other or if there is likely strong compositionality-induced sparsity.
max_significance	The FDR corrected q-value threshold for significance used in selecting which associations to write as significant and to plot.
plot_summary_plot	Generate a summary plot of significant associations.
summary_plot_first_n	Include the top summary_plot_first_n features with significant associations.
coef_plot_vars	Vector of variable names to be used in the coefficient plot section of the summary plot. Continuous variables should match the metadata column name, and categorical variables should be of the form "[variable] [level]".
heatmap_vars	Vector of variable names to be used in the heatmap section of the summary plot. Continuous variables should match the metadata column name, and categorical variables should be of the form "[variable] [level]".
plot_associations	Whether to generate plots for significant associations.
max_pngs	The top max_pngs significant associations will be plotted.
balanced	If set to TRUE the summary plot will show the top N features of each variable included in coef_plot_vars where N is equal to: $\text{ceiling}(\text{summary_plot_first_n}/\text{length}(\text{coef_plot_vars}))$. Will error if coef_plot_vars = NULL
save_plots_rds	Whether to return the plots to an RDS file.

Value

Results will be written to the figures folder within the folder output. The list of individual association plots is returned if plot_associations=TRUE. In the heatmap of the summary plot, one star corresponds to the user-set max_significance and two stars corresponds to the user-set max_significance divided by 10.

Author(s)

William Nickols<willnickols@g.harvard.edu>,
 Jacob Nearing<nearing@broadinstitute.org>,
 Maintainers: Lauren McIver<lauren.j.mciver@gmail.com>,

Examples

```

# Read features table
taxa_table_name <- system.file("extdata", "HMP2_taxonomy.tsv", package =
"maaslin3")
taxa_table <- read.csv(taxa_table_name, sep = '\t')

# Read metadata table
metadata_name <- system.file("extdata", "HMP2_metadata.tsv", package =
"maaslin3")
metadata <- read.csv(metadata_name, sep = '\t')

metadata$diagnosis <-
  factor(metadata$diagnosis, levels = c('nonIBD', 'UC', 'CD'))
metadata$dysbiosis_state <-
  factor(metadata$dysbiosis_state, levels = c('none', 'dysbiosis_UC',
'dysbiosis_CD'))
metadata$antibiotics <-
  factor(metadata$antibiotics, levels = c('No', 'Yes'))

#Run MaASLin3
maaslin3::maaslin_log_arguments(
  input_data = taxa_table,
  input_metadata = metadata,
  output = 'output',
  formula = '~ diagnosis + dysbiosis_state + antibiotics +
age + reads')

read_data_list <- maaslin3::maaslin_read_data(
  taxa_table,
  metadata)
read_data_list <- maaslin3::maaslin_reorder_data(
  read_data_list$data,
  read_data_list$metadata)

data <- read_data_list$data
metadata <- read_data_list$metadata

formulas <- maaslin3::maaslin_check_formula(
  data,
  metadata,
  input_formula = '~ diagnosis + dysbiosis_state + antibiotics +
age + reads')

formula <- formulas$formula
random_effects_formula <- formulas$random_effects_formula

normalized_data = maaslin3::maaslin_normalize(data,
  output = 'output')

filtered_data = maaslin3::maaslin_filter(normalized_data,
  output = 'output')

```



```

transformed_data = maaslin3::maaslin_transform(filtered_data,
                                              output = 'output')

standardized_metadata = maaslin3::maaslin_process_metadata(
  metadata,
  formula = formula)

maaslin_results = maaslin3::maaslin_fit(
  filtered_data,
  transformed_data,
  standardized_metadata,
  formula,
  random_effects_formula,
  warn_prevalence = FALSE)

maaslin3::maaslin_write_results(
  output = 'output',
  maaslin_results$fit_data_abundance,
  maaslin_results$fit_data_prevalence,
  random_effects_formula)

maaslin3::maaslin_plot_results(
  output = 'output',
  transformed_data,
  metadata,
  maaslin_results$fit_data_abundance,
  maaslin_results$fit_data_prevalence,
  normalization = "TSS",
  transform = "LOG")

unlink('output', recursive=TRUE)
logging::logReset()

```

```
maaslin_plot_results_from_output
```

Plot the results from a MaAsLin 3 run.

Description

Two types of plots are generated. First, the summary plot contains sorted per-feature coefficients plotted with their standard errors for key variables and a heatmap summarizing the remaining variables. Second, for significant features, association plots (scatterplots, boxplots, or tables depending on the association) are generated to visualize and verify the model fits. The data are shown with their transformed values in the association plots since this is the scale on which the models are fit. In comparison to `maaslin_plot_results` that needs the entire `maaslin_fit` list, only the parameter list and an outputs directory containing a completed run are needed for `maaslin_plot_results_from_output`.

Usage

```
maaslin_plot_results_from_output(output,
```

```

metadata,
normalization,
transform,
feature_specific_covariate = NULL,
feature_specific_covariate_name = NULL,
feature_specific_covariate_record = NULL,
median_comparison_abundance = TRUE,
median_comparison_prevalence = FALSE,
max_significance = 0.1,
plot_summary_plot = TRUE,
summary_plot_first_n = 25,
coef_plot_vars = NULL,
heatmap_vars = NULL,
plot_associations = TRUE,
max_pngs = 30,
balanced = FALSE,
save_plots_rds = FALSE)

```

Arguments

output	The output folder to write results.
metadata	A data frame of per-sample metadata. It should be formatted with variables as columns and samples as rows. The column and row names should be the variable names and sample names respectively.
normalization	The normalization to apply to the features before transformation and analysis. The option TSS (total sum scaling) is recommended, but CLR (centered log ratio) and NONE can also be used.
transform	The transformation to apply to the features after normalization and before analysis. The option LOG (base 2) is recommended, but PLOG (pseudo-log) and NONE can also be used.
feature_specific_covariate	A table of feature-specific covariates or a filepath to a tab-delimited file with feature-specific covariates. It should be formatted with features as columns and samples as rows (or the transpose). The row names and column names should be the same as those of the input_data: the column and row names should be the feature names and sample names respectively.
feature_specific_covariate_name	The name for the feature-specific covariates when fitting the models.
feature_specific_covariate_record	Whether to keep the feature-specific covariates in the outputs when calculating p-values, writing results, and displaying plots.
median_comparison_abundance	Test abundance coefficients against a null value corresponding to the median coefficient for a metadata variable across the features. This is recommended for relative abundance data but should not be used for absolute abundance data.
median_comparison_prevalence	Test prevalence coefficients against a null value corresponding to the median coefficient for a metadata variable across the features. This is only recommended

if the analyst is interested in how feature prevalence associations compare to each other or if there is likely strong compositionality-induced sparsity.

max_significance	The FDR corrected q-value threshold for significance used in selecting which associations to write as significant and to plot.
plot_summary_plot	Generate a summary plot of significant associations.
summary_plot_first_n	Include the top summary_plot_first_n features with significant associations.
coef_plot_vars	Vector of variable names to be used in the coefficient plot section of the summary plot. Continuous variables should match the metadata column name, and categorical variables should be of the form "[variable] [level]".
heatmap_vars	Vector of variable names to be used in the heatmap section of the summary plot. Continuous variables should match the metadata column name, and categorical variables should be of the form "[variable] [level]".
plot_associations	Whether to generate plots for significant associations.
max_pngs	The top max_pngs significant associations will be plotted.
balanced	If set to TRUE the summary plot will show the top N features of each variable included in coef_plot_vars where N is equal to: ceiling(summary_plot_first_n/length(coef_plot_vars)). Will error if coef_plot_vars = NULL
save_plots_rds	Whether to return the plots to an RDS file.

Value

Results will be written to the figures folder within the folder output. The list of individual association plots is returned if plot_associations=TRUE. In the heatmap of the summary plot, one star corresponds to the user-set max_significance and two stars corresponds to the user-set max_significance divided by 10.

Author(s)

William Nickols<willnickols@g.harvard.edu>,
 Jacob Nearing<nearing@broadinstitute.org>,
 Maintainers: Lauren McIver<lauren.j.mciver@gmail.com>,

Examples

```
# Read features table
taxa_table_name <- system.file("extdata", "HMP2_taxonomy.tsv", package =
"maaslin3")
taxa_table <- read.csv(taxa_table_name, sep = '\t')

# Read metadata table
metadata_name <- system.file("extdata", "HMP2_metadata.tsv", package =
"maaslin3")
metadata <- read.csv(metadata_name, sep = '\t')
```

```
metadata$diagnosis <-
  factor(metadata$diagnosis, levels = c('nonIBD', 'UC', 'CD'))
metadata$dysbiosis_state <-
  factor(metadata$dysbiosis_state, levels = c('none', 'dysbiosis_UC',
  'dysbiosis_CD'))
metadata$antibiotics <-
  factor(metadata$antibiotics, levels = c('No', 'Yes'))

#Run MaAsLin3
maaslin3::maaslin_log_arguments(
  input_data = taxa_table,
  input_metadata = metadata,
  output = 'output',
  formula = '~ diagnosis + dysbiosis_state + antibiotics +
  age + reads')

read_data_list <- maaslin3::maaslin_read_data(
  taxa_table,
  metadata)
read_data_list <- maaslin3::maaslin_reorder_data(
  read_data_list$data,
  read_data_list$metadata)

data <- read_data_list$data
metadata <- read_data_list$metadata

formulas <- maaslin3::maaslin_check_formula(
  data,
  metadata,
  input_formula = '~ diagnosis + dysbiosis_state + antibiotics +
  age + reads')

formula <- formulas$formula
random_effects_formula <- formulas$random_effects_formula

normalized_data = maaslin3::maaslin_normalize(data,
  output = 'output')

filtered_data = maaslin3::maaslin_filter(normalized_data,
  output = 'output')

transformed_data = maaslin3::maaslin_transform(filtered_data,
  output = 'output')

standardized_metadata = maaslin3::maaslin_process_metadata(
  metadata,
  formula = formula)

maaslin_results = maaslin3::maaslin_fit(
  filtered_data,
  transformed_data,
  standardized_metadata,
```

```

    formula,
    random_effects_formula,
    warn_prevalence = FALSE)

maaslin3::maaslin_write_results(
  output = 'output',
  maaslin_results$fit_data_abundance,
  maaslin_results$fit_data_prevalence,
  random_effects_formula)

maaslin3::maaslin_plot_results_from_output(
  output = 'output',
  metadata,
  normalization = "TSS",
  transform = "LOG")

unlink('output', recursive=TRUE)
logging::logReset()

```

maaslin_process_metadata

Process metadata before MaAsLin 3 model fitting.

Description

Check that references are set properly if the metadata variables are categorical and provided through `fixed_effects`. Standardize the continuous metadata variables as a z-score (subtract the mean, divide by the standard deviation) if `standardize` is set.

Usage

```

maaslin_process_metadata(metadata,
  formula = NULL,
  fixed_effects = NULL,
  reference = NULL,
  feature_specific_covariate_name = NULL,
  standardize = TRUE)

```

Arguments

metadata	A data frame of per-sample metadata. It should be formatted with variables as columns and samples as rows. The column and row names should be the variable names and sample names respectively.
formula	A formula in lme4 format. Random effects, interactions, and functions of the metadata can be included (note that these functions will be applied after standardization if <code>standardize=TRUE</code>). Group, ordered, and strata variables can be specified as: <code>group(grouping_variable)</code> , <code>ordered(ordered_variable)</code> and <code>strata(strata_variable)</code> . The other variable options below will not be considered if a formula is set.

fixed_effects A vector of variable names to be included as fixed effects.

reference For a variable with more than two levels supplied with **fixed_effects**, the factor to use as a reference provided as a string of 'variable,reference' semi-colon delimited for multiple variables.

feature_specific_covariate_name
The name for the feature-specific covariates when fitting the models.

standardize Whether to apply z-scores to continuous metadata variables so they are on the same scale. This is recommended in order to compare coefficients across metadata variables, but note that functions of the metadata specified in the formula will apply after standardization.

Value

The processed metadata.

Author(s)

William Nickols<willnickols@g.harvard.edu>,
Jacob Nearing<nearing@broadinstitute.org>,
Maintainers: Lauren McIver<lauren.j.mciver@gmail.com>,

Examples

```
# Read features table
taxa_table_name <- system.file("extdata", "HMP2_taxonomy.tsv", package =
"maaslin3")
taxa_table <- read.csv(taxa_table_name, sep = '\t')

# Read metadata table
metadata_name <- system.file("extdata", "HMP2_metadata.tsv", package =
"maaslin3")
metadata <- read.csv(metadata_name, sep = '\t')

metadata$diagnosis <-
  factor(metadata$diagnosis, levels = c('nonIBD', 'UC', 'CD'))
metadata$dysbiosis_state <-
  factor(metadata$dysbiosis_state, levels = c('none', 'dysbiosis_UC',
'dysbiosis_CD'))
metadata$antibiotics <-
  factor(metadata$antibiotics, levels = c('No', 'Yes'))

#Run MaAsLin3
maaslin3::maaslin_log_arguments(
  input_data = taxa_table,
  input_metadata = metadata,
  output = 'output',
  formula = '~ diagnosis + dysbiosis_state + antibiotics +
age + reads',
  plot_summary_plot = FALSE,
  plot_associations = FALSE)
```

```
read_data_list <- maaslin3::maaslin_read_data(
  taxa_table,
  metadata)
read_data_list <- maaslin3::maaslin_reorder_data(
  read_data_list$data,
  read_data_list$metadata)

data <- read_data_list$data
metadata <- read_data_list$metadata

formulas <- maaslin3::maaslin_check_formula(
  data,
  metadata,
  input_formula = '~ diagnosis + dysbiosis_state + antibiotics +
age + reads')

formula <- formulas$formula
random_effects_formula <- formulas$random_effects_formula

normalized_data = maaslin3::maaslin_normalize(data,
  output = 'output')

filtered_data = maaslin3::maaslin_filter(normalized_data,
  output = 'output')

standardized_metadata = maaslin3::maaslin_process_metadata(
  metadata,
  formula = formula)

unlink('output', recursive=TRUE)
logging::logReset()
```

maaslin_read_data *Read in the abundance data and metadata.*

Description

Read in the abundance data and metadata from files if necessary.

Usage

```
maaslin_read_data(input_data,
  input_metadata,
  feature_specific_covariate = NULL,
  unscaled_abundance = NULL)
```

Arguments

- input_data** A data frame of feature abundances or read counts or a filepath to a tab-delimited file with abundances. It should be formatted with features as columns and samples as rows (or the transpose). The column and row names should be the feature names and sample names respectively.
- input_metadata** A data frame of per-sample metadata or a filepath to a tab-delimited file with metadata. It should be formatted with variables as columns and samples as rows (or the transpose). The column and row names should be the variable names and sample names respectively.
- feature_specific_covariate** A table of feature-specific covariates or a filepath to a tab-delimited file with feature-specific covariates. It should be formatted with features as columns and samples as rows (or the transpose). The row names and column names should be the same as those of the `input_data`: the column and row names should be the feature names and sample names respectively.
- unscaled_abundance** A data frame with a single column of absolute abundances or a filepath to such a tab-delimited file. The row names should match the names of the samples in `input_data` and `input_metadata`. When using spike-ins, the single column should have the same name as one of the features in `input_data`, and the `unscaled_abundance` should correspond to the absolute quantity of the spike-in. When using total abundance scaling, the single column should have the name 'total', and the `unscaled_abundance` should correspond to the total abundance of each sample.

Value

A list containing the following items:

- (1) `data`: A data frame of feature abundances.
- (2) `metadata`: A data frame of metadata.
- (3) `feature_specific_covariate`: A data frame of feature specific covariates.
- (4) `unscaled_abundance`: A data frame of unscaled abundances.

Author(s)

William Nickols<willnickols@g.harvard.edu>,
Jacob Nearing<nearing@broadinstitute.org>,
Maintainers: Lauren McIver<lauren.j.mciver@gmail.com>,

Examples

```
# Read features table
taxa_table_name <- system.file("extdata", "HMP2_taxonomy.tsv", package =
"maaslin3")
taxa_table <- read.csv(taxa_table_name, sep = '\t')
```



```

# Read metadata table
metadata_name <- system.file("extdata", "HMP2_metadata.tsv", package =
"maaslin3")
metadata <- read.csv(metadata_name, sep = '\t')

metadata$diagnosis <-
  factor(metadata$diagnosis, levels = c('nonIBD', 'UC', 'CD'))
metadata$dysbiosis_state <-
  factor(metadata$dysbiosis_state, levels = c('none', 'dysbiosis_UC',
'dysbiosis_CD'))
metadata$antibiotics <-
  factor(metadata$antibiotics, levels = c('No', 'Yes'))

#Run MaAsLin3
maaslin3::maaslin_log_arguments(
  input_data = taxa_table,
  input_metadata = metadata,
  output = 'output',
  formula = '~ diagnosis + dysbiosis_state + antibiotics +
age + reads',
  plot_summary_plot = FALSE,
  plot_associations = FALSE)
read_data_list <- maaslin3::maaslin_read_data(
  taxa_table,
  metadata)

unlink('output', recursive=TRUE)
logging::logReset()

```

maaslin_reorder_data *Reorder the abundance data and metadata.*

Description

Reorder the abundance data and metadata to ensure samples are rows and remove any samples without abundances or metadata.

Usage

```

maaslin_reorder_data(data,
                     metadata,
                     feature_specific_covariate = NULL,
                     unscaled_abundance = NULL)

```

Arguments

data A data frame of feature abundances or read counts. It should be formatted with features as columns and samples as rows (or the transpose). The column and row names should be the feature names and sample names respectively.

metadata	A data frame of per-sample metadata. It should be formatted with variables as columns and samples as rows (or the transpose). The column and row names should be the variable names and sample names respectively.
feature_specific_covariate	A table of feature-specific covariates. It should be formatted with features as columns and samples as rows (or the transpose). The row names and column names should be the same as those of the <code>input_data</code> : the column and row names should be the feature names and sample names respectively.
unscaled_abundance	A data frame with a single column of absolute abundances. The row names should match the names of the samples in <code>input_data</code> and <code>input_metadata</code> . When using spike-ins, the single column should have the same name as one of the features in <code>input_data</code> , and the <code>unscaled_abundance</code> should correspond to the absolute quantity of the spike-in. When using total abundance scaling, the single column should have the name 'total', and the <code>unscaled_abundance</code> should correspond to the total abundance of each sample.

Value

A list containing the following items:

- (1) `data`: A data frame of feature abundances.
- (2) `metadata`: A data frame of metadata.
- (3) `feature_specific_covariate`: A data frame of feature specific covariates.
- (4) `unscaled_abundance`: A data frame of unscaled abundances.

Author(s)

William Nickols<willnickols@g.harvard.edu>,
 Jacob Nearing<nearing@broadinstitute.org>,
 Maintainers: Lauren McIver<lauren.j.mciver@gmail.com>,

Examples

```
# Read features table
taxa_table_name <- system.file("extdata", "HMP2_taxonomy.tsv", package =
"maaslin3")
taxa_table <- read.csv(taxa_table_name, sep = '\t')

# Read metadata table
metadata_name <- system.file("extdata", "HMP2_metadata.tsv", package =
"maaslin3")
metadata <- read.csv(metadata_name, sep = '\t')

metadata$diagnosis <-
  factor(metadata$diagnosis, levels = c('nonIBD', 'UC', 'CD'))
metadata$dysbiosis_state <-
  factor(metadata$dysbiosis_state, levels = c('none', 'dysbiosis_UC',
```

```

      'dysbiosis_CD'))
metadata$antibiotics <-
  factor(metadata$antibiotics, levels = c('No', 'Yes'))

#Run MaAsLin3
maaslin3::maaslin_log_arguments(
  input_data = taxa_table,
  input_metadata = metadata,
  output = 'output',
  formula = '~ diagnosis + dysbiosis_state + antibiotics +
  age + reads',
  plot_summary_plot = FALSE,
  plot_associations = FALSE)
read_data_list <- maaslin3::maaslin_read_data(
  taxa_table,
  metadata)
read_data_list <- maaslin3::maaslin_reorder_data(
  taxa_table,
  metadata)

unlink('output', recursive=TRUE)
logging::logReset()

```

maaslin_transform	<i>Transform abundance data for MaAsLin 3 modeling.</i>
-------------------	---

Description

Transform the abundance data according to the transform parameter.

Usage

```

maaslin_transform(filtered_data,
                  output,
                  transform = 'LOG')

```

Arguments

filtered_data	A data frame of filtered feature abundances. It should be formatted with features as columns and samples as rows. The column and row names should be the feature names and sample names respectively.
output	The output folder to write results.
transform	The transformation to apply to the features after normalization and before analysis. The option LOG (base 2) is recommended, but PLOG (pseudo-log) and NONE can also be used.

Value

A dataframe of transformed features (features are columns; samples are rows).

Author(s)

William Nickols<willnickols@g.harvard.edu>
 Jacob Nearing<nearing@broadinstitute.org>
 Maintainers: Lauren McIver<lauren.j.mciver@gmail.com>

Examples

```
# Read features table
taxa_table_name <- system.file("extdata", "HMP2_taxonomy.tsv", package =
"maaslin3")
taxa_table <- read.csv(taxa_table_name, sep = '\t')

# Read metadata table
metadata_name <- system.file("extdata", "HMP2_metadata.tsv", package =
"maaslin3")
metadata <- read.csv(metadata_name, sep = '\t')

metadata$diagnosis <-
  factor(metadata$diagnosis, levels = c('nonIBD', 'UC', 'CD'))
metadata$dysbiosis_state <-
  factor(metadata$dysbiosis_state, levels = c('none', 'dysbiosis_UC',
'dysbiosis_CD'))
metadata$antibiotics <-
  factor(metadata$antibiotics, levels = c('No', 'Yes'))

#Run MaAsLin3
maaslin3::maaslin_log_arguments(
  input_data = taxa_table,
  input_metadata = metadata,
  output = 'output',
  formula = '~ diagnosis + dysbiosis_state + antibiotics +
age + reads',
  plot_summary_plot = FALSE,
  plot_associations = FALSE)

read_data_list <- maaslin3::maaslin_read_data(
  taxa_table,
  metadata)
read_data_list <- maaslin3::maaslin_reorder_data(
  read_data_list$data,
  read_data_list$metadata)

data <- read_data_list$data
metadata <- read_data_list$metadata

formulas <- maaslin3::maaslin_check_formula(
  data,
  metadata,
  input_formula = '~ diagnosis + dysbiosis_state + antibiotics +
age + reads')
```

```
normalized_data = maaslin3::maaslin_normalize(data,
                                             output = 'output')

filtered_data = maaslin3::maaslin_filter(normalized_data,
                                         output = 'output')

transformed_data = maaslin3::maaslin_transform(filtered_data,
                                               output = 'output')

unlink('output', recursive=TRUE)
logging::logReset()
```

maaslin_write_results *Write the results from a MaAsLin 3 run.*

Description

Write the results from a MaAsLin 3 run to the output folder as a TSV.

Usage

```
maaslin_write_results(output,
                      fit_data_abundance,
                      fit_data_prevalence,
                      random_effects_formula = NULL,
                      max_significance = 0.1,
                      save_models = FALSE)
```

Arguments

output The output folder to write results.

fit_data_abundance
 The abundance outputs of [maaslin_fit](#).

fit_data_prevalence
 The prevalence outputs of [maaslin_fit](#).

random_effects_formula
 A formula in lme4 format as from [maaslin_check_formula](#).

max_significance
 The FDR corrected q-value threshold for significance used in selecting which associations to write as significant and to plot.

save_models Whether to return the fit models and save them to an RData file.

Value

Results will be written to the `all_results.tsv` and `significant_results.tsv` files in the folder output. The file `all_results.tsv` will contain all results in the `fit_data_abundance` and `fit_data_prevalence` items of the input list (with 'linear' and 'logistic' replaced by 'abundance' and 'prevalence' in the model column). The file `significant_results.tsv` will contain all results with joint or individual q-values below the 'max_significance' parameter and only 'NA' in the 'error' column of the results (the 'error' column is subsequently dropped). No value is returned.

Author(s)

William Nickols<willnickols@g.harvard.edu>
 Jacob Nearing<nearing@broadinstitute.org>
 Maintainers: Lauren McIver<lauren.j.mciver@gmail.com>

Examples

```
# Read features table
taxa_table_name <- system.file("extdata", "HMP2_taxonomy.tsv", package =
"maaslin3")
taxa_table <- read.csv(taxa_table_name, sep = '\t')

# Read metadata table
metadata_name <- system.file("extdata", "HMP2_metadata.tsv", package =
"maaslin3")
metadata <- read.csv(metadata_name, sep = '\t')

metadata$diagnosis <-
  factor(metadata$diagnosis, levels = c('nonIBD', 'UC', 'CD'))
metadata$dysbiosis_state <-
  factor(metadata$dysbiosis_state, levels = c('none', 'dysbiosis_UC',
'dysbiosis_CD'))
metadata$antibiotics <-
  factor(metadata$antibiotics, levels = c('No', 'Yes'))

#Run MaASLin3
maaslin3::maaslin_log_arguments(
  input_data = taxa_table,
  input_metadata = metadata,
  output = 'output',
  formula = '~ diagnosis + dysbiosis_state + antibiotics +
age + reads',
  plot_summary_plot = FALSE,
  plot_associations = FALSE)

read_data_list <- maaslin3::maaslin_read_data(
  taxa_table,
  metadata)
read_data_list <- maaslin3::maaslin_reorder_data(
  read_data_list$data,
  read_data_list$metadata)
```

```

data <- read_data_list$data
metadata <- read_data_list$metadata

formulas <- maaslin3::maaslin_check_formula(
  data,
  metadata,
  input_formula = '~ diagnosis + dysbiosis_state + antibiotics +
age + reads')

formula <- formulas$formula
random_effects_formula <- formulas$random_effects_formula

normalized_data = maaslin3::maaslin_normalize(data,
                                             output = 'output')

filtered_data = maaslin3::maaslin_filter(normalized_data,
                                         output = 'output')

transformed_data = maaslin3::maaslin_transform(filtered_data,
                                              output = 'output')

standardized_metadata = maaslin3::maaslin_process_metadata(
  metadata,
  formula = formula)

maaslin_results = maaslin3::maaslin_fit(
  filtered_data,
  transformed_data,
  standardized_metadata,
  formula,
  random_effects_formula,
  warn_prevalence = FALSE)

maaslin3::maaslin_write_results(
  output = 'output',
  maaslin_results$fit_data_abundance,
  maaslin_results$fit_data_prevalence,
  random_effects_formula)

unlink('output', recursive=TRUE)
logging::logReset()

```

```
maaslin_write_results_lefse_format
```

Write the results from a MaAsLin 3 run in LEfSe format.

Description

Write the results from a MaAsLin 3 run to the output folder in LEfSe format.

Usage

```
maaslin_write_results_lefse_format(output,  
                                  fit_data_abundance,  
                                  fit_data_prevalence)
```

Arguments

`output` The output folder to write results.
`fit_data_abundance`
 The abundance outputs of [maaslin_fit](#).
`fit_data_prevalence`
 The prevalence outputs of [maaslin_fit](#).

Value

Results will be written to the `lefse_style_results_abundance.res` file in the folder `output`.
No value is returned.

Author(s)

William Nickols<willnickols@g.harvard.edu>,
Jacob Nearing<nearing@broadinstitute.org>,
Maintainers: Lauren McIver<lauren.j.mciver@gmail.com>,

Examples

```
# Read features table  
taxa_table_name <- system.file("extdata", "HMP2_taxonomy.tsv", package =  
"maaslin3")  
taxa_table <- read.csv(taxa_table_name, sep = '\t')  
  
# Read metadata table  
metadata_name <- system.file("extdata", "HMP2_metadata.tsv", package =  
"maaslin3")  
metadata <- read.csv(metadata_name, sep = '\t')  
  
metadata$diagnosis <-  
  factor(metadata$diagnosis, levels = c('nonIBD', 'UC', 'CD'))  
metadata$dysbiosis_state <-  
  factor(metadata$dysbiosis_state, levels = c('none', 'dysbiosis_UC',  
  'dysbiosis_CD'))  
metadata$antibiotics <-  
  factor(metadata$antibiotics, levels = c('No', 'Yes'))  
  
#Run MaASLin3  
maaslin3::maaslin_log_arguments(  
  input_data = taxa_table,  
  input_metadata = metadata,  
  output = 'output',
```



```
    formula = '~ diagnosis + dysbiosis_state + antibiotics +
    age + reads',
    plot_summary_plot = FALSE,
    plot_associations = FALSE)

read_data_list <- maaslin3::maaslin_read_data(
  taxa_table,
  metadata)
read_data_list <- maaslin3::maaslin_reorder_data(
  read_data_list$data,
  read_data_list$metadata)

data <- read_data_list$data
metadata <- read_data_list$metadata

formulas <- maaslin3::maaslin_check_formula(
  data,
  metadata,
  input_formula = '~ diagnosis + dysbiosis_state + antibiotics +
  age + reads')

formula <- formulas$formula
random_effects_formula <- formulas$random_effects_formula

normalized_data = maaslin3::maaslin_normalize(data,
  output = 'output')

filtered_data = maaslin3::maaslin_filter(normalized_data,
  output = 'output')

transformed_data = maaslin3::maaslin_transform(filtered_data,
  output = 'output')

standardized_metadata = maaslin3::maaslin_process_metadata(
  metadata,
  formula = formula)

maaslin_results = maaslin3::maaslin_fit(
  filtered_data,
  transformed_data,
  standardized_metadata,
  formula,
  random_effects_formula,
  warn_prevalence = FALSE)

maaslin3::maaslin_write_results_lefse_format(
  output = 'output',
  maaslin_results$fit_data_abundance,
  maaslin_results$fit_data_prevalence)

unlink('output', recursive=TRUE)
logging::logReset()
```

preprocess_dna_mtx *Pre-process the DNA covariates for metatranscriptomics*

Description

Pre-process the DNA covariates for metatranscriptomics by total-sum-scaling DNA abundances per sample and then, for each sample in each feature:

1. Log 2 transforming the DNA abundance if the DNA abundance is ≥ 0
2. Setting the DNA abundance to $\log_2(\text{[minimum non-zero relative abundance in the dataset]} / 2)$ if the corresponding RNA abundance is non-zero but the DNA abundance is zero
3. Setting the DNA abundance to NA if both are zero

When the DNA is present, the RNA data can be modeled as usual in MaAsLin 3 with $\log_2(\text{DNA})$ as a covariate. When the DNA is not present, if the RNA is present, we assume the DNA was missed due to finite read depth, so the DNA abundance is imputed with a small pseudo-count. When neither the DNA nor RNA is present, we assume the gene/microbe was not in the sample and therefore no information about the transcription level can be obtained. Setting the DNA covariate to NA has the effect of dropping the sample when fitting the relevant feature's model in MaAsLin 3. Unlike most MaAsLin functions that will infer the samples from the row names and column names, **the rna_table must be formatted as samples (rows) by features (columns)**.

Usage

```
preprocess_dna_mtx(dna_table, rna_table)
```

Arguments

<code>dna_table</code>	The samples (rows) by features (columns) data frame of DNA or taxon abundances to preprocess. These can be relative abundances or counts.
<code>rna_table</code>	The samples (rows) by features (columns) data frame of RNA to preprocess. These can be relative abundances or counts.

Value

A list containing the following named items:

1. `dna_table`: The table of \log_2 transformed DNA relative abundances with NAs for any feature-sample pairs for which both the DNA and RNA abundances were 0.
2. `rna_table`: The table of total sum scaled RNA abundances. These are not \log_2 transformed.

Author(s)

William Nickols<willnickols@g.harvard.edu>,
Jacob Nearing<nearing@broadinstitute.org>,
Maintainers: Lauren McIver<lauren.j.mciver@gmail.com>,

Examples

```
mgx_in <- data.frame('a' = c(1, 2, 0, 4, 5),  
                    'b' = c(2, 3, 4, 5, 6),  
                    'c' = c(3, 4, 5, 6, 0))  
rownames(mgx_in) <- paste0("sample", c(1:5))  
  
mtx_in <- data.frame('a' = c(1, 2, 3, 4, 5),  
                    'b' = c(2, 3, 4, 5, 0),  
                    'c' = c(3, 4, 5, 6, 0))  
rownames(mtx_in) <- paste0("sample", c(1:5))  
  
preprocess_out <- preprocess_dna_mtx(mgx_in, mtx_in)
```

Index

maaslin3, [2](#)
maaslin_check_arguments, [7](#)
maaslin_check_formula, [10](#), [19](#), [45](#)
maaslin_compute_formula, [11](#)
maaslin_contrast_test, [14](#)
maaslin_filter, [16](#)
maaslin_fit, [6](#), [14](#), [18](#), [30](#), [45](#), [48](#)
maaslin_log_arguments, [22](#)
maaslin_normalize, [27](#)
maaslin_plot_results, [29](#)
maaslin_plot_results_from_output, [33](#)
maaslin_process_metadata, [37](#)
maaslin_read_data, [39](#)
maaslin_reorder_data, [41](#)
maaslin_transform, [43](#)
maaslin_write_results, [45](#)
maaslin_write_results_lefse_format, [47](#)

preprocess_dna_mtx, [50](#)