

# Package ‘HS’

October 12, 2022

**Type** Package

**Title** Homogenous Segmentation for Spatial Lines Data

**Date** 2019-08-31

**Version** 1.1

**Maintainer** Yongze Song <yongze.song@postgrad.curtin.edu.au>

**Description** Methods of homogenous segmentation for spatial lines data, such as pavement performance indicators and traffic volumes. Three methods are available for homogenous segmentation, including cumulative difference approach, minimization coefficient of variation, and spatial heterogeneity based method.

**Imports** zoo, ggpubr, data.table, tidyr, reshape2, ggplot2, partitions, utils

**Depends** R (>= 3.4.0)

**License** GPL-2

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 6.0.1

**NeedsCompilation** no

**Author** Yongze Song [aut, cre] (<<https://orcid.org/0000-0003-3420-9622>>)

**Repository** CRAN

**Date/Publication** 2019-09-10 04:40:03 UTC

## R topics documented:

cda . . . . .	2
deflection . . . . .	3
findbreak . . . . .	3
hs . . . . .	4
hsctg . . . . .	5
mcv . . . . .	5
preprocessing . . . . .	6
segbycategory . . . . .	7

segcompare . . . . .	7
segid.matrix . . . . .	8
segplot . . . . .	9
segsmooth . . . . .	9
segsummary . . . . .	10
shs . . . . .	11
splitlong . . . . .	12
tsdwa . . . . .	12

<b>Index</b>	<b>14</b>
--------------	-----------

---

cda	<i>Cummulative difference approach (CDA) for homogeneous segmentation of spatial lines data.</i>
-----	--

---

### Description

Function for homogeneous segmentation of spatial lines data using a cummulative difference approach (CDA).

### Usage

```
cda(var = "deflection", length = "length", data, range = NULL)
```

### Arguments

var	A character or a character vector of variable names, such as a road pavement performance indicator.
length	A character of road length name in data.
data	A data frame of a dataset.
range	A vector of length threshold.

### Examples

```
testdata <- tsdwa[1:100,]
testdata$Length <- testdata$SLK.end - testdata$SLK.start
testdata <- cda(var = "Deflection", length = "Length", testdata)
```

---

deflection	<i>Road deflection dataset.</i>
------------	---------------------------------

---

**Description**

The "deflection" dataset is a sample of the road deflection data monitored and collected by Main Roads Western Australia.

**Usage**

```
deflection
```

**Format**

deflection: A data frame with 1000 rows and 4 variables.

- id. Number of observation.
- SLK.start. Spatial start location of data. SLK is short for the straight line kilometer.
- SLK.end. Spatial end location of data.
- Deflection. The monitored road deflection value.

**Author(s)**

Yongze Song <yongze.song@postgrad.curtin.edu.au>

---

findbreak	<i>Find spaital breaking locations and add a column of breaks.</i>
-----------	--

---

**Description**

Find spaital breaking locations and add a column of breaks.

**Usage**

```
findbreak(start = "SLK.start", end = "SLK.end", data,
          dist.allow = 0.05, line.no = NULL)
```

**Arguments**

start	A character of start location name of a spatial line.
end	A character of end location name of a spatial line.
data	A data frame of a dataset.
dist.allow	A number of the maximum allowed breaks within a line segment.
line.no	A character of spatial line name.

**Examples**

```
testdata <- tsdwa[1:100,]
testdata <- findbreak(start = "SLK.start", end = "SLK.end",
                      data = testdata, dist.allow = 0.05)
```

---

hs *Homogeneous segmentation function with continuous variables.*

---

**Description**

Homogeneous segmentation function with continuous variables.

**Usage**

```
hs(start = "SLK.start", end = "SLK.end", var = "deflection",
    data, method = "shs", range = NULL)
```

**Arguments**

start	A character of start location name of a spatial line.
end	A character of end location name of a spatial line.
var	A character or a character vector of variable names, such as a road pavement performance indicator.
data	A data frame of a dataset.
method	A character of homogeneous segmentation method. Available methods include "shs", "cda" and "mcv".
range	A vector of segment length threshold.

**Examples**

```
testdata <- tsdwa[1:100,]
hs1 <- hs(start = "SLK.start", end = "SLK.end", var = c("Curvature", "Deflection", "BLI"),
          testdata, method = "shs", range = c(0.1, 0.5))
```

---

hsctg	<i>Homogeneous segmentation function with both categorical and continuous variables.</i>
-------	--

---

**Description**

Homogeneous segmentation function with both categorical and continuous variables.

**Usage**

```
hsctg(start = "SLK.start", end = "SLK.end", var = "deflection",
      data, method = "shs", range = NULL, by.ctg = NULL)
```

**Arguments**

start	A character of start location name of a spatial line.
end	A character of end location name of a spatial line.
var	A character or a character vector of variable names, such as a road pavement performance indicator.
data	A data frame of a dataset.
method	A character of homogeneous segmentation method. Available methods include "shs", "cda" and "mcv".
range	A vector of segment length threshold.
by.ctg	A vector of categorical variable names.

**Examples**

```
testdata <- tsdwa[1:300,]
hc1 <- hsctg(start = "SLK.start", end = "SLK.end", var = c("Curvature", "Deflection", "BLI"),
            testdata, method = "shs", range = c(0.1, 0.5), by.ctg = c("SurfType", "PvtType"))
```

---

mcv	<i>Minimization coefficient of variation (MCV) for homogeneous segmentation of spatial lines data.</i>
-----	--

---

**Description**

Minimization coefficient of variation (MCV) for homogeneous segmentation of spatial lines data.

**Usage**

```
mcv(var = "deflection", length = "length", data, range = NULL)
```

**Arguments**

var	A character or a character vector of variable names, such as a road pavement performance indicator.
length	A character of road length name in data.
data	A data frame of a dataset.
range	A vector of segment length threshold.

**Examples**

```
testdata <- tsdwa[1:100,]
testdata$length <- testdata$SLK.end - testdata$SLK.start
testdata <- mcv(var = "Deflection", length = "length", testdata, range = c(0.1, 0.5))
```

---

preprocessing

*Preprocessing for field monitoring data.*


---

**Description**

The preprocessing includes two steps: removing missing data and ordering data by spatial locations.

**Usage**

```
preprocessing(var = "deflection", location = "SLK", data = data)
```

**Arguments**

var	A character of the name of a variable in a dataset, such as a road pavement performance indicator.
location	A character of the name of spatial locations in a dataset.
data	A data frame of monitoring data.

**Examples**

```
testdata <- tsdwa[1:100,]
testdata <- preprocessing(var = "Deflection", location = "SLK.start", data = testdata)
```

---

segbycategory	<i>Segmentation with categorical variables.</i>
---------------	---

---

**Description**

Segmentation with categorical variables.

**Usage**

```
segbycategory(data, by = NULL)
```

**Arguments**

data	A data frame of a dataset.
by	A character or a vector of categorical variable names.

**Examples**

```
testdata <- tsdwa[1:100,]  
testdata <- segbycategory(testdata, by = c("SurfType", "PvtType"))
```

---

segcompare	<i>Segments comparison of different homogeneous segmentations methods.</i>
------------	--

---

**Description**

Segments comparison of different homogeneous segmentations methods.

**Usage**

```
segcompare(start = "SLK.start", end = "SLK.end", var = "deflection",  
           data, segid.matrix, methods = NULL)  
## S3 method for class 'segcompare'  
print(x, ...)  
## S3 method for class 'segcompare'  
plot(x, ...)
```

**Arguments**

start	A character of start location name of a spatial line.
end	A character of end location name of a spatial line.
var	A character or a character vector of variable names, such as a road pavement performance indicator.
data	A list of segmentation result.
segid.matrix	A matrix of segmentations.
methods	A vector of segmentation method names, default NULL.
x	A list of segments comparison result.
...	Ignore

**Examples**

```
testdata <- tsdwa[1:300, ]
testdata$length <- testdata$SLK.end - testdata$SLK.start
variable <- c("Curvature", "Deflection", "BLI")

seg1 <- hs(start = "SLK.start", end = "SLK.end", var = variable,
           testdata, method = "shs", range = c(0.1, 0.5)) # 0.3 s
seg2 <- hs(start = "SLK.start", end = "SLK.end", var = variable,
           testdata, method = "cda", range = c(0.1, 0.5)) # 0.7 s
seg3 <- hs(start = "SLK.start", end = "SLK.end", var = variable,
           testdata, method = "mcv", range = c(0.1, 0.5)) # 0.6 s
segid.matrix <- cbind(seg1$seg.id, seg2$seg.id, seg3$seg.id)

data(segid.matrix)
cp <- segcompare(start = "SLK.start", end = "SLK.end", var = variable,
                 testdata, segid.matrix, methods = c("SHS", "CDA", "MCV")) # 4.8 s
cp
plot(cp)
```

---

segid.matrix                      *A matrix of segmentations with different methods for data "tsdwa".*

---

**Description**

Segmentation results of CDA, MCV and SHS methods for data "tsdwa".

**Usage**

```
segid.matrix
```

**Format**

segid.matrix: A matrix with 300 rows and 3 columns, representing segmentations of three methods, CDA, MCV and SHS.



**Author(s)**

Yongze Song <yongze.song@postgrad.curtin.edu.au>

---

segplot                      *Visualization of homogeneous segments.*

---

**Description**

Visualization of homogeneous segments.

**Usage**

```
segplot(start = "SLK.start", var = "deflection",
        seg.id = "seg.id", data, plot.range = NULL)
```

**Arguments**

start	A character of start location name of a spatial line.
var	A character or a character vector of variable names, such as a road pavement performance indicator.
seg.id	A character of the name of new segment number.
data	A data frame of a dataset.
plot.range	A vector of plot range.

**Examples**

```
testdata <- tsdwa[1:300,]
testdata$length <- testdata$SLK.end - testdata$SLK.start
testdata <- shs(var = c("Curvature", "Deflection"), length = "length",
               testdata, range = c(0.1, 0.5))
segplot(start = "SLK.start", var = c("Curvature", "Deflection"),
        seg.id = "seg.id", testdata, plot.range = 1:300)
```

---

segsmooth                      *Smoothing data using the moving average method for the homogeneous segmentation.*

---

**Description**

A center aligned moving window is used for the moving average method.

**Usage**

```
segsmooth(var = "deflection", range = 11, data)
```

**Arguments**

var	A character of the name of a variable in a dataset, such as a road pavement performance indicator.
range	A number of the size of moving window. An odd number is required.
data	A data frame of monitoring data.

**Examples**

```
# preprocessing
testdata <- tsdwa[1:500,]
testdata <- preprocessing(var = "Deflection", location = "SLK.start", data = testdata)
# smoothing
testdata <- segsmooth(var = "Deflection", range = 11, data = testdata)
# plot
plot(testdata$SLK.start, testdata$Deflection, type = "l",
      col = "lightblue", xlab = "location", ylab = "deflection")
lines(testdata$SLK.start, testdata$smooth.Deflection)
```

---

 segsummary

*Statistical summary of homogeneous segments.*


---

**Description**

Statistical summary of homogeneous segments.

**Usage**

```
segsummary(start = "SLK.start", end = "SLK.end", var = "deflection",
           seg.id = "seg.id", data, by.ctg = NULL)
## S3 method for class 'segsummary'
print(x, ...)
```

**Arguments**

start	A character of start location name of a spatial line.
end	A character of end location name of a spatial line.
var	A character or a character vector of variable names, such as a road pavement performance indicator.
seg.id	A character of the name of new segment number.
data	A data frame of a dataset.
by.ctg	A character of categorical variable names.
x	A list of segmentation result.
...	Ignore

**Examples**

```

testdata <- tsdwa[1:100,]
testdata$length <- testdata$SLK.end - testdata$SLK.start
testdata <- shs(var = c("Curvature", "Deflection"), length = "length",
               testdata, range = c(0.1, 0.5))
s1 <- segsummary(start = "SLK.start", end = "SLK.end", var = c("Curvature", "Deflection"),
                seg.id = "seg.id", testdata)
s1

```

---

shs	<i>Spatial heterogeneity-based segmentation (SHS) for homogeneous segmentation of spatial lines data.</i>
-----	---

---

**Description**

Spatial heterogeneity-based segmentation (SHS) for homogeneous segmentation of spatial lines data.

**Usage**

```
shs(var = "deflection", length = "length", data, range = NULL)
```

**Arguments**

var	A character or a character vector of variable names, such as a road pavement performance indicator.
length	A character of road length name in data.
data	A data frame of a dataset.
range	A vector of segment length threshold.

**Examples**

```

testdata <- tsdwa[1:100,]
testdata$length <- testdata$SLK.end - testdata$SLK.start
testdata <- shs(var = "Deflection", length = "length", testdata, range = c(0.1, 0.5))

```

---

splitlong	<i>Split long segments to segments within length threshold.</i>
-----------	---

---

**Description**

Split long segments to segments within length threshold.

**Usage**

```
splitlong(var = "deflection", length = "length",
          seg.id = "seg.id", data, range = NULL)
```

**Arguments**

var	A character or a character vector of variable names, such as a road pavement performance indicator.
length	A character of length name.
seg.id	A character of the name of new segment number.
data	A data frame of a dataset.
range	A vector of segment length threshold.

**Examples**

```
testdata <- tsdwa[1:1000,]
testdata$length <- round(testdata$SLK.end - testdata$SLK.start, digits = 10)
testdata <- cda(var = "Deflection", length = "length", testdata, range = c(0.1, 0.5))
testdata <- splitlong(var = "Deflection", length = "length",
                     seg.id = "seg.id", testdata, range = c(0.1, 0.5))
seglength.summary <- testdata[, .(sum(length)), by = .(seg.id)]
```

---

tsdwa	<i>Traffic speed deflectometer (TSD) data of pavement deteriorations.</i>
-------	---

---

**Description**

The "tsdwa" dataset is a sample of the pavement deterioration data monitored and collected by Main Roads Western Australia.

**Usage**

```
tsdwa
```

**Format**

*tsdwa*: A data frame with 5000 rows and 8 variables.

- *id*. Number of observation.
- *SLK.start*. Spatial start location of data. SLK is short for the straight line kilometer.
- *SLK.end*. Spatial end location of data.
- *SurfType*. Surfacing type.
- *PvtType*. Pavement type.
- *Curvature*.
- *Deflection*.
- *BLI*. Base layer index.

**Author(s)**

Yongze Song <yongze.song@postgrad.curtin.edu.au>

# Index

- \* **TSD**
  - tsdwa, 12
- \* **dataset**
  - deflection, 3
  - segid.matrix, 8
  - tsdwa, 12
- \* **deflection**
  - deflection, 3
- \* **segmentations**
  - segid.matrix, 8

cda, 2

deflection, 3

findbreak, 3

hs, 4

hsctg, 5

mcv, 5

plot.segcompare (segcompare), 7

preprocessing, 6

print.segcompare (segcompare), 7

print.segsummary (segsummary), 10

segbycategory, 7

segcompare, 7

segid.matrix, 8

segplot, 9

segsmooth, 9

segsummary, 10

shs, 11

splitlong, 12

tsdwa, 12