

Package ‘PolyTree’

March 25, 2024

Title Estimate Causal Polytree from Data

Version 0.0.1

Maintainer Sourav Chatterjee <souravc@stanford.edu>

Description Given a data matrix with rows representing data vectors and columns representing variables, produces a directed polytree for the underlying causal structure. Based on the algorithm developed in Chatterjee and Vidyasagar (2022) <[arxiv:2209.07028](https://arxiv.org/abs/2209.07028)>. The method is fully nonparametric, making no use of linearity assumptions, and especially useful when the number of variables is large.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.1

Imports FOCI, igraph

NeedsCompilation no

Author Sourav Chatterjee [aut, cre] (<<https://orcid.org/0000-0003-4460-209X>>)

Repository CRAN

Date/Publication 2024-03-25 19:10:12 UTC

R topics documented:

condeptree	2
outgoing	2
polytree	3
xicorln	3
Index	5

condeptree	<i>This is the function that computes the skeleton tree from data. The input is a matrix x whose rows are the data vectors. The sample size n is the number of rows. The number of variables p is the number of columns The function outputs the skeleton tree g.</i>
------------	---

Description

This is the function that computes the skeleton tree from data. The input is a matrix x whose rows are the data vectors. The sample size n is the number of rows. The number of variables p is the number of columns The function outputs the skeleton tree g .

Usage

```
condeptree(x)
```

Arguments

x	The input data matrix.
-----	------------------------

outgoing	<i>Creates an outgoing tree from a given undirected tree.</i>
----------	---

Description

Creates an outgoing tree from a given undirected tree.

Usage

```
outgoing(tree, dir_tree = NULL, a = NULL, b = 1)
```

Arguments

tree	Input tree, undirected.
dir_tree	Directionalities that must be present.
a	The node being inspected.
b	The neighbor being inspected.

polytree

Causal Polytree Estimation

Description

Estimates directed causal polytree from data, using algorithm developed in Chatterjee and Vidyasagar (2022).

Usage

```
polytree(x)
```

Arguments

`x` Data matrix, whose rows are i.i.d. data vectors generated from the model.

Value

A directed polytree estimated from the input data, as an igraph object.

References

Sourav Chatterjee and Mathukumalli Vidyasagar (2022). Estimating large causal polytrees from small samples. Available at <https://arxiv.org/abs/2209.07028>

Examples

```
p <- 10
n <- 200
x <- matrix(nrow = n, ncol = p)
for (i in 1:n) {
  x[i,1] = rnorm(1)
  for (j in 2:p) {
    x[i,j] = (x[i,j-1] + rnorm(1))/sqrt(2)
  }
}
p <- polytree(x)
```

xicorln

This function computes the xi correlation coefficient.

Description

This function computes the xi correlation coefficient.

Usage`xicorln(xvec, yvec)`**Arguments**

<code>xvec</code>	The vector of x values.
<code>yvec</code>	The vector of y values.

Index

condeptree, 2

outgoing, 2

polytree, 3

xicorln, 3