

Package ‘microeco’

May 23, 2024

Type Package

Title Microbial Community Ecology Data Analysis

Version 1.7.1

Author Chi Liu [aut, cre],
Felipe R. P. Mansoldo [ctb],
Minjie Yao [ctb],
Xiangzhen Li [ctb]

Maintainer Chi Liu <liuchi0426@126.com>

Description A series of statistical and plotting approaches in microbial community ecology based on the R6 class. The classes are designed for data preprocessing, taxa abundance plotting, alpha diversity analysis, beta diversity analysis, differential abundance test, null model analysis, network analysis, machine learning, environmental data analysis and functional analysis.

URL <https://github.com/ChiLiubio/microeco>

Depends R (>= 3.5.0)

Imports R6, stats, ape, vegan, rlang, data.table, magrittr, dplyr,
tibble, scales, grid, ggplot2 (>= 3.5.0), RColorBrewer,
reshape2, igraph

Suggests GUniFrac, MASS, ggpubr, randomForest, ggdendro, ggrepel,
agricolae, gridExtra, picante, pheatmap, rgexf, mice, GGally

License GPL-3

LazyData true

Encoding UTF-8

NeedsCompilation no

Repository CRAN

Date/Publication 2024-05-23 06:20:02 UTC

RoxygenNote 7.3.1

R topics documented:

clone	2
dataset	3
dropallfactors	4
env_data_16S	4
fungi_func_FungalTraits	5
fungi_func_FUNGuild	5
microeco	5
microtable	6
otu_table_16S	17
otu_table_ITS	18
phylo_tree_16S	18
prok_func_FAPROTAX	18
prok_func_NJC19_list	19
sample_info_16S	19
sample_info_ITS	19
Tax4Fun2_KEGG	19
taxonomy_table_16S	20
taxonomy_table_ITS	20
tidy_taxonomy	20
trans_abund	21
trans_alpha	32
trans_beta	37
trans_classifier	46
trans_diff	54
trans_env	64
trans_func	79
trans_network	86
trans_norm	102
trans_nullmodel	106
trans_venn	116
Index	121

clone	<i>Copy an R6 class object</i>
-------	--------------------------------

Description

Copy an R6 class object

Usage

```
clone(x, deep = TRUE)
```

Arguments

x	R6 class object
deep	default TRUE; TRUE means deep copy, i.e. copied object is unlinked with the original one.

Value

identical but unlinked R6 object

Examples

```
data("dataset")
clone(dataset)
```

dataset	<i>The dataset structured with microtable class for the demonstration of examples</i>
---------	---

Description

The dataset arose from 16S rRNA gene amplicon sequencing of wetland soils in China <doi:10.1016/j.geoderma.2018.09.035>. In `dataset$sample_table`, the 'Group' column means Chinese inland wetlands (IW), coastal wetland (CW) and Tibet plateau wetlands (TW). The column 'Type' denotes the sampling region: northeastern region (NE), northwest region (NW), North China area (NC), middle-lower reaches of the Yangtze River (YML), southern coastal area (SC), upper reaches of the Yangtze River (YU) and Qinghai-Tibet Plateau (QTP). The column 'Saline' represents the saline soils and non-saline soils.

Usage

```
data(dataset)
```

Format

An R6 class object

Details

- `sample_table`: sample information table
- `otu_table`: species-community abundance table
- `tax_table`: taxonomic table
- `phylo_tree`: phylogenetic tree
- `taxa_abund`: taxa abundance list with several tables for Phylum...Genus
- `alpha_diversity`: alpha diversity table
- `beta_diversity`: list with several beta diversity distance matrix

dropallfactors *Remove all factors in a data frame*

Description

Remove all factors in a data frame

Usage

```
dropallfactors(x, unfac2num = FALSE, char2num = FALSE)
```

Arguments

x	data frame
unfac2num	default FALSE; whether try to convert all character columns to numeric; if FALSE, only try to convert column with factor attribute. Note that this can only transform the columns that may be transformed to numeric without using factor.
char2num	default FALSE; whether force all the character to be numeric class by using factor as an intermediate.

Value

data frame without factor

Examples

```
data("taxonomy_table_16S")
taxonomy_table_16S[, 1] <- as.factor(taxonomy_table_16S[, 1])
str(dropallfactors(taxonomy_table_16S))
```

env_data_16S *The environmental factors for the 16S example data*

Description

The environmental factors for the 16S example data

Usage

```
data(env_data_16S)
```

 fungi_func_FungalTraits

The FungalTraits database for fungi trait prediction

Description

The FungalTraits database for fungi trait prediction

Usage

```
data(fungi_func_FungalTraits)
```

fungi_func_FUNGuild

The FUNGuild database for fungi trait prediction

Description

The FUNGuild database for fungi trait prediction

Usage

```
data(fungi_func_FUNGuild)
```

microeco

*Introduction to microeco package
([Rhrefhttps://github.com/ChiLiubio/microeco](https://github.com/ChiLiubio/microeco)<https://github.com/ChiLiubio/microeco>)*

Description

For the detailed tutorial on microeco package, please follow the links:

Online tutorial website: https://chiliubio.github.io/microeco_tutorial/

Download tutorial: https://github.com/ChiLiubio/microeco_tutorial/releases

For each R6 class, please open the help document by searching the class name. For example, to search microtable class, please run the command `help(microtable)` or `?microtable`.

Another way to open the help document of R6 class is to click the following links collected:

[microtable](#)

[trans_abund](#)

[trans_venn](#)

[trans_alpha](#)

[trans_beta](#)

[trans_diff](#)

[trans_network](#)

[trans_nullmodel](#)

```
trans_classifier
trans_env
trans_func
trans_norm
```

To report bugs or discuss questions, please use Github Issues (<https://github.com/ChiLiubio/microeco/issues>). Before creating a new issue, please read the guideline (https://chiliubio.github.io/microeco_tutorial/notes.html#github-issues).

To cite microeco package in publications, please run the following command to get the reference:

```
citation("microeco")
```

To read the paper, please turn to the publication website (<https://academic.oup.com/femsec/article/97/2/fiaa255/6041020>).

Reference:

Chi Liu, Yaoming Cui, Xiangzhen Li and Minjie Yao. 2021. microeco: an R package for data mining in microbial community ecology. FEMS Microbiology Ecology, 97(2): fiaa255. DOI:10.1093/femsec/fiaa255

microtable

Create microtable object to store and manage all the basic files.

Description

This class is a wrapper for a series of operations on the input files and basic manipulations, including microtable object creation, data trimming, data filtering, rarefaction based on Paul et al. (2013) <doi:10.1371/journal.pone.0061217>, taxonomic abundance calculation, alpha and beta diversity calculation based on the An et al. (2019) <doi:10.1016/j.geoderma.2018.09.035> and Lozupone et al. (2005) <doi:10.1128/AEM.71.12.8228-8235.2005> and other basic operations.

Online tutorial: https://chiliubio.github.io/microeco_tutorial/

Download tutorial: https://github.com/ChiLiubio/microeco_tutorial/releases

Format

microtable.

Methods

Public methods:

- `microtable$new()`
- `microtable$filter_pollution()`
- `microtable$filter_taxa()`
- `microtable$rarefy_samples()`
- `microtable$tidy_dataset()`
- `microtable$add_rownames2taxonomy()`
- `microtable$sample_sums()`
- `microtable$taxa_sums()`
- `microtable$sample_names()`

- `microtable$taxa_names()`
- `microtable$rename_taxa()`
- `microtable$merge_samples()`
- `microtable$merge_taxa()`
- `microtable$save_table()`
- `microtable$cal_abund()`
- `microtable$save_abund()`
- `microtable$cal_alphadiv()`
- `microtable$save_alphadiv()`
- `microtable$cal_betadiv()`
- `microtable$save_betadiv()`
- `microtable$print()`
- `microtable$clone()`

Method `new()`:

Usage:

```
microtable$new(
  otu_table,
  sample_table = NULL,
  tax_table = NULL,
  phylo_tree = NULL,
  rep_fasta = NULL,
  auto_tidy = FALSE
)
```

Arguments:

`otu_table` `data.frame`; The feature abundance table; rownames are features (e.g. OTUs/ASVs/species/genes); column names are samples.

`sample_table` `data.frame`; default `NULL`; The sample information table; rownames are samples; columns are sample metadata; If not provided, the function can generate a table automatically according to the sample names in `otu_table`.

`tax_table` `data.frame`; default `NULL`; The taxonomic information table; rownames are features; column names are taxonomic classes.

`phylo_tree` `phylo`; default `NULL`; The phylogenetic tree; use `read.tree` function in `ape` package for input.

`rep_fasta` `DNASTringSet` or `list` format; default `NULL`; The representative sequences; use `read.fasta` function in `seqinr` package or `readDNASTringSet` function in `Biostrings` package for input.

`auto_tidy` default `FALSE`; Whether trim the files in the `microtable` object automatically; If `TRUE`, running the functions in `microtable` class can invoke the `tidy_dataset` function automatically.

Returns: an object of class `microtable` with the following components:

`sample_table` The sample information table.

`otu_table` The feature table.

`tax_table` The taxonomic table.

phylo_tree The phylogenetic tree.
 rep_fasta The representative sequence.
 taxa_abund default NULL; use cal_abund function to calculate.
 alpha_diversity default NULL; use cal_alphadiv function to calculate.
 beta_diversity default NULL; use cal_betadiv function to calculate.

Examples:

```

data(otu_table_16S)
data(taxonomy_table_16S)
data(sample_info_16S)
data(phylo_tree_16S)
m1 <- microtable$new(otu_table = otu_table_16S)
m1 <- microtable$new(sample_table = sample_info_16S, otu_table = otu_table_16S,
  tax_table = taxonomy_table_16S, phylo_tree = phylo_tree_16S)
# trim the files in the dataset
m1$tidy_dataset()

```

Method filter_pollution(): Filter the features considered pollution in microtable\$tax_table. This operation will remove any line of the microtable\$tax_table containing any the word in taxa parameter regardless of word case.

Usage:

```
microtable$filter_pollution(taxa = c("mitochondria", "chloroplast"))
```

Arguments:

taxa default c("mitochondria", "chloroplast"); filter mitochondria and chloroplast, or others as needed.

Returns: None

Examples:

```
m1$filter_pollution(taxa = c("mitochondria", "chloroplast"))
```

Method filter_taxa(): Filter the feature with low abundance and/or low occurrence frequency.

Usage:

```
microtable$filter_taxa(rel_abund = 0, freq = 1, include_lowest = TRUE)
```

Arguments:

rel_abund default 0; the relative abundance threshold, such as 0.0001.

freq default 1; the occurrence frequency threshold. For example, the number 2 represents filtering the feature that occurs less than 2 times. A number smaller than 1 is also allowable. For instance, the number 0.1 represents filtering the feature that occurs in less than 10% samples.

include_lowest default TRUE; whether include the feature with the threshold.

Returns: None

Examples:

```

\donttest{
d1 <- clone(m1)
d1$filter_taxa(rel_abund = 0.0001, freq = 0.2)
}

```


Method `rarefy_samples()`: Rarefy communities to make all samples have same count number.

Usage:

```
microtable$rarefy_samples(method = c("rarefy", "SRS")[1], sample.size, ...)
```

Arguments:

`method` default `c("rarefy", "SRS")[1]`; "rarefy" represents the classical resampling like `rrarefy` function of `vegan` package. "SRS" is scaling with ranked subsampling method based on the SRS package provided by Lukas Beule and Petr Karlovsky (2020) <DOI:10.7717/peerj.9593>.

`sample.size` default `NULL`; library size. If not provided, use the minimum number across all samples. For "SRS" method, this parameter is passed to `Cmin` parameter of SRS function of SRS package.

... parameters pass to `norm` function of `trans_norm` class.

Returns: `None`; rarefied dataset.

Examples:

```
\donttest{
m1$rarefy_samples(sample.size = min(m1$sample_sums()))
}
```

Method `tidy_dataset()`: Trim all the data in the `microtable` object to make taxa and samples consistent. So the results are intersections.

Usage:

```
microtable$tidy_dataset(main_data = FALSE)
```

Arguments:

`main_data` default `FALSE`; if `TRUE`, only basic data in `microtable` object is trimmed. Otherwise, all data, including `taxa_abund`, `alpha_diversity` and `beta_diversity`, are all trimmed.

Returns: `None`, object of `microtable` itself cleaned up.

Examples:

```
m1$tidy_dataset(main_data = TRUE)
```

Method `add_rownames2taxonomy()`: Add the rownames of `microtable$tax_table` as its last column. This is especially useful when the rownames of `microtable$tax_table` are required as a taxonomic level for the taxonomic abundance calculation and biomarker identification.

Usage:

```
microtable$add_rownames2taxonomy(use_name = "OTU")
```

Arguments:

`use_name` default "OTU"; The column name used in the `tax_table`.

Returns: `NULL`, a new `tax_table` stored in the object.

Examples:

```
\donttest{
m1$add_rownames2taxonomy()
}
```

Method `sample_sums()`: Sum the species number for each sample.

Usage:

```
microtable$sample_sums()
```

Returns: species number of samples.

Examples:

```
\donttest{  
m1$sample_sums()  
}
```

Method taxa_sums(): Sum the species number for each taxa.

Usage:

```
microtable$taxa_sums()
```

Returns: species number of taxa.

Examples:

```
\donttest{  
m1$taxa_sums()  
}
```

Method sample_names(): Show sample names.

Usage:

```
microtable$sample_names()
```

Returns: sample names.

Examples:

```
\donttest{  
m1$sample_names()  
}
```

Method taxa_names(): Show taxa names of tax_table.

Usage:

```
microtable$taxa_names()
```

Returns: taxa names.

Examples:

```
\donttest{  
m1$taxa_names()  
}
```

Method rename_taxa(): Rename the features, including the rownames of otu_table, rownames of tax_table, tip labels of phylo_tree and rep_fasta.

Usage:

```
microtable$rename_taxa(newname_prefix = "ASV_")
```

Arguments:

newname_prefix default "ASV_"; the prefix of new names; new names will be newname_prefix + numbers according to the rownames order of otu_table.

Returns: None; renamed dataset.

Examples:

```
\donttest{
m1$rename_taxa()
}
```

Method `merge_samples()`: Merge samples according to specific group to generate a new microtable.

Usage:

```
microtable$merge_samples(use_group)
```

Arguments:

`use_group` the group column in `sample_table`.

Returns: a new merged microtable object.

Examples:

```
\donttest{
m1$merge_samples(use_group = "Group")
}
```

Method `merge_taxa()`: Merge taxa according to specific taxonomic rank to generate a new microtable.

Usage:

```
microtable$merge_taxa(taxa = "Genus")
```

Arguments:

`taxa` default "Genus"; the specific rank in `tax_table`.

Returns: a new merged microtable object.

Examples:

```
\donttest{
m1$merge_taxa(taxa = "Genus")
}
```

Method `save_table()`: Save each basic data in microtable object as local file.

Usage:

```
microtable$save_table(dirpath = "basic_files", sep = ",", ...)
```

Arguments:

`dirpath` default "basic_files"; directory to save the tables, phylogenetic tree and sequences in microtable object. It will be created if not found.

`sep` default ","; the field separator string, used to save tables. Same with `sep` parameter in [write.table](#) function. default ' ' correspond to the file name suffix 'csv'. The option '\t' correspond to the file name suffix 'tsv'. For other options, suffix are all 'txt'.

... parameters passed to [write.table](#).

Examples:

```
\dontrun{
m1$save_table()
}
```

Method `cal_abund()`: Calculate the taxonomic abundance at each taxonomic level or selected levels.

Usage:

```
microtable$cal_abund(
  select_cols = NULL,
  rel = TRUE,
  merge_by = "|",
  split_group = FALSE,
  split_by = "&&",
  split_column = NULL
)
```

Arguments:

`select_cols` default NULL; numeric vector or character vector of colnames of `microtable$tax_table`; applied to select columns to merge and calculate abundances according to ordered hierarchical levels. This is very useful if there are commented columns or some columns with multiple structure that cannot be used directly.

`rel` default TRUE; if TRUE, relative abundance is used; if FALSE, absolute abundance (i.e. raw values) will be summed.

`merge_by` default "|"; the symbol to merge and concatenate taxonomic names of different levels.

`split_group` default FALSE; if TRUE, split the rows to multiple rows according to one or more columns in `tax_table`. Very useful when multiple mapping information exist.

`split_by` default "&&"; Separator delimiting collapsed values; only useful when `split_group = TRUE`; see `sep` parameter in `separate_rows` function of `tidyr` package.

`split_column` default NULL; character vector or list; only useful when `split_group = TRUE`; character vector: fixed column or columns used for the splitting in `tax_table` for each abundance calculation; list: containing more character vectors to assign the column names to each calculation, such as `list(c("Phylum"), c("Phylum", "Class"))`.

Returns: `taxa_abund` list in object.

Examples:

```
\donttest{
m1$cal_abund()
}
```

Method `save_abund()`: Save taxonomic abundance as local file.

Usage:

```
microtable$save_abund(
  dirpath = "taxa_abund",
  merge_all = FALSE,
  rm_un = FALSE,
  rm_pattern = "__$",
  sep = ",",
  ...
)
```

Arguments:

`dirpath` default "taxa_abund"; directory to save the taxonomic abundance files. It will be created if not found.

`merge_all` default FALSE; Whether merge all tables into one. The merged file format is generally called 'mpa' style.

`rm_un` default FALSE; Whether remove unclassified taxa in which the name ends with '___' generally.

`rm_pattern` default "__\$"; The pattern searched through the merged taxonomic names. See also `pattern` parameter in `grepl` function. Only available when `rm_un = TRUE`. The default "__\$" means removing the names end with '___'.

`sep` default ","; the field separator string. Same with `sep` parameter in `write.table` function. default ', ' correspond to the file name suffix 'csv'. The option '\t' correspond to the file name suffix 'tsv'. For other options, suffix are all 'txt'.

... parameters passed to `write.table`.

Examples:

```
\dontrun{
m1$save_abund(dirpath = "taxa_abund")
m1$save_abund(merge_all = TRUE, rm_un = TRUE, sep = "\t")
}
```

Method `cal_alphadiv()`: Calculate alpha diversity.

Usage:

```
microtable$cal_alphadiv(measures = NULL, PD = FALSE)
```

Arguments:

`measures` default NULL; one or more indexes in `c("Observed", "Coverage", "Chao1", "ACE", "Shannon", "Simpson", "InvSimpson", "Fisher", "Pielou")`; The default NULL represents that all the measures are calculated. 'Shannon', 'Simpson' and 'InvSimpson' are calculated based on `vegan::diversity` function; 'Chao1' and 'ACE' depend on the function `vegan::estimateR`. 'Fisher' index relies on the function `vegan::fisher.alpha`. "Observed" means the observed species number in a community, i.e. richness. "Coverage" represents good's coverage. It is defined:

$$Coverage = 1 - \frac{f1}{n}$$

where n is the total abundance of a sample, and $f1$ is the number of singleton (species with abundance 1) in the sample. "Pielou" denotes the Pielou evenness index. It is defined:

$$J = \frac{H'}{\ln(S)}$$

where H' is Shannon index, and S is the species number.

`PD` default FALSE; whether Faith's phylogenetic diversity is calculated. The calculation depends on the function `picante::pd`. Note that the phylogenetic tree (`phylo_tree` object in the data) is required for PD.

Returns: `alpha_diversity` stored in the object. The `se.chao1` and `se.ACE` are the standard erros of Chao1 and ACE, respectively.

Examples:

```
\donttest{
m1$cal_alphadiv(measures = NULL, PD = FALSE)
class(m1$alpha_diversity)
}
```

Method `save_alphadiv()`: Save alpha diversity table to the computer.

Usage:

```
microtable$save_alphadiv(dirpath = "alpha_diversity")
```

Arguments:

`dirpath` default "alpha_diversity"; directory name to save the alpha_diversity.csv file.

Method `cal_betadiv()`: Calculate beta diversity dissimilarity matrix, such as Bray-Curtis, Jaccard, and UniFrac. See An et al. (2019) <doi:10.1016/j.geoderma.2018.09.035> and Lozupone et al. (2005) <doi:10.1128/AEM.71.12.8228-8235.2005>.

Usage:

```
microtable$cal_betadiv(method = NULL, unifrac = FALSE, binary = FALSE, ...)
```

Arguments:

`method` default NULL; a character vector with one or more elements; `c("bray", "jaccard")` is used when `method = NULL`; See the `method` parameter in `vegdist` function for more available options, such as 'aitchison' and 'robust.aitchison'.

`unifrac` default FALSE; whether UniFrac indexes (weighted and unweighted) are calculated. Phylogenetic tree is necessary when `unifrac = TRUE`.

`binary` default FALSE; Whether convert abundance to binary data (presence/absence) when `method` is not "jaccard". TRUE is used for "jaccard" automatically.

... parameters passed to `vegdist` function.

Returns: `beta_diversity` list stored in the object.

Examples:

```
\donttest{
m1$cal_betadiv(unifrac = FALSE)
class(m1$beta_diversity)
}
```

Method `save_betadiv()`: Save beta diversity matrix to the computer.

Usage:

```
microtable$save_betadiv(dirpath = "beta_diversity")
```

Arguments:

`dirpath` default "beta_diversity"; directory name to save the beta diversity matrix files.

Method `print()`: Print the microtable object.

Usage:

```
microtable$print()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
microtable$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```

## -----
## Method `microtable$new`
## -----

data(otu_table_16S)
data(taxonomy_table_16S)
data(sample_info_16S)
data(phylo_tree_16S)
m1 <- microtable$new(otu_table = otu_table_16S)
m1 <- microtable$new(sample_table = sample_info_16S, otu_table = otu_table_16S,
  tax_table = taxonomy_table_16S, phylo_tree = phylo_tree_16S)
# trim the files in the dataset
m1$tidy_dataset()

## -----
## Method `microtable$filter_pollution`
## -----

m1$filter_pollution(taxa = c("mitochondria", "chloroplast"))

## -----
## Method `microtable$filter_taxa`
## -----

d1 <- clone(m1)
d1$filter_taxa(rel_abund = 0.0001, freq = 0.2)

## -----
## Method `microtable$rarefy_samples`
## -----

m1$rarefy_samples(sample.size = min(m1$sample_sums()))

## -----
## Method `microtable$tidy_dataset`
## -----

m1$tidy_dataset(main_data = TRUE)

## -----
## Method `microtable$add_rownames2taxonomy`
## -----

m1$add_rownames2taxonomy()

```

```
## -----  
## Method `microtable$sample_sums`  
## -----  
  
m1$sample_sums()  
  
## -----  
## Method `microtable$taxa_sums`  
## -----  
  
m1$taxa_sums()  
  
## -----  
## Method `microtable$sample_names`  
## -----  
  
m1$sample_names()  
  
## -----  
## Method `microtable$taxa_names`  
## -----  
  
m1$taxa_names()  
  
## -----  
## Method `microtable$rename_taxa`  
## -----  
  
m1$rename_taxa()  
  
## -----  
## Method `microtable$merge_samples`  
## -----  
  
m1$merge_samples(use_group = "Group")  
  
## -----  
## Method `microtable$merge_taxa`  
## -----
```



```

m1$merge_taxa(taxa = "Genus")

## -----
## Method `microtable$save_table`
## -----

## Not run:
m1$save_table()

## End(Not run)

## -----
## Method `microtable$scal_abund`
## -----

m1$scal_abund()

## -----
## Method `microtable$save_abund`
## -----

## Not run:
m1$save_abund(dirpath = "taxa_abund")
m1$save_abund(merge_all = TRUE, rm_un = TRUE, sep = "\t")

## End(Not run)

## -----
## Method `microtable$scal_alphadiv`
## -----

m1$scal_alphadiv(measures = NULL, PD = FALSE)
class(m1$alpha_diversity)

## -----
## Method `microtable$scal_betadiv`
## -----

m1$scal_betadiv(unifrac = FALSE)
class(m1$beta_diversity)

```

Description

The OTU table of the 16S example data

Usage

```
data(otu_table_16S)
```

otu_table_ITS	<i>The OTU table of the ITS example data</i>
---------------	--

Description

The OTU table of the ITS example data

Usage

```
data(otu_table_ITS)
```

phylo_tree_16S	<i>The phylogenetic tree of 16S example data</i>
----------------	--

Description

The phylogenetic tree of 16S example data

Usage

```
data(phylo_tree_16S)
```

prok_func_FAPROTAX	<i>The modified FAPROTAX trait database</i>
--------------------	---

Description

The modified FAPROTAX trait database

Usage

```
data(prok_func_FAPROTAX)
```

prok_func_NJC19_list *The modified NJC19 database*

Description

The modified NJC19 database

Usage

data(prok_func_NJC19_list)

sample_info_16S *The sample information of 16S example data*

Description

The sample information of 16S example data

Usage

data(sample_info_16S)

sample_info_ITS *The sample information of ITS example data*

Description

The sample information of ITS example data

Usage

data(sample_info_ITS)

Tax4Fun2_KEGG *The KEGG data files used in the trans_func class*

Description

The KEGG data files used in the trans_func class

Usage

data(Tax4Fun2_KEGG)

taxonomy_table_16S	<i>The taxonomic information of 16S example data</i>
--------------------	--

Description

The taxonomic information of 16S example data

Usage

```
data(taxonomy_table_16S)
```

taxonomy_table_ITS	<i>The taxonomic information of ITS example data</i>
--------------------	--

Description

The taxonomic information of ITS example data

Usage

```
data(taxonomy_table_ITS)
```

tidy_taxonomy	<i>Clean up the taxonomic table to make taxonomic assignments consistent.</i>
---------------	---

Description

Clean up the taxonomic table to make taxonomic assignments consistent.

Usage

```
tidy_taxonomy(
  taxonomy_table,
  column = "all",
  pattern = c(".*unassigned.*", ".*uncultur.*", ".*unknown.*", ".*unidentif.*",
    ".*unclassified.*", ".*No blast hit.*", ".*Incertae.sedis.*"),
  replacement = "",
  ignore.case = TRUE,
  na_fill = ""
)
```

Arguments

taxonomy_table	a data.frame with taxonomic information.
column	default "all"; "all" or a number; 'all' represents cleaning up all the columns; a number represents cleaning up this column.
pattern	default c(".*unassigned.*", ".*uncultur.*", ".*unknown.*", ".*unidentif.*", ".*unclassified.*", ".*No blast hit.*", ".*Incertae.sedis.*"); the characters (regular expressions) to be removed or replaced; removed when parameter replacement = "", replaced when parameter replacement has something; Note that the capital and small letters are not distinguished when ignore.case = TRUE.
replacement	default ""; the characters used to replace the character in pattern parameter.
ignore.case	default TRUE; if FALSE, the pattern matching is case sensitive and if TRUE, case is ignored during matching.
na_fill	default ""; used to replace NA.

Format

data.frame object.

Value

data.frame

Examples

```
data("taxonomy_table_16S")
tidy_taxonomy(taxonomy_table_16S)
```

trans_abund	<i>Create trans_abund object for taxonomic abundance visualization.</i>
-------------	---

Description

This class is a wrapper for the taxonomic abundance transformations and visualization. The converted data style is the long-format for ggplot2 plot. The plotting methods include bar plot, box-plot, heatmap, pie chart and line chart.

Methods**Public methods:**

- `trans_abund$new()`
- `trans_abund$plot_bar()`
- `trans_abund$plot_heatmap()`
- `trans_abund$plot_box()`
- `trans_abund$plot_line()`
- `trans_abund$plot_pie()`

- `trans_abund$plot_donut()`
- `trans_abund$plot_radar()`
- `trans_abund$plot_tern()`
- `trans_abund$print()`
- `trans_abund$clone()`

Method new():

Usage:

```
trans_abund$new(
  dataset = NULL,
  taxrank = "Phylum",
  show = 0,
  ntaxa = 10,
  groupmean = NULL,
  group_morestats = FALSE,
  delete_taxonomy_lineage = TRUE,
  delete_taxonomy_prefix = TRUE,
  prefix = NULL,
  use_percentage = TRUE,
  input_taxaname = NULL,
  high_level = NULL,
  high_level_fix_nsub = NULL
)
```

Arguments:

`dataset` default NULL; the object of `microtable` class.

`taxrank` default "Phylum"; taxonomic rank.

`show` default 0; the relative abundance threshold for filtering the taxa with low abundance.

`ntaxa` default 10; how many taxa are selected to show. Taxa are ordered by abundance from high to low. This parameter does not conflict with the parameter `show`. Both can be used. `ntaxa = NULL` means it is unavailable.

`groupmean` default NULL; calculate mean abundance for each group. Select a column name in `microtable$sample_table`.

`group_morestats` default FALSE; only available when `groupmean` parameter is provided; Whether output more statistics for each group, including min, max, median and quantile; Thereinto, `quantile25` and `quantile75` denote 25% and 75% quantiles, respectively.

`delete_taxonomy_lineage` default TRUE; whether delete the taxonomy lineage in front of the target level.

`delete_taxonomy_prefix` default TRUE; whether delete the prefix of taxonomy, such as "g__".

`prefix` default NULL; character string; available when `delete_taxonomy_prefix = T`; default NULL represents using the "letter+__", e.g. "k__" for Phylum level; Please provide the customized prefix when it is not standard, otherwise the program can not correctly recognize it.

`use_percentage` default TRUE; show the abundance percentage.

`input_taxaname` default NULL; character vector; input taxa names to select some taxa.

`high_level` default NULL; a taxonomic rank, such as "Phylum", used to add the taxonomic information of higher level. It is necessary for the legend with nested taxonomic levels in the bar plot.

`high_level_fix_nsub` default NULL; an integer, used to fix the number of selected abundant taxa in each taxon from higher taxonomic level. If the total number under one taxon of higher level is less than the `high_level_fix_nsub`, the total number will be used. When `high_level_fix_nsub` is provided, the taxa number of higher level is calculated as: $\text{ceiling}(\text{ntaxa}/\text{high_level_fix_nsub})$. Note that `ntaxa` means either the parameter `ntaxa` or the taxonomic number obtained by filtering according to the `show` parameter.

Returns: `data_abund` stored in the object. The column 'all_mean_abund' represents mean relative abundance across all the samples. So the values in one taxon are all same across all the samples. If the sum of column 'Abundance' in one sample is larger than 1, the 'Abundance', 'SD' and 'SE' has been multiplied by 100.

Examples:

```
\donttest{
data(dataset)
t1 <- trans_abund$new(dataset = dataset, taxrank = "Phylum", ntaxa = 10)
}
```

Method `plot_bar()`: Bar plot.

Usage:

```
trans_abund$plot_bar(
  color_values = RColorBrewer::brewer.pal(8, "Dark2"),
  bar_full = TRUE,
  others_color = "grey90",
  facet = NULL,
  order_x = NULL,
  x_axis_name = NULL,
  barwidth = NULL,
  use_alluvium = FALSE,
  clustering = FALSE,
  clustering_plot = FALSE,
  cluster_plot_width = 0.2,
  facet_color = "grey95",
  strip_text = 11,
  legend_text_italic = FALSE,
  xtext_angle = 0,
  xtext_size = 10,
  xtext_keep = TRUE,
  xtitle_keep = TRUE,
  ytitle_size = 17,
  coord_flip = FALSE,
  ggnested = FALSE,
  high_level_add_other = FALSE,
  ...
)
```

Arguments:

`color_values` default `RColorBrewer::brewer.pal(8, "Dark2")`; colors palette for the bars.
`bar_full` default `TRUE`; Whether the bar shows all the features (including 'Others'). Default `TRUE` means total abundance are summed to 1 or 100 (percentage). `FALSE` means 'Others' will not be shown.
`others_color` default `"grey90"`; the color for "Others" taxa.
`facet` default `NULL`; a character vector for the facet; group column name of `sample_table`, such as, "Group"; If multiple facets are needed, please provide ordered names, such as `c("Group", "Type")`. The latter should have a finer scale than the former one; Please adjust the facet orders in the plot by assigning factors in `sample_table` before creating `trans_abund` object or assigning factors in the `data_abund` table of `trans_abund` object. When multiple facets are used, please first install package `ggh4x` using the command `install.packages("ggh4x")`.
`order_x` default `NULL`; vector; used to order the sample names in x axis; must be the samples vector, such as `c("S1", "S3", "S2")`.
`x_axis_name` `NULL`; a character string; a column name of `sample_table` in dataset; used to show the sample names in x axis.
`barwidth` default `NULL`; bar width, see width in [geom_bar](#).
`use_alluvium` default `FALSE`; whether add alluvium plot. If `TRUE`, please first install `ggalluvial` package.
`clustering` default `FALSE`; whether order samples by the clustering.
`clustering_plot` default `FALSE`; whether add clustering plot. If `clustering_plot = TRUE`, `clustering` will be also `TRUE` in any case for the clustering.
`cluster_plot_width` default `0.2`, the dendrogram plot width; available when `clustering_plot = TRUE`.
`facet_color` default `"grey95"`; facet background color.
`strip_text` default `11`; facet text size.
`legend_text_italic` default `FALSE`; whether use italic in legend.
`xtext_angle` default `0`; number ranging from 0 to 90; used to adjust x axis text angle to reduce text overlap;
`xtext_size` default `10`; x axis text size.
`xtext_keep` default `TRUE`; whether retain x text.
`xtitle_keep` default `TRUE`; whether retain x title.
`ytitle_size` default `17`; y axis title size.
`coord_flip` default `FALSE`; whether flip cartesian coordinates so that horizontal becomes vertical, and vertical becomes horizontal.
`ggnested` default `FALSE`; whether use nested legend. Need `ggnested` package to be installed (<https://github.com/gmteunisse/ggnested>). To make it available, please assign `high_level` parameter when creating the object.
`high_level_add_other` default `FALSE`; whether add 'Others' (all the unknown taxa) in each taxon of higher taxonomic level. Only available when `ggnested = TRUE`.
... Capture unknown parameters.

Returns: `ggplot2` object.

Examples:


```
\donttest{
t1$plot_bar(facet = "Group", xtext_keep = FALSE)
}
```

Method plot_heatmap(): Plot the heatmap.

Usage:

```
trans_abund$plot_heatmap(
  color_values = rev(RColorBrewer::brewer.pal(n = 11, name = "RdYlBu")),
  facet = NULL,
  x_axis_name = NULL,
  order_x = NULL,
  withmargin = TRUE,
  plot_numbers = FALSE,
  plot_text_size = 4,
  plot_breaks = NULL,
  margincolor = "white",
  plot_colorscale = "log10",
  min_abundance = 0.01,
  max_abundance = NULL,
  strip_text = 11,
  xtext_size = 10,
  ytext_size = 11,
  xtext_keep = TRUE,
  xtitle_keep = TRUE,
  grid_clean = TRUE,
  xtext_angle = 0,
  legend_title = "% Relative\nAbundance",
  pheatmap = FALSE,
  ...
)
```

Arguments:

`color_values` default `rev(RColorBrewer::brewer.pal(n = 11, name = "RdYlBu"))`; colors palette for the plotting.

`facet` default `NULL`; a character vector for the facet; a group column name of `sample_table`, such as, "Group"; If multiple facets are needed, please provide ordered names, such as `c("Group", "Type")`. The latter should have a finer scale than the former one; Please adjust the facet orders in the plot by assigning factors in `sample_table` before creating `trans_abund` object or assigning factors in the `data_abund` table of `trans_abund` object. When multiple facets are used, please first install package `ggh4x` using the command `install.packages("ggh4x")`.

`x_axis_name` `NULL`; a character string; a column name of `sample_table` used to show the sample names in x axis.

`order_x` default `NULL`; vector; used to order the sample names in x axis; must be the samples vector, such as, `c("S1", "S3", "S2")`.

`withmargin` default `TRUE`; whether retain the tile margin.

`plot_numbers` default `FALSE`; whether plot the number in heatmap.

`plot_text_size` default 4; If `plot_numbers` `TRUE`, text size in plot.

plot_breaks default NULL; The legend breaks.
 margincolor default "white"; If withmargin TRUE, use this as the margin color.
 plot_colorscale default "log10"; color scale.
 min_abundance default .01; the minimum abundance percentage in plot.
 max_abundance default NULL; the maximum abundance percentage in plot, NULL represent the max percentage.
 strip_text default 11; facet text size.
 xtext_size default 10; x axis text size.
 ytext_size default 11; y axis text size.
 xtext_keep default TRUE; whether retain x text.
 xtitle_keep default TRUE; whether retain x title.
 grid_clean default TRUE; whether remove grid lines.
 xtext_angle default 0; number ranging from 0 to 90; used to adjust x axis text angle to reduce text overlap;
 legend_title default "% Relative\nAbundance"; legend title text.
 pheatmap default FALSE; whether use pheatmap package to plot the heatmap.
 ... parameters pass to pheatmap when pheatmap = TRUE.
Returns: ggplot2 object or grid object based on pheatmap.

Examples:

```

\donttest{
t1 <- trans_abund$new(dataset = dataset, taxrank = "Genus", ntaxa = 40)
t1$plot_heatmap(facet = "Group", xtext_keep = FALSE, withmargin = FALSE)
}

```

Method plot_box(): Box plot.

Usage:

```

trans_abund$plot_box(
  color_values = RColorBrewer::brewer.pal(8, "Dark2"),
  group = NULL,
  show_point = FALSE,
  point_color = "black",
  point_size = 3,
  point_alpha = 0.3,
  plot_flip = FALSE,
  boxfill = TRUE,
  middlecolor = "grey95",
  middlesize = 1,
  xtext_angle = 0,
  xtext_size = 10,
  ytitle_size = 17,
  ...
)

```

Arguments:

color_values default RColorBrewer::brewer.pal(8, "Dark2"); colors palette for the box.

group default NULL; a column name of sample table to show abundance across groups.
 show_point default FALSE; whether show points in plot.
 point_color default "black"; If show_point TRUE; use the color
 point_size default 3; If show_point TRUE; use the size
 point_alpha default .3; If show_point TRUE; use the transparency.
 plot_flip default FALSE; Whether rotate plot.
 boxfill default TRUE; Whether fill the box with colors.
 middlecolor default "grey95"; The middle line color.
 middlesize default 1; The middle line size.
 xtext_angle default 0; number ranging from 0 to 90; used to adjust x axis text angle to reduce text overlap;
 xtext_size default 10; x axis text size.
 ytitle_size default 17; y axis title size.
 ... parameters pass to `geom_boxplot` function.

Returns: ggplot2 object.

Examples:

```

\donttest{
t1$plot_box(group = "Group")
}

```

Method `plot_line()`: Plot the line chart.

Usage:

```

trans_abund$plot_line(
  color_values = RColorBrewer::brewer.pal(8, "Dark2"),
  plot_SE = TRUE,
  position = position_dodge(0.1),
  errorbar_size = 1,
  errorbar_width = 0.1,
  point_size = 3,
  point_alpha = 0.8,
  line_size = 0.8,
  line_alpha = 0.8,
  line_type = 1,
  xtext_angle = 0,
  xtext_size = 10,
  ytitle_size = 17
)

```

Arguments:

color_values default `RColorBrewer::brewer.pal(8, "Dark2")`; colors palette for the points and lines.
 plot_SE default TRUE; TRUE: the errorbar is *meanse*; FALSE: the errorbar is *meansd*.
 position default `position_dodge(0.1)`; Position adjustment, either as a string (such as "identity"), or the result of a call to a position adjustment function.
 errorbar_size default 1; errorbar line size.

errorbar_width default 0.1; errorbar width.
 point_size default 3; point size for taxa.
 point_alpha default 0.8; point transparency.
 line_size default 0.8; line size.
 line_alpha default 0.8; line transparency.
 line_type default 1; an integer; line type.
 xtext_angle default 0; number ranging from 0 to 90; used to adjust x axis text angle to reduce text overlap;
 xtext_size default 10; x axis text size.
 ytitle_size default 17; y axis title size.

Returns: ggplot2 object.

Examples:

```
\donttest{
t1 <- trans_abund$new(dataset = dataset, taxrank = "Genus", ntaxa = 5)
t1$plot_line(point_size = 3)
t1 <- trans_abund$new(dataset = dataset, taxrank = "Genus", ntaxa = 5, groupmean = "Group")
t1$plot_line(point_size = 5, errorbar_size = 1, xtext_angle = 30)
}
```

Method plot_pie(): Pie chart.

Usage:

```
trans_abund$plot_pie(
  color_values = RColorBrewer::brewer.pal(8, "Dark2"),
  facet_nrow = 1,
  strip_text = 11,
  add_label = FALSE,
  legend_text_italic = FALSE
)
```

Arguments:

color_values default RColorBrewer::brewer.pal(8, "Dark2"); colors palette for each section.
 facet_nrow default 1; how many rows in the plot.
 strip_text default 11; sample title size.
 add_label default FALSE; Whether add the percentage label in each section of pie chart.
 legend_text_italic default FALSE; whether use italic in legend.

Returns: ggplot2 object.

Examples:

```
\donttest{
t1 <- trans_abund$new(dataset = dataset, taxrank = "Phylum", ntaxa = 6, groupmean = "Group")
t1$plot_pie(facet_nrow = 1)
}
```

Method plot_donut(): Donut chart based on the ggpubr::ggdonutchart function.

Usage:

```
trans_abund$plot_donut(
  color_values = RColorBrewer::brewer.pal(8, "Dark2"),
  label = TRUE,
  facet_nrow = 1,
  legend_text_italic = FALSE,
  ...
)
```

Arguments:

color_values default RColorBrewer::brewer.pal(8, "Dark2"); colors palette for the donut.

label default TRUE; whether show the percentage label.

facet_nrow default 1; how many rows in the plot.

legend_text_italic default FALSE; whether use italic in legend.

... parameters passed to ggpubr::ggdonutchart.

Returns: combined ggplot2 objects list, generated by ggpubr::ggarrange function.

Examples:

```
\dontrun{
t1 <- trans_abund$new(dataset = dataset, taxrank = "Phylum", ntaxa = 6, groupmean = "Group")
t1$plot_donut(label = TRUE)
}
```

Method plot_radar(): Radar chart based on the ggradar package (<https://github.com/ricardobion/ggradar>).

Usage:

```
trans_abund$plot_radar(
  color_values = RColorBrewer::brewer.pal(8, "Dark2"),
  ...
)
```

Arguments:

color_values default RColorBrewer::brewer.pal(8, "Dark2"); colors palette for samples.

... parameters passed to ggradar::ggradar function except group.colours parameter.

Returns: ggplot2 object.

Examples:

```
\dontrun{
t1 <- trans_abund$new(dataset = dataset, taxrank = "Phylum", ntaxa = 6, groupmean = "Group")
t1$plot_radar()
}
```

Method plot_tern(): Ternary diagrams based on the ggtern package.

Usage:

```
trans_abund$plot_tern(
  color_values = RColorBrewer::brewer.pal(8, "Dark2"),
  color_legend_guide_size = 4
)
```

Arguments:

color_values default RColorBrewer::brewer.pal(8, "Dark2"); colors palette for the samples.

color_legend_guide_size default 4; The size of legend guide for color.

Returns: ggplot2 object.

Examples:

```
\dontrun{
t1 <- trans_abund$new(dataset = dataset, taxrank = "Phylum", ntaxa = 6, groupmean = "Group")
t1$plot_tern()
}
```

Method print(): Print the trans_abund object.

Usage:

```
trans_abund$print()
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
trans_abund$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## -----
## Method `trans_abund$new`
## -----

data(dataset)
t1 <- trans_abund$new(dataset = dataset, taxrank = "Phylum", ntaxa = 10)

## -----
## Method `trans_abund$plot_bar`
## -----

t1$plot_bar(facet = "Group", xtext_keep = FALSE)

## -----
## Method `trans_abund$plot_heatmap`
## -----

t1 <- trans_abund$new(dataset = dataset, taxrank = "Genus", ntaxa = 40)
t1$plot_heatmap(facet = "Group", xtext_keep = FALSE, withmargin = FALSE)
```

```

## -----
## Method `trans_abund$plot_box`
## -----

t1$plot_box(group = "Group")

## -----
## Method `trans_abund$plot_line`
## -----

t1 <- trans_abund$new(dataset = dataset, taxrank = "Genus", ntaxa = 5)
t1$plot_line(point_size = 3)
t1 <- trans_abund$new(dataset = dataset, taxrank = "Genus", ntaxa = 5, groupmean = "Group")
t1$plot_line(point_size = 5, errorbar_size = 1, xtext_angle = 30)

## -----
## Method `trans_abund$plot_pie`
## -----

t1 <- trans_abund$new(dataset = dataset, taxrank = "Phylum", ntaxa = 6, groupmean = "Group")
t1$plot_pie(facet_nrow = 1)

## -----
## Method `trans_abund$plot_donut`
## -----

## Not run:
t1 <- trans_abund$new(dataset = dataset, taxrank = "Phylum", ntaxa = 6, groupmean = "Group")
t1$plot_donut(label = TRUE)

## End(Not run)

## -----
## Method `trans_abund$plot_radar`
## -----

## Not run:
t1 <- trans_abund$new(dataset = dataset, taxrank = "Phylum", ntaxa = 6, groupmean = "Group")
t1$plot_radar()

## End(Not run)

## -----
## Method `trans_abund$plot_tern`
## -----

## Not run:

```

```
t1 <- trans_abund$new(dataset = dataset, taxrank = "Phylum", ntaxa = 6, groupmean = "Group")
t1$plot_tern()

## End(Not run)
```

trans_alpha

Create trans_alpha object for alpha diversity statistics and plot.

Description

This class is a wrapper for a series of alpha diversity analysis, including the statistics and visualization.

Methods

Public methods:

- `trans_alpha$new()`
- `trans_alpha$cal_diff()`
- `trans_alpha$plot_alpha()`
- `trans_alpha$print()`
- `trans_alpha$clone()`

Method `new()`:

Usage:

```
trans_alpha$new(
  dataset = NULL,
  group = NULL,
  by_group = NULL,
  by_ID = NULL,
  order_x = NULL
)
```

Arguments:

`dataset` the object of `microtable` class.

`group` default NULL; a column of `sample_table` used for the statistics; If provided, can return `data_stat`.

`by_group` default NULL; a column of `sample_table` used to perform the differential test among groups (`group` parameter) for each group (`by_group` parameter). So `by_group` has a higher level than `group` parameter.

`by_ID` default NULL; a column of `sample_table` used to perform paired t test or paired wilcox test for the paired data, such as the data of plant compartments for different plant species (ID). So `by_ID` in `sample_table` should be the smallest unit of sample collection without any repetition in it.

`order_x` default NULL; a `sample_table` column name or a vector with sample names; if provided, order samples by using factor.

Returns: data_alpha and data_stat stored in the object.

Examples:

```
\dotttest{
data(dataset)
t1 <- trans_alpha$new(dataset = dataset, group = "Group")
}
```

Method cal_diff(): Differential test on alpha diversity.

Usage:

```
trans_alpha$cal_diff(
  method = c("KW", "KW_dunn", "wilcox", "t.test", "anova", "scheirerRayHare", "lm",
    "lme", "betareg", "glmm", "glmm_beta")[1],
  measure = NULL,
  p_adjust_method = "fdr",
  formula = NULL,
  KW_dunn_letter = TRUE,
  alpha = 0.05,
  anova_post_test = "duncan.test",
  return_model = FALSE,
  ...
)
```

Arguments:

method default "KW"; see the following available options:

- 'KW' Kruskal-Wallis Rank Sum Test for all groups (≥ 2)
- 'KW_dunn' Dunn's Kruskal-Wallis Multiple Comparisons <10.1080/00401706.1964.10490181> based on dunnTest function in FSA package
- 'wilcox' Wilcoxon Rank Sum Test for all paired groups
- 't.test' Student's t-Test for all paired groups
- 'anova' Variance analysis. For one-way anova, the post hoc test is Duncan's new multiple range test based on duncan.test function of agricolae package. Please use anova_post_test parameter to select other post hoc method. For multi-way anova, Please use formula parameter to specify the model and see [aov](#) for more details
- 'scheirerRayHare' Scheirer-Ray-Hare test (nonparametric test) for a two-way factorial experiment; see scheirerRayHare function of rcompanion package
- 'lm' Linear Model based on the lm function
- 'lme' Linear Mixed Effect Model based on the lmerTest package
- 'betareg' Beta Regression for Rates and Proportions based on the betareg package
- 'glmm' Generalized linear mixed model (GLMM) based on the glmmTMB package
- 'glmm_beta' Generalized linear mixed model (GLMM) with a family function of beta distribution. This is an extension of the GLMM model in 'glmm' option. The only difference is in glmm_beta the family function is fixed with the beta distribution function, facilitating the fitting for proportional data (ranging from 0 to 1). The link function is fixed with "logit".

measure default NULL; character vector; If NULL, all indexes will be calculated; see names of microtable\$alpha_diversity, e.g. c("Observed", "Chao1", "Shannon").

`p_adjust_method` default "fdr" (for "KW", "wilcox", "t.test") or "holm" (for "KW_dunn"); P value adjustment method; For method = 'KW', 'wilcox' or 't.test', please see method parameter of `p.adjust` function for available options; For method = 'KW_dunn', please see `dunn.test::p.adjustment.methods` for available options.

`formula` default NULL; applied to two-way or multi-factor anova when method = "anova" or "scheirerRayHare" or "lme" or "betareg" or "glm"; specified set for independent variables, i.e. the latter part of a general formula, such as 'block + N*P*K'.

`KW_dunn_letter` default TRUE; For method = 'KW_dunn', TRUE denotes paired significances are presented by letters; FALSE means significances are shown by asterisk for paired comparison.

`alpha` default 0.05; Significant level; used for generating significance letters when method is 'anova' or 'KW_dunn'.

`anova_post_test` default "duncan.test". The post hoc test method for one-way anova. Other available options include "LSD.test" and "HSD.test". All those are the function names in `agricolae` package.

`return_model` default FALSE; whether return the original lmer or glmm model list in the object.

... parameters passed to `kruskal.test` (when method = "KW") or `wilcox.test` function (when method = "wilcox") or `dunnTest` function of FSA package (when method = "KW_dunn") or `agricolae::duncan.test/agricolae::LSD.test/agricolae::HSD.test` (when method = "anova", one-way anova) or `rcompanion::scheirerRayHare` (when method = "scheirerRayHare") or `lmerTest::lmer` (when method = "lme") or `betareg::betareg` (when method = "betareg") or `glmmTMB::glmmTMB` (when method = "glm").

Returns: `res_diff`, stored in object with the format data.frame.

Examples:

```
\donttest{
t1$cal_diff(method = "KW")
t1$cal_diff(method = "anova")
t1 <- trans_alpha$new(dataset = dataset, group = "Type", by_group = "Group")
t1$cal_diff(method = "anova")
}
```

Method `plot_alpha()`: Plot the alpha diversity. Box plot is used for the visualization of alpha diversity when the group is found in the object. Heatmap is employed automatically to show the significances of differential test when the formula is found in the `res_diff` table of the object.

Usage:

```
trans_alpha$plot_alpha(
  color_values = RColorBrewer::brewer.pal(8, "Dark2"),
  measure = "Shannon",
  group = NULL,
  add_sig = TRUE,
  add_sig_label = "Significance",
  add_sig_text_size = 3.88,
  add_sig_label_num_dec = 4,
  boxplot_add = "jitter",
  order_x_mean = FALSE,
```

```

y_start = 0.1,
y_increase = 0.05,
xtext_angle = 30,
xtext_size = 13,
ytitle_size = 17,
barwidth = 0.9,
use_boxplot = TRUE,
plot_SE = TRUE,
errorbar_size = 1,
errorbar_width = 0.2,
point_size = 3,
point_alpha = 0.8,
add_line = FALSE,
line_size = 0.8,
line_type = 1,
line_color = "grey50",
line_alpha = 0.5,
heatmap_cell = "P.unadj",
heatmap_sig = "Significance",
heatmap_x = "Factors",
heatmap_y = "Measure",
heatmap_lab_fill = "P value",
...
)

```

Arguments:

`color_values` default `RColorBrewer::brewer.pal(8, "Dark2")`; color pallete for groups.

`measure` default "Shannon"; one alpha diversity index in the object.

`group` default NULL; group name used for the plot.

`add_sig` default TRUE; wheter add significance label using the result of `cal_diff` function, i.e. `object$res_diff`; This is manily designed to add post hoc test of anova or other significances to make the label mapping easy.

`add_sig_label` default "Significance"; select a colname of `object$res_diff` for the label text when 'Letter' is not in the table, such as 'P.adj' or 'Significance'.

`add_sig_text_size` default 3.88; the size of text in added label.

`add_sig_label_num_dec` default 4; reserved decimal places when the parameter `add_sig_label` use numeric column, like 'P.adj'.

`boxplot_add` default "jitter"; points type, see the `add` parameter in `ggpubr::ggboxplot`.

`order_x_mean` default FALSE; whether order x axis by the means of groups from large to small.

`y_start` default 0.1; the y axis value from which to add the significance asterisk label; the default 0.1 means $\max(\text{values}) + 0.1 * (\max(\text{values}) - \min(\text{values}))$.

`y_increase` default 0.05; the increasing y axia space to add the label (asterisk or letter); the default 0.05 means $0.05 * (\max(\text{values}) - \min(\text{values}))$; this parameter is also used to label the letters of anova result with the fixed space.

`xtext_angle` default 30; number (e.g. 30) used to make x axis text generate angle.

`xtext_size` default 13; x axis text size. NULL means the default size in `ggplot2`.

ytitle_size default 17; y axis title size.
 barwidth default 0.9; the bar width in plot; applied when by_group is not NULL.
 use_boxplot default TRUE; TRUE denotes boxplot by using the data_alpha table in the object.
 FALSE represents mean-sd or mean-se plot by invoking the data_stat table in the object.
 plot_SE default TRUE; TRUE: the errorbar is *meanse*; FALSE: the errorbar is *meansd*.
 errorbar_size default 1; errorbar size. Available when use_boxplot = FALSE.
 errorbar_width default 0.2; errorbar width. Available when use_boxplot = FALSE and by_group is NULL.
 point_size default 3; point size for taxa. Available when use_boxplot = FALSE.
 point_alpha default 0.8; point transparency. Available when use_boxplot = FALSE.
 add_line default FALSE; whether add line. Available when use_boxplot = FALSE.
 line_size default 0.8; line size when add_line = TRUE. Available when use_boxplot = FALSE.
 line_type default 1; an integer; line type when add_line = TRUE. Available when use_boxplot = FALSE.
 line_color default "grey50"; line color when add_line = TRUE. Available when use_boxplot = FALSE and by_group is NULL.
 line_alpha default 0.5; line transparency when add_line = TRUE. Available when use_boxplot = FALSE.
 heatmap_cell default "P.unadj"; the column of res_diff table for the cell of heatmap when formula with multiple factors is found in the method.
 heatmap_sig default "Significance"; the column of res_diff for the significance label of heatmap.
 heatmap_x default "Factors"; the column of res_diff for the x axis of heatmap.
 heatmap_y default "Taxa"; the column of res_diff for the y axis of heatmap.
 heatmap_lab_fill default "P value"; legend title of heatmap.
 ... parameters passing to ggpubr::ggboxplot function when box plot is used or plot_cor function in trans_env class for the heatmap of multiple factors when formula is found in the res_diff of the object.

Returns: ggplot.

Examples:

```

\donttest{
t1 <- trans_alpha$new(dataset = dataset, group = "Group")
t1$cal_diff(method = "wilcox")
t1$plot_alpha(measure = "Shannon", add_sig = TRUE)
t1 <- trans_alpha$new(dataset = dataset, group = "Type", by_group = "Group")
t1$cal_diff(method = "wilcox")
t1$plot_alpha(measure = "Shannon", add_sig = TRUE)
}

```

Method print(): Print the trans_alpha object.

Usage:

```
trans_alpha$print()
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
trans_alpha$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## -----
## Method `trans_alpha$new`
## -----

data(dataset)
t1 <- trans_alpha$new(dataset = dataset, group = "Group")

## -----
## Method `trans_alpha$cal_diff`
## -----

t1$cal_diff(method = "KW")
t1$cal_diff(method = "anova")
t1 <- trans_alpha$new(dataset = dataset, group = "Type", by_group = "Group")
t1$cal_diff(method = "anova")

## -----
## Method `trans_alpha$plot_alpha`
## -----

t1 <- trans_alpha$new(dataset = dataset, group = "Group")
t1$cal_diff(method = "wilcox")
t1$plot_alpha(measure = "Shannon", add_sig = TRUE)
t1 <- trans_alpha$new(dataset = dataset, group = "Type", by_group = "Group")
t1$cal_diff(method = "wilcox")
t1$plot_alpha(measure = "Shannon", add_sig = TRUE)
```

trans_beta

Create trans_beta object for beta-diversity analysis

Description

This class is a wrapper for a series of beta-diversity related analysis, including ordination analysis based on An et al. (2019) <doi:10.1016/j.geoderma.2018.09.035>, group distance comparison, clustering, perMANOVA based on Anderson al. (2008) <doi:10.1111/j.1442-9993.2001.01070.pp.x>, ANOSIM and PERMDISP. Note that the beta diversity analysis methods related with environmental variables are encapsulated within trans_env class.

Methods

Public methods:

- `trans_beta$new()`
- `trans_beta$cal_ordination()`
- `trans_beta$plot_ordination()`
- `trans_beta$cal_manova()`
- `trans_beta$cal_anosim()`
- `trans_beta$cal_betadisper()`
- `trans_beta$cal_group_distance()`
- `trans_beta$cal_group_distance_diff()`
- `trans_beta$plot_group_distance()`
- `trans_beta$plot_clustering()`
- `trans_beta$clone()`

Method `new()`:

Usage:

```
trans_beta$new(dataset = NULL, measure = NULL, group = NULL)
```

Arguments:

`dataset` the object of `microtable` class.

`measure` default NULL; bray, jaccard, wei_unifrac or unwei_unifrac, or other name of matrix stored in `microtable$beta_diversity`; used for ordination, manova, group distance comparison, etc. The measure must be one of names in `microtable$beta_diversity` list. Please see `cal_betadiv` function of `microtable` class for more details.

`group` default NULL; sample group used for manova, betadisper or group distance comparison.

Returns: parameters stored in the object.

Examples:

```
data(dataset)
t1 <- trans_beta$new(dataset = dataset, measure = "bray", group = "Group")
```

Method `cal_ordination()`: Unconstrained ordination.

Usage:

```
trans_beta$cal_ordination(
  ordination = "PCoA",
  ncomp = 3,
  trans = FALSE,
  scale_species = FALSE,
  scale_species_ratio = 0.8,
  ...
)
```

Arguments:

`ordination` default "PCoA"; "PCA", "DCA", "PCoA" or "NMDS". PCA: principal component analysis; DCA: detrended correspondence analysis; PCoA: principal coordinates analysis; NMDS: non-metric multidimensional scaling.

ncomp default 3; dimensions shown in the results.
 trans default FALSE; whether species abundance will be square transformed; only available when ordination is "PCA" or "DCA".
 scale_species default FALSE; whether species loading in PCA or DCA is scaled.
 scale_species_ratio default 0.8; the ratio to scale up the loading; multiply by the maximum distance between samples and origin. Only available when scale_species = TRUE.
 ... parameters passed to vegan::rda function when ordination = "PCA", or vegan::decorana function when ordination = "DCA", or ape::pcoa function when ordination = "PCoA", or vegan::metaMDS function when when ordination = "NMDS".

Returns: res_ordination stored in the object.

Examples:

```
t1$cal_ordination(ordination = "PCoA")
```

Method plot_ordination(): Plot the ordination result.

Usage:

```
trans_beta$plot_ordination(
  plot_type = "point",
  color_values = RColorBrewer::brewer.pal(8, "Dark2"),
  shape_values = c(16, 17, 7, 8, 15, 18, 11, 10, 12, 13, 9, 3, 4, 0, 1, 2, 14),
  plot_color = NULL,
  plot_shape = NULL,
  plot_group_order = NULL,
  add_sample_label = NULL,
  point_size = 3,
  point_alpha = 0.8,
  centroid_segment_alpha = 0.6,
  centroid_segment_size = 1,
  centroid_segment_linetype = 3,
  ellipse_chull_fill = TRUE,
  ellipse_chull_alpha = 0.1,
  ellipse_level = 0.9,
  ellipse_type = "t",
  NMDS_stress_pos = c(1, 1),
  NMDS_stress_text_prefix = "",
  loading_arrow = FALSE,
  loading_taxa_num = 10,
  loading_text_color = "black",
  loading_arrow_color = "grey30",
  loading_text_size = 3,
  loading_text_italic = FALSE
)
```

Arguments:

plot_type default "point"; one or more elements of "point", "ellipse", "chull" and "centroid".

'point' add point

'ellipse' add confidence ellipse for points of each group

'chull' add convex hull for points of each group

'centroid' add centroid line of each group

color_values default `RColorBrewer::brewer.pal(8, "Dark2")`; colors palette for different groups.

shape_values default `c(16, 17, 7, 8, 15, 18, 11, 10, 12, 13, 9, 3, 4, 0, 1, 2, 14)`; a vector for point shape types of groups, see `ggplot2` tutorial.

plot_color default `NULL`; a colname of `sample_table` to assign colors to different groups in plot.

plot_shape default `NULL`; a colname of `sample_table` to assign shapes to different groups in plot.

plot_group_order default `NULL`; a vector used to order the groups in the legend of plot.

add_sample_label default `NULL`; a column name in `sample_table`; If provided, show the point name in plot.

point_size default 3; point size when "point" is in `plot_type` parameter.

point_alpha default .8; point transparency in plot when "point" is in `plot_type` parameter.

centroid_segment_alpha default 0.6; segment transparency in plot when "centroid" is in `plot_type` parameter.

centroid_segment_size default 1; segment size in plot when "centroid" is in `plot_type` parameter.

centroid_segment_linetype default 3; the line type related with centroid in plot when "centroid" is in `plot_type` parameter.

ellipse_chull_fill default `TRUE`; whether fill colors to the area of ellipse or chull.

ellipse_chull_alpha default 0.1; color transparency in the ellipse or convex hull depending on whether "ellipse" or "centroid" is in `plot_type` parameter.

ellipse_level default .9; confidence level of ellipse when "ellipse" is in `plot_type` parameter.

ellipse_type default "t"; ellipse type when "ellipse" is in `plot_type` parameter; see type in [stat_ellipse](#).

NMDS_stress_pos default `c(1, 1)`; a numerical vector with two values used to represent the insertion position of the stress text. The first one denotes the x-axis, while the second one corresponds to the y-axis. The assigned position is determined by multiplying the respective value with the maximum point on the corresponding coordinate axis. Thus, the x-axis position is equal to `max(points of x axis) * NMDS_stress_pos[1]`, and the y-axis position is equal to `max(points of y axis) * NMDS_stress_pos[2]`. Negative values can also be utilized for the negative part of the axis. `NMDS_stress_pos = NULL` denotes no stress text to show.

NMDS_stress_text_prefix default `""`; If `NMDS_stress_pos` is not `NULL`, this parameter can be used to add text in front of the stress value.

loading_arrow default `FALSE`; whether show the loading using arrow.

loading_taxa_num default 10; the number of taxa used for the loading. Only available when `loading_arrow = TRUE`.

loading_text_color default "black"; the color of taxa text. Only available when `loading_arrow = TRUE`.

loading_arrow_color default "grey30"; the color of taxa arrow. Only available when `loading_arrow = TRUE`.

loading_text_size default 3; the size of taxa text. Only available when `loading_arrow = TRUE`.

loading_text_italic default FALSE; whether using italic for the taxa text. Only available when loading_arrow = TRUE.

Returns: ggplot.

Examples:

```
t1$plot_ordination(plot_type = "point")
t1$plot_ordination(plot_color = "Group", plot_shape = "Group", plot_type = "point")
t1$plot_ordination(plot_color = "Group", plot_type = c("point", "ellipse"))
t1$plot_ordination(plot_color = "Group", plot_type = c("point", "centroid"),
  centroid_segment_linetype = 1)
```

Method cal_manova(): Calculate perMANOVA (Permutational Multivariate Analysis of Variance) based on <doi:10.1111/j.1442-9993.2001.01070.pp.x> and R vegan adonis2 function.

Usage:

```
trans_beta$cal_manova(
  manova_all = TRUE,
  manova_set = NULL,
  group = NULL,
  by_group = NULL,
  p_adjust_method = "fdr",
  ...
)
```

Arguments:

manova_all default TRUE; TRUE represents test for all the groups, i.e. the overall test; FALSE represents test for all the paired groups.

manova_set default NULL; other specified group set for manova, such as "Group + Type" and "Group*Type"; see also [adonis2](#). manova_set has higher priority than manova_all parameter. If manova_set is provided; manova_all is disabled.

group default NULL; a column name of sample_table used for manova. If NULL, search group variable stored in the object. Available when manova_set is not provided.

by_group default NULL; one column name in sample_table; used to perform paired comparisons within each group. Only available when manova_all = FALSE and manova_set is not provided.

p_adjust_method default "fdr"; p.adjust method; available when manova_all = FALSE; see method parameter of p.adjust function for available options.

... parameters passed to [adonis2](#) function of vegan package.

Returns: res_manova stored in object.

Examples:

```
t1$cal_manova(manova_all = TRUE)
```

Method cal_anosim(): Analysis of similarities (ANOSIM) based on R vegan anosim function.

Usage:

```
trans_beta$cal_anosim(
  paired = FALSE,
  group = NULL,
  by_group = NULL,
```

```

    p_adjust_method = "fdr",
    ...
)

```

Arguments:

paired default FALSE; whether perform paired test between any two combined groups from all the input groups.

group default NULL; a column name of sample_table. If NULL, search group variable stored in the object.

by_group default NULL; one column name in sample_table; used to perform paired comparisons within each group. Only available when paired = TRUE.

p_adjust_method default "fdr"; p.adjust method; available when paired = TRUE; see method parameter of p.adjust function for available options.

... parameters passed to anosim function of vegan package.

Returns: res_anosim stored in object.

Examples:

```
t1$cal_anosim()
```

Method cal_betadisper(): A wrapper for betadisper function in vegan package for multivariate homogeneity test of groups dispersions (PERMDISP).

Usage:

```
trans_beta$cal_betadisper(...)
```

Arguments:

... parameters passed to betadisper function.

Returns: res_betadisper stored in object.

Examples:

```
t1$cal_betadisper()
```

Method cal_group_distance(): Convert sample distances within groups or between groups.

Usage:

```

trans_beta$cal_group_distance(
  within_group = TRUE,
  by_group = NULL,
  ordered_group = NULL,
  sep = " vs "
)

```

Arguments:

within_group default TRUE; whether transform sample distance within groups, if FALSE, transform sample distance between any two groups.

by_group default NULL; one colname name of sample_table in microtable object. If provided, transform distances by the provided by_group parameter. This is especially useful for ordering and filtering values further. When within_group = TRUE, the result of by_group parameter is the format of paired groups. When within_group = FALSE, the result of by_group parameter is the format same with the group information in sample_table.

ordered_group default NULL; a vector representing the ordered elements of group parameter; only useful when within_group = FALSE.

sep default TRUE; a character string to separate the group names after merging them into a new name.

Returns: res_group_distance stored in object.

Examples:

```
\donttest{
t1$cal_group_distance(within_group = TRUE)
}
```

Method cal_group_distance_diff(): Differential test of distances among groups.

Usage:

```
trans_beta$cal_group_distance_diff(
  group = NULL,
  by_group = NULL,
  by_ID = NULL,
  ...
)
```

Arguments:

group default NULL; a column name of object\$res_group_distance used for the statistics; If NULL, use the group inside the object.

by_group default NULL; a column of object\$res_group_distance used to perform the differential test among elements in group parameter for each element in by_group parameter. So by_group has a larger scale than group parameter. This by_group is very different from the by_group parameter in the cal_group_distance function.

by_ID default NULL; a column of object\$res_group_distance used to perform paired t test or paired wilcox test for the paired data, such as the data of plant compartments for different plant species (ID). So by_ID should be the smallest unit of sample collection without any repetition in it.

... parameters passed to cal_diff function of [trans_alpha](#) class.

Returns: res_group_distance_diff stored in object.

Examples:

```
\donttest{
t1$cal_group_distance_diff()
}
```

Method plot_group_distance(): Plotting the distance between samples within or between groups.

Usage:

```
trans_beta$plot_group_distance(plot_group_order = NULL, ...)
```

Arguments:

plot_group_order default NULL; a vector used to order the groups in the plot.

... parameters (except measure) passed to plot_alpha function of [trans_alpha](#) class.

Returns: ggplot.

Examples:

```
\donttest{
t1$plot_group_distance()
}
```

Method `plot_clustering()`: Plotting clustering result based on the `ggdendro` package.

Usage:

```
trans_beta$plot_clustering(
  color_values = RColorBrewer::brewer.pal(8, "Dark2"),
  measure = NULL,
  group = NULL,
  replace_name = NULL
)
```

Arguments:

`color_values` default `RColorBrewer::brewer.pal(8, "Dark2")`; color palette for the text.
`measure` default `NULL`; beta diversity index; If `NULL`, using the measure when creating object
`group` default `NULL`; if provided, use this group to assign color.
`replace_name` default `NULL`; if provided, use this as label.

Returns: `ggplot`.

Examples:

```
t1$plot_clustering(group = "Group", replace_name = c("Saline", "Type"))
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
trans_beta$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
## -----
## Method `trans_beta$new`
## -----

data(dataset)
t1 <- trans_beta$new(dataset = dataset, measure = "bray", group = "Group")

## -----
## Method `trans_beta$cal_ordination`
## -----

t1$cal_ordination(ordination = "PCoA")

## -----
## Method `trans_beta$plot_ordination`
## -----
```

```

t1$plot_ordination(plot_type = "point")
t1$plot_ordination(plot_color = "Group", plot_shape = "Group", plot_type = "point")
t1$plot_ordination(plot_color = "Group", plot_type = c("point", "ellipse"))
t1$plot_ordination(plot_color = "Group", plot_type = c("point", "centroid"),
  centroid_segment_linetype = 1)

## -----
## Method `trans_beta$scal_manova`
## -----

t1$scal_manova(manova_all = TRUE)

## -----
## Method `trans_beta$scal_anosim`
## -----

t1$scal_anosim()

## -----
## Method `trans_beta$scal_betadisper`
## -----

t1$scal_betadisper()

## -----
## Method `trans_beta$scal_group_distance`
## -----

t1$scal_group_distance(within_group = TRUE)

## -----
## Method `trans_beta$scal_group_distance_diff`
## -----

t1$scal_group_distance_diff()

## -----
## Method `trans_beta$plot_group_distance`
## -----

t1$plot_group_distance()

## -----
## Method `trans_beta$plot_clustering`
## -----

```

```
t1$plot_clustering(group = "Group", replace_name = c("Saline", "Type"))
```

trans_classifier	<i>Create trans_classifier object for machine-learning-based model prediction.</i>
------------------	--

Description

This class is a wrapper for methods of machine-learning-based classification or regression models, including data pre-processing, feature selection, data split, model training, prediction, confusion-Matrix and ROC (Receiver Operator Characteristic) or PR (Precision-Recall) curve.

Author(s): Felipe Mansoldo and Chi Liu

Methods

Public methods:

- `trans_classifier$new()`
- `trans_classifier$cal_preProcess()`
- `trans_classifier$cal_feature_sel()`
- `trans_classifier$cal_split()`
- `trans_classifier$set_trainControl()`
- `trans_classifier$cal_train()`
- `trans_classifier$cal_feature_imp()`
- `trans_classifier$plot_feature_imp()`
- `trans_classifier$cal_predict()`
- `trans_classifier$plot_confusionMatrix()`
- `trans_classifier$cal_ROC()`
- `trans_classifier$plot_ROC()`
- `trans_classifier$cal_caretList()`
- `trans_classifier$clone()`

Method `new()`: Create the `trans_classifier` object.

Usage:

```
trans_classifier$new(
  dataset,
  x.predictors = "Genus",
  y.response = NULL,
  n.cores = 1
)
```

Arguments:

`dataset` the object of `microtable` Class.

`x.predictors` default "Genus"; character string or data.frame; a character string represents selecting the corresponding data from `microtable$taxa_abund`; data.frame represents other customized input. See the following available options:

'Genus' use Genus level table in `microtable$taxa_abund`, or other specific taxonomic rank, e.g. `'Phylum'`

'all' use all the taxa stored in `microtable$taxa_abund`

other input must be a `data.frame`; It should have the same format with the `data.frame` in `microtable$taxa_abund`, i.e. rows are features; cols are samples with same names in `sample_table`

`y.response` default `NULL`; the response variable in `sample_table` of input `microtable` object.

`n.cores` default 1; the CPU thread used.

Returns: `data_feature` and `data_response` in the object.

Examples:

```
\donttest{
data(dataset)
t1 <- trans_classifier$new(
dataset = dataset,
x.predictors = "Genus",
y.response = "Group")
}
```

Method `cal_preProcess()`: Pre-process (centering, scaling etc.) of the feature data based on the `caret::preProcess` function. See <https://topepo.github.io/caret/pre-processing.html> for more details.

Usage:

```
trans_classifier$cal_preProcess(...)
```

Arguments:

... parameters pass to `preProcess` function of `caret` package.

Returns: converted `data_feature` in the object.

Examples:

```
\dontrun{
t1$cal_preProcess(method = c("center", "scale", "nzv"))
}
```

Method `cal_feature_sel()`: Perform feature selection. See <https://topepo.github.io/caret/feature-selection-overview.html> for more details.

Usage:

```
trans_classifier$cal_feature_sel(
  boruta.maxRuns = 300,
  boruta.pValue = 0.01,
  boruta.repetitions = 4,
  ...
)
```

Arguments:

`boruta.maxRuns` default 300; maximal number of importance source runs; passed to the `maxRuns` parameter in `Boruta` function of `Boruta` package.

boruta.pValue default 0.01; p value passed to the pValue parameter in Boruta function of Boruta package.

boruta.repetitions default 4; repetition runs for the feature selection.

... parameters pass to Boruta function of Boruta package.

Returns: optimized data_feature in the object.

Examples:

```
\dontrun{
t1$cal_feature_sel(boruta.maxRuns = 300, boruta.pValue = 0.01)
}
```

Method cal_split(): Split data for training and testing.

Usage:

```
trans_classifier$cal_split(prop.train = 3/4)
```

Arguments:

prop.train default 3/4; the ratio of the data used for the training.

Returns: data_train and data_test in the object.

Examples:

```
\dontrun{
t1$cal_split(prop.train = 3/4)
}
```

Method set_trainControl(): Control parameters for the following training. See trainControl function of caret package for details.

Usage:

```
trans_classifier$set_trainControl(
  method = "repeatedcv",
  classProbs = TRUE,
  savePredictions = TRUE,
  ...
)
```

Arguments:

method default 'repeatedcv'; 'repeatedcv': Repeated k-Fold cross validation; see method parameter in trainControl function of caret package for available options.

classProbs default TRUE; should class probabilities be computed for classification models?; see classProbs parameter in caret::trainControl function.

savePredictions default TRUE; see savePredictions parameter in caret::trainControl function.

... parameters pass to trainControl function of caret package.

Returns: trainControl in the object.

Examples:

```
\dontrun{
t1$set_trainControl(method = 'repeatedcv')
}
```


Method `cal_train()`: Run the model training.

Usage:

```
trans_classifier$cal_train(method = "rf", max.mtry = 2, max.ntree = 200, ...)
```

Arguments:

`method` default "rf"; "rf": random forest; see method in `caret::train` function for other options.

`max.mtry` default 2; for method = "rf"; maximum mtry used for the tune grid to do hyperparameter tuning to optimize the model.

`max.ntree` default 200; for method = "rf"; maximum number of trees used to optimize the model.

... parameters pass to `caret::train` function.

Returns: `res_train` in the object.

Examples:

```
\dontrun{
# random forest
t1$cal_train(method = "rf")
# Support Vector Machines with Radial Basis Function Kernel
t1$cal_train(method = "svmRadial", tuneLength = 15)
}
```

Method `cal_feature_imp()`: Get feature importance from the training model.

Usage:

```
trans_classifier$cal_feature_imp(...)
```

Arguments:

... parameters pass to `varImp` function of `caret` package.

Returns: `res_feature_imp` in the object. One row for each predictor variable. The column(s) are different importance measures. For the method 'rf', it is `MeanDecreaseGini` (classification) or `IncNodePurity` (regression).

Examples:

```
\dontrun{
t1$cal_feature_imp()
}
```

Method `plot_feature_imp()`: Bar plot for feature importance.

Usage:

```
trans_classifier$plot_feature_imp(...)
```

Arguments:

... parameters pass to `plot_diff_bar` function of `trans_diff` package.

Returns: `ggplot2` object.

Examples:

```
\dontrun{
t1$plot_feature_imp(use_number = 1:20, coord_flip = FALSE)
}
```

Method `cal_predict()`: Run the prediction.

Usage:

```
trans_classifier$cal_predict(positive_class = NULL)
```

Arguments:

`positive_class` default NULL; see `positive` parameter in `confusionMatrix` function of `caret` package; If `positive_class` is NULL, use the first group in data as the positive class automatically.

Returns: `res_predict`, `res_confusion_fit` and `res_confusion_stats` stored in the object.

Examples:

```
\dontrun{
t1$cal_predict()
}
```

Method `plot_confusionMatrix()`: Plot the cross-tabulation of observed and predicted classes with associated statistics.

Usage:

```
trans_classifier$plot_confusionMatrix(
  plot_confusion = TRUE,
  plot_statistics = TRUE
)
```

Arguments:

`plot_confusion` default TRUE; whether plot the confusion matrix.

`plot_statistics` default TRUE; whether plot the statistics.

Returns: `ggplot` object.

Examples:

```
\dontrun{
t1$plot_confusionMatrix()
}
```

Method `cal_ROC()`: Get ROC (Receiver Operator Characteristic) curve data and the performance data.

Usage:

```
trans_classifier$cal_ROC(input = "pred")
```

Arguments:

`input` default "pred"; 'pred' or 'train'; 'pred' represents using prediction results; 'train' represents using training results.

Returns: a list `res_ROC` stored in the object.

Examples:

```
\dontrun{
t1$cal_ROC()
}
```

Method `plot_ROC()`: Plot ROC curve.

Usage:

```
trans_classifier$plot_ROC(
  plot_type = c("ROC", "PR")[1],
  plot_group = "all",
  color_values = RColorBrewer::brewer.pal(8, "Dark2"),
  add_AUC = TRUE,
  plot_method = FALSE,
  ...
)
```

Arguments:

`plot_type` default `c("ROC", "PR")[1]`; 'ROC' represents ROC (Receiver Operator Characteristic) curve; 'PR' represents PR (Precision-Recall) curve.

`plot_group` default `"all"`; 'all' represents all the classes in the model; 'add' represents all adding micro-average and macro-average results, see https://scikit-learn.org/stable/auto_examples/model_selection/ other options should be one or more class names, same with the names in Group column of `res_ROC$res_roc` from `cal_ROC` function.

`color_values` default `RColorBrewer::brewer.pal(8, "Dark2")`; colors used in the plot.

`add_AUC` default `TRUE`; whether add AUC in the legend.

`plot_method` default `FALSE`; If `TRUE`, show the method in the legend though only one method is found.

... parameters pass to `geom_path` function of `ggplot2` package.

Returns: `ggplot2` object.

Examples:

```
\dontrun{
t1$plot_ROC(size = 1, alpha = 0.7)
}
```

Method `cal_caretList()`: Use `caretList` function of `caretEnsemble` package to run multiple models. For the available models, please run `names(getModelInfo())`.

Usage:

```
trans_classifier$cal_caretList(...)
```

Arguments:

... parameters pass to `caretList` function of `caretEnsemble` package.

Returns: `res_caretList_models` object.

Examples:

```
\dontrun{
t1$cal_caretList(methodList = c('rf', 'svmRadial'))
}
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
trans_classifier$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
## -----  
## Method `trans_classifier$new`  
## -----  
  
data(dataset)  
t1 <- trans_classifier$new(  
  dataset = dataset,  
  x.predictors = "Genus",  
  y.response = "Group")  
  
## -----  
## Method `trans_classifier$cal_preProcess`  
## -----  
  
## Not run:  
t1$cal_preProcess(method = c("center", "scale", "nzv"))  
  
## End(Not run)  
  
## -----  
## Method `trans_classifier$cal_feature_sel`  
## -----  
  
## Not run:  
t1$cal_feature_sel(boruta.maxRuns = 300, boruta.pValue = 0.01)  
  
## End(Not run)  
  
## -----  
## Method `trans_classifier$cal_split`  
## -----  
  
## Not run:  
t1$cal_split(prop.train = 3/4)  
  
## End(Not run)  
  
## -----  
## Method `trans_classifier$set_trainControl`  
## -----  
  
## Not run:  
t1$set_trainControl(method = 'repeatedcv')  
  
## End(Not run)  
  
## -----  
## Method `trans_classifier$cal_train`
```

```
## -----  
  
## Not run:  
# random forest  
t1$cal_train(method = "rf")  
# Support Vector Machines with Radial Basis Function Kernel  
t1$cal_train(method = "svmRadial", tuneLength = 15)  
  
## End(Not run)  
  
## -----  
## Method `trans_classifier$cal_feature_imp`  
## -----  
  
## Not run:  
t1$cal_feature_imp()  
  
## End(Not run)  
  
## -----  
## Method `trans_classifier$plot_feature_imp`  
## -----  
  
## Not run:  
t1$plot_feature_imp(use_number = 1:20, coord_flip = FALSE)  
  
## End(Not run)  
  
## -----  
## Method `trans_classifier$cal_predict`  
## -----  
  
## Not run:  
t1$cal_predict()  
  
## End(Not run)  
  
## -----  
## Method `trans_classifier$plot_confusionMatrix`  
## -----  
  
## Not run:  
t1$plot_confusionMatrix()  
  
## End(Not run)  
  
## -----  
## Method `trans_classifier$cal_ROC`  
## -----  
  
## Not run:  
t1$cal_ROC()
```

```
## End(Not run)

## -----
## Method `trans_classifier$plot_ROC`
## -----

## Not run:
t1$plot_ROC(size = 1, alpha = 0.7)

## End(Not run)

## -----
## Method `trans_classifier$cal_caretList`
## -----

## Not run:
t1$cal_caretList(methodList = c('rf', 'svmRadial'))

## End(Not run)
```

trans_diff	<i>Create trans_diff object for the differential analysis on the taxonomic abundance</i>
------------	--

Description

This class is a wrapper for a series of differential abundance test and indicator analysis methods, including LEfSe based on the Segata et al. (2011) <doi:10.1186/gb-2011-12-6-r60>, random forest <doi:10.1016/j.geoderma.2018.09.035>, metastat based on White et al. (2009) <doi:10.1371/journal.pcbi.1000352>, non-parametric Kruskal-Wallis Rank Sum Test, Dunn's Kruskal-Wallis Multiple Comparisons based on the FSA package, Wilcoxon Rank Sum and Signed Rank Tests, t-test, anova, Scheirer Ray Hare test, R package metagenomeSeq Paulson et al. (2013) <doi:10.1038/nmeth.2658>, R package ANCOMBC <doi:10.1038/s41467-020-17041-7>, R package ALDEx2 <doi:10.1371/journal.pone.0067019; 10.1186/2049-2618-2-15>, R package MicrobiomeStat <doi:10.1186/s13059-022-02655-5>, beta regression <doi:10.18637/jss.v034.i02>, R package maaslin2, linear mixed-effects model and generalized linear mixed model.

Methods

Public methods:

- `trans_diff$new()`
- `trans_diff$plot_diff_abund()`
- `trans_diff$plot_diff_bar()`
- `trans_diff$plot_diff_cladogram()`
- `trans_diff$print()`
- `trans_diff$clone()`

Method `new()`:

Usage:

```
trans_diff$new(
  dataset = NULL,
  method = c("lelse", "rf", "metastat", "metagenomeSeq", "KW", "KW_dunn", "wilcox",
    "t.test", "anova", "scheirerRayHare", "lm", "ancombc2", "ALDEx2_t", "ALDEx2_kw",
    "DESeq2", "edgeR", "linda", "maaslin2", "betareg", "lme", "glmm", "glmm_beta")[1],
  group = NULL,
  taxa_level = "all",
  filter_thres = 0,
  alpha = 0.05,
  p_adjust_method = "fdr",
  transformation = NULL,
  remove_unknown = TRUE,
  lelse_subgroup = NULL,
  lelse_min_subsam = 10,
  lelse_norm = 1e+06,
  nresam = 0.6667,
  boots = 30,
  rf_ntree = 1000,
  group_choose_paired = NULL,
  metagenomeSeq_count = 1,
  ALDEx2_sig = c("wi.eBH", "kw.eBH"),
  by_group = NULL,
  by_ID = NULL,
  beta_pseudo = .Machine$double.eps,
  ...
)
```

Arguments:

`dataset` default NULL; [microtable](#) object.

`method` default "lelse"; see the following available options:

'lelse' LEfSe method based on Segata et al. (2011) <doi:10.1186/gb-2011-12-6-r60>

'rf' random forest and non-parametric test method based on An et al. (2019) <doi:10.1016/j.geoderma.2018.09.035>

'metastat' Metastat method for all paired groups based on White et al. (2009) <doi:10.1371/journal.pcbi.1000352>

'metagenomeSeq' zero-inflated log-normal model-based differential test method from metagenomeSeq package.

'KW' KW: Kruskal-Wallis Rank Sum Test for all groups (≥ 2)

'KW_dunn' Dunn's Kruskal-Wallis Multiple Comparisons when group number > 2 ; see `dunnTest` function in FSA package

'wilcox' Wilcoxon Rank Sum and Signed Rank Tests for all paired groups

't.test' Student's t-Test for all paired groups

'anova' ANOVA for one-way or multi-factor analysis; see `cal_diff` function of `trans_alpha` class

'scheirerRayHare' Scheirer Ray Hare test for nonparametric test used for a two-way factorial experiment; see `scheirerRayHare` function of `rcompanion` package

'lm' Linear Model based on the `lm` function

- 'ALDEx2_t'** runs Welch's t and Wilcoxon tests with ALDEx2 package; see also the test parameter in `ALDEx2::aldex` function; ALDEx2 uses the centred log-ratio (clr) transformation and estimates per-feature technical variation within each sample using Monte-Carlo instances drawn from the Dirichlet distribution; Reference: <doi:10.1371/journal.pone.0067019> and <doi:10.1186/2049-2618-2-15>; require ALDEx2 package to be installed (<https://bioconductor.org/packages/rel>)
- 'ALDEx2_kw'** runs Kruskal-Wallis and generalized linear model (glm) test with ALDEx2 package; see also the test parameter in `ALDEx2::aldex` function.
- 'DESeq2'** Differential expression analysis based on the Negative Binomial (a.k.a. Gamma-Poisson) distribution based on the DESeq2 package.
- 'edgeR'** The exactTest method of edgeR package is implemented.
- 'ancombc2'** Analysis of Compositions of Microbiomes with Bias Correction (ANCOM-BC) based on the `ancombc2` function from ANCOMBC package. If the `fix_formula` parameter is not provided, the function can automatically assign it by using `group` parameter. For this method, the `group` parameter is directly passed to the `group` parameter of `ancombc2` function. Reference: <doi:10.1038/s41467-020-17041-7><10.1038/s41592-023-02092-7>; Require ANCOMBC package to be installed (<https://bioconductor.org/packages/release/bioc/html/ANCOMBC2>)
- 'linda'** Linear Model for Differential Abundance Analysis of High-dimensional Compositional Data based on the `linda` function of MicrobiomeStat package. For `linda` method, please provide either the `group` parameter or the `formula` parameter. When the `formula` parameter is provided, it should start with '~' as it is directly used by the `linda` function. If the `group` parameter is used, the prefix '~' is not necessary as the function can automatically add it. The parameter `feature.dat.type = 'count'` has been fixed. Other parameters can be passed to the `linda` function. Reference: <doi:10.1186/s13059-022-02655-5>
- 'maaslin2'** finding associations between metadata and potentially high-dimensional microbial multi-omics data based on the Maaslin2 package. Using this option can invoke the `trans_env$cal_cor` function with `cor_method = "maaslin2"`.
- 'betareg'** Beta Regression based on the `betareg` package. Please see the `beta_pseudo` parameter for the use of pseudo value when there is 0 or 1 in the data
- 'lme'** Linear Mixed Effect Model based on the `lmerTest` package. In the return table, the significance of fixed factors are tested by function `anova`. The significance of 'Estimate' in each term of fixed factors comes from the model.
- 'glmm'** Generalized linear mixed model (GLMM) based on the `glmmTMB` package. The `formula` and `family` parameters are needed. Please refer to `glmmTMB` package to select the family function, e.g. `family = glmmTMB::lognormal(link = "log")`. The usage of `formula` is similar with that in 'lme' method. For more available parameters, please see `glmmTMB::glmmTMB` function and use parameter passing. In the return table, `Conditional_R2` and `Marginal_R2` represent total variance (explained by both fixed and random effects) and the variance explained by fixed effects, respectively. The significance of fixed factors are tested by Chi-square test from function `car::Anova`. The significance of 'Estimate' in each term of fixed factors comes from the model.
- 'glmm_beta'** Generalized linear mixed model with a family function of beta distribution, developed for the relative abundance (ranging from 0 to 1) of taxa specifically. This is an extension of the GLMM model in 'glmm' option. The only difference is in `glmm_beta` the family function is fixed with the beta distribution function, i.e. `family = glmmTMB::beta_family(link = "logit")`. Please see the `beta_pseudo` parameter for the use of pseudo value when there is 0 or 1 in the data

group default NULL; sample group used for the comparison; a colname of input `microtable$sample_table`; It is necessary when method is not "anova" or method is "anova" but formula is not provided. Once group is provided, the return `res_abund` will have mean and sd values for group.

taxa_level default "all"; 'all' represents using abundance data at all taxonomic ranks; For testing at a specific rank, provide taxonomic rank name, such as "Genus". If the provided taxonomic name is neither 'all' nor a colname in `tax_table` of input dataset, the function will use the features in input `microtable$otu_table` automatically.

filter_thres default 0; the abundance threshold, such as 0.0005 when the input is relative abundance; only available when method != "metastat". The features with abundances lower than `filter_thres` will be filtered.

alpha default 0.05; significance threshold to select taxa when method is "lefse" or "rf"; or used to generate significance letters when method is 'anova' or 'KW_dunn' like the alpha parameter in `cal_diff` of `trans_alpha` class.

p_adjust_method default "fdr"; p.adjust method; see method parameter of p.adjust function for other available options; "none" means disable p value adjustment; So when `p_adjust_method` = "none", `P.adj` is same with `P.unadj`.

transformation default NULL; feature abundance transformation method in the class `trans_norm`, such as 'AST' for the arc sine square root transformation. Only available when method is one of "KW", "KW_dunn", "wilcox", "t.test", "anova", "scheirerRayHare", "betareg" and "lme".

remove_unknown default TRUE; whether remove unknown features that donot have clear classification information.

lefse_subgroup default NULL; sample sub group used for sub-comparison in lefse; Segata et al. (2011) <doi:10.1186/gb-2011-12-6-r60>.

lefse_min_subsam default 10; sample numbers required in the subgroup test.

lefse_norm default 1000000; scale value in lefse.

nresam default 0.6667; sample number ratio used in each bootstrap for method = "lefse" or "rf".

boots default 30; bootstrap test number for method = "lefse" or "rf".

rf_ntree default 1000; see ntree in randomForest function of randomForest package when method = "rf".

group_choose_paired default NULL; a vector used for selecting the required groups for paired testing, only used for method = "metastat" or "metagenomeSeq".

metagenomeSeq_count default 1; Filter features to have at least 'counts' counts.; see the count parameter in `MRcoefs` function of `metagenomeSeq` package.

ALDEx2_sig default c("wi.eBH", "kw.eBH"); which column of the final result is used as the significance asterisk assignment; applied to method = "ALDEx2_t" or "ALDEx2_kw"; the first element is provided to "ALDEx2_t"; the second is provided to "ALDEx2_kw"; for "ALDEx2_t", the available choice is "wi.eBH" (Expected Benjamini-Hochberg corrected P value of Wilcoxon test) and "we.eBH" (Expected BH corrected P value of Welch's t test); for "ALDEx2_kw"; for "ALDEx2_t", the available choice is "kw.eBH" (Expected BH corrected P value of Kruskal-Wallis test) and "glm.eBH" (Expected BH corrected P value of glm test).

by_group default NULL; a column of `sample_table` used to perform the differential test among groups (group parameter) for each group (by_group parameter). So `by_group` has a higher level than group parameter. Same with the `by_group` parameter in `trans_alpha` class.

Only available when method is one of `c("KW", "KW_dunn", "wilcox", "t.test", "anova", "scheirerRayHare")`.

`by_ID` default NULL; a column of `sample_table` used to perform paired t test or paired wilcox test for the paired data, such as the data of plant compartments for different plant species (ID). So `by_ID` in `sample_table` should be the smallest unit of sample collection without any repetition in it. Same with the `by_ID` parameter in `trans_alpha` class.

`beta_pseudo` default `.Machine$double.eps`; the pseudo value used when the parameter method is 'betareg' or 'glmm_beta'. As the beta distribution function limits $0 < \text{response value} < 1$, a pseudo value will be added for the data that equal to 0. The data that equal to 1 will be replaced by $1/(1 + \text{beta_pseudo})$.

... parameters passed to `cal_diff` function of `trans_alpha` class when method is one of "KW", "KW_dunn", "wilcox", "t.test", "anova", "betareg", "lme", "glmm" or "glmm_beta"; passed to `ANCOMBC::ancombc2` function when method is "ancombc2" (except `tax_level`, `global` and `fix_formula` parameters); passed to `ALDEx2::aldex` function when method = "ALDEx2_t" or "ALDEx2_kw"; passed to `DESeq2::DESeq` function when method = "DESeq2"; passed to `MicrobiomeStat::linda` function when method = "linda"; passed to `trans_env$cal_cor` function when method = "maaslin2".

Returns: `res_diff` and `res_abund`.

res_abund includes mean abundance of each taxa (Mean), standard deviation (SD), standard error (SE) and sample number (N) in the group (Group).

res_diff is the detailed differential test result, may containing:

"Comparison": The groups for the comparison, maybe all groups or paired groups. If this column is not found, all groups are used;

"Group": Which group has the maximum median or mean value across the test groups; For non-parametric methods, median value; For t.test, mean value;

"Taxa": which taxa is used in this comparison;

"Method": Test method used in the analysis depending on the method input;

"LDA" or "MeanDecreaseGini": LDA: linear discriminant score in LEfSe; MeanDecreaseGini: mean decreasing gini index in random forest;

"P.unadj": original p value;

"P.adj": adjusted p value;

Others: qvalue: qvalue in metastat analysis.

Examples:

```
\donttest{
data(dataset)
t1 <- trans_diff$new(dataset = dataset, method = "lefse", group = "Group")
t1 <- trans_diff$new(dataset = dataset, method = "rf", group = "Group")
t1 <- trans_diff$new(dataset = dataset, method = "metastat", group = "Group", taxa_level = "Genus")
t1 <- trans_diff$new(dataset = dataset, method = "wilcox", group = "Group")
}
```

Method `plot_diff_abund()`: Plot the abundance of differential taxa

Usage:

```
trans_diff$plot_diff_abund(
  use_number = 1:20,
  color_values = RColorBrewer::brewer.pal(8, "Dark2"),
  select_group = NULL,
```

```

select_taxa = NULL,
simplify_names = TRUE,
keep_prefix = TRUE,
group_order = NULL,
barwidth = 0.9,
use_se = TRUE,
add_sig = FALSE,
add_sig_label = "Significance",
add_sig_label_color = "black",
add_sig_tip_length = 0.01,
y_start = 1.01,
y_increase = 0.05,
text_y_size = 10,
coord_flip = TRUE,
xtext_angle = 45,
...
)

```

Arguments:

`use_number` default 1:20; numeric vector; the taxa numbers (1:n) selected in the plot; If the n is larger than the number of total significant taxa, automatically use all the taxa.

`color_values` default `RColorBrewer::brewer.pal(8, "Dark2")`; colors palette.

`select_group` default NULL; this is used to select the paired groups. This parameter is especially useful when the comparison methods is applied to paired groups; The input `select_group` must be one of `objectres_diffComparison`.

`select_taxa` default NULL; character vector to provide taxa names. The taxa names should be same with the names shown in the plot, not the 'Taxa' column names in `objectres_diffTaxa`.

`simplify_names` default TRUE; whether use the simplified taxonomic name.

`keep_prefix` default TRUE; whether retain the taxonomic prefix.

`group_order` default NULL; a vector to order groups, i.e. reorder the legend and colors in plot; If NULL, the function can first check whether the group column of `sample_table` is factor. If yes, use the levels in it. If provided, overlook the levels in the group of `sample_table`.

`barwidth` default 0.9; the bar width in plot.

`use_se` default TRUE; whether use SE in plot, if FALSE, use SD.

`add_sig` default FALSE; whether add the significance label to the plot.

`add_sig_label` default "Significance"; select a colname of `object$res_diff` for the label text, such as 'P.adj' or 'Significance'.

`add_sig_label_color` default "black"; the color for the label text when `add_sig = TRUE`.

`add_sig_tip_length` default 0.01; the tip length for the added line when `add_sig = TRUE`.

`y_start` default 1.01; the y axis position from which to add the label; the default 1.01 means $1.01 * \text{Value}$; For method != "anova", all the start positions are same, i.e. $\text{Value} = \max(\text{Mean} + \text{SD} \text{ or } \text{Mean} + \text{SE})$; For method = "anova"; the stat position is calculated for each point, i.e. $\text{Value} = \text{Mean} + \text{SD} \text{ or } \text{Mean} + \text{SE}$.

`y_increase` default 0.05; the increasing y axis space to add label for paired groups; the default 0.05 means $0.05 * y_start * \text{Value}$; In addition, this parameter is also used to label the letters of anova result with the fixed $(1 + y_increase) * y_start * \text{Value}$.

`text_y_size` default 10; the size for the y axis text, i.e. feature text.

coord_flip default TRUE; whether flip cartesian coordinates so that horizontal becomes vertical, and vertical becomes horizontal.

xtext_angle default 45; number ranging from 0 to 90; used to make x axis text generate angle to reduce text overlap; only available when coord_flip = FALSE.

... parameters passed to ggsignif::stat_signif when add_sig = TRUE.

Returns: ggplot.

Examples:

```
\donttest{
t1 <- trans_diff$new(dataset = dataset, method = "anova", group = "Group", taxa_level = "Genus")
t1$plot_diff_abund(use_number = 1:10)
t1$plot_diff_abund(use_number = 1:10, add_sig = TRUE)
t1 <- trans_diff$new(dataset = dataset, method = "wilcox", group = "Group")
t1$plot_diff_abund(use_number = 1:20)
t1$plot_diff_abund(use_number = 1:20, add_sig = TRUE)
t1 <- trans_diff$new(dataset = dataset, method = "lelse", group = "Group")
t1$plot_diff_abund(use_number = 1:20)
t1$plot_diff_abund(use_number = 1:20, add_sig = TRUE)
}
```

Method plot_diff_bar(): Bar plot for indicator index, such as LDA score and P value.

Usage:

```
trans_diff$plot_diff_bar(
  color_values = RColorBrewer::brewer.pal(8, "Dark2"),
  color_group_map = FALSE,
  use_number = 1:10,
  threshold = NULL,
  select_group = NULL,
  keep_full_name = FALSE,
  keep_prefix = TRUE,
  group_order = NULL,
  axis_text_y = 12,
  coord_flip = TRUE,
  xtext_angle = 45,
  xtext_size = 10,
  heatmap_cell = "P.unadj",
  heatmap_sig = "Significance",
  heatmap_x = "Factors",
  heatmap_y = "Taxa",
  heatmap_lab_fill = "P value",
  ...
)
```

Arguments:

color_values default RColorBrewer::brewer.pal(8, "Dark2"); colors palette for different groups.

color_group_map default FALSE; whether match the colors to groups in order to fix the color in each group when part of groups are not shown in the plot. When color_group_map =

TRUE, the group_order inside the object will be used as full groups set to guide the color extraction.

use_number default 1:10; numeric vector; the taxa numbers used in the plot, i.e. 1:n.

threshold default NULL; threshold value of indicators for selecting taxa, such as 3 for LDA score of LEfSe.

select_group default NULL; this is used to select the paired group when multiple comparisons are generated; The input select_group must be one of object\$res_diff\$Comparison.

keep_full_name default FALSE; whether keep the taxonomic full lineage names.

keep_prefix default TRUE; whether retain the taxonomic prefix, such as "g__".

group_order default NULL; a vector to order the legend and colors in plot; If NULL, the function can first determine whether the group column of microtable\$sample_table is factor. If yes, use the levels in it. If provided, this parameter can overwrite the levels in the group of microtable\$sample_table.

axis_text_y default 12; the size for the y axis text.

coord_flip default TRUE; whether flip cartesian coordinates so that horizontal becomes vertical, and vertical becomes horizontal.

xtext_angle default 45; number ranging from 0 to 90; used to make x axis text generate angle to reduce text overlap; only available when coord_flip = FALSE.

xtext_size default 10; the text size of x axis.

heatmap_cell default "P.unadj"; the column of data for the cell of heatmap when formula with multiple factors is found in the method.

heatmap_sig default "Significance"; the column of data for the significance label of heatmap.

heatmap_x default "Factors"; the column of data for the x axis of heatmap.

heatmap_y default "Taxa"; the column of data for the y axis of heatmap.

heatmap_lab_fill default "P value"; legend title of heatmap.

... parameters passing to `geom_bar` for the bar plot or `plot_cor` function in `trans_env` class for the heatmap of multiple factors when formula is found in the method.

Returns: ggplot.

Examples:

```
\donttest{
t1$plot_diff_bar(use_number = 1:20)
}
```

Method `plot_diff_cladogram()`: Plot the cladogram using taxa with significant difference.

Usage:

```
trans_diff$plot_diff_cladogram(
  color = RColorBrewer::brewer.pal(8, "Dark2"),
  group_order = NULL,
  use_taxa_num = 200,
  filter_taxa = NULL,
  use_feature_num = NULL,
  clade_label_level = 4,
  select_show_labels = NULL,
  only_select_show = FALSE,
  sep = "|",
```

```

branch_size = 0.2,
alpha = 0.2,
clade_label_size = 2,
clade_label_size_add = 5,
clade_label_size_log = exp(1),
node_size_scale = 1,
node_size_offset = 1,
annotation_shape = 22,
annotation_shape_size = 5
)

```

Arguments:

`color` default `RColorBrewer::brewer.pal(8, "Dark2")`; color palette used in the plot.

`group_order` default `NULL`; a vector to order the legend in plot; If `NULL`, the function can first check whether the `group` column of `sample_table` is factor. If yes, use the levels in it. If provided, this parameter can overwrite the levels in the `group` of `sample_table`. If the number of provided `group_order` is less than the number of groups in `res_diff$Group`, the function will select the groups of `group_order` automatically.

`use_taxa_num` default 200; integer; The taxa number used in the background tree plot; select the taxa according to the mean abundance .

`filter_taxa` default `NULL`; The mean relative abundance used to filter the taxa with low abundance.

`use_feature_num` default `NULL`; integer; The feature number used in the plot; select the features according to the LDA score (method = "lfe") or MeanDecreaseGini (method = "rf") from high to low.

`clade_label_level` default 4; the taxonomic level for marking the label with letters, root is the largest.

`select_show_labels` default `NULL`; character vector; The features to show in the plot with full label names, not the letters.

`only_select_show` default `FALSE`; whether only use the the select features in the parameter `select_show_labels`.

`sep` default "|"; the separate character in the taxonomic information.

`branch_size` default 0.2; numeric, size of branch.

`alpha` default 0.2; shading of the color.

`clade_label_size` default 2; basic size for the clade label; please also see `clade_label_size_add` and `clade_label_size_log`.

`clade_label_size_add` default 5; added basic size for the clade label; see the formula in `clade_label_size_log` parameter.

`clade_label_size_log` default `exp(1)`; the base of log function for added size of the clade label; the size formula: `clade_label_size + log(clade_label_level + clade_label_size_add, base = clade_label_size_log)`; so use `clade_label_size_log`, `clade_label_size_add` and `clade_label_size` can totally control the label size for different taxonomic levels.

`node_size_scale` default 1; scale for the node size.

`node_size_offset` default 1; offset for the node size.

`annotation_shape` default 22; shape used in the annotation legend.

`annotation_shape_size` default 5; size used in the annotation legend.

Returns: ggplot.

Examples:

```
\donttest{
t1$plot_diff_cladogram(use_taxa_num = 100, use_feature_num = 30, select_show_labels = NULL)
}
```

Method print(): Print the trans_alpha object.

Usage:

```
trans_diff$print()
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
trans_diff$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## -----
## Method `trans_diff$new`
## -----

data(dataset)
t1 <- trans_diff$new(dataset = dataset, method = "lelse", group = "Group")
t1 <- trans_diff$new(dataset = dataset, method = "rf", group = "Group")
t1 <- trans_diff$new(dataset = dataset, method = "metastat", group = "Group", taxa_level = "Genus")
t1 <- trans_diff$new(dataset = dataset, method = "wilcox", group = "Group")

## -----
## Method `trans_diff$plot_diff_abund`
## -----

t1 <- trans_diff$new(dataset = dataset, method = "anova", group = "Group", taxa_level = "Genus")
t1$plot_diff_abund(use_number = 1:10)
t1$plot_diff_abund(use_number = 1:10, add_sig = TRUE)
t1 <- trans_diff$new(dataset = dataset, method = "wilcox", group = "Group")
t1$plot_diff_abund(use_number = 1:20)
t1$plot_diff_abund(use_number = 1:20, add_sig = TRUE)
t1 <- trans_diff$new(dataset = dataset, method = "lelse", group = "Group")
t1$plot_diff_abund(use_number = 1:20)
t1$plot_diff_abund(use_number = 1:20, add_sig = TRUE)

## -----
## Method `trans_diff$plot_diff_bar`
## -----
```

```
t1$plot_diff_bar(use_number = 1:20)

## -----
## Method `trans_diff$plot_diff_cladogram`
## -----

t1$plot_diff_cladogram(use_taxa_num = 100, use_feature_num = 30, select_show_labels = NULL)
```

trans_env	<i>Create trans_env object to analyze the association between environmental factor and microbial community.</i>
-----------	---

Description

This class is a wrapper for a series of operations associated with environmental measurements, including redundancy analysis, mantel test, correlation analysis and linear fitting.

Methods

Public methods:

- `trans_env$new()`
- `trans_env$scal_diff()`
- `trans_env$plot_diff()`
- `trans_env$scal_autocor()`
- `trans_env$scal_ordination()`
- `trans_env$scal_ordination_anova()`
- `trans_env$scal_ordination_envfit()`
- `trans_env$trans_ordination()`
- `trans_env$plot_ordination()`
- `trans_env$scal_mantel()`
- `trans_env$scal_cor()`
- `trans_env$plot_cor()`
- `trans_env$plot_scatterfit()`
- `trans_env$print()`
- `trans_env$clone()`

Method `new()`:

Usage:


```
trans_env$new(
  dataset = NULL,
  env_cols = NULL,
  add_data = NULL,
  character2numeric = FALSE,
  standardize = FALSE,
  complete_na = FALSE
)
```

Arguments:

dataset the object of `microtable` Class.

env_cols default NULL; either numeric vector or character vector to select columns in `microtable$sample_table`, i.e. `dataset$sample_table`. This parameter should be used in the case that all the required environmental data is in `sample_table` of your `microtable` object. Otherwise, please use `add_data` parameter.

add_data default NULL; `data.frame` format; provide the environmental data in the format `data.frame`; rownames should be sample names. This parameter should be used when the `microtable$sample_table` object does not have environmental data. Under this circumstance, the `env_cols` parameter can not be used because no data can be selected.

character2numeric default FALSE; whether convert the characters or factors to numeric values.

standardize default FALSE; whether scale environmental variables to zero mean and unit variance.

complete_na default FALSE; Whether fill the NA (missing value) in the environmental data; If TRUE, the function can run the interpolation with the `mice` package.

Returns: `data_env` stored in the object.

Examples:

```
data(dataset)
data(env_data_16S)
t1 <- trans_env$new(dataset = dataset, add_data = env_data_16S[, 4:11])
```

Method `cal_diff()`: Differential test of environmental variables across groups.

Usage:

```
trans_env$cal_diff(
  group = NULL,
  by_group = NULL,
  method = c("KW", "KW_dunn", "wilcox", "t.test", "anova", "scheirerRayHare", "lm",
    "lme", "glm")[1],
  ...
)
```

Arguments:

group default NULL; a colname of `sample_table` used to compare values across groups.

by_group default NULL; perform differential test among groups (`group` parameter) within each group (`by_group` parameter).

method default "KW"; see the following available options:

'KW' KW: Kruskal-Wallis Rank Sum Test for all groups (≥ 2)

- '**KW_dunn**' Dunn's Kruskal-Wallis Multiple Comparisons, see `dunnTest` function in FSA package
- '**wilcox**' Wilcoxon Rank Sum and Signed Rank Tests for all paired groups
- '**t.test**' Student's t-Test for all paired groups
- '**anova**' Duncan's new multiple range test for one-way anova; see `duncan.test` function of `agricolae` package. For multi-factor anova, see `aov`
- '**scheirerRayHare**' Scheirer Ray Hare test for nonparametric test used for a two-way factorial experiment; see `scheirerRayHare` function of `rcompanion` package
- '**lm**' Linear model based on the `lm` function
- '**lme**' lme: Linear Mixed Effect Model based on the `lmerTest` package. The formula parameter should be provided.
- '**glmm**' Generalized linear mixed model (GLMM) based on the `glmmTMB` package. The formula and family parameters are needed. Please refer to `glmmTMB` package to select the family function, e.g. `family = glmmTMB::lognormal(link = "log")`. The usage of formula is similar with that in 'lme' method. For the details of return table, please refer to the help document of `trans_diff` class.

... parameters passed to `cal_diff` function of `trans_alpha` class.

Returns: `res_diff` stored in the object. In the data frame, 'Group' column means that the group has the maximum median or mean value across the test groups; For non-parametric methods, median value; For `t.test`, mean value.

Examples:

```
\donttest{
t1$cal_diff(group = "Group", method = "KW")
t1$cal_diff(group = "Group", method = "anova")
}
```

Method `plot_diff()`: Plot environmental variables across groups and add the significance label.

Usage:

```
trans_env$plot_diff(...)
```

Arguments:

... parameters passed to `plot_alpha` in `trans_alpha` class. Please see `plot_alpha` function of `trans_alpha` for all the available parameters.

Method `cal_autocor()`: Calculate the autocorrelations among environmental variables.

Usage:

```
trans_env$cal_autocor(
  group = NULL,
  ggpairs = TRUE,
  color_values = RColorBrewer::brewer.pal(8, "Dark2"),
  alpha = 0.8,
  ...
)
```

Arguments:

group default NULL; a colname of sample_table; used to perform calculations for different groups.

ggpairs default TRUE; whether use GGally::ggpairs function to plot the correlation results.

color_values default RColorBrewer::brewer.pal(8, "Dark2"); colors palette.

alpha default 0.8; the alpha value to add transparency in colors; useful when group is not NULL.

... parameters passed to GGally::ggpairs when ggpairs = TRUE or passed to cal_cor of trans_env class when ggpairs = FALSE.

Returns: ggmatrix when ggpairs = TRUE or data.frame object when ggpairs = FALSE.

Examples:

```
\dontrun{
# Spearman correlation
t1$cal_autocor(upper = list(continuous = GGally::wrap("cor", method= "spearman")))
}
```

Method cal_ordination(): Redundancy analysis (RDA) and Correspondence Analysis (CCA) based on the vegan package.

Usage:

```
trans_env$cal_ordination(
  method = c("RDA", "dbRDA", "CCA")[1],
  feature_sel = FALSE,
  taxa_level = NULL,
  taxa_filter_thres = NULL,
  use_measure = NULL,
  add_matrix = NULL,
  ...
)
```

Arguments:

method default c("RDA", "dbRDA", "CCA")[1]; the ordination method.

feature_sel default FALSE; whether perform the feature selection based on forward selection method.

taxa_level default NULL; If use RDA or CCA, provide the taxonomic rank, such as "Phylum" or "Genus"; If use otu_table; please set taxa_level = "OTU".

taxa_filter_thres default NULL; relative abundance threshold used to filter taxa when method is "RDA" or "CCA".

use_measure default NULL; a name of beta diversity matrix; only available when parameter method = "dbRDA"; If not provided, use the first beta diversity matrix in the microtable\$beta_diversity automatically.

add_matrix default NULL; additional distance matrix provided, when the user does not want to use the beta diversity matrix within the dataset; only available when method = "dbRDA".

... parameters passed to dbrda, rda or cca function according to the method parameter.

Returns: res_ordination and res_ordination_R2 stored in the object.

Examples:

```
\donttest{
t1$cal_ordination(method = "dbRDA", use_measure = "bray")
t1$cal_ordination(method = "RDA", taxa_level = "Genus")
t1$cal_ordination(method = "CCA", taxa_level = "Genus")
}
```

Method `cal_ordination_anova()`: Use anova to test the significance of the terms and axis in ordination.

Usage:

```
trans_env$cal_ordination_anova(...)
```

Arguments:

... parameters passed to anova function.

Returns: `res_ordination_terms` and `res_ordination_axis` stored in the object.

Examples:

```
\donttest{
t1$cal_ordination_anova()
}
```

Method `cal_ordination_envfit()`: Fit each environmental vector onto the ordination to obtain the contribution of each variable.

Usage:

```
trans_env$cal_ordination_envfit(...)
```

Arguments:

... the parameters passed to `vegan::envfit` function.

Returns: `res_ordination_envfit` stored in the object.

Examples:

```
\donttest{
t1$cal_ordination_envfit()
}
```

Method `trans_ordination()`: Transform ordination results for the following plot.

Usage:

```
trans_env$trans_ordination(
  show_taxa = 10,
  adjust_arrow_length = FALSE,
  min_perc_env = 0.1,
  max_perc_env = 0.8,
  min_perc_tax = 0.1,
  max_perc_tax = 0.8
)
```

Arguments:

`show_taxa` default 10; taxa number shown in the plot.

`adjust_arrow_length` default FALSE; whether adjust the arrow length to be clearer.

min_perc_env default 0.1; used for scaling up the minimum of env arrow; multiply by the maximum distance between samples and origin.

max_perc_env default 0.8; used for scaling up the maximum of env arrow; multiply by the maximum distance between samples and origin.

min_perc_tax default 0.1; used for scaling up the minimum of tax arrow; multiply by the maximum distance between samples and origin.

max_perc_tax default 0.8; used for scaling up the maximum of tax arrow; multiply by the maximum distance between samples and origin.

Returns: res_ordination_trans stored in the object.

Examples:

```
\donttest{
t1$trans_ordination(adjust_arrow_length = TRUE, min_perc_env = 0.1, max_perc_env = 1)
}
```

Method plot_ordination(): plot ordination result.

Usage:

```
trans_env$plot_ordination(
  plot_color = NULL,
  plot_shape = NULL,
  color_values = RColorBrewer::brewer.pal(8, "Dark2"),
  shape_values = c(16, 17, 7, 8, 15, 18, 11, 10, 12, 13, 9, 3, 4, 0, 1, 2, 14),
  env_text_color = "black",
  env_arrow_color = "grey30",
  taxa_text_color = "firebrick1",
  taxa_arrow_color = "firebrick1",
  env_text_size = 3.7,
  taxa_text_size = 3,
  taxa_text_italic = TRUE,
  plot_type = "point",
  point_size = 3,
  point_alpha = 0.8,
  centroid_segment_alpha = 0.6,
  centroid_segment_size = 1,
  centroid_segment_linetype = 3,
  ellipse_chull_fill = TRUE,
  ellipse_chull_alpha = 0.1,
  ellipse_level = 0.9,
  ellipse_type = "t",
  add_sample_label = NULL,
  env_nudge_x = NULL,
  env_nudge_y = NULL,
  taxa_nudge_x = NULL,
  taxa_nudge_y = NULL,
  ...
)
```

Arguments:

plot_color default NULL; a colname of sample_table to assign colors to different groups.
 plot_shape default NULL; a colname of sample_table to assign shapes to different groups.
 color_values default RColorBrewer::brewer.pal(8, "Dark2"); color pallete for different groups.
 shape_values default c(16, 17, 7, 8, 15, 18, 11, 10, 12, 13, 9, 3, 4, 0, 1, 2, 14); a vector for point shape types of groups, see ggplot2 tutorial.
 env_text_color default "black"; environmental variable text color.
 env_arrow_color default "grey30"; environmental variable arrow color.
 taxa_text_color default "firebrick1"; taxa text color.
 taxa_arrow_color default "firebrick1"; taxa arrow color.
 env_text_size default 3.7; environmental variable text size.
 taxa_text_size default 3; taxa text size.
 taxa_text_italic default TRUE; "italic"; whether use "italic" style for the taxa text.
 plot_type default "point"; plotting type of samples; one or more elements of "point", "ellipse", "chull", "centroid" and "none"; "none" denotes nothing.

- 'point' add point
- 'ellipse' add confidence ellipse for points of each group
- 'chull' add convex hull for points of each group
- 'centroid' add centroid line of each group

point_size default 3; point size in plot when "point" is in plot_type.
 point_alpha default .8; point transparency in plot when "point" is in plot_type.
 centroid_segment_alpha default 0.6; segment transparency in plot when "centroid" is in plot_type.
 centroid_segment_size default 1; segment size in plot when "centroid" is in plot_type.
 centroid_segment_linetype default 3; an integer; the line type related with centroid in plot when "centroid" is in plot_type.
 ellipse_chull_fill default TRUE; whether fill colors to the area of ellipse or chull.
 ellipse_chull_alpha default 0.1; color transparency in the ellipse or convex hull depending on whether "ellipse" or "centroid" is in plot_type.
 ellipse_level default .9; confidence level of ellipse when "ellipse" is in plot_type.
 ellipse_type default "t"; ellipse type when "ellipse" is in plot_type; see type in [stat_ellipse](#).
 add_sample_label default NULL; the column name in sample table, if provided, show the point name in plot.
 env_nudge_x default NULL; numeric vector to adjust the env text x axis position; passed to nudge_x parameter of ggrepel::geom_text_repel function; default NULL represents automatic adjustment; the length must be same with the row number of object\$res_ordination_trans\$df_arrows. For example, if there are 5 env variables, env_nudge_x should be something like c(0.1, 0, -0.2, 0, 0). Note that this parameter and env_nudge_y is generally used when the automatic text adjustment is not very well.
 env_nudge_y default NULL; numeric vector to adjust the env text y axis position; passed to nudge_y parameter of ggrepel::geom_text_repel function; default NULL represents automatic adjustment; the length must be same with the row number of object\$res_ordination_trans\$df_arrows. For example, if there are 5 env variables, env_nudge_y should be something like c(0.1, 0, -0.2, 0, 0).

`taxa_nudge_x` default NULL; numeric vector to adjust the taxa text x axis position; passed to `nudge_x` parameter of `ggrepel::geom_text_repel` function; default NULL represents automatic adjustment; the length must be same with the row number of `object$res_ordination_trans$df_arrows_sp`. For example, if 3 taxa are shown, `taxa_nudge_x` should be something like `c(0.3, -0.2, 0)`.

`taxa_nudge_y` default NULL; numeric vector to adjust the taxa text y axis position; passed to `nudge_y` parameter of `ggrepel::geom_text_repel` function; default NULL represents automatic adjustment; the length must be same with the row number of `object$res_ordination_trans$df_arrows_sp`. For example, if 3 taxa are shown, `taxa_nudge_y` should be something like `c(-0.2, 0, 0.4)`.

... parameters passed to `geom_point` for controlling sample points.

Returns: ggplot object.

Examples:

```
\donttest{
t1$cal_ordination(method = "RDA")
t1$trans_ordination(adjust_arrow_length = TRUE, max_perc_env = 1.5)
t1$plot_ordination(plot_color = "Group")
t1$plot_ordination(plot_color = "Group", plot_shape = "Group", plot_type = c("point", "ellipse"))
t1$plot_ordination(plot_color = "Group", plot_type = c("point", "chull"))
t1$plot_ordination(plot_color = "Group", plot_type = c("point", "centroid"),
  centroid_segment_linetype = 1)
t1$plot_ordination(plot_color = "Group", env_nudge_x = c(0.4, 0, 0, 0, 0, -0.2, 0, 0),
  env_nudge_y = c(0.6, 0, 0.2, 0.5, 0, 0.1, 0, 0.2))
}
```

Method `cal_mantel()`: Mantel test between beta diversity matrix and environmental data.

Usage:

```
trans_env$cal_mantel(
  partial_mantel = FALSE,
  add_matrix = NULL,
  use_measure = NULL,
  method = "pearson",
  p_adjust_method = "fdr",
  by_group = NULL,
  ...
)
```

Arguments:

`partial_mantel` default FALSE; whether use partial mantel test; If TRUE, use other all measurements as the `zdis` in each calculation.

`add_matrix` default NULL; additional distance matrix provided when the beta diversity matrix in the dataset is not used.

`use_measure` default NULL; a name of beta diversity matrix. If necessary and not provided, use the first beta diversity matrix.

`method` default "pearson"; one of "pearson", "spearman" and "kendall"; correlation method; see `method` parameter in `vegan::mantel` function.

`p_adjust_method` default "fdr"; `p.adjust` method; see `method` parameter of `p.adjust` function for available options.

by_group default NULL; one column name or number in sample_table; used to perform mantel test for different groups separately.

... parameters passed to `mantel` of `vegan` package.

Returns: `res_mantel` in object.

Examples:

```
\donttest{
t1$cal_mantel(use_measure = "bray")
t1$cal_mantel(partial_mantel = TRUE, use_measure = "bray")
}
```

Method `cal_cor()`: Calculate the correlations between taxonomic abundance and environmental variables. Actually, it can also be applied to other correlation between any two variables from two tables.

Usage:

```
trans_env$cal_cor(
  use_data = c("Genus", "all", "other")[1],
  cor_method = c("pearson", "spearman", "kendall", "maaslin2")[1],
  add_abund_table = NULL,
  filter_thres = 0,
  use_taxa_num = NULL,
  other_taxa = NULL,
  p_adjust_method = "fdr",
  p_adjust_type = c("All", "Taxa", "Env")[1],
  by_group = NULL,
  group_use = NULL,
  group_select = NULL,
  taxa_name_full = TRUE,
  tmp_input_maaslin2 = "tmp_input",
  tmp_output_maaslin2 = "tmp_output",
  ...
)
```

Arguments:

`use_data` default "Genus"; "Genus", "all" or "other"; "Genus" or other taxonomic name: use genus or other taxonomic abundance table in `taxa_abund`; "all": use all merged taxonomic abundance table; "other": provide additional taxa name with `other_taxa` parameter which is necessary.

`cor_method` default "pearson"; "pearson", "spearman", "kendall" or "maaslin2"; correlation method. "pearson", "spearman" or "kendall" all refer to the correlation analysis based on the `cor.test` function in R. "maaslin2" is the method in `Maaslin2` package for finding associations between metadata and potentially high-dimensional microbial multi-omics data.

`add_abund_table` default NULL; additional data table to be used. Samples must be rows.

`filter_thres` default 0; the abundance threshold, such as 0.0005 when the input is relative abundance. The features with abundances lower than `filter_thres` will be filtered. This parameter cannot be applied when `add_abund_table` parameter is provided.

`use_taxa_num` default NULL; integer; a number used to select high abundant taxa; only useful when `use_data` parameter is a taxonomic level, e.g., "Genus".

other_taxa default NULL; character vector containing a series of feature names; used when use_data = "other"; provided names should be standard full names used to select taxa from all the tables in taxa_abund list of the microtable object; please see the example.

p_adjust_method default "fdr"; p.adjust method; see method parameter of p.adjust function for available options. p_adjust_method = "none" can disable the p value adjustment.

p_adjust_type default "All"; "All", "Taxa" or "Env"; P value adjustment type. "Env": adjustment for each environmental variable separately; "Taxa": adjustment for each taxon separately; "All": adjustment for all the data together no matter whether by_group is provided.

by_group default NULL; one column name or number in sample_table; calculate correlations for different groups separately.

group_use default NULL; numeric or character vector to select one column in sample_table for selecting samples; together with group_select.

group_select default NULL; the group name used; remain samples within the group.

taxa_name_full default TRUE; Whether use the complete taxonomic name of taxa.

tmp_input_maaslin2 default "tmp_input"; the temporary folder used to save the input files for Maaslin2.

tmp_output_maaslin2 default "tmp_output"; the temporary folder used to save the output files of Maaslin2.

... parameters passed to Maaslin2 function of Maaslin2 package.

Returns: res_cor stored in the object.

Examples:

```
\donttest{
t2 <- trans_diff$new(dataset = dataset, method = "rf", group = "Group", rf_taxa_level = "Genus")
t1 <- trans_env$new(dataset = dataset, add_data = env_data_16S[, 4:11])
t1$cal_cor(use_data = "other", p_adjust_method = "fdr", other_taxa = t2$res_diff$Taxa[1:40])
}
```

Method plot_cor(): Plot correlation heatmap.

Usage:

```
trans_env$plot_cor(
  color_vector = c("#053061", "white", "#A50026"),
  color_palette = NULL,
  pheatmap = FALSE,
  filter_feature = NULL,
  filter_env = NULL,
  ylab_type_italic = FALSE,
  keep_full_name = FALSE,
  keep_prefix = TRUE,
  text_y_order = NULL,
  text_x_order = NULL,
  xtext_angle = 30,
  xtext_size = 10,
  xtext_color = "black",
  ytext_size = NULL,
  ytext_color = "black",
```

```

sig_label_size = 4,
font_family = NULL,
cluster_ggplot = "none",
cluster_height_rows = 0.2,
cluster_height_cols = 0.2,
text_y_position = "right",
mylabels_x = NULL,
na.value = "grey50",
trans = "identity",
...
)

```

Arguments:

`color_vector` default `c("#053061", "white", "#A50026")`; colors with only three values representing low, middle and high values.

`color_palette` default `NULL`; a customized palette with more color values to be used instead of the parameter `color_vector`.

`pheatmap` default `FALSE`; whether use `pheatmap` package to plot the heatmap.

`filter_feature` default `NULL`; character vector; used to filter features that only have labels in the `filter_feature` vector. For example, `filter_feature = ""` can be used to remove features that only have "", no any "*".

`filter_env` default `NULL`; character vector; used to filter environmental variables that only have labels in the `filter_env` vector. For example, `filter_env = ""` can be used to remove features that only have "", no any "*".

`ylab_type_italic` default `FALSE`; whether use italic type for y lab text.

`keep_full_name` default `FALSE`; whether use the complete taxonomic name.

`keep_prefix` default `TRUE`; whether retain the taxonomic prefix.

`text_y_order` default `NULL`; character vector; provide customized text order for y axis; shown in the plot from the top down.

`text_x_order` default `NULL`; character vector; provide customized text order for x axis.

`xtext_angle` default 30; number ranging from 0 to 90; used to adjust x axis text angle.

`xtext_size` default 10; x axis text size.

`xtext_color` default "black"; x axis text color.

`ytext_size` default `NULL`; y axis text size. `NULL` means default `ggplot2` value.

`ytext_color` default "black"; y axis text color.

`sig_label_size` default 4; the size of significance label shown in the cell.

`font_family` default `NULL`; font family used in `ggplot2`; only available when `pheatmap = FALSE`.

`cluster_ggplot` default "none"; add clustering dendrogram for `ggplot2` based heatmap. Available options: "none", "row", "col" or "both". "none": no any clustering used; "row": add clustering for rows; "col": add clustering for columns; "both": add clustering for both rows and columns. Only available when `pheatmap = FALSE`.

`cluster_height_rows` default 0.2, the dendrogram plot height for rows; available when `cluster_ggplot` is not "none".

`cluster_height_cols` default 0.2, the dendrogram plot height for columns; available when `cluster_ggplot` is not "none".

text_y_position default "right"; "left" or "right"; the y axis text position for ggplot2 based heatmap.

mylabels_x default NULL; provide x axis text labels additionally; only available when pheatmap = TRUE.

na.value default "grey50"; the color for the missing values when pheatmap = FALSE.

trans default "identity"; the transformation for continuous scales in the legend when pheatmap = FALSE; see the trans item in ggplot2::scale_colour_gradientn.

... parameters passed to ggplot2::geom_tile or pheatmap::pheatmap, depending on the parameter pheatmap is FALSE or TRUE.

Returns: plot.

Examples:

```
\donttest{
t1$plot_cor(pheatmap = FALSE)
}
```

Method plot_scatterfit(): Scatter plot with fitted line based on the correlation or regression. The most important thing is to make sure that the input x and y have corresponding sample orders. If one of x and y is a matrix, the other will be also transformed to matrix with Euclidean distance. Then, both of them are transformed to be vectors. If x or y is a vector with a single value, x or y will be assigned according to the column selection of the data_env in the object.

Usage:

```
trans_env$plot_scatterfit(
  x = NULL,
  y = NULL,
  group = NULL,
  group_order = NULL,
  color_values = RColorBrewer::brewer.pal(8, "Dark2"),
  shape_values = NULL,
  type = c("cor", "lm")[1],
  cor_method = "pearson",
  label_sep = ";",
  label.x.npc = "left",
  label.y.npc = "top",
  label.x = NULL,
  label.y = NULL,
  x_axis_title = "",
  y_axis_title = "",
  point_size = 5,
  point_alpha = 0.6,
  line_size = 0.8,
  line_alpha = 1,
  line_color = "black",
  line_se = TRUE,
  line_se_color = "grey70",
  pvalue_trim = 4,
  cor_coef_trim = 3,
  lm_equation = TRUE,
```

```

lm_fir_trim = 2,
lm_sec_trim = 2,
lm_squ_trim = 2,
...
)

```

Arguments:

- x default NULL; a single numeric or character value, a vector, or a distance matrix used for the x axis. If x is a single value, it will be used to select the column of data_env in the object. If x is a distance matrix, it will be transformed to be a vector.
- y default NULL; a single numeric or character value, a vector, or a distance matrix used for the y axis. If y is a single value, it will be used to select the column of data_env in the object. If y is a distance matrix, it will be transformed to be a vector.
- group default NULL; a character vector; if length is 1, must be a colname of sample_table in the input dataset; Otherwise, group should be a vector having same length with x/y (for vector) or column number of x/y (for matrix).
- group_order default NULL; a vector used to order groups, i.e. reorder the legend and colors in plot when group is not NULL; If group_order is NULL and group is provided, the function can first check whether the group column of sample_table is factor. If group_order is provided, disable the group orders or factor levels in the group column of sample_table.
- color_values default RColorBrewer::brewer.pal(8, "Dark2"); color pallete for different groups.
- shape_values default NULL; a numeric vector for point shape types of groups when group is not NULL, see ggplot2 tutorial.
- type default c("cor", "lm")[1]; "cor": correlation; "lm" for regression.
- cor_method default "pearson"; one of "pearson", "kendall" and "spearman"; correlation method.
- label_sep default ";"; the separator string between different label parts.
- label.x.npc default "left"; can be numeric or character vector of the same length as the number of groups and/or panels. If too short, they will be recycled.
 - numeric** value should be between 0 and 1. Coordinates to be used for positioning the label, expressed in "normalized parent coordinates"
 - character** allowed values include: i) one of c('right', 'left', 'center', 'centre', 'middle') for x-axis; ii) and one of c('bottom', 'top', 'center', 'centre', 'middle') for y-axis.
- label.y.npc default "top"; same usage with label.x.npc; also see label.y.npc parameter of ggpubr::stat_cor function.
- label.x default NULL; x axis absolute position for adding the statistic label.
- label.y default NULL; x axis absolute position for adding the statistic label.
- x_axis_title default ""; the title of x axis.
- y_axis_title default ""; the title of y axis.
- point_size default 5; point size value.
- point_alpha default 0.6; alpha value for the point color transparency.
- line_size default 0.8; line size value.
- line_alpha default 1; alpha value for the line color transparency.
- line_color default "black"; fitted line color; only available when group = NULL.
- line_se default TRUE; Whether show the confidence interval for the fitting.

line_se_color default "grey70"; the color to fill the confidence interval when line_se = TRUE.

pvalue_trim default 4; trim the decimal places of p value.

cor_coef_trim default 3; trim the decimal places of correlation coefficient.

lm_equation default TRUE; whether include the equation in the label when type = "lm".

lm_fir_trim default 2; trim the decimal places of first coefficient in regression.

lm_sec_trim default 2; trim the decimal places of second coefficient in regression.

lm_squ_trim default 2; trim the decimal places of R square in regression.

... other arguments passed to geom_text or geom_label.

Returns: ggplot.

Examples:

```
\donttest{
t1$plot_scatterfit(x = 1, y = 2, type = "cor")
t1$plot_scatterfit(x = 1, y = 2, type = "lm", point_alpha = .3)
t1$plot_scatterfit(x = "pH", y = "TOC", type = "lm", group = "Group", line_se = FALSE)
t1$plot_scatterfit(x =
  dataset$beta_diversity$bray[rownames(t1$data_env), rownames(t1$data_env)], y = "pH")
}
```

Method print(): Print the trans_env object.

Usage:

```
trans_env$print()
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
trans_env$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## -----
## Method `trans_env$new`
## -----

data(dataset)
data(env_data_16S)
t1 <- trans_env$new(dataset = dataset, add_data = env_data_16S[, 4:11])

## -----
## Method `trans_env$cal_diff`
## -----

t1$cal_diff(group = "Group", method = "KW")
t1$cal_diff(group = "Group", method = "anova")
```

```
## -----
## Method `trans_env$cal_autocor`
## -----

## Not run:
# Spearman correlation
t1$cal_autocor(upper = list(continuous = GGally::wrap("cor", method= "spearman")))

## End(Not run)

## -----
## Method `trans_env$cal_ordination`
## -----

t1$cal_ordination(method = "dbRDA", use_measure = "bray")
t1$cal_ordination(method = "RDA", taxa_level = "Genus")
t1$cal_ordination(method = "CCA", taxa_level = "Genus")

## -----
## Method `trans_env$cal_ordination_anova`
## -----

t1$cal_ordination_anova()

## -----
## Method `trans_env$cal_ordination_envfit`
## -----

t1$cal_ordination_envfit()

## -----
## Method `trans_env$trans_ordination`
## -----

t1$trans_ordination(adjust_arrow_length = TRUE, min_perc_env = 0.1, max_perc_env = 1)

## -----
## Method `trans_env$plot_ordination`
## -----

t1$cal_ordination(method = "RDA")
t1$trans_ordination(adjust_arrow_length = TRUE, max_perc_env = 1.5)
```

```

t1$plot_ordination(plot_color = "Group")
t1$plot_ordination(plot_color = "Group", plot_shape = "Group", plot_type = c("point", "ellipse"))
t1$plot_ordination(plot_color = "Group", plot_type = c("point", "chull"))
t1$plot_ordination(plot_color = "Group", plot_type = c("point", "centroid"),
  centroid_segment_linetype = 1)
t1$plot_ordination(plot_color = "Group", env_nudge_x = c(0.4, 0, 0, 0, 0, -0.2, 0, 0),
  env_nudge_y = c(0.6, 0, 0.2, 0.5, 0, 0.1, 0, 0.2))

## -----
## Method `trans_env$scal_mantel`
## -----

t1$scal_mantel(use_measure = "bray")
t1$scal_mantel(partial_mantel = TRUE, use_measure = "bray")

## -----
## Method `trans_env$scal_cor`
## -----

t2 <- trans_diff$new(dataset = dataset, method = "rf", group = "Group", rf_taxa_level = "Genus")
t1 <- trans_env$new(dataset = dataset, add_data = env_data_16S[, 4:11])
t1$scal_cor(use_data = "other", p_adjust_method = "fdr", other_taxa = t2$res_diff$Taxa[1:40])

## -----
## Method `trans_env$plot_cor`
## -----

t1$plot_cor(pheatmap = FALSE)

## -----
## Method `trans_env$plot_scatterfit`
## -----

t1$plot_scatterfit(x = 1, y = 2, type = "cor")
t1$plot_scatterfit(x = 1, y = 2, type = "lm", point_alpha = .3)
t1$plot_scatterfit(x = "pH", y = "TOC", type = "lm", group = "Group", line_se = FALSE)
t1$plot_scatterfit(x =
  dataset$beta_diversity$bray[rownames(t1$data_env), rownames(t1$data_env)], y = "pH")

```

Description

This class is a wrapper for a series of functional prediction analysis on species and communities, including the prokaryotic trait prediction based on Louca et al. (2016) <doi:10.1126/science.aaf4507> and Lim et al. (2020) <10.1038/s41597-020-0516-5>, or fungal trait prediction based on Nguyen et al. (2016) <10.1016/j.funeco.2015.06.006> and Polme et al. (2020) <doi:10.1007/s13225-020-00466-2>; functional redundancy calculation and metabolic pathway abundance prediction Abhauer et al. (2015) <10.1093/bioinformatics/btv287>.

Active bindings

func_group_list store and show the function group list

Methods

Public methods:

- `trans_func$new()`
- `trans_func$cal_spe_func()`
- `trans_func$cal_spe_func_perc()`
- `trans_func$show_prok_func()`
- `trans_func$trans_spe_func_perc()`
- `trans_func$plot_spe_func_perc()`
- `trans_func$cal_tax4fun()`
- `trans_func$cal_tax4fun2()`
- `trans_func$cal_tax4fun2_FRI()`
- `trans_func$print()`
- `trans_func$clone()`

Method `new()`: Create the `trans_func` object. This function can identify the data type for Prokaryotes or Fungi automatically.

Usage:

```
trans_func$new(dataset = NULL)
```

Arguments:

`dataset` the object of `microtable` Class.

Returns: `for_what`: "prok" or "fungi" or NA, "prok" represent prokaryotes. "fungi" represent fungi. NA stand for unknown according to the Kingdom information. In this case, if the user still want to use the function to identify species traits, please provide "prok" or "fungi" manually, e.g. `t1$for_what <- "prok"`.

Examples:

```
data(dataset)
t1 <- trans_func$new(dataset = dataset)
```

Method `cal_spe_func()`: Identify traits of each feature by matching taxonomic assignments to functional database.

Usage:


```
trans_func$cal_spe_func(
  prok_database = c("FAPROTAX", "NJC19")[1],
  fungi_database = c("FUNGuild", "FungalTraits")[1]
)
```

Arguments:

prok_database default "FAPROTAX"; "FAPROTAX" or "NJC19"; select a prokaryotic trait database:

'FAPROTAX' FAPROTAX; Reference: Louca et al. (2016). Decoupling function and taxonomy in the global ocean microbiome. *Science*, 353(6305), 1272. <doi:10.1126/science.aaf4507>

'NJC19' NJC19: Lim et al. (2020). Large-scale metabolic interaction network of the mouse and human gut microbiota. *Scientific Data*, 7(1). <10.1038/s41597-020-0516-5>. Note that the matching in this database is performed at the species level, hence utilizing it demands a higher level of precision in regards to the assignments of species in the taxonomic information table.

fungi_database default "FUNGuild"; "FUNGuild" or "FungalTraits"; select a fungal trait database:

'FUNGuild' Nguyen et al. (2016) FUNGuild: An open annotation tool for parsing fungal community datasets by ecological guild. *Fungal Ecology*, 20(1), 241-248, <doi:10.1016/j.funeco.2015.06.006>

'FungalTraits' version: FungalTraits_1.2_ver_16Dec_2020V.1.2; Polme et al. Fungal-Traits: a user-friendly traits database of fungi and fungus-like stramenopiles. *Fungal Diversity* 105, 1-16 (2020). <doi:10.1007/s13225-020-00466-2>

Returns: res_spe_func stored in object.

Examples:

```
\donttest{
t1$cal_spe_func(prok_database = "FAPROTAX")
t1$cal_spe_func(fungi_database = "FungalTraits")
}
```

Method cal_spe_func_perc(): Calculating the percentages of species with specific trait in communities. The percentages of the taxa with specific trait can reflect corresponding functional potential in the community. So this method is one representation of functional redundancy (FR) without the consideration of phylogenetic distance among taxa. The FR is defined:

$$FR_{kj}^{unweighted} = \frac{N_j}{N_k}$$

$$FR_{kj}^{weighted} = \frac{\sum_{i=1}^{N_j} A_i}{\sum_{i=1}^{N_k} A_i}$$

where FR_{kj} denotes the FR for sample k and function j. N_k is the species number in sample k. N_j is the number of species with function j in sample k. A_i is the abundance (counts) of species i in sample k.

Usage:

```
trans_func$cal_spe_func_perc(abundance_weighted = FALSE, perc = TRUE, dec = 2)
```

Arguments:

abundance_weighted default FALSE; whether use abundance of taxa. If FALSE, calculate the functional population percentage. If TRUE, calculate the functional individual percentage.

perc default TRUE; whether to use percentages in the result. If TRUE, value is bounded between 0 and 100. If FALSE, the result is relative proportion ('abundance_weighted = FALSE') or relative abundance ('abundance_weighted = TRUE') bounded between 0 and 1.

dec default 2; remained decimal places.

Returns: res_spe_func_perc stored in the object.

Examples:

```
\donttest{
t1$cal_spe_func_perc(abundance_weighted = TRUE)
}
```

Method show_prok_func(): Show the annotation information for a function of prokaryotes from FAPROTAX database.

Usage:

```
trans_func$show_prok_func(use_func = NULL)
```

Arguments:

use_func default NULL; the function name.

Returns: None.

Examples:

```
\donttest{
t1$show_prok_func(use_func = "methanotrophy")
}
```

Method trans_spe_func_perc(): Transform the res_spe_func_perc table to the long table format for the following visualization. Also add the group information if the database has hierarchical groups.

Usage:

```
trans_func$trans_spe_func_perc()
```

Returns: res_spe_func_perc_trans stored in the object.

Examples:

```
\donttest{
t1$trans_spe_func_perc()
}
```

Method plot_spe_func_perc(): Plot the percentages of species with specific trait in communities.

Usage:

```
trans_func$plot_spe_func_perc(
  add_facet = TRUE,
  order_x = NULL,
  color_gradient_low = "#00008B",
  color_gradient_high = "#9E0142"
)
```

Arguments:

add_facet default TRUE; whether use group names as the facets in the plot, see trans_func\$func_group_list object.

order_x default NULL; character vector; to sort the x axis text; can be also used to select partial samples to show.

color_gradient_low default "#00008B"; the color used as the low end in the color gradient.

color_gradient_high default "#9E0142"; the color used as the high end in the color gradient.

Returns: ggplot2.

Examples:

```
\donttest{
t1$plot_spe_func_perc()
}
```

Method cal_tax4fun(): Predict functional potential of communities using tax4fun package. please cite: Tax4Fun: Predicting functional profiles from metagenomic 16S rRNA data. Bioinformatics, 31(17), 2882-2884, <doi:10.1093/bioinformatics/btv287>. Note that this function requires a standard prefix in taxonomic table with double underlines (e.g. 'g__').

Usage:

```
trans_func$cal_tax4fun(keep_tem = FALSE, folderReferenceData = NULL)
```

Arguments:

keep_tem default FALSE; whether keep the intermediate file, that is, the feature table in local place.

folderReferenceData default NULL; the folder, see <http://tax4fun.gobics.de/> and Tax4Fun function in Tax4Fun package.

Returns: tax4fun_K0 and tax4fun_path in object.

Method cal_tax4fun2(): Predict functional potential of communities with Tax4Fun2 method. The function was adapted from the raw Tax4Fun2 package to make it compatible with the microtable object. Please cite: Tax4Fun2: prediction of habitat-specific functional profiles and functional redundancy based on 16S rRNA gene sequences. Environmental Microbiome 15, 11 (2020). <doi:10.1186/s40793-020-00358-7>

Usage:

```
trans_func$cal_tax4fun2(
  blast_tool_path = NULL,
  path_to_reference_data = "Tax4Fun2_ReferenceData_v2",
  path_to_temp_folder = NULL,
  database_mode = "Ref99NR",
  normalize_by_copy_number = T,
  min_identity_to_reference = 97,
  use_uproc = T,
  num_threads = 1,
  normalize_pathways = F
)
```

Arguments:

`blast_tool_path` default NULL; the folder path, e.g., ncbi-blast-2.5.0+/bin ; blast tools folder downloaded from "ftp://ftp.ncbi.nlm.nih.gov/blast/executables/blast+" ; e.g., ncbi-blast-2.5.0+x64-win64.tar.gz for windows system; if `blast_tool_path` is NULL, search the tools in the environmental path variable.

`path_to_reference_data` default "Tax4Fun2_ReferenceData_v2"; the path that points to files used in the prediction; The directory must contain the Ref99NR or Ref100NR folder; download Ref99NR.zip from "https://cloudstor.aarnet.edu.au/plus/s/DkoZIyZpMNbrzSw/download" or Ref100NR.zip from "https://cloudstor.aarnet.edu.au/plus/s/jIByczak9ZAFUB4/download".

`path_to_temp_folder` default NULL; The temporary folder to store the logfile, intermediate file and result files; if NULL, use the default temporary in the computer system.

`database_mode` default 'Ref99NR'; "Ref99NR" or "Ref100NR"; Ref99NR: 99% clustering reference database; Ref100NR: no clustering.

`normalize_by_copy_number` default TRUE; whether normalize the result by the 16S rRNA copy number in the genomes.

`min_identity_to_reference` default 97; the sequences identity threshold used for finding the nearest species.

`use_uproc` default TRUE; whether use UProC to functionally anotate the genomes in the reference data.

`num_threads` default 1; the threads used in the blastn.

`normalize_pathways` default FALSE; Different to Tax4Fun, when converting from KEGG functions to KEGG pathways, Tax4Fun2 does not equally split KO gene abundances between pathways a functions is affiliated to. The full predicted abundance is affiliated to each pathway. Use TRUE to split the abundances (default is FALSE).

Returns: `res_tax4fun2_KO` and `res_tax4fun2_pathway` in object.

Examples:

```
\dontrun{
t1$cal_tax4fun2(blast_tool_path = "ncbi-blast-2.5.0+/bin",
  path_to_reference_data = "Tax4Fun2_ReferenceData_v2")
}
```

Method `cal_tax4fun2_FRI()`: Calculate (multi-) functional redundancy index (FRI) of prokaryotic community with Tax4Fun2 method. This function is used to calculating aFRI and rFRI use the intermediate files generated by the function `cal_tax4fun2()`. please also cite: Tax4Fun2: prediction of habitat-specific functional profiles and functional redundancy based on 16S rRNA gene sequences. Environmental Microbiome 15, 11 (2020). <doi:10.1186/s40793-020-00358-7>

Usage:

```
trans_func$cal_tax4fun2_FRI()
```

Returns: `res_tax4fun2_aFRI` and `res_tax4fun2_rFRI` in object.

Examples:

```
\dontrun{
t1$cal_tax4fun2_FRI()
}
```

Method `print()`: Print the `trans_func` object.

Usage:

```
trans_func$print()
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
trans_func$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## -----
## Method `trans_func$new`
## -----

data(dataset)
t1 <- trans_func$new(dataset = dataset)

## -----
## Method `trans_func$cal_spe_func`
## -----

t1$cal_spe_func(prok_database = "FAPROTAX")
t1$cal_spe_func(fungi_database = "FungalTraits")

## -----
## Method `trans_func$cal_spe_func_perc`
## -----

t1$cal_spe_func_perc(abundance_weighted = TRUE)

## -----
## Method `trans_func$show_prok_func`
## -----

t1$show_prok_func(use_func = "methanotrophy")

## -----
## Method `trans_func$trans_spe_func_perc`
## -----

t1$trans_spe_func_perc()
```

```

## -----
## Method `trans_func$plot_spe_func_perc`
## -----

t1$plot_spe_func_perc()

## -----
## Method `trans_func$cal_tax4fun2`
## -----

## Not run:
t1$cal_tax4fun2(blast_tool_path = "ncbi-blast-2.5.0+/bin",
  path_to_reference_data = "Tax4Fun2_ReferenceData_v2")

## End(Not run)

## -----
## Method `trans_func$cal_tax4fun2_FRI`
## -----

## Not run:
t1$cal_tax4fun2_FRI()

## End(Not run)

```

trans_network

Create trans_network object for network analysis.

Description

This class is a wrapper for a series of network analysis methods, including the network construction, network attributes analysis, eigengene analysis, network subsetting, node and edge properties, network visualization and other operations.

Methods

Public methods:

- `trans_network$new()`
- `trans_network$cal_network()`
- `trans_network$cal_module()`
- `trans_network$save_network()`
- `trans_network$cal_network_attr()`
- `trans_network$get_node_table()`
- `trans_network$get_edge_table()`
- `trans_network$get_adjacency_matrix()`
- `trans_network$plot_network()`

- `trans_network$cal_eigen()`
- `trans_network$plot_taxa_roles()`
- `trans_network$subset_network()`
- `trans_network$cal_powerlaw()`
- `trans_network$cal_sum_links()`
- `trans_network$plot_sum_links()`
- `trans_network$random_network()`
- `trans_network$trans_comm()`
- `trans_network$print()`
- `trans_network$clone()`

Method `new()`: Create the `trans_network` object, store the important intermediate data and calculate correlations if `cor_method` parameter is not NULL.

Usage:

```
trans_network$new(
  dataset = NULL,
  cor_method = NULL,
  use_WGCNA_pearson_spearman = FALSE,
  use_NetCoMi_pearson_spearman = FALSE,
  use_sparcc_method = c("NetCoMi", "SpiecEasi")[1],
  taxa_level = "OTU",
  filter_thres = 0,
  nThreads = 1,
  SparCC_simu_num = 100,
  env_cols = NULL,
  add_data = NULL,
  ...
)
```

Arguments:

`dataset` default NULL; the object of `microtable` class. Default NULL means customized analysis.

`cor_method` default NULL; NULL or one of "bray", "pearson", "spearman", "sparcc", "bi-cor", "cclasso" and "ccrepe"; All the methods referred to NetCoMi package are performed based on `netConstruct` function of NetCoMi package and require NetCoMi to be installed from Github (<https://github.com/stefpeschel/NetCoMi>); For the algorithm details, please see Peschel et al. 2020 Brief. Bioinform <doi: 10.1093/bib/bbaa290>;

NULL NULL denotes non-correlation network, i.e. do not use correlation-based network. If so, the return `res_cor_p` list will be NULL.

'bray' 1-B, where B is Bray-Curtis dissimilarity; based on `vegan::vegdist` function

'pearson' Pearson correlation; If `use_WGCNA_pearson_spearman` and `use_NetCoMi_pearson_spearman` are both FALSE, use the function `cor.test` in R; `use_WGCNA_pearson_spearman = TRUE` invoke `corAndPvalue` function of WGCNA package; `use_NetCoMi_pearson_spearman = TRUE` invoke `netConstruct` function of NetCoMi package

'spearman' Spearman correlation; other details are same with the 'pearson' option

'sparcc' SparCC algorithm (Friedman & Alm, PLoS Comp Biol, 2012, <doi:10.1371/journal.pcbi.1002687>); use NetCoMi package when use_sparcc_method = "NetCoMi"; use SpiecEasi package when use_sparcc_method = "SpiecEasi" and require SpiecEasi to be installed from Github (<https://github.com/zdk123/SpiecEasi>)

'bicolor' Calculate biweight midcorrelation efficiently for matrices based on WGCNA: :bicolor function; This option can invoke netConstruct function of NetCoMi package; Make sure WGCNA and NetCoMi packages are both installed

'cclasso' Correlation inference of Composition data through Lasso method based on netConstruct function of NetCoMi package; for details, see NetCoMi: :cclasso function

'ccrepe' Calculates compositionality-corrected p-values and q-values for compositional data using an arbitrary distance metric based on NetCoMi: :netConstruct function; also see NetCoMi: :ccrepe function

use_WGCNA_pearson_spearman default FALSE; whether use WGCNA package to calculate correlation when cor_method = "pearson" or "spearman".

use_NetCoMi_pearson_spearman default FALSE; whether use NetCoMi package to calculate correlation when cor_method = "pearson" or "spearman". The important difference between NetCoMi and others is the features of zero handling and data normalization; See <doi: 10.1093/bib/bbaa290>.

use_sparcc_method default c("NetCoMi", "SpiecEasi")[1]; use NetCoMi package or SpiecEasi package to perform SparCC when cor_method = "sparcc".

taxa_level default "OTU"; taxonomic rank; 'OTU' denotes using feature abundance table; other available options should be one of the colnames of tax_table of input dataset.

filter_thres default 0; the relative abundance threshold.

nThreads default 1; the CPU thread number; available when use_WGCNA_pearson_spearman = TRUE or use_sparcc_method = "SpiecEasi".

SparCC_simu_num default 100; SparCC simulation number for bootstrap when use_sparcc_method = "SpiecEasi".

env_cols default NULL; numeric or character vector to select the column names of environmental data in dataset\$sample_table; the environmental data can be used in the correlation network (as the nodes) or FlashWeave network.

add_data default NULL; provide environmental variable table additionally instead of env_cols parameter; rownames must be sample names.

... parameters pass to NetCoMi: :netConstruct for other operations, such as zero handling and/or data normalization when cor_method and other parameters refer to NetCoMi package.

Returns: res_cor_p list with the correlation (association) matrix and p value matrix. Note that when cor_method and other parameters refer to NetCoMi package, the p value table are all zero as the significant associations have been selected.

Examples:

```
\donttest{
data(dataset)
# for correlation network
t1 <- trans_network$new(dataset = dataset, cor_method = "pearson",
taxa_level = "OTU", filter_thres = 0.0002)
# for non-correlation network
t1 <- trans_network$new(dataset = dataset, cor_method = NULL)
}
```


Method cal_network(): Construct network based on the igraph package or SpiecEasi package or julia FlashWeave package or beamStatic package.

Usage:

```
trans_network$cal_network(
  network_method = c("COR", "SpiecEasi", "gcod", "FlashWeave", "beamStatic")[1],
  COR_p_thres = 0.01,
  COR_p_adjust = "fdr",
  COR_weight = TRUE,
  COR_cut = 0.6,
  COR_optimization = FALSE,
  COR_optimization_low_high = c(0.01, 0.8),
  COR_optimization_seq = 0.01,
  SpiecEasi_method = "mb",
  FlashWeave_tempdir = NULL,
  FlashWeave_meta_data = FALSE,
  FlashWeave_other_para = "alpha=0.01,sensitive=true,heterogeneous=true",
  beamStatic_t_strength = 0.001,
  beamStatic_t_stab = 0.8,
  add_taxa_name = "Phylum",
  delete_unlinked_nodes = TRUE,
  username_rawtaxa_when_taxalevel_notOTU = FALSE,
  ...
)
```

Arguments:

network_method default "COR"; "COR", "SpiecEasi", "gcod", "FlashWeave" or "beamStatic";
network_method = NULL means skipping the network construction for the customized use.

The option details:

'**COR**' correlation-based network; use the correlation and p value matrices in res_cor_p list stored in the object; See Deng et al. (2012) <doi:10.1186/1471-2105-13-113> for other details

'**SpiecEasi**' SpiecEasi network; relies on algorithms of sparse neighborhood and inverse covariance selection; belong to the category of conditional dependence and graphical models; see <https://github.com/zdk123/SpiecEasi> for installing the R package; see Kurtz et al. (2015) <doi:10.1371/journal.pcbi.1004226> for the algorithm details

'**gcod**' hypothesize the logistic normal distribution of microbiome data; use penalized maximum likelihood method to estimate the sparse structure of inverse covariance for latent normal variables to address the high dimensionality of the microbiome data; belong to the category of conditional dependence and graphical models; depend on the R NetCoMi package <https://github.com/stefpeschel/NetCoMi>; see FANG et al. (2017) <doi:10.1089/cmb.2017.0054> for the algorithm details

'**FlashWeave**' FlashWeave network; Local-to-global learning framework; belong to the category of conditional dependence and graphical models; good performance on heterogeneous datasets to find direct associations among taxa; see <https://github.com/meringlab/FlashWeave.jl> for installing julia language and FlashWeave package; julia must be in the computer system env path, otherwise the program can not find it; see Tackmann et al. (2019) <doi:10.1016/j.cels.2019.08.002> for the algorithm details

'beemStatic' beemStatic network; extend generalized Lotka-Volterra model to cases of cross-sectional datasets to infer interaction among taxa based on expectation-maximization algorithm; see <https://github.com/CSB5/BEEM-static> for installing the R package; see Li et al. (2021) <doi:10.1371/journal.pcbi.1009343> for the algorithm details

COR_p_thres default 0.01; the p value threshold for the correlation-based network.

COR_p_adjust default "fdr"; p value adjustment method, see method parameter of p.adjust function for available options, in which COR_p_adjust = "none" means giving up the p value adjustment.

COR_weight default TRUE; whether use correlation coefficient as the weight of edges; FALSE represents weight = 1 for all edges.

COR_cut default 0.6; correlation coefficient threshold for the correlation network.

COR_optimization default FALSE; whether use random matrix theory (RMT) based method to determine the correlation coefficient; see <https://doi.org/10.1186/1471-2105-13-113>

COR_optimization_low_high default c(0.01, 0.8); the low and high value threshold used for the RMT optimization; only useful when COR_optimization = TRUE.

COR_optimization_seq default 0.01; the interval of correlation coefficient used for RMT optimization; only useful when COR_optimization = TRUE.

SpiecEasi_method default "mb"; either 'glasso' or 'mb'; see spiec.easi function in package SpiecEasi and <https://github.com/zdk123/SpiecEasi>.

FlashWeave_tempdir default NULL; The temporary directory used to save the temporary files for running FlashWeave; If not assigned, use the system user temp.

FlashWeave_meta_data default FALSE; whether use env data for the optimization, If TRUE, the function automatically find the env_data in the object and generate a file for meta_data_path parameter of FlashWeave package.

FlashWeave_other_para default "alpha=0.01, sensitive=true, heterogeneous=true"; the parameters passed to julia FlashWeave package; user can change the parameters or add more according to FlashWeave help document; An exception is meta_data_path parameter as it is generated based on the data inside the object, see FlashWeave_meta_data parameter for the description.

beemStatic_t_strength default 0.001; for network_method = "beemStatic"; the threshold used to limit the number of interactions (strength); same with the t.strength parameter in showInteraction function of beemStatic package.

beemStatic_t_stab default 0.8; for network_method = "beemStatic"; the threshold used to limit the number of interactions (stability); same with the t.stab parameter in showInteraction function of beemStatic package.

add_taxa_name default "Phylum"; one or more taxonomic rank name; used to add taxonomic rank name to network node properties.

delete_unlinked_nodes default TRUE; whether delete the nodes without any link.

username_rawtaxa_when_taxa_level_notOTU default FALSE; whether use OTU name as representatives of taxa when taxa_level != "OTU". Default FALSE means using taxonomic information of taxa_level instead of OTU name.

... parameters pass to SpiecEasi::spiec.easi when network_method = "SpiecEasi"; pass to NetCoMi::netConstruct when network_method = "gcoda"; pass to beemStatic::func.EM when network_method = "beemStatic".

Returns: res_network stored in object.

Examples:

```
\dontrun{
# for correlation network
t1 <- trans_network$new(dataset = dataset, cor_method = "pearson",
taxa_level = "OTU", filter_thres = 0.001)
t1$cal_network(COR_p_thres = 0.05, COR_cut = 0.6)
t1 <- trans_network$new(dataset = dataset, cor_method = NULL, filter_thres = 0.003)
t1$cal_network(network_method = "SpiecEasi", SpiecEasi_method = "mb")
t1 <- trans_network$new(dataset = dataset, cor_method = NULL, filter_thres = 0.005)
t1$cal_network(network_method = "beemStatic")
t1 <- trans_network$new(dataset = dataset, cor_method = NULL, filter_thres = 0.001)
t1$cal_network(network_method = "FlashWeave")
}
```

Method `cal_module()`: Calculate network modules and add module names to the network node properties.

Usage:

```
trans_network$cal_module(
  method = "cluster_fast_greedy",
  module_name_prefix = "M"
)
```

Arguments:

`method` default "cluster_fast_greedy"; the method used to find the optimal community structure of a graph; the following are available functions (options) from igraph package: "cluster_fast_greedy", "cluster_walktrap", "cluster_edge_betweenness", "cluster_infomap", "cluster_label_prop", "cluster_leading_eigen", "cluster_louvain", "cluster_spinglass", "cluster_optimal".

For the details of these functions, please see the help document, such as `help(cluster_fast_greedy)`;

Note that the default "cluster_fast_greedy" method can not be applied to directed network. If directed network is provided, the function can automatically switch the default method from "cluster_fast_greedy" to "cluster_walktrap".

`module_name_prefix` default "M"; the prefix of module names; module names are made of the `module_name_prefix` and numbers; numbers are assigned according to the sorting result of node numbers in modules with decreasing trend.

Returns: `res_network` with modules, stored in object.

Examples:

```
\donttest{
t1 <- trans_network$new(dataset = dataset, cor_method = "pearson",
taxa_level = "OTU", filter_thres = 0.0002)
t1$cal_network(COR_p_thres = 0.01, COR_cut = 0.6)
t1$cal_module(method = "cluster_fast_greedy")
}
```

Method `save_network()`: Save network as gexf style, which can be opened by Gephi (<https://gephi.org/>).

Usage:

```
trans_network$save_network(filepath = "network.gexf")
```

Arguments:

filepath default "network.gexf"; file path to save the network.

Returns: None

Examples:

```
\dontrun{
t1$save_network(filepath = "network.gexf")
}
```

Method cal_network_attr(): Calculate network properties.

Usage:

```
trans_network$cal_network_attr()
```

Returns: res_network_attr stored in object.

Examples:

```
\donttest{
t1$cal_network_attr()
}
```

Method get_node_table(): Get the node property table. The properties may include the node names, modules allocation, degree, betweenness, abundance, taxonomy, within-module connectivity (z_i) and among-module connectivity (P_i) <doi:10.1186/1471-2105-13-113; 10.1016/j.geoderma.2022.115866>.

Usage:

```
trans_network$get_node_table(node_roles = TRUE)
```

Arguments:

node_roles default TRUE; whether calculate the node roles <doi:10.1038/nature03288; 10.1186/1471-2105-13-113>. The role of node i is characterized by its within-module connectivity (z_i) and among-module connectivity (P_i) as follows

$$z_i = \frac{k_{ib} - \bar{k}_b}{\sigma_{k_b}}$$

$$P_i = 1 - \sum_{c=1}^{N_M} \left(\frac{k_{ic}}{k_i} \right)^2$$

where k_{ib} is the number of links of node i to other nodes in its module b , \bar{k}_b and σ_{k_b} are the average and standard deviation of within-module connectivity, respectively over all the nodes in module b , k_i is the number of links of node i in the whole network, k_{ic} is the number of links from node i to nodes in module c , and N_M is the number of modules in the network.

Returns: res_node_table in object; Abundance expressed as a percentage; betweenness centrality; betweenness centrality; betweenness centrality: closeness centrality; eigenvector centrality: eigenvector centrality; z : within-module connectivity; p : among-module connectivity.

Examples:

```
\donttest{
t1$get_node_table(node_roles = TRUE)
}
```

Method `get_edge_table()`: Get the edge property table, including connected nodes, label and weight.

Usage:

```
trans_network$get_edge_table()
```

Returns: res_edge_table in object.

Examples:

```
\donttest{
t1$get_edge_table()
}
```

Method `get_adjacency_matrix()`: Get the adjacency matrix from the network graph.

Usage:

```
trans_network$get_adjacency_matrix(...)
```

Arguments:

... parameters passed to as_adjacency_matrix function of igraph package.

Returns: res_adjacency_matrix in object.

Examples:

```
\donttest{
t1$get_adjacency_matrix(attr = "weight")
}
```

Method `plot_network()`: Plot the network based on a series of methods from other packages, such as igraph, ggraph and networkD3. The networkD3 package provides dynamic network. It is especially useful for a glimpse of the whole network structure and finding the interested nodes and edges in a large network. In contrast, the igraph and ggraph methods are suitable for relatively small network.

Usage:

```
trans_network$plot_network(
  method = c("igraph", "ggraph", "networkD3")[1],
  node_label = "name",
  node_color = NULL,
  ggraph_layout = "fr",
  ggraph_node_size = 2,
  ggraph_node_text = TRUE,
  ggraph_text_color = NULL,
  ggraph_text_size = 3,
  networkD3_node_legend = TRUE,
  networkD3_zoom = TRUE,
  ...
)
```

Arguments:

method default "igraph"; The available options:

'igraph' call plot.igraph function in igraph package for a static network; see plot.igraph for the parameters

'ggraph' call ggraph function in ggraph package for a static network

'networkD3' use forceNetwork function in networkD3 package for a dynamic network; see forceNetwork function for the parameters

node_label default "name"; node label shown in the plot for method = "ggraph" or method = "networkD3"; Please see the column names of object\$res_node_table, which is the returned table of function object\$get_node_table; User can select other column names in res_node_table.

node_color default NULL; node color assignment for method = "ggraph" or method = "networkD3"; Select a column name of object\$res_node_table, such as "module".

ggraph_layout default "fr"; for method = "ggraph"; see layout parameter of create_layout function in ggraph package.

ggraph_node_size default 2; for method = "ggraph"; the node size.

ggraph_node_text default TRUE; for method = "ggraph"; whether show the label text of nodes.

ggraph_text_color default NULL; for method = "ggraph"; a column name of object\$res_node_table used to assign label text colors.

ggraph_text_size default 3; for method = "ggraph"; the node label text size.

networkD3_node_legend default TRUE; used for method = "networkD3"; logical value to enable node colour legends; Please see the legend parameter in networkD3::forceNetwork function.

networkD3_zoom default TRUE; used for method = "networkD3"; logical value to enable (TRUE) or disable (FALSE) zooming; Please see the zoom parameter in networkD3::forceNetwork function.

... parameters passed to plot.igraph function when method = "igraph" or forceNetwork function when method = "networkD3".

Returns: network plot.

Examples:

```
\donttest{
t1$plot_network(method = "igraph", layout = layout_with_kk)
t1$plot_network(method = "ggraph", node_color = "module")
t1$plot_network(method = "networkD3", node_color = "module")
}
```

Method cal_eigen(): Calculate eigengenes of modules, i.e. the first principal component based on PCA analysis, and the percentage of variance <doi:10.1186/1471-2105-13-113>.

Usage:

```
trans_network$cal_eigen()
```

Returns: res_eigen and res_eigen_expla in object.

Examples:

```
\donttest{
t1$cal_eigen()
}
```

Method plot_taxa_roles(): Plot the classification and importance of nodes, see object\$res_node_table for the variable names used in the parameters.

Usage:

```

trans_network$plot_taxa_roles(
  use_type = c(1, 2)[1],
  roles_color_background = FALSE,
  roles_color_values = NULL,
  add_label = FALSE,
  add_label_group = "Network hubs",
  add_label_text = "name",
  label_text_size = 4,
  label_text_color = "grey50",
  label_text_italic = FALSE,
  label_text_parse = FALSE,
  plot_module = FALSE,
  x_lim = c(0, 1),
  use_level = "Phylum",
  show_value = c("z", "p"),
  show_number = 1:10,
  plot_color = "Phylum",
  plot_shape = "taxa_roles",
  plot_size = "Abundance",
  color_values = RColorBrewer::brewer.pal(12, "Paired"),
  shape_values = c(16, 17, 7, 8, 15, 18, 11, 10, 12, 13, 9, 3, 4, 0, 1, 2, 14),
  ...
)

```

Arguments:

`use_type` default 1; 1 or 2; 1 represents taxa roles area plot (node roles include Module hubs, Network hubs, Connectors and Peripherals <doi:10.1038/nature03288; 10.1186/1471-2105-13-113>); 2 represents the layered plot with taxa as x axis.

`roles_color_background` default FALSE; for `use_type=1`; TRUE: use background colors for each area; FALSE: use classic point colors.

`roles_color_values` default NULL; for `use_type=1`; color palette for background or points.

`add_label` default FALSE; for `use_type = 1`; whether add labels for the points.

`add_label_group` default "Network hubs"; If `add_label = TRUE`; which part of `tax_roles` is used to show labels; character vectors.

`add_label_text` default "name"; If `add_label = TRUE`; which column of `object$res_node_table` is used to label the text.

`label_text_size` default 4; The text size of the label.

`label_text_color` default "grey50"; The text color of the label.

`label_text_italic` default FALSE; whether use italic style for the label text.

`label_text_parse` default FALSE; whether parse the label text. See the `parse` parameter in `ggrepel::geom_text_repel` function.

`plot_module` default FALSE; for `use_type=1`; whether plot the modules information.

`x_lim` default `c(0, 1)`; for `use_type=1`; x axis range when `roles_color_background = FALSE`.

`use_level` default "Phylum"; for `use_type=2`; used taxonomic level in x axis.

`show_value` default `c("z", "p")`; for `use_type=2`; used variable in y axis.

show_number default 1:10; for use_type=2; showed number in x axis, sorting according to the nodes number.

plot_color default "Phylum"; for use_type=2; used variable for color.

plot_shape default "taxa_roles"; for use_type=2; used variable for shape.

plot_size default "Abundance"; for use_type=2; used for point size; a fixed number (e.g. 5) is also available.

color_values default RColorBrewer::brewer.pal(12, "Paired"); for use_type=2; color vector

shape_values default c(16, 17, 7, 8, 15, 18, 11, 10, 12, 13, 9, 3, 4, 0, 1, 2, 14); for use_type=2; shape vector, see ggplot2 tutorial for the shape meaning.

... parameters pass to geom_point.

Returns: ggplot.

Examples:

```
\donttest{
t1$plot_taxa_roles(roles_color_background = FALSE)
}
```

Method subset_network(): Subset of the network.

Usage:

```
trans_network$subset_network(node = NULL, edge = NULL, rm_single = TRUE)
```

Arguments:

node default NULL; provide the node names that you want to use in the sub-network.

edge default NULL; provide the edge name needed; must be one of "+" or "-".

rm_single default TRUE; whether remove the nodes without any edge in the sub-network. So this function can also be used to remove the nodes without any edge when node and edge are both NULL.

Returns: a new network

Examples:

```
\donttest{
t1$subset_network(node = t1$res_node_table %>% base::subset(module == "M1") %>%
rownames, rm_single = TRUE)
# return a sub network that contains all nodes of module M1
}
```

Method cal_powerlaw(): Fit degrees to a power law distribution. First, perform a bootstrapping hypothesis test to determine whether degrees follow a power law distribution. If the distribution follows power law, then fit degrees to power law distribution and return the parameters.

Usage:

```
trans_network$cal_powerlaw(...)
```

Arguments:

... parameters pass to bootstrap_p function in powerLaw package.

Returns: res_powerlaw_p and res_powerlaw_fit; see powerLaw::bootstrap_p function for the bootstrapping p value details; see igraph::fit_power_law function for the power law fit return details.

Examples:

```
\donttest{
t1$cal_powerlaw()
}
```

Method `cal_sum_links()`: This function is used to sum the links number from one taxa to another or in the same taxa, for example, at Phylum level. This is very useful to fast see how many nodes are connected between different taxa or within the taxa.

Usage:

```
trans_network$cal_sum_links(taxa_level = "Phylum")
```

Arguments:

`taxa_level` default "Phylum"; taxonomic rank.

Returns: `res_sum_links_pos` and `res_sum_links_neg` in object.

Examples:

```
\donttest{
t1$cal_sum_links(taxa_level = "Phylum")
}
```

Method `plot_sum_links()`: Plot the summed linkages among taxa.

Usage:

```
trans_network$plot_sum_links(
  plot_pos = TRUE,
  plot_num = NULL,
  color_values = RColorBrewer::brewer.pal(8, "Dark2"),
  method = c("chorddiag", "circlize")[1],
  ...
)
```

Arguments:

`plot_pos` default TRUE; If TRUE, plot the summed positive linkages; If FALSE, plot the summed negative linkages.

`plot_num` default NULL; number of taxa presented in the plot.

`color_values` default `RColorBrewer::brewer.pal(8, "Dark2")`; colors palette for taxa.

`method` default `c("chorddiag", "circlize")[1]`; chorddiag package <<https://github.com/mattflor/chorddiag>> or circlize package.

... pass to `chorddiag::chorddiag` function when `method = "chorddiag"` or `circlize::chordDiagram` function when `method = "circlize"`. Note that for `circlize::chordDiagram` function, `keep.diagonal`, `symmetric` and `self.link` parameters have been fixed to fit the input data.

Returns: please see the invoked function.

Examples:

```
\dontrun{
test1$plot_sum_links(method = "chorddiag", plot_pos = TRUE, plot_num = 10)
test1$plot_sum_links(method = "circlize", transparency = 0.2,
  annotationTrackHeight = circlize::mm_h(c(5, 5)))
}
```

Method random_network(): Generate random networks, compare them with the empirical network and get the p value of topological properties. The generation of random graph is based on the erdos.renyi.game function of igraph package. The numbers of vertices and edges in the random graph are same with the empirical network stored in the object.

Usage:

```
trans_network$random_network(runs = 100, output_sim = FALSE)
```

Arguments:

runs default 100; simulation number of random network.

output_sim default FALSE; whether output each simulated network result.

Returns: a data.frame with the following components:

Observed Topological properties of empirical network

Mean_sim Mean of properties of simulated networks

SD_sim SD of properties of simulated networks

p_value Significance, i.e. p values

When output_sim = TRUE, the columns from the five to the last are each simulated result.

Examples:

```
\dontrun{
t1$random_network(runs = 100)
}
```

Method trans_comm(): Transform classified features to community-like microtable object for further analysis, such as module-taxa table.

Usage:

```
trans_network$trans_comm(use_col = "module", abundance = TRUE)
```

Arguments:

use_col default "module"; which column to use as the 'community'; must be one of the name of res_node_table from function get_node_table.

abundance default TRUE; whether sum abundance of taxa. TRUE: sum the abundance for a taxon across all samples; FALSE: sum the frequency for a taxon across all samples.

Returns: a new [microtable](#) class.

Examples:

```
\donttest{
t2 <- t1$trans_comm(use_col = "module")
}
```

Method print(): Print the trans_network object.

Usage:

```
trans_network$print()
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
trans_network$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```

## -----
## Method `trans_network$new`
## -----

data(dataset)
# for correlation network
t1 <- trans_network$new(dataset = dataset, cor_method = "pearson",
taxa_level = "OTU", filter_thres = 0.0002)
# for non-correlation network
t1 <- trans_network$new(dataset = dataset, cor_method = NULL)

## -----
## Method `trans_network$cal_network`
## -----

## Not run:
# for correlation network
t1 <- trans_network$new(dataset = dataset, cor_method = "pearson",
taxa_level = "OTU", filter_thres = 0.001)
t1$cal_network(COR_p_thres = 0.05, COR_cut = 0.6)
t1 <- trans_network$new(dataset = dataset, cor_method = NULL, filter_thres = 0.003)
t1$cal_network(network_method = "SpiecEasi", SpiecEasi_method = "mb")
t1 <- trans_network$new(dataset = dataset, cor_method = NULL, filter_thres = 0.005)
t1$cal_network(network_method = "beemStatic")
t1 <- trans_network$new(dataset = dataset, cor_method = NULL, filter_thres = 0.001)
t1$cal_network(network_method = "FlashWeave")

## End(Not run)

## -----
## Method `trans_network$cal_module`
## -----

t1 <- trans_network$new(dataset = dataset, cor_method = "pearson",
taxa_level = "OTU", filter_thres = 0.0002)
t1$cal_network(COR_p_thres = 0.01, COR_cut = 0.6)
t1$cal_module(method = "cluster_fast_greedy")

## -----
## Method `trans_network$save_network`
## -----

## Not run:
t1$save_network(filepath = "network.gexf")

## End(Not run)

```

```
## -----  
## Method `trans_network$cal_network_attr`  
## -----  
  
t1$cal_network_attr()  
  
## -----  
## Method `trans_network$get_node_table`  
## -----  
  
t1$get_node_table(node_roles = TRUE)  
  
## -----  
## Method `trans_network$get_edge_table`  
## -----  
  
t1$get_edge_table()  
  
## -----  
## Method `trans_network$get_adjacency_matrix`  
## -----  
  
t1$get_adjacency_matrix(attr = "weight")  
  
## -----  
## Method `trans_network$plot_network`  
## -----  
  
t1$plot_network(method = "igraph", layout = layout_with_kk)  
t1$plot_network(method = "ggraph", node_color = "module")  
t1$plot_network(method = "networkD3", node_color = "module")  
  
## -----  
## Method `trans_network$cal_eigen`  
## -----  
  
t1$cal_eigen()  
  
## -----  
## Method `trans_network$plot_taxa_roles`
```

```

## -----

t1$plot_taxa_roles(roles_color_background = FALSE)

## -----
## Method `trans_network$subset_network`
## -----

t1$subset_network(node = t1$res_node_table %>% base::subset(module == "M1") %>%
  rownames, rm_single = TRUE)
# return a sub network that contains all nodes of module M1

## -----
## Method `trans_network$scal_powerlaw`
## -----

t1$scal_powerlaw()

## -----
## Method `trans_network$scal_sum_links`
## -----

t1$scal_sum_links(taxa_level = "Phylum")

## -----
## Method `trans_network$plot_sum_links`
## -----

## Not run:
test1$plot_sum_links(method = "chorddiag", plot_pos = TRUE, plot_num = 10)
test1$plot_sum_links(method = "circlize", transparency = 0.2,
  annotationTrackHeight = circlize::mm_h(c(5, 5)))

## End(Not run)

## -----
## Method `trans_network$random_network`
## -----

## Not run:
t1$random_network(runs = 100)

## End(Not run)

## -----

```

```
## Method `trans_network$trans_comm`
## -----

t2 <- t1$trans_comm(use_col = "module")
```

trans_norm

Feature abundance normalization/transformation.

Description

Feature abundance normalization/transformation for a microtable object or data.frame object.

Methods

Public methods:

- `trans_norm$new()`
- `trans_norm$norm()`
- `trans_norm$clone()`

Method `new()`: Get a transposed abundance table if the input is microtable object. In the table, rows are samples, and columns are features. This can make the further operations same with the traditional ecological methods.

Usage:

```
trans_norm$new(dataset = NULL)
```

Arguments:

`dataset` the `microtable` object or `data.frame` object. If it is `data.frame` object, please make sure that rows are samples, and columns are features.

Returns: `data_table`, stored in the object.

Examples:

```
library(microeco)
data(dataset)
t1 <- trans_norm$new(dataset = dataset)
```

Method `norm()`: Normalization/transformation methods.

Usage:

```
trans_norm$norm(
  method = "rarefy",
  sample.size = NULL,
  rngseed = 123,
  replace = TRUE,
  pseudocount = 1,
  intersect.no = 10,
  ct.min = 1,
```

```

condition = NULL,
MARGIN = NULL,
logbase = 2,
...
)

```

Arguments:

method default "rarefy"; See the following available options.

Methods for normalization:

- "rarefy": classic rarefaction based on R sample function.
- "SRS": scaling with ranked subsampling method based on the SRS package provided by Lukas Beule and Petr Karlovsky (2020) <doi:10.7717/peerj.9593>.
- "clr": Centered log-ratio normalization <ISBN:978-0-412-28060-3> <doi: 10.3389/fmicb.2017.02224>. It is defined:

$$clr_{ki} = \log \frac{x_{ki}}{g(x_i)}$$

where x_{ki} is the abundance of k th feature in sample i , $g(x_i)$ is the geometric mean of abundances for sample i . A pseudocount need to be added to deal with the zero. For more information, please see the 'clr' method in decostand function of vegan package.

- "rclr": Robust centered log-ratio normalization <doi: doi:10.1128/msystems.00016-19>. It is defined:

$$rclr_{ki} = \log \frac{x_{ki}}{g(x_i > 0)}$$

where x_{ki} is the abundance of k th feature in sample i , $g(x_i > 0)$ is the geometric mean of abundances (> 0) for sample i . In rclr, zero values are kept as zeroes, and not taken into account.

- "GMPR": Geometric mean of pairwise ratios <doi: 10.7717/peerj.4600>. For a given sample i , the size factor s_i is defined:

$$s_i = \left(\prod_{j=1}^n \text{Median}_{k|c_{ki}c_{kj} \neq 0} \left\{ \frac{c_{ki}}{c_{kj}} \right\} \right)^{1/n}$$

where k denotes all the features, and n denotes all the samples. For sample i , $GMPR = \frac{x_i}{s_i}$, where x_i is the feature abundances of sample i .

- "CSS": Cumulative sum scaling normalization based on the metagenomeSeq package <doi:10.1038/nmeth.2658>. For a given sample j , the scaling factor s_j^l is defined:

$$s_j^l = \sum_{i|c_{ij} \leq q_j^l} c_{ij}$$

where q_j^l is the l th quantile of sample j , that is, in sample j there are l features with counts smaller than q_j^l . c_{ij} denotes the count (abundance) of feature i in sample j . For $l = 0.95m$ (feature number), q_j^l corresponds to the 95th percentile of the count distribution for sample j . Normalized counts $\tilde{c}_{ij} = \left(\frac{c_{ij}}{s_j^l}\right)(N)$, where N is an appropriately chosen normalization constant.

- "TSS": Total sum scaling. Abundance is divided by the sequencing depth. For a given sample j , normalized counts is defined:

$$\tilde{c}_{ij} = \frac{c_{ij}}{\sum_{i=1}^{N_j} c_{ij}}$$

where c_{ij} is the counts of feature i in sample j , and N_j is the feature number of sample j .

- "eBay": Empirical Bayes approach to normalization <10.1186/s12859-020-03552-z>. The implemented method is not tree-related. In the output, the sum of each sample is 1.
- "TMM": Trimmed mean of M-values method based on the normLibSizes function of edgeR package <doi: 10.1186/gb-2010-11-3-r25>.
- "DESeq2": Median ratio of gene counts relative to geometric mean per gene based on the DESeq function of DESeq2 package <doi: 10.1186/s13059-014-0550-8>. This option can invoke the trans_diff class and extract the normalized data from the original result. Note that either group or formula should be provided. The scaling factor is defined:

$$s_j = \text{Median}_i \frac{c_{ij}}{(\prod_{j=1}^n c_{ij})^{1/n}}$$

where c_{ij} is the counts of feature i in sample j , and n is the total sample number.

- "Wrench": Group-wise and sample-wise compositional bias factor <doi: 10.1186/s12864-018-5160-5>. Note that condition parameter is necessary to be passed to condition parameter in wrench function of Wrench package. As the input data must be microtable object, so the input condition parameter can be a column name of sample_table. The scaling factor is defined:

$$s_j = \frac{1}{p} \sum_{ij} W_{ij} \frac{X_{ij}}{\bar{X}_i}$$

where X_{ij} represents the relative abundance (proportion) for feature i in sample j , \bar{X}_i is the average proportion of feature i across the dataset, W_{ij} represents a weight specific to each technique, and p is the feature number in sample.

- "RLE": Relative log expression.

Methods based on `decostand` function:

- "total": divide by margin total (default MARGIN = 1, i.e. rows - samples).
- "max": divide by margin maximum (default MARGIN = 2, i.e. columns - features).
- "normalize": make margin sum of squares equal to one (default MARGIN = 1).
- "range": standardize values into range 0...1 (default MARGIN = 2). If all values are constant, they will be transformed to 0.
- "standardize": scale x to zero mean and unit variance (default MARGIN = 2).
- "pa": scale x to presence/absence scale (0/1).
- "log": logarithmic transformation.

Other methods for transformation:

- "AST": Arc sine square root transformation.

sample.size default NULL; library size for rarefaction when method = "rarefy" or "SRS". If not provided, use the minimum number across all samples. For "SRS" method, this parameter is passed to `Cmin` parameter of SRS function of SRS package.

rngseed default 123; random seed. Available when method = "rarefy" or "SRS".

replace default TRUE; see [sample](#) for the random sampling; Available when method = "rarefy".

pseudocount default 1; add pseudocount for those features with 0 abundance when method = "clr".

intersect.no default 10; the intersecting taxa number between paired sample for method = "GMPR".

ct.min default 1; the minimum number of counts required to calculate ratios for method = "GMPR".

condition default NULL; Only available when method = "Wrench". This parameter is passed to the condition parameter of wrench function in Wrench package It must be a column name of sample_table or a vector with same length of samples.

MARGIN default NULL; 1 = samples, and 2 = features of abundance table; only available when method comes from [decostand](#) function. If MARGIN is NULL, use the default value in decostand function.

logbase default 2; The logarithm base.

... parameters pass to [decostand](#), or metagenomeSeq::cumNorm when method = "CSS", or edgeR::normLibSizes when method = "TMM" or "RLE", or trans_diff class when method = "DESeq2", or wrench function of Wrench package when method = "Wrench".

Returns: new microtable object or data.frame object.

Examples:

```
newdataset <- t1$norm(method = "clr")
newdataset <- t1$norm(method = "log")
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
trans_norm$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## -----
## Method `trans_norm$new`
## -----

library(microeco)
data(dataset)
t1 <- trans_norm$new(dataset = dataset)

## -----
## Method `trans_norm$norm`
## -----

newdataset <- t1$norm(method = "clr")
newdataset <- t1$norm(method = "log")
```

trans_nullmodel	<i>Create trans_nullmodel object for phylogeny- and taxonomy-based null model analysis.</i>
-----------------	---

Description

This class is a wrapper for a series of null model related approaches, including the mantel correlogram analysis of phylogenetic signal, beta nearest taxon index (betaNTI), beta net relatedness index (betaNRI), NTI, NRI and RCbray calculations; See Stegen et al. (2013) <doi:10.1038/ismej.2013.93> and Liu et al. (2017) <doi:10.1038/s41598-017-17736-w> for the algorithms and applications.

Methods

Public methods:

- `trans_nullmodel$new()`
- `trans_nullmodel$cal_mantel_corr()`
- `trans_nullmodel$plot_mantel_corr()`
- `trans_nullmodel$cal_betampd()`
- `trans_nullmodel$cal_betamntd()`
- `trans_nullmodel$cal_ses_betampd()`
- `trans_nullmodel$cal_ses_betamntd()`
- `trans_nullmodel$cal_rcbray()`
- `trans_nullmodel$cal_process()`
- `trans_nullmodel$cal_NRI()`
- `trans_nullmodel$cal_NTI()`
- `trans_nullmodel$cal_Cscore()`
- `trans_nullmodel$cal_NST()`
- `trans_nullmodel$cal_NST_test()`
- `trans_nullmodel$cal_NST_convert()`
- `trans_nullmodel$clone()`

Method new():

Usage:

```
trans_nullmodel$new(
  dataset = NULL,
  filter_thres = 0,
  taxa_number = NULL,
  group = NULL,
  select_group = NULL,
  env_cols = NULL,
  add_data = NULL,
  complete_na = FALSE
)
```

Arguments:

dataset the object of `microtable` Class.
 filter_thres default 0; the relative abundance threshold.
 taxa_number default NULL; how many taxa the user want to keep, if provided, filter_thres parameter will be forcible invalid.
 group default NULL; which column name in sample_table is selected as the group for the following selection.
 select_group default NULL; one or more elements in group, used to select samples.
 env_cols default NULL; number or name vector to select the environmental data in dataset\$sample_table.
 add_data default NULL; provide environmental data table additionally.
 complete_na default FALSE; whether fill the NA in environmental data based on the method in mice package.

Returns: data_comm and data_tree in object.

Examples:

```
data(dataset)
data(env_data_16S)
t1 <- trans_nullmodel$new(dataset, filter_thres = 0.0005, add_data = env_data_16S)
```

Method `cal_mantel_corr()`: Calculate mantel correlogram.

Usage:

```
trans_nullmodel$cal_mantel_corr(
  use_env = NULL,
  break.pts = seq(0, 1, 0.02),
  cutoff = FALSE,
  ...
)
```

Arguments:

use_env default NULL; numeric or character vector to select env_data; if provide multiple variables or NULL, use PCA (principal component analysis) to reduce dimensionality.
 break.pts default seq(0, 1, 0.02); see break.pts parameter in `mantel.correlog` of vegan package.
 cutoff default FALSE; see cutoff parameter in `mantel.correlog`.
 ... parameters pass to `mantel.correlog`

Returns: res_mantel_corr in object.

Examples:

```
\dontrun{
t1$cal_mantel_corr(use_env = "pH")
}
```

Method `plot_mantel_corr()`: Plot mantel correlogram.

Usage:

```
trans_nullmodel$plot_mantel_corr(point_shape = 22, point_size = 3)
```

Arguments:

point_shape default 22; the number for selecting point shape type; see ggplot2 manual for the number meaning.

point_size default 3; the point size.

Returns: ggplot.

Examples:

```
\dontrun{
t1$plot_mantel_corr()
}
```

Method cal_betampd(): Calculate betaMPD (mean pairwise distance). Same with picante::comdist function, but faster.

Usage:

```
trans_nullmodel$cal_betampd(abundance.weighted = TRUE)
```

Arguments:

abundance.weighted default TRUE; whether use abundance-weighted method.

Returns: res_betampd in object.

Examples:

```
\donttest{
t1$cal_betampd(abundance.weighted = TRUE)
}
```

Method cal_betamntd(): Calculate betaMNTD (mean nearest taxon distance). Same with picante::comdistnt package, but faster.

Usage:

```
trans_nullmodel$cal_betamntd(
  abundance.weighted = TRUE,
  exclude.conspecific = FALSE,
  use_iCAMP = FALSE,
  use_iCAMP_force = TRUE,
  iCAMP_tempdir = NULL,
  ...
)
```

Arguments:

abundance.weighted default TRUE; whether use abundance-weighted method.

exclude.conspecific default FALSE; see exclude.conspecific parameter in comdistnt function of picante package.

use_iCAMP default FALSE; whether use bmntd.big function of iCAMP package to calculate betaMNTD. This method can store the phylogenetic distance matrix on the disk to lower the memory spending and perform the calculation parallelly.

use_iCAMP_force default FALSE; whether use bmntd.big function of iCAMP package automatically when the feature number is large.

iCAMP_tempdir default NULL; the temporary directory used to place the large tree file; If NULL; use the system user tempdir.

... parameters pass to iCAMP::pdist.big function.

Returns: res_betamntd in object.

Examples:

```
\donttest{
t1$cal_betamntd(abundance.weighted = TRUE)
}
```

Method cal_ses_betampd(): Calculate standardized effect size of betaMPD, i.e. beta net relatedness index (betaNRI).

Usage:

```
trans_nullmodel$cal_ses_betampd(
  runs = 1000,
  null.model = c("taxa.labels", "richness", "frequency", "sample.pool", "phylogeny.pool",
    "independentswap", "trialswap")[1],
  abundance.weighted = TRUE,
  iterations = 1000
)
```

Arguments:

runs default 1000; simulation runs.

null.model default "taxa.labels"; The available options include "taxa.labels", "richness", "frequency", "sample.pool", "phylogeny.pool", "independentswap" and "trialswap"; see null.model parameter of ses.mntd function in picante package for the algorithm details.

abundance.weighted default TRUE; whether use weighted abundance.

iterations default 1000; iteration number for part null models to perform; see iterations parameter of picante::randomizeMatrix function.

Returns: res_ses_betampd in object.

Examples:

```
\dontrun{
# only run 50 times for the example; default 1000
t1$cal_ses_betampd(runs = 50, abundance.weighted = TRUE)
}
```

Method cal_ses_betamntd(): Calculate standardized effect size of betaMNTD, i.e. beta nearest taxon index (betaNTI).

Usage:

```
trans_nullmodel$cal_ses_betamntd(
  runs = 1000,
  null.model = c("taxa.labels", "richness", "frequency", "sample.pool", "phylogeny.pool",
    "independentswap", "trialswap")[1],
  abundance.weighted = TRUE,
  exclude.conspecifics = FALSE,
  use_iCAMP = FALSE,
  use_iCAMP_force = TRUE,
  iCAMP_tempdir = NULL,
  nworker = 2,
  iterations = 1000
)
```

Arguments:

runs default 1000; simulation number of null model.
 null.model default "taxa.labels"; The available options include "taxa.labels", "richness", "frequency", "sample.pool", "phylogeny.pool", "independentswap" and "trialsmap"; see null.model parameter of ses.mntd function in picante package for the algorithm details.
 abundance.weighted default TRUE; whether use abundance-weighted method.
 exclude.conspecificity default FALSE; see comdistnt in picante package.
 use_iCAMP default FALSE; whether use bmntd.big function of iCAMP package to calculate betaMNTD. This method can store the phylogenetic distance matrix on the disk to lower the memory spending and perform the calculation parallelly.
 use_iCAMP_force default FALSE; whether to make use_iCAMP to be TRUE when the feature number is large.
 iCAMP_tempdir default NULL; the temporary directory used to place the large tree file; If NULL; use the system user tempdir.
 nworker default 2; the CPU thread number.
 iterations default 1000; iteration number for part null models to perform; see iterations parameter of picante::randomizeMatrix function.

Returns: res_ses_betamntd in object.

Examples:

```

\dontrun{
# only run 50 times for the example; default 1000
t1$cal_ses_betamntd(runs = 50, abundance.weighted = TRUE, exclude.conspecificity = FALSE)
}

```

Method cal_rcbray(): Calculate Bray–Curtis-based Raup–Crick (RCbray) <doi: 10.1890/ES10-00117.1>.

Usage:

```

trans_nullmodel$cal_rcbray(
  runs = 1000,
  verbose = TRUE,
  null.model = "independentswap"
)

```

Arguments:

runs default 1000; simulation runs.
 verbose default TRUE; whether show the calculation process message.
 null.model default "independentswap"; see more available options in randomizeMatrix function of picante package.

Returns: res_rcbray in object.

Examples:

```

\dontrun{
# only run 50 times for the example; default 1000
t1$cal_rcbray(runs = 50)
}

```

Method `cal_process()`: Infer the ecological processes according to `ses.betaMNTD/ses.betaMPD` and `rcbray`.

Usage:

```
trans_nullmodel$cal_process(use_betamntd = TRUE, group = NULL)
```

Arguments:

`use_betamntd` default TRUE; whether use `ses.betaMNTD`; if false, use `ses.betaMPD`.
`group` default NULL; a column name in `sample_table` of `microtable` object. If provided, the analysis will be performed for each group instead of the whole.

Returns: `res_process` in object.

Examples:

```
\dontrun{
t1$cal_process(use_betamntd = TRUE)
}
```

Method `cal_NRI()`: Calculates Nearest Relative Index (NRI), equivalent to -1 times the standardized effect size of MPD.

Usage:

```
trans_nullmodel$cal_NRI(
  null.model = "taxa.labels",
  abundance.weighted = FALSE,
  runs = 999,
  ...
)
```

Arguments:

`null.model` default "taxa.labels"; Null model to use; see `null.model` parameter in `ses.mpd` function of `picante` package for available options.
`abundance.weighted` default FALSE; Should mean nearest relative distances for each species be weighted by species abundance?
`runs` default 999; Number of randomizations.
... parameters pass to `ses.mpd` function in `picante` package.

Returns: `res_NRI` in object, equivalent to -1 times `ses.mpd`.

Examples:

```
\donttest{
# only run 50 times for the example; default 999
t1$cal_NRI(null.model = "taxa.labels", abundance.weighted = FALSE, runs = 50)
}
```

Method `cal_NTI()`: Calculates Nearest Taxon Index (NTI), equivalent to -1 times the standardized effect size of MNTD.

Usage:

```
trans_nullmodel$cal_NTI(
  null.model = "taxa.labels",
  abundance.weighted = FALSE,
  runs = 999,
  ...
)
```

Arguments:

null.model default "taxa.labels"; Null model to use; see null.model parameter in ses.mntd function of picante package for available options.

abundance.weighted default FALSE; Should mean nearest taxon distances for each species be weighted by species abundance?

runs default 999; Number of randomizations.

... parameters pass to ses.mntd function in picante package.

Returns: res_NTI in object, equivalent to -1 times ses.mntd.

Examples:

```
\donttest{
# only run 50 times for the example; default 999
t1$cal_NTI(null.model = "taxa.labels", abundance.weighted = TRUE, runs = 50)
}
```

Method cal_Cscore(): Calculates the (normalised) mean number of checkerboard combinations (C-score) using C.score function in bipartite package.

Usage:

```
trans_nullmodel$cal_Cscore(by_group = NULL, ...)
```

Arguments:

by_group default NULL; one column name or number in sample_table; calculate C-score for different groups separately.

... parameters pass to bipartite::C.score function.

Returns: vector.

Examples:

```
\dontrun{
t1$cal_Cscore(normalise = FALSE)
t1$cal_Cscore(by_group = "Group", normalise = FALSE)
}
```

Method cal_NST(): Calculate normalized stochasticity ratio (NST) based on the NST package.

Usage:

```
trans_nullmodel$cal_NST(method = "tNST", group, ...)
```

Arguments:

method default "tNST"; 'tNST' or 'pNST'. See the help document of tNST or pNST function in NST package for more details.

group a colname of sample_table in microtable object; the function can select the data from sample_table to generate a one-column (n x 1) matrix and provide it to the group parameter of tNST or pNST function.

... parameters pass to NST::tNST or NST::pNST function; see the document of corresponding function for more details.

Returns: res_NST stored in the object.

Examples:


```
\dontrun{
t1$cal_NST(group = "Group", dist.method = "bray", output.rand = TRUE, SES = TRUE)
}
```

Method `cal_NST_test()`: Test the significance of NST difference between each pair of groups.

Usage:

```
trans_nullmodel$cal_NST_test(method = "nst.boot", ...)
```

Arguments:

`method` default "nst.boot"; "nst.boot" or "nst.panova"; see `NST::nst.boot` function or `NST::nst.panova` function for the details.

... parameters pass to `NST::nst.boot` when `method = "nst.boot"` or `NST::nst.panova` when `method = "nst.panova"`.

Returns: list. See the Return part of `NST::nst.boot` function or `NST::nst.panova` function in NST package.

Examples:

```
\dontrun{
t1$cal_NST_test()
}
```

Method `cal_NST_convert()`: Convert NST paired long format table to symmetric matrix form.

Usage:

```
trans_nullmodel$cal_NST_convert(column = 10)
```

Arguments:

`column` default 10; which column is selected for the conversion. See the columns of `res_NST$index.pair` stored in the object.

Returns: symmetric matrix.

Examples:

```
\dontrun{
t1$cal_NST_convert(column = 10)
}
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
trans_nullmodel$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
## -----
## Method `trans_nullmodel$new`
## -----
```

```

data(dataset)
data(env_data_16S)
t1 <- trans_nullmodel$new(dataset, filter_thres = 0.0005, add_data = env_data_16S)

## -----
## Method `trans_nullmodel$cal_mantel_corr`
## -----

## Not run:
t1$cal_mantel_corr(use_env = "pH")

## End(Not run)

## -----
## Method `trans_nullmodel$plot_mantel_corr`
## -----

## Not run:
t1$plot_mantel_corr()

## End(Not run)

## -----
## Method `trans_nullmodel$cal_betampd`
## -----

t1$cal_betampd(abundance.weighted = TRUE)

## -----
## Method `trans_nullmodel$cal_betamntd`
## -----

t1$cal_betamntd(abundance.weighted = TRUE)

## -----
## Method `trans_nullmodel$cal_ses_betampd`
## -----

## Not run:
# only run 50 times for the example; default 1000
t1$cal_ses_betampd(runs = 50, abundance.weighted = TRUE)

## End(Not run)

## -----
## Method `trans_nullmodel$cal_ses_betamntd`
## -----

## Not run:

```

```
# only run 50 times for the example; default 1000
t1$cal_ses_betamntd(runs = 50, abundance.weighted = TRUE, exclude.conspecifics = FALSE)

## End(Not run)

## -----
## Method `trans_nullmodel$cal_rcbray`
## -----

## Not run:
# only run 50 times for the example; default 1000
t1$cal_rcbray(runs = 50)

## End(Not run)

## -----
## Method `trans_nullmodel$cal_process`
## -----

## Not run:
t1$cal_process(use_betamntd = TRUE)

## End(Not run)

## -----
## Method `trans_nullmodel$cal_NRI`
## -----

# only run 50 times for the example; default 999
t1$cal_NRI(null.model = "taxa.labels", abundance.weighted = FALSE, runs = 50)

## -----
## Method `trans_nullmodel$cal_NTI`
## -----

# only run 50 times for the example; default 999
t1$cal_NTI(null.model = "taxa.labels", abundance.weighted = TRUE, runs = 50)

## -----
## Method `trans_nullmodel$cal_Cscore`
## -----

## Not run:
t1$cal_Cscore(normalise = FALSE)
t1$cal_Cscore(by_group = "Group", normalise = FALSE)

## End(Not run)

## -----
```

```

## Method `trans_nullmodel$cal_NST`
## -----

## Not run:
t1$cal_NST(group = "Group", dist.method = "bray", output.rand = TRUE, SES = TRUE)

## End(Not run)

## -----
## Method `trans_nullmodel$cal_NST_test`
## -----

## Not run:
t1$cal_NST_test()

## End(Not run)

## -----
## Method `trans_nullmodel$cal_NST_convert`
## -----

## Not run:
t1$cal_NST_convert(column = 10)

## End(Not run)

```

trans_venn

Create trans_venn object for the Venn diagram, petal plot and UpSet plot.

Description

This class is a wrapper for a series of intersection analysis related methods, including 2- to 5-way venn diagram, more than 5-way petal or UpSet plot and intersection transformations based on David et al. (2012) <doi:10.1128/AEM.01459-12>.

Methods

Public methods:

- `trans_venn$new()`
- `trans_venn$plot_venn()`
- `trans_venn$plot_bar()`
- `trans_venn$trans_comm()`
- `trans_venn$print()`
- `trans_venn$clone()`

Method `new()`:

Usage:

```
trans_venn$new(dataset, ratio = NULL, name_joint = "&")
```

Arguments:

`dataset` the object of `microtable` class or a matrix-like table (data.frame or matrix object). If `dataset` is a matrix-like table, features must be rows.

`ratio` default NULL; NULL, "numratio" or "seqratio"; "numratio": calculate the percentage of feature number; "seqratio": calculate the percentage of feature abundance; NULL: no additional percentage.

`name_joint` default "&"; the joint mark for generating multi-sample names.

Returns: `data_details` and `data_summary` stored in the object.

Examples:

```
\donttest{
data(dataset)
t1 <- dataset$merge_samples(use_group = "Group")
t1 <- trans_venn$new(dataset = t1, ratio = "numratio")
}
```

Method `plot_venn()`: Plot venn diagram.

Usage:

```
trans_venn$plot_venn(
  color_circle = RColorBrewer::brewer.pal(8, "Dark2"),
  fill_color = TRUE,
  text_size = 4.5,
  text_name_size = 6,
  text_name_position = NULL,
  alpha = 0.3,
  linesize = 1.1,
  petal_plot = FALSE,
  petal_color = "#BEAED4",
  petal_color_center = "#BEBADA",
  petal_a = 4,
  petal_r = 1,
  petal_use_lim = c(-12, 12),
  petal_center_size = 40,
  petal_move_xy = 4,
  petal_move_k = 2.3,
  petal_move_k_count = 1.3,
  petal_text_move = 40,
  other_text_show = NULL,
  other_text_position = c(2, 2),
  other_text_size = 5
)
```

Arguments:

`color_circle` default `RColorBrewer::brewer.pal(8, "Dark2")`; color pallete.

`fill_color` default TRUE; whether fill the area color.

`text_size` default 4.5; text size in plot.

text_name_size default 6; name size in plot.
 text_name_position default NULL; name position in plot.
 alpha default .3; alpha for transparency.
 linesize default 1.1; cycle line size.
 petal_plot default FALSE; whether use petal plot.
 petal_color default "#BEAED4"; color of the petals; If petal_color only has one color value, all the petals will be assigned with this color value. If petal_color has multiple colors, and the number of color values is smaller than the petal number, the function can append more colors automatically with the color interpolation.
 petal_color_center default "#BEBADA"; color of the center in the petal plot.
 petal_a default 4; the length of the ellipse.
 petal_r default 1; scaling up the size of the ellipse.
 petal_use_lim default c(-12, 12); the width of the plot.
 petal_center_size default 40; petal center circle size.
 petal_move_xy default 4; the distance of text to circle.
 petal_move_k default 2.3; the distance of title to circle.
 petal_move_k_count default 1.3; the distance of data text to circle.
 petal_text_move default 40; the distance between two data text.
 other_text_show default NULL; other characters used to show in the plot.
 other_text_position default c(1, 1); the text position for text in other_text_show.
 other_text_size default 5; the text size for text in other_text_show.

Returns: ggplot.

Examples:

```

\donttest{
t1$plot_venn()
}

```

Method plot_bar(): Plot the intersections using histogram, i.e. UpSet plot. Especially useful when samples > 5.

Usage:

```

trans_venn$plot_bar(
  left_plot = TRUE,
  sort_samples = FALSE,
  up_y_title = "Intersection size",
  up_y_title_size = 15,
  up_y_text_size = 8,
  up_bar_fill = "grey70",
  bottom_y_text_size = 12,
  bottom_height = 1,
  bottom_point_size = 3,
  bottom_point_color = "black",
  bottom_background_fill = "grey95",
  left_width = 0.3,
  left_bar_fill = "grey70",
  left_x_text_size = 10,

```

```
  left_background_fill = "grey95"
)
```

Arguments:

`left_plot` default TRUE; whether add the left bar plot to show the feature number of each sample.

`sort_samples` default FALSE; TRUE is used to sort samples according to the number of features in each sample. FALSE means the sample order is same with that in `sample_table` of the raw dataset.

`up_y_title` default "Intersection set"; y axis title of upper plot.

`up_y_title_size` default 15; y axis title size of upper plot.

`up_y_text_size` default 4; y axis text size of upper plot.

`up_bar_fill` default "grey70"; bar fill color of upper plot.

`bottom_y_text_size` default 12; y axis text size, i.e. sample name size, of bottom sample plot.

`bottom_height` default 1; bottom plot height relative to the upper bar plot. 1 represents the height of bottom plot is same with the upper bar plot.

`bottom_point_size` default 3; point size of bottom plot.

`bottom_point_color` default "black"; point color of bottom plot.

`bottom_background_fill` default "grey95"; fill color for the striped background in the bottom sample plot.

`left_width` default 0.3; left bar plot width relative to the right bottom plot.

`left_bar_fill` default "grey70"; fill color for the left bar plot presenting feature number.

`left_x_text_size` default 10; x axis text size of the left bar plot.

`left_background_fill` default "grey95"; fill color for the striped background in the left plot.

Returns: a ggplot2 object.

Examples:

```
\donttest{
t2 <- t1$plot_bar()
}
```

Method `trans_comm()`: Transform intersection result to community-like microtable object for further composition analysis.

Usage:

```
trans_venn$trans_comm(use_frequency = TRUE)
```

Arguments:

`use_frequency` default TRUE; whether only use OTUs occurrence frequency, i.e. presence/absence data; if FALSE, use abundance data.

Returns: a new `microtable` class.

Examples:

```
\donttest{
t2 <- t1$trans_comm(use_frequency = TRUE)
}
```

Method print(): Print the trans_venn object.

Usage:

```
trans_venn$print()
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
trans_venn$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## -----
## Method `trans_venn$new`
## -----

data(dataset)
t1 <- dataset$merge_samples(use_group = "Group")
t1 <- trans_venn$new(dataset = t1, ratio = "numratio")

## -----
## Method `trans_venn$plot_venn`
## -----

t1$plot_venn()

## -----
## Method `trans_venn$plot_bar`
## -----

t2 <- t1$plot_bar()

## -----
## Method `trans_venn$trans_comm`
## -----

t2 <- t1$trans_comm(use_frequency = TRUE)
```


Index

- * **Description**
 - microeco, [5](#)
- * **R6**
 - dataset, [3](#)
- * **data.frame**
 - env_data_16S, [4](#)
 - fungi_func_FungalTraits, [5](#)
 - fungi_func_FUNGuild, [5](#)
 - otu_table_16S, [17](#)
 - otu_table_ITS, [18](#)
 - phylo_tree_16S, [18](#)
 - prok_func_FAPROTAX, [18](#)
 - prok_func_NJC19_list, [19](#)
 - sample_info_16S, [19](#)
 - sample_info_ITS, [19](#)
 - taxonomy_table_16S, [20](#)
 - taxonomy_table_ITS, [20](#)
- * **list**
 - Tax4Fun2_KEGG, [19](#)
- * **object**
 - dataset, [3](#)

- adonis2, [41](#)
- anosim, [42](#)
- aov, [33](#)

- betadisper, [42](#)

- clone, [2](#)

- data.frame, [21](#)
- dataset, [3](#)
- decostrand, [104](#), [105](#)
- dropallfactors, [4](#)

- env_data_16S, [4](#)

- fungi_func_FungalTraits, [5](#)
- fungi_func_FUNGuild, [5](#)

- geom_bar, [24](#), [61](#)

- geom_boxplot, [27](#)
- grepl, [13](#)

- mantel, [72](#)
- mantel.correlog, [107](#)
- microeco, [5](#)
- microtable, [5](#), [6](#), [22](#), [32](#), [38](#), [46](#), [55](#), [65](#), [80](#), [87](#), [98](#), [102](#), [107](#), [117](#), [119](#)

- otu_table_16S, [17](#)
- otu_table_ITS, [18](#)

- phylo_tree_16S, [18](#)
- prok_func_FAPROTAX, [18](#)
- prok_func_NJC19_list, [19](#)

- rrarefy, [9](#)

- sample, [105](#)
- sample_info_16S, [19](#)
- sample_info_ITS, [19](#)
- stat_ellipse, [40](#), [70](#)

- Tax4Fun2_KEGG, [19](#)
- taxonomy_table_16S, [20](#)
- taxonomy_table_ITS, [20](#)
- tidy_taxonomy, [20](#)
- trans_abund, [5](#), [21](#)
- trans_alpha, [5](#), [32](#), [43](#), [66](#)
- trans_beta, [5](#), [37](#)
- trans_classifier, [6](#), [46](#)
- trans_diff, [5](#), [54](#)
- trans_env, [6](#), [36](#), [61](#), [64](#)
- trans_func, [6](#), [79](#)
- trans_network, [5](#), [86](#)
- trans_norm, [6](#), [9](#), [57](#), [102](#)
- trans_nullmodel, [5](#), [106](#)
- trans_venn, [5](#), [116](#)

- vegdist, [14](#)

- write.table, [11](#), [13](#)