

Package ‘GenomicInteractions’

October 9, 2015

Type Package

Title R package for handling genomic interaction data

URL <https://github.com/ComputationalRegulatoryGenomicsICL/GenomicInteractions/>

Version 1.2.3

Date 2014-07-14

Author Harmston, N., Ing-Simmons, E., Perry, M., Baresic, A., Lenhard, B.

Maintainer Malcolm Perry <mgperry32@gmail.com>, Liz Ing-Simmons <liz.ing-simmons12@csc.mrc.ac.uk>

Imports Rsamtools, GenomicRanges, IRanges, BiocGenerics, data.table, stringr, rtracklayer, GenomeInfoDb, ggplot2, gridExtra, methods, igraph, plotrix, S4Vectors, dplyr

Suggests knitr, BiocStyle, testthat

VignetteBuilder knitr

Description R package for handling Genomic interaction data, such as ChIA-PET/Hi-C, annotating genomic features with interaction information and producing various plots / statistics

biocViews Software,Infrastructure,DataImport,DataRepresentation,HiC

License GPL-3

Depends R (>= 2.10)

NeedsCompilation no

R topics documented:

GenomicInteractions-package	2
annotateAnchors	3
annotateInteractions	3
c	4
calculateDistances	5
capitalize	6
categoriseInteractions	6

countsBetweenAnchors	7
export.bed12	7
export.bedpe	8
export.chiasig	9
export.igraph	9
findOverlaps	10
GenomicInteractions	11
GenomicInteractions-class	12
getters	13
get_binom_ligation_threshold	14
get_self_ligation_threshold	15
hg19.refseq.transcripts	15
hic_example_data	16
is.pp	17
length,GenomicInteractions-method	18
makeGenomicInteractionsFromFile	19
mm9_refseq_promoters	20
plotCisTrans	20
plotCounts	21
plotDists	21
plotInteractionAnnotations	22
plotSummaryStats	23
plotViewpoint	24
print,GenomicInteractions-method	24
removeDups	25
resetAnnotations	25
sameStrand	26
seqinfo,GenomicInteractions-method	26
setters	27
show,GenomicInteractions-method	28
sort,GenomicInteractions-method	28
subsetByFeatures	29
sum,GenomicInteractions-method	30
summariseByFeatures	30
trim,GenomicInteractions-method	31
viewPoint	32
[.	33
\$.GenomicInteractions-method	33

Index**35**

 GenomicInteractions-package

A package for looking at genomic interaction data.

Description

A package for looking at genomic interaction data.

annotateAnchors *Annotate anchors*

Description

This function directly annotates a single set of anchors using the GRanges elementMetadata.

Usage

```
annotateAnchors(GIObject, oneOrTwo, name, dat)
```

```
## S4 method for signature 'GenomicInteractions,numeric,character,vector'
annotateAnchors(GIObject,
  oneOrTwo, name, dat)
```

Arguments

GIObject	A GenomicInteractions object
oneOrTwo	An integer indicating which anchor to annotate
name	Character. Will be used as a column name for the elementMetadata of the annotated anchor.
dat	Vector of the same length as the GenomicInteractions object, containing data with which to annotate the object.

Value

invisible(1)

annotateInteractions *Annotate the interactions in a GenomicInteractions object*

Description

This function will annotate both anchors with a list of named GRanges objects. Each metadata column is labeled "name.id" and contains the id of the genomic interval(s) it overlaps. Anonymous lists will be given names "FEATURE#.id" where # is the position in the list.

Usage

```
annotateInteractions(GIObject, annotations)
```

```
## S4 method for signature 'GenomicInteractions,list'
annotateInteractions(GIObject, annotations)
```

Arguments

GIObject A GenomicInteractions object to be annotated
 annotations A list containing GRanges (or GRangesList) objects with which to annotate the GenomicInteractions object.

Details

For each anchor a "node.class" metadata column will also be added, containing the name of the list element which was *first* annotated to each range. Ranges with no overlaps will be classified as "distal". The identifiers for each individual feature/annotation are taken from either the name of the list item in the case of a GRangesList or from either the names of a the provided GRanges or an id column in its associated metadata.

Value

invisible(1)

Examples

```
data(hic_example_data)
data(mm9_refseq_promoters)
## Not run:
annotateInteractions(hic_example_data, list(promoter=mm9_refseq_promoters))

## End(Not run)
```

c

Combine GenomicInteractions Methods

Description

This method will fail if the seqlengths of the objects to be combined do not match. If some chromosomes appear in one set of seqinfo but not the other, the seqinfo will be merged.

Usage

```
## S4 method for signature 'GenomicInteractions'
c(x, ..., ignore.mcols = FALSE,
  recursive = FALSE)
```

Arguments

x, ... GenomicInteractions objects to be concatenated
 ignore.mcols Logical, default FALSE, remove mcols in combined object.
 recursive Not supported

Value

A GenomicInteractions object.

calculateDistances	<i>Calculate interaction distances</i>
--------------------	--

Description

This function takes a GenomicInteractions object and calculates the distances between the anchors according to the value of method. The distances returned follow the same convention as distance(x, y) in GenomicRanges where the distance between adjacent regions is 0. Note that if anchors are overlapping this method will print a warning and return the distance as 0.

Usage

```
calculateDistances(GIObject, method = "midpoint", floor = TRUE)

## S4 method for signature 'GenomicInteractions'
calculateDistances(GIObject,
  method = "midpoint", floor = TRUE)
```

Arguments

GIObject	A GenomicInteractions object
method	Character vector indicating how to calculate distances, must be one of 'midpoint', 'outer', 'inner'.
floor	A logical specifying whether to round down distances to nearest base pair or not. Default TRUE.

Value

An vector containing the distances between anchors/GRanges, NA if on different chromosomes, rounded down to the nearest bp.

Examples

```
library(GenomicRanges)

anchor.one = GRanges(c("chr1", "chr1", "chr1", "chr1"), IRanges(c(10, 20, 30, 20), width=5))
anchor.two = GRanges(c("chr1", "chr1", "chr1", "chr2"), IRanges(c(100, 200, 300, 50), width=5))
interaction_counts = sample(1:10, 4)
test <- GenomicInteractions(anchor.one, anchor.two, experiment_name="test",
  description="this is a test", counts=interaction_counts)
calculateDistances(test, method="midpoint")
```

capitalize	<i>Capitalize first letter of string</i>
------------	--

Description

This function will capitalize the first letter of each string in a character vector, and lowercase following letters.

Usage

```
capitalize(x)
```

Arguments

x	A character vector
---	--------------------

Value

a string with the first letter capitalised

categoriseInteractions	<i>Get the numbers of interaction types existing in your data</i>
------------------------	---

Description

Get the numbers of interaction types existing in your data

Usage

```
categoriseInteractions(GIObject, node.classes = NULL, viewpoints = NULL)
```

Arguments

GIObject	A GenomicInteractions object
node.classes	Optional. All node.classes to include in the analysis. Default: all node classes.
viewpoints	Optional. If set will only consider interactions where at least one anchor is of this node class. Default: all classes in node.classes.

Value

A data.frame.

Examples

```
data(hic_example_data)
categoriseInteractions(hic_example_data)
```

countsBetweenAnchors *Summarise Interactions between defined anchors*

Description

Calculate the number of of paired-end reads mapping between a defined set of anchors. This function will ignore counts present in the input data.

Usage

```
countsBetweenAnchors(x, y, ...)
```

```
## S4 method for signature 'GenomicInteractions,GRanges'
countsBetweenAnchors(x, y,
  ignore_overlaps = FALSE, ...)
```

Arguments

x	A GenomicInteractions object
y	A GenomicRanges object
...	Extra parameters to pass to findOverlaps
ignore_overlaps	Allow overlapping anchors. Use this when you have overlapping anchors but be careful with multi-mapping. The "within" option can help with this.

Value

A GenomicInteractions object with annotated counts between anchors

export.bed12 *Export interactions in BED12 format.*

Description

Export interactions in BED12 format.

Usage

```
export.bed12(GIObject, fn = NULL, score = "counts", drop.trans = c(FALSE,
  TRUE))
```

```
## S4 method for signature 'GenomicInteractions'
export.bed12(GIObject, fn = NULL,
  score = "counts", drop.trans = c(FALSE, TRUE))
```

Arguments

GIObject	A GenomicInteractions object.
fn	A filename to write the object to
score	Which metadata column to export as score
drop.trans	Logical indicating whether to allow dropping trans interactions (otherwise an error is produced)

Exports a GenomicInteractions object to BED12 format, and writes to a specified file. If filename is not specified, then a data.frame containing the information is returned. Please note some large datasets may take a long time to export.

Value

invisible(1) if outputting to file or a data.frame containing all of the corresponding information

export.bedpe	<i>Export interactions in BED Paired-End format.</i>
--------------	--

Description

#' Exports a GenomicInteractions object to BED-PE format, and writes to a specified file. If filename is not specified, then a data.frame containing the information is returned. The value of the score parameter defines which field is used to populate the score field.

Usage

```
export.bedpe(GIObject, fn = NULL, score = "counts")

## S4 method for signature 'GenomicInteractions'
export.bedpe(GIObject, fn = NULL,
             score = "counts")
```

Arguments

GIObject	A GenomicInteractions object.
fn	A filename to write the interactions data to
score	Which metadata column to use as score

Value

invisible(1) if outputting to file or a data.frame containing all of the corresponding information

export.chiasig	<i>Export interactions in a BEDPE-like format for use with ChiaSig</i>
----------------	--

Description

Exports a GenomicInteractions object to BEDPE like format, (anchor specifications and a column for reads connecting them) and writes to a specified file. If filename is not specified, then a data.frame containing the information is returned. The value of the score parameter defines which field is used to populate the score field.

Usage

```
export.chiasig(GIObject, fn = NULL, score = "counts")

## S4 method for signature 'GenomicInteractions'
export.chiasig(GIObject, fn = NULL,
               score = "counts")
```

Arguments

GIObject	A GenomicInteractions object.
fn	A filename to write the interactions data to
score	Which metadata column to use as the score: counts or normalised

Value

invisible(1) if outputting to file or a data.frame containing all of the corresponding information

export.igraph	<i>Export interactions to an igraph object.</i>
---------------	---

Description

Exports a GenomicInteractions object to graph.data.frame for use by igraph package. This uses unique anchors as nodes and generates edges between them. For the resulting graph to be easily interpretable, anchors should be non-overlapping. This should already be the case for HiC data (either binned or restriction fragments), however ChIA-PET data can contain overlapping anchors, which may need to be reduced to non-overlapping regions before graph export.

Usage

```
export.igraph(GIObject)

## S4 method for signature 'GenomicInteractions'
export.igraph(GIObject)
```

Arguments

GIObject A GenomicInteractions object.

Value

a graph.data.frame representation of the GenomicInteractions object

findOverlaps	<i>Find overlaps between GRanges and GenomicInteractions objects</i>
--------------	--

Description

When called with a GRanges and a GenomicInteractions object, this function calls findOverlaps separately on each anchor and returns a list. countOverlaps and overlapsAny return a list of integer vectors and logical vectors respectively.

Usage

```
## S4 method for signature 'GenomicInteractions,GRanges'
findOverlaps(query, subject,
  maxgap = 0L, minoverlap = 1L, type = c("any", "start", "end", "within",
    "equal"), select = c("all", "first", "last", "arbitrary"),
  ignore.strand = FALSE)

## S4 method for signature 'GRanges,GenomicInteractions'
findOverlaps(query, subject,
  maxgap = 0L, minoverlap = 1L, type = c("any", "start", "end", "within",
    "equal"), select = c("all", "first", "last", "arbitrary"),
  ignore.strand = FALSE)

## S4 method for signature 'GenomicInteractions,GRanges'
countOverlaps(query, subject,
  maxgap = 0L, minoverlap = 1L, select = c("all", "first", "last",
    "arbitrary"), type = c("any", "start", "end", "within", "equal"),
  ignore.strand = FALSE)

## S4 method for signature 'GRanges,GenomicInteractions'
countOverlaps(query, subject,
  maxgap = 0L, minoverlap = 1L, type = c("any", "start", "end", "within",
    "equal"), select = c("all", "first", "last", "arbitrary"),
  ignore.strand = FALSE)

## S4 method for signature 'GenomicInteractions,GRanges'
overlapsAny(query, subject,
  maxgap = 0L, minoverlap = 1L, type = c("any", "start", "end", "within",
    "equal"), select = c("all", "first", "last", "arbitrary"),
  ignore.strand = FALSE)
```

```
## S4 method for signature 'GRanges,GenomicInteractions'
overlapsAny(query, subject,
  maxgap = 0L, minoverlap = 1L, type = c("any", "start", "end", "within",
    "equal"), select = c("all", "first", "last", "arbitrary"),
  ignore.strand = FALSE)

## S4 method for signature 'GenomicInteractions,GenomicInteractions'
findOverlaps(query, subject)
```

Arguments

query GenomicInteractions or GRanges
 subject GRanges or GenomicInteractions
 maxgap,minoverlap,type,select,ignore.strand
 See 'findOverlaps' in the IRanges package.

Details

When
 See 'findOverlaps' in the GenomicRanges package for detailed documentation for this function.

Value

A Hits object or a list containing Hits objects for both anchors.

GenomicInteractions *Function to create a GenomicInteraction object*

Description

Create GenomicInteraction objects from two GRanges objects.

Usage

```
GenomicInteractions(anchor_one = GRanges(), anchor_two = GRanges(),
  counts = integer(), experiment_name = NULL, description = NULL, ...)
```

Arguments

anchor_one, anchor_two
 GRanges objects.
 counts An integer vector, defaults to 1.
 experiment_name Experiment name.
 description Description of experiment.
 ... Additional data to be added to mcols

Value

a GenomicInteractions object

Examples

```
library(GenomicRanges)

anchor.one = GRanges(c("chr1", "chr1", "chr1", "chr1"), IRanges(c(10, 20, 30, 20), width=5))
anchor.two = GRanges(c("chr1", "chr1", "chr1", "chr2"), IRanges(c(100, 200, 300, 50), width=5))
interaction_counts = sample(1:10, 4)
test <- GenomicInteractions(anchor.one, anchor.two, experiment_name="test",
                             description="this is a test", counts=interaction_counts)
```

GenomicInteractions-class

A S4 class to represent interactions between genomic regions.

Description

A S4 class to represent interactions between genomic regions.

Slots

metadata List, defaults to "experiment_name" and "description", inherited from S4Vectors::Vector

anchor_one, anchor_two GRanges. Set of anchors of interactions.

counts integer vector, contains raw counts

elementMetadata DataFrame

This class is used to store information on which genomic regions are interacting with each other. Objects of this class contain information of the genomic coordinates of the interacting regions and the strength of these interactions, and associated metadata such as the name of the dataset and a brief description of the dataset. Interacting regions are stored as a pair of GenomicRanges: each set of anchor regions is stored as a separate GenomicRanges object, accessed by getAnchorOne and getAnchorTwo.

Examples

```
showClass("GenomicInteractions")
library(GenomicRanges)

anchor.one = GRanges(c("chr1", "chr1", "chr1", "chr1"), IRanges(c(10, 20, 30, 20), width=5))
anchor.two = GRanges(c("chr1", "chr1", "chr1", "chr2"), IRanges(c(100, 200, 300, 50), width=5))
interaction_counts = sample(1:10, 4)
test <- GenomicInteractions(anchor.one, anchor.two, experiment_name="test",
                             description="this is a test", counts=interaction_counts)
```

`getters`*Functions to access data held in a GenomicInteractions object.*

Description

Use these functions to access data stored in each of the slots of a `GenomicInteractions` object.

Usage`name(GIObject)``description(GIObject)``anchorOne(GIObject)``anchorTwo(GIObject)``interactionCounts(GIObject)``annotationFeatures(GIObject)`

```
## S4 method for signature 'GenomicInteractions'  
name(GIObject)
```

```
## S4 method for signature 'GenomicInteractions'  
description(GIObject)
```

```
## S4 method for signature 'GenomicInteractions'  
anchorOne(GIObject)
```

```
## S4 method for signature 'GenomicInteractions'  
anchorTwo(GIObject)
```

```
## S4 method for signature 'GenomicInteractions'  
interactionCounts(GIObject)
```

```
## S4 method for signature 'GenomicInteractions'  
annotationFeatures(GIObject)
```

Arguments

`GIObject` A `GenomicInteractions` object

Value

For `'anchorOne'` and `'anchorTwo'`, a `GRanges`. For `'interactionCounts'`, a numeric vector with counts for each interaction in the object. For `'description'` and `'name'`, a character vector with length

1. For 'annotationFeatures', a character vector of features with which the object was previously annotated, or 'NA' if the object is unannotated.

Examples

```
library(GenomicRanges)

anchor.one = GRanges(c("chr1", "chr1", "chr1", "chr1"), IRanges(c(10, 20, 30, 20), width=5))
anchor.two = GRanges(c("chr1", "chr1", "chr1", "chr2"), IRanges(c(100, 200, 300, 50), width=5))
interaction_counts = sample(1:10, 4)
test <- GenomicInteractions(anchor.one, anchor.two, experiment_name="test",
                             description="this is a test", counts=interaction_counts)

name(test)
description(test)
anchorOne(test)
anchorTwo(test)
interactionCounts(test)
```

`get_binom_ligation_threshold`

get self ligation threshold with binomial test

Description

This function calculates a self ligation threshold according to a method based on that of Heidari et al., Genome Research, 2014. Briefly, paired reads are divided into evenly spaced bins. For each bin, the number of reads that are aligned to opposite strand vs to the same strand is calculated. A binomial test is used to test if this is significantly different from the 50:50 ratio expected by chance if all reads are real interactions.

Usage

```
get_binom_ligation_threshold(GIObject, max.distance = 20000, bin.size = 500,
                             p.cutoff = 0.05, adjust = "fdr", plot = TRUE)
```

Arguments

<code>GIObject</code>	a <code>GenomicInteractions</code> object of paired end reads
<code>max.distance</code>	The maximum distance to consider between reads. Reads further apart than this distance should be very unlikely to be self ligations.
<code>bin.size</code>	Bin size in base pairs.
<code>p.cutoff</code>	P value cut off for a significant difference from 50:50. Default: 0.05
<code>adjust</code>	Method to use to adjust p values. Default: <code>fdr</code> . See 'help(p.adjust)' for accepted values. Can also be <code>NA</code> for no adjustment.
<code>plot</code>	<code>TRUE</code> by default. Whether to plot the percentage of reads on opposite strands vs difference and the binomial test p value vs distance.

Value

The cutoff in base pairs below which an interaction is likely to be a self ligation.

get_self_ligation_threshold

Get self ligation threshold with SD method from Heidari et al

Description

This function calculates a self ligation threshold according to the method published in Heidari et al., Genome Research, 2014. Briefly, paired reads are divided into in evenly sized bins. For each bin, the log2 ratio of reads that are aligned to opposite strand vs to the same strand is calculated. Twice the standard deviation of this ratio at high distances is used a cutoff to determine which bins are likely to contain mostly self-liagted reads.

Usage

```
get_self_ligation_threshold(GIObject, bins = 100, distance_th = 4e+05,
                             plot = TRUE)
```

Arguments

GIObject	a GenomicInteractions object of paired end reads
bins	Number of evenly sized bins to use.
distance_th	The threshold, in base pairs, to use as a cutoff to pick which bins to use to determine the standard deviation.
plot	TRUE by default. Whether to plot the log2ratio of opposite to same strand reads vs distance.

Value

The cutoff in base pairs below which an interaction is likely to be a self ligation.

hg19.refseq.transcripts

Human Refseq transcripts from chr 17-18

Description

This dataset contains a subset of the transcripts from the Refseq annotation for mouse genome build hg19 See the ChIA-PET analysis vignette (vignettes(GenomicInteractions)) for more information on how this dataset was created.

Usage

```
data(hg19.refseq.transcripts)
```

Format

A GRanges object with length 2441.

Value

A GRanges object.

hic_example_data	<i>Example HiC dataset</i>
------------------	----------------------------

Description

This dataset contains HiC data from Seitan et al. 2013. The data was analysed using HOMER (Heinz et al. 2010) at a resolution of 100kb to find significant interactions. This example dataset has been filtered to retain only interactions on chromosomes 14 and 15 with a FDR < 0.1. The data has also been annotated for overlaps with Refseq promoters. See the HiC analysis vignette (vignettes(GenomicInteractions)) for more information on how this dataset was created.

Usage

```
data(hic_example_data)
```

Format

A GenomicInteractions object with length 8171.

Value

GenomicInteractions object

References

Seitan, V. C. et al. Cohesin-based chromatin interactions enable regulated gene expression within pre-existing architectural compartments. *Genome Res.* 23, 2066-77 (2013).

Heinz S, Benner C, Spann N, Bertolino E et al. Simple Combinations of Lineage-Determining Transcription Factors Prime cis-Regulatory Elements Required for Macrophage and B Cell Identities. *Mol Cell* 2010 May 28;38(4):576-589.

`is.pp`*Interaction Type Helpers*

Description

Functions to classify interactions within GenomicInteractions objects.

- "isInteractionType" takes two character arguments which are annotated node classes and returns interactions between them.
- "is.pp", "is.pd" etc. are bindings for common annotations:
 - p** promoter
 - d** distal
 - t** terminator
- "is.trans" & "is.cis" select trans-chromosomal and intra-chromosomal interactions, respectively

Usage`is.pp(GIObject)``is.pd(GIObject)``is.pt(GIObject)``is.dd(GIObject)``is.dt(GIObject)``is.tt(GIObject)``isInteractionType(GIObject, x, y)``is.trans(GIObject)``is.cis(GIObject)`

```
## S4 method for signature 'GenomicInteractions'  
is.pp(GIObject)
```

```
## S4 method for signature 'GenomicInteractions'  
is.pd(GIObject)
```

```
## S4 method for signature 'GenomicInteractions'  
is.pt(GIObject)
```

```
## S4 method for signature 'GenomicInteractions'
```

```
is.dd(GIObject)

## S4 method for signature 'GenomicInteractions'
is.dt(GIObject)

## S4 method for signature 'GenomicInteractions'
is.tt(GIObject)

## S4 method for signature 'GenomicInteractions'
isInteractionType(GIObject, x, y)

## S4 method for signature 'GenomicInteractions'
is.trans(GIObject)

## S4 method for signature 'GenomicInteractions'
is.cis(GIObject)
```

Arguments

GIObject	A GenomicInteractions object
x,y	Names of annotated node classes

Value

A logical vector

length, GenomicInteractions-method

Get the length of a GenomicInteractions GIObjct

Description

Get the length of a GenomicInteractions GIObjct

Usage

```
## S4 method for signature 'GenomicInteractions'
length(x)
```

Arguments

x	GenomicInteractions GIObjct
---	-----------------------------

Value

A numeric vector containing the length of the GIObjct

 makeGenomicInteractionsFromFile

Function to create GenomicInteraction objects from a file

Description

Function to create GenomicInteraction objects from a variety of files. The resulting objects contain information on which genomic regions are interacting with each other, and the number of counts supporting each interaction. It is also possible to store information on associated p-values and false-discovery rates (FDR). It is possible to create GenomicInteractions objects for various datasets including Hi-C and ChIA-PET. It is possible to read interactions from a variety of files including BAM files, bed files (BED12 and BEDPE) and from the output from standard processing pipelines, such as HOMER and ChIA-PET tool. GenomicInteractions objects can also be created using calls of the form `new("GenomicInteractions", ...)`. For hiclib, it expects the directory in which the files extracted using `h5dictToTxt.py` from the hdf5 file are located, where as for all of the other file types it expects the full filename.

Usage

```
makeGenomicInteractionsFromFile(fn, type, experiment_name = "",
  description = "", chr_names = NULL)
```

Arguments

<code>fn</code>	Filename or, if type="hiclib", folder
<code>type</code>	One of "chiapet.tool", "chiapet.encode", "bed12", "bedpe", "hiclib", "homer", "bam", "two.bams".
<code>experiment_name</code>	Experiment name.
<code>description</code>	Description of experiment.
<code>chr_names</code>	a vector of chromosome names in order, required for re-naming chromosomes for hiclib import

Value

a GenomicInteractions object

Examples

```
k562.rep1 = makeGenomicInteractionsFromFile(file.path(system.file(package="GenomicInteractions"), "extdata", "k562.rep1"),
  type="chiapet.tool", experiment_name="k562", description="k562 pol2 8wg16")
```

```
k562.rep1
```

mm9_refseq_promoters *Mouse Refseq promoters from chr 14-15*

Description

This dataset contains a subset of the promoters from the Refseq annotation for mouse genome build mm9. See the HiC analysis vignette (`vignettes(GenomicInteractions)`) for more information on how this dataset was created.

Usage

```
data(mm9_refseq_promoters)
```

Format

A GRanges object with length 2441.

Value

A GRanges object.

plotCisTrans *Plots the percentages of cis and trans interactions for a GenomicInteractions object as a donut plot.*

Description

Plots the percentages of cis and trans interactions for a GenomicInteractions object as a donut plot.

Usage

```
plotCisTrans(GIobject)
```

Arguments

GIobject A GenomicInteractions object

Value

A ggplot2 plot

Examples

```
data(hic_example_data)
plotCisTrans(hic_example_data)
```

plotCounts	<i>Plot a bar chart of the number of interactions supported by different numbers of reads in your data.</i>
------------	---

Description

Plot a bar chart of the number of interactions supported by different numbers of reads in your data.

Usage

```
plotCounts(GIObject, normalise = FALSE, cut = 10)
```

Arguments

GIObject	A GenomicInteractions object.
normalise	Logical. If TRUE, plots proportion of total reads instead of count.
cut	Numeric, can be NULL. Default: 10. All interactions with counts > cut are consolidated into a single category.

Value

A ggplot2 plot

Examples

```
data(hic_example_data)
plotCounts(hic_example_data)
plotCounts(hic_example_data, normalise=TRUE)
```

plotDists	<i>Plots a histogram of interaction distances for a GenomicInteractions Object</i>
-----------	--

Description

Plots a histogram of interaction distances for a GenomicInteractions Object

Usage

```
plotDists(GIObject, breaks = c(0, 1000, 5000, 10000, 50000, 1e+05, 5e+05,
  1e+06, 2e+06), method = "midpoint")
```

Arguments

GIObject	A GenomicInteractions object
breaks	A numeric vector of breaks for the histogram
method	Method used for distance between anchors. Passed to calculateDistances. One of "midpoint", "inner", or "outer".

Value

A ggplot2 plot

Examples

```
data(hic_example_data)
plotDists(hic_example_data)
```

plotInteractionAnnotations

Plot a donut plot of interaction types for an annotated GenomicInteractions object

Description

Plot a donut plot of interaction types for an annotated GenomicInteractions object

Usage

```
plotInteractionAnnotations(GIObject, node.classes = NULL, viewpoints = NULL,
  other = 0, keep.order = FALSE, legend = FALSE)
```

Arguments

GIObject	A GenomicInteractions object
node.classes	Optional. All node.classes to include in the analysis. Default: all node classes.
viewpoints	Optional. If set will only consider interactions where at least one anchor is of this node class. Default: all classes in node.classes.
other	Optional. Interaction types making up fewer than "other" percent of the total interactions will be consolidated into a single "other" category.
keep.order	Optional. Logical. Keep original order of node.classes for plotting or not. Default: FALSE, alphabetical order.
legend	Optional. Logical. If TRUE, legend is plotted to right of donut plot. If FALSE, donut plot is annotated with category names.

Value

A ggplot2 plot

Examples

```
data(hic_example_data)
plotInteractionAnnotations(hic_example_data)
```

plotSummaryStats	<i>Plot summary statistics for a GenomicInteractions object</i>
------------------	---

Description

Makes summary plots of the counts, interaction distances, interaction annotations, and percentage of cis and trans interactions for a GenomicInteractions object using ‘plotCounts’, ‘plotDists’, ‘plotCisTrans’, and ‘plotInteractionAnnotations’.

Usage

```
plotSummaryStats(GIObject, other = 5, cut = 10)
```

Arguments

GIObject	A GenomicInteractions object
other	Default 5. Passed to plotInteractionAnnotations. Interaction types making up fewer than "other" percent of the total interactions will be consolidated into a single "other" category.
cut	Default 10. Passed to plotCounts. All interactions with counts > cut are consolidated into a single category.

Value

```
invisible(1)
```

Examples

```
data(hic_example_data)
plotSummaryStats(hic_example_data)
```

plotViewpoint	<i>Plot coverage around a virtual 4C viewpoint</i>
---------------	--

Description

Plots coverage of interactions around a given viewpoint. This function requires the output of ‘viewPoint()’ as input. You should additionally specify the total region you wish to plot.

Usage

```
plotViewpoint(x, region, ylab = "Signal", xlab = NULL, ...)
```

Arguments

x	a GenomicInteractions object which is output from viewPoint
region	The genomic region to plot
ylab	Y axis label.
xlab	X axis label. By default this is the chromosome of the region that is being plotted.
...	additional arguments to plot

Value

output of plot()

print,GenomicInteractions-method	<i>Print function for GenomicInteractions</i>
----------------------------------	---

Description

Print function for GenomicInteractions

Usage

```
## S4 method for signature 'GenomicInteractions'
print(x)
```

Arguments

x	GenomicInteractionsObject
---	---------------------------

Value

invisible(1)

removeDups	<i>Remove all but one occurrences of a duplicated interaction</i>
------------	---

Description

Removes all but the first occurrence of a duplicated interaction (defined as having identical coordinates for both anchors). N.B. this does not summarise the total counts of all the duplicates. It is designed for removing potential PCR duplicates after reading in .bam files.

Usage

```
removeDups(GIObject)
```

Arguments

GIObject A GenomicInteractions object.

Value

A GenomicInteractions object that is a subset of the input object.

resetAnnotations	<i>Reset annotations made to a GenomicInteractions object</i>
------------------	---

Description

This function removes all annotations from a GenomicInteractions object by deleting all of the metadata columns associated with both anchors.

Usage

```
resetAnnotations(GIObject)
```

```
## S4 method for signature 'GenomicInteractions'
resetAnnotations(GIObject)
```

Arguments

GIObject An annotated GenomicInteractions object

Value

```
invisible(1)
```

sameStrand	<i>Tests whether anchors have the same strand.</i>
------------	--

Description

This is designed for processing .bam files.

Usage

```
sameStrand(GIObject)
```

Arguments

GIObject	A GenomicInteractions object
----------	------------------------------

Value

A logical vector denoting with TRUE if both anchors of an interaction are on the same strand and FALSE otherwise.

seqinfo, GenomicInteractions-method	<i>Accessing/modifying sequence information for a GenomicInteractions object</i>
-------------------------------------	--

Description

Allows access/modification of seqinfo for GenomicInteractions objects. When used with "force=True", interactions with either (or both) anchors on invalid chromosomes will be removed.

Usage

```
## S4 method for signature 'GenomicInteractions'
seqinfo(x)

## S4 replacement method for signature 'GenomicInteractions'
seqinfo(x, new2old = NULL, force = FALSE) <-
  value
```

Arguments

x	A GenomicInteractions object
new2old	Mapping between new and old seqnames. See ?seqinfo in GenomeInfoDb for details.
force	A logical indicating whether or not to drop invalid levels.
value	A replacement seqinfo object

Details

For more information see `?seqinfo` in the `GenomeInfoDb` package.

Value

A `seqinfo` object,

setters

Functions to set data held in a `GenomicInteractions` object.

Description

Use these functions to set data stored in each of the slots of a `GenomicInteractions` object.

Usage

```
name(GIObject) <- value

description(GIObject) <- value

interactionCounts(GIObject) <- value

## S4 replacement method for signature 'GenomicInteractions'
name(GIObject) <- value

## S4 replacement method for signature 'GenomicInteractions'
description(GIObject) <- value

## S4 replacement method for signature 'GenomicInteractions'
interactionCounts(GIObject) <- value
```

Arguments

`GIObject` A `GenomicInteractions` object
`value` A vector to replace a slot in the object

Value

`GenomicInteractions` object

Examples

```
library(GenomicRanges)

anchor.one = GRanges(c("chr1", "chr1", "chr1", "chr1"), IRanges(c(10, 20, 30, 20), width=5))
anchor.two = GRanges(c("chr1", "chr1", "chr1", "chr2"), IRanges(c(100, 200, 300, 50), width=5))
interaction_counts = sample(1:10, 4)
```

```

test <- GenomicInteractions(anchor.one, anchor.two, experiment_name="test",
                           description="this is a test", counts=interaction_counts)

name(test) <- "Mouse test"
name(test)

description(test) <- "This is a test using the mouse genome"
description(test)

interactionCounts(test) <- c(2,3,8,5)
interactionCounts(test)

```

show,GenomicInteractions-method

Representation function for GenomicInteractions

Description

Representation function for GenomicInteractions

Usage

```

## S4 method for signature 'GenomicInteractions'
show(object)

```

Arguments

object A GenomicInteractionsObject

Value

invisible(1)

sort,GenomicInteractions-method

Sort GenomicInteractions Object

Description

This method will sort a GenomicInteractions object by first arranging all interactions start on the lower-ordered anchor; for trans-chromosomal interactions this is the anchor on the lower ordered chromosome (defined by the seqlevels factor); and then by the position of the first anchor. See ?"GenomicRanges-comparison" for ordering rules.

Usage

```
## S4 method for signature 'GenomicInteractions'
sort(x, decreasing = FALSE,
     order.interactions = TRUE)
```

Arguments

x GenomicInteractions Object

decreasing A logical indicating sort order

order.interactions A logical indicating if interactions should be reordered, or only rearranged so that start(anchorOne) < start(anchorTwo)

Value

A sorted GenomicInteractions object

subsetByFeatures *Subset a GenomicInteractions object by features*

Description

Subsets interactions for which at least one of the anchors overlaps with a given GRanges object. Alternatively, subsets interactions based on annotated feature IDs for a particular feature.

Usage

```
subsetByFeatures(GIObject, features, feature.class = NULL)

## S4 method for signature 'GenomicInteractions,GRanges,missing'
subsetByFeatures(GIObject,
                 features, feature.class = NULL)

## S4 method for signature 'GenomicInteractions,GRangesList,missing'
subsetByFeatures(GIObject,
                 features, feature.class = NULL)

## S4 method for signature 'GenomicInteractions,character,character'
subsetByFeatures(GIObject,
                 features, feature.class = NULL)
```

Arguments

GIObject A GenomicInteractions object

features A GRanges or GRangesList object, or a character vector containing IDs of annotated features, e.g. promoter IDs.

feature.class If 'features' is a character vector, the corresponding feature name, e.g. "promoter".

Value

a subsetting GenomicInteractions object

sum, GenomicInteractions-method

Return the total number of interactions in a GenomicInteractions GIObjct

Description

Return the total number of interactions in a GenomicInteractions GIObjct

Usage

```
## S4 method for signature 'GenomicInteractions'
sum(x)
```

Arguments

x GenomicInteractions GIObjct

Value

The sum of the counts in GIObjct

summariseByFeatures *Summary statistics of interactions for a given feature set*

Description

This function will calculate summary statistics for each element in the given feature set, including the number of interactions (the sum of all interaction counts), number of unique interactions and number of trans- (interchromosomal) interactions. It also returns some statistics for the distances of interactions for all interactions of the feature, and for the different interaction types e.g. promoter-distal.

Usage

```
summariseByFeatures(GIObjct, features, feature.name,
  distance.method = "midpoint", annotate.self = FALSE)
```

```
## S4 method for signature 'GenomicInteractions'
summariseByFeatures(GIObjct, features,
  feature.name, distance.method = "midpoint", annotate.self = FALSE)
```

Arguments

GIObject	An annotated GenomicInteractions object
features	A GRanges object containing the feature set
feature.name	The name of the feature set
distance.method	Method for calculating distances between anchors, see ?calculateDistances
annotate.self	Logical. Indicates whether to annotate self interactions, i.e. where a feature in 'features' overlaps both anchors of an interaction. Default: FALSE.

Value

A data frame with one line for each range in 'features'

```
trim, GenomicInteractions-method
```

Trim a GenomicInteractions object

Description

This will remove any interactions with an anchor falling outside of the seqlengths in a GenomicInteractions object, and trim ranges which cross the ends of chromosomes.

Usage

```
## S4 method for signature 'GenomicInteractions'
trim(x, minAnchorSize = 1, ...)
```

Arguments

x	A GenomicInteractions object
minAnchorSize	The minimum size anchor to allow when trimming ranges.
...	any additional arguments to trim

Value

A trimmed GenomicInteractions object

viewPoint	<i>Virtual 4C viewpoint</i>
-----------	-----------------------------

Description

This function creates a GenomicInteractions object representing interactions originating at a given viewpoint ("bait"), or set of viewpoints. This is similar to the idea of a virtual 4C experiment where you are interested in interactions with a specific region.

Usage

```
viewPoint(x, bait, region = NULL, ...)
```

Arguments

x	A GenomicInteractions object.
bait	A GRanges object describing bait regions.
region	If present, a GenomicInteractions object specifying the region to look for bait interactions in.
...	additional arguments to findoverlaps

Details

The object returned has the "bait" as anchor one, and the interacting regions as anchor two. By default this is genome wide. If you only want to consider interactions within a certain distance around the bait, you can specify a region to consider.

Multiple baits can be given, e.g. to find all interactions around promoters.

You may want to visualise the resulting interactions in a genome browser - you can do this by creating coverage over anchor two of the object and exporting as a wig or bedgraph file.

Value

A GenomicInteractions object.

Examples

```
## Not run:
data(hic_data)
library(GenomicRanges)
pos <- GRanges(seqnames="chr5", ranges=IRanges(start=115938063, end=115941352))
region <- GRanges(seqnames="chr5", ranges=IRanges(start=115838063, end=116041352))
viewPoint(hic_data, pos, region)

## End(Not run)
```

[*Standard subsetting methods for GenomicInteractions objects*]

Description

Standard subsetting methods for GenomicInteractions objects

Usage

```
## S4 method for signature 'GenomicInteractions,ANY,ANY'
x[i, j, drop]
```

Arguments

x	A genomicInteractions object
i	A numeric, logical or Rle vector
j	A numeric or logical vector
drop	Logical. If TRUE, result is coerced to lowest possible dimension.

Value

A GenomicInteractions object containing only the features specified by ‘i’.

`$.GenomicInteractions-method`

Quick access to GenomicInteractions metadata columns

Description

Quick access to GenomicInteractions metadata columns

Usage

```
## S4 method for signature 'GenomicInteractions'
x$name

## S4 replacement method for signature 'GenomicInteractions'
x$name <- value
```

Arguments

x	A GenomicInteractions object
name	Column to select
value	Replacement value

Value

A vector containing the contents of the column

Index

*Topic **datasets**

hg19.refseq.transcripts, 15
hic_example_data, 16
mm9_refseq_promoters, 20
[, 33
[, GenomicInteractions, ANY, ANY-method
 [, 33
\$, GenomicInteractions-method, 33
\$<-, GenomicInteractions-method
 (\$, GenomicInteractions-method),
 33

anchorOne (getters), 13
anchorOne, GenomicInteractions-method
 (getters), 13
anchorTwo (getters), 13
anchorTwo, GenomicInteractions-method
 (getters), 13
annotateAnchors, 3
annotateAnchors, GenomicInteractions, numeric, character, vector-method
 (annotateAnchors), 3
annotateInteractions, 3
annotateInteractions, GenomicInteractions, list-method
 (annotateInteractions), 3
annotationFeatures (getters), 13
annotationFeatures, GenomicInteractions-method
 (getters), 13

c, 4
c, GenomicInteractions-method (c), 4
calculateDistances, 5
calculateDistances, GenomicInteractions-method
 (calculateDistances), 5
capitalize, 6
categoriseInteractions, 6
countOverlaps, GenomicInteractions, GRanges-method
 (findOverlaps), 10
countOverlaps, GRanges, GenomicInteractions-method
 (findOverlaps), 10
countsBetweenAnchors, 7

countsBetweenAnchors, GenomicInteractions, GRanges-method
 (countsBetweenAnchors), 7

description (getters), 13
description, GenomicInteractions-method
 (getters), 13
description<- (setters), 27
description<-, GenomicInteractions-method
 (setters), 27

export.bed12, 7
export.bed12, GenomicInteractions-method
 (export.bed12), 7
export.bedpe, 8
export.bedpe, GenomicInteractions-method
 (export.bedpe), 8
export.chiasig, 9
export.chiasig, GenomicInteractions-method
 (export.chiasig), 9
export.igraph, GenomicInteractions-method
 (export.igraph), 9

findOverlaps, 10
findOverlaps, GenomicInteractions, GenomicInteractions-method
 (findOverlaps), 10
findOverlaps, GenomicInteractions, GRanges-method
 (findOverlaps), 10
findOverlaps, GRanges, GenomicInteractions-method
 (findOverlaps), 10

GenomicInteractions, 11
GenomicInteractions-class, 12
GenomicInteractions-package, 2
get_binom_ligation_threshold, 14
get_self_ligation_threshold, 15
getters, 13
hg19.refseq.transcripts, 15
hic_example_data, 16

interactionCounts (getters), 13
 interactionCounts, GenomicInteractions-method
 (getters), 13
 interactionCounts<- (setters), 27
 interactionCounts<-, GenomicInteractions-method
 (setters), 27
 InteractionHelpers (is.pp), 17
 is.cis (is.pp), 17
 is.cis, GenomicInteractions-method
 (is.pp), 17
 is.dd (is.pp), 17
 is.dd, GenomicInteractions-method
 (is.pp), 17
 is.dt (is.pp), 17
 is.dt, GenomicInteractions-method
 (is.pp), 17
 is.pd (is.pp), 17
 is.pd, GenomicInteractions-method
 (is.pp), 17
 is.pp, 17
 is.pp, GenomicInteractions-method
 (is.pp), 17
 is.pt (is.pp), 17
 is.pt, GenomicInteractions-method
 (is.pp), 17
 is.trans (is.pp), 17
 is.trans, GenomicInteractions-method
 (is.pp), 17
 is.tt (is.pp), 17
 is.tt, GenomicInteractions-method
 (is.pp), 17
 isInteractionType (is.pp), 17
 isInteractionType, GenomicInteractions-method
 (is.pp), 17

 length, GenomicInteractions-method, 18

 makeGenomicInteractionsFromFile, 19
 mm9_refseq_promoters, 20

 name (getters), 13
 name, GenomicInteractions-method
 (getters), 13
 name<- (setters), 27
 name<-, GenomicInteractions-method
 (setters), 27

 overlapsAny, GenomicInteractions, GRanges-method
 (findOverlaps), 10

 overlapsAny, GRanges, GenomicInteractions-method
 (findOverlaps), 10

 plotCisTrans, 20
 plotCounts, 21
 plotDists, 21
 plotInteractionAnnotations, 22
 plotSummaryStats, 23
 plotViewpoint, 24
 print, GenomicInteractions-method, 24

 removeDups, 25
 resetAnnotations, 25
 resetAnnotations, GenomicInteractions-method
 (resetAnnotations), 25

 sameStrand, 26
 seqinfo, GenomicInteractions-method, 26
 seqinfo<-, GenomicInteractions-method
 (seqinfo, GenomicInteractions-method),
 26
 setters, 27
 show, GenomicInteractions-method, 28
 sort, GenomicInteractions-method, 28
 subsetByFeatures, 29
 subsetByFeatures, GenomicInteractions, character, character-m
 (subsetByFeatures), 29
 subsetByFeatures, GenomicInteractions, GRanges, missing-metho
 (subsetByFeatures), 29
 subsetByFeatures, GenomicInteractions, GRangesList, missing-m
 (subsetByFeatures), 29
 sum, GenomicInteractions-method, 30
 summariseByFeatures, 30
 summariseByFeatures, GenomicInteractions-method
 (summariseByFeatures), 30

 trim, GenomicInteractions-method, 31

 viewPoint, 32