

Package ‘parglms’

October 9, 2015

Title support for parallelized estimation of GLMs/GEEs

Version 1.0.0

Author VJ Carey <stvjc@channing.harvard.edu>

Description support for parallelized estimation of GLMs/GEEs,
catering for dispersed data

Suggests RUnit, sandwich, MASS

Depends methods

Imports BiocGenerics, BiocParallel, BatchJobs

Maintainer VJ Carey <stvjc@channing.harvard.edu>

License Artistic-2.0

LazyLoad yes

BiocViews statistics, genetics

ByteCompile TRUE

NeedsCompilation no

R topics documented:

parglms-package	1
parGLM-methods	3

Index	5
--------------	----------

parglms-package	<i>support for parallelized estimation of GLMs/GEEs</i>
-----------------	---

Description

support for parallelized estimation of GLMs/GEEs, catering for dispersed data

Details

The DESCRIPTION file:

Package: parGLMs
Title: support for parallelized estimation of GLMs/GEEs
Version: 1.0.0
Author: VJ Carey <stvjc@channing.harvard.edu>
Description: support for parallelized estimation of GLMs/GEEs, catering for dispersed data
Suggests: RUnit, sandwich, MASS
Depends: methods
Imports: BiocGenerics, BiocParallel, BatchJobs
Maintainer: VJ Carey <stvjc@channing.harvard.edu>
License: Artistic-2.0
LazyLoad: yes
BiocViews: statistics, genetics
ByteCompile: TRUE

Index of help topics:

parGLM-methods	fit GLM-like models with parallelized contributions to sufficient statistics
parGLMs-package	support for parallelized estimation of GLMs/GEEs

In version 0.0.0 we established an approach to fitting GLM from data that have been persistently dispersed and managed by a [Registry](#).

Author(s)

VJ Carey <stvjc@channing.harvard.edu>

Maintainer: VJ Carey <stvjc@channing.harvard.edu>

References

This package shares an objective with the [bigglm](#) methods of `biglm`. In `bigglm`, a small-RAM-footprint algorithm is employed, with sequential chunking to update statistics in each iteration. In `parGLM` the footprint is likewise controllable, but statistics in each iteration are evaluated in parallel over chunks.

Examples

```
showMethods("parGLM")
```

parGLM-methods	<i>fit GLM-like models with parallelized contributions to sufficient statistics</i>
----------------	---

Description

This package addresses the problem of fitting GLM-like models in a scalable way, recognizing that data may be dispersed, with chunks processed in parallel, to create low-dimensional summaries from which model fits may be constructed.

Methods

`signature(formula = "formula", store = "Registry")` The model data are assumed to lie in the `file.dir/jobs/*` folders, with `file.dir` defined in the store, which is an instance of `Registry`.

Additional arguments must be supplied:

family a function that serves as a family for `stats::glm`

binit a vector of initial values for regression parameter estimation, must conform to expectations of `formula`

maxit an integer giving the maximum number of iterations allowed

tol a numeric giving the tolerance criterion

Failure to specify these triggers a fatal error.

The `Registry` instance can be modified to include a list element `'extractor'`. This must be a function with arguments `store`, and `codei`. The standard extraction function is

```
function(store, i) loadResult(store, i)
```

It must return a data frame, conformant with the expectations of `formula`. Limited checking is performed.

The `predict` method computes the linear predictor on data identified by `jobid` in a `BatchJobs` registry. Results are returned as output of `bplapply` over the `jobids` specified in the `predict` call.

Examples

```
if (require(MASS) & require(BatchJobs) & require(BiocParallel)) {
  register(SerialParam())
  data(anorexia) # N = 72
  myr = makeRegistry("abc", file.dir=tempfile())
  chs = chunk(1:nrow(anorexia), n.chunks=18) # 4 recs/chunk
  f = function(x) anorexia[x,]
  batchMap(myr, f, chs)
  submitJobs(myr) # now getResult(myr,1) gives back a data.frame
  waitForJobs(myr) # simple dispersal
  pp = parGLM(Postwt ~ Treat + Prewt, myr,
    family=gaussian, binit = c(0,0,0,0), maxit=10, tol=.001 )
  print(summary(theLM <- lm(Postwt~Treat+Prewt, data=anorexia)))
  print(pp$coefficients - coef(theLM))
  if (require(sandwich)) {
```

```
    hc0 <- vcovHC(theLM, type="HC0")
    print(pp$robust.variance - hc0)
  }

predict(pp, store=myr, jobids=2:3)
closeAllConnections()

}
```

Index

*Topic **methods**

parGLM-methods, 3

*Topic **modeling**

parGLM-methods, 3

*Topic **package**

parGLMs-package, 1

bigglm, 2

parGLM (parGLM-methods), 3

parGLM, formula, Registry-method
(parGLM-methods), 3

parGLM-methods, 3

parGLMs (parGLMs-package), 1

parGLMs-package, 1

predict (parGLM-methods), 3

print (parGLM-methods), 3

Registry, 2, 3

summary (parGLM-methods), 3