

Package ‘DelayedMatrixStats’

April 10, 2023

Type Package

Title Functions that Apply to Rows and Columns of 'DelayedMatrix' Objects

Version 1.20.0

Date 2022-10-12

Description A port of the 'matrixStats' API for use with DelayedMatrix objects from the 'DelayedArray' package. High-performing functions operating on rows and columns of DelayedMatrix objects, e.g. col / rowMedians(), col / rowRanks(), and col / rowSds(). Functions optimized per data type and for subsetted calculations such that both memory usage and processing time is minimized.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.1.1

Depends MatrixGenerics (>= 1.5.3), DelayedArray (>= 0.17.6)

Imports methods, matrixStats (>= 0.60.0), sparseMatrixStats, Matrix (>= 1.5-0), S4Vectors (>= 0.17.5), IRanges (>= 2.25.10)

Suggests testthat, knitr, rmarkdown, covr, BiocStyle, microbenchmark, profmem, HDF5Array

VignetteBuilder knitr

URL <https://github.com/PeteHaitch/DelayedMatrixStats>

BugReports <https://github.com/PeteHaitch/DelayedMatrixStats/issues>

biocViews Infrastructure, DataRepresentation, Software

git_url <https://git.bioconductor.org/packages/DelayedMatrixStats>

git_branch RELEASE_3_16

git_last_commit 1ed1425

git_last_commit_date 2022-11-01

Date/Publication 2023-04-10

Author Peter Hickey [aut, cre],
Hervé Pagès [ctb],
Aaron Lun [ctb]

Maintainer Peter Hickey <peter.hickey@gmail.com>

R topics documented:

colAlls,DelayedMatrix-method	2
colAnyMissings	5
colAvgPerRowSet,DelayedMatrix-method	7
colCollapse,DelayedMatrix-method	9
colCounts,DelayedMatrix-method	11
colCummaxs,DelayedMatrix-method	13
colDiffs,DelayedMatrix-method	17
colIQRDiffs,DelayedMatrix-method	19
colIQRs,DelayedMatrix-method	23
colLogSumExps,DelayedMatrix-method	25
colMads,DelayedMatrix-method	26
colMeans2,DelayedMatrix-method	29
colMedians,DelayedMatrix-method	31
colOrderStats,DelayedMatrix-method	33
colProds,DelayedMatrix-method	35
colQuantiles,DelayedMatrix-method	37
colRanks,DelayedMatrix-method	39
colSums2,DelayedMatrix-method	41
colTabulates,DelayedMatrix-method	43
colVars,DelayedMatrix-method	45
colWeightedMads,DelayedMatrix-method	47
colWeightedMeans,DelayedMatrix-method	49
colWeightedMedians,DelayedMatrix-method	51
colWeightedSds,DelayedMatrix-method	53
DelayedMatrixStats	55
subset_by_Nindex	55

Index **57**

colAlls,DelayedMatrix-method

Check if all elements in a row (column) of a matrix-like object are equal to a value

Description

Check if all elements in a row (column) of a matrix-like object are equal to a value.

Usage

```
## S4 method for signature 'DelayedMatrix'
colAlls(
  x,
  rows = NULL,
  cols = NULL,
  value = TRUE,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)

## S4 method for signature 'DelayedMatrix'
colAnys(
  x,
  rows = NULL,
  cols = NULL,
  value = TRUE,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)

## S4 method for signature 'DelayedMatrix'
rowAlls(
  x,
  rows = NULL,
  cols = NULL,
  value = TRUE,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)

## S4 method for signature 'DelayedMatrix'
rowAnys(
  x,
  rows = NULL,
  cols = NULL,
  value = TRUE,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)
```

Arguments

x	A NxK DelayedMatrix .
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
value	The value to search for.
na.rm	If TRUE , NAs are excluded first, otherwise not.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
...	Additional arguments passed to specific methods.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set. Only useNames = NA is currently supported, other values are silently ignored.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowAlls/matrixStats::colAlls`.

Value

Returns a [logical vector](#) of length N (K).

Author(s)

Peter Hickey

Peter Hickey

See Also

- `matrixStats::rowAlls()` and `matrixStats::colAlls()` which are used when the input is a [matrix](#) or [numeric](#) vector.
- For checks if *any* element is equal to a value, see `rowAnys()`.
- `base::all()`.

Examples

```
# A DelayedMatrix with a 'matrix' seed
dm_matrix <- DelayedArray(matrix(c(rep(1L, 5),
                                as.integer((0:4) ^ 2),
                                seq(-5L, -1L, 1L)),
```

```

                                ncol = 3))
# A DelayedMatrix with a 'SolidRleArraySeed' seed
dm_Rle <- RleArray(Rle(c(rep(1L, 5),
                        as.integer((0:4) ^ 2),
                        seq(-5L, -1L, 1L))),
                 dim = c(5, 3))

colAlls(dm_matrix, value = 1)
colAnys(dm_matrix, value = 2)
rowAlls(dm_Rle, value = 1)
rowAnys(dm_Rle, value = 2)

```

colAnyMissings	<i>Checks if there are any missing values in an object or not</i>
----------------	---

Description

Checks if there are any missing values in an object or not. *Please use* `base::anyNA()` *instead of* `anyMissing()`, `colAnyNAs()` *instead of* `colAnyMissings()`, *and* `rowAnyNAs()` *instead of* `rowAnyMissings()`.

Usage

```
colAnyMissings(x, rows = NULL, cols = NULL, ..., useNames = NA)
```

```
rowAnyMissings(x, rows = NULL, cols = NULL, ..., useNames = NA)
```

```
## S4 method for signature 'DelayedMatrix'
```

```
colAnyMissings(
  x,
  rows = NULL,
  cols = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)
```

```
## S4 method for signature 'DelayedMatrix'
```

```
colAnyNAs(
  x,
  rows = NULL,
  cols = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)
```

```
## S4 method for signature 'DelayedMatrix'
```

```
rowAnyMissings(
```

```

x,
rows = NULL,
cols = NULL,
force_block_processing = FALSE,
...,
useNames = NA
)

## S4 method for signature 'DelayedMatrix'
rowAnyNAs(
x,
rows = NULL,
cols = NULL,
force_block_processing = FALSE,
...,
useNames = NA
)

```

Arguments

x	A NxK DelayedMatrix .
rows	A vector indicating subset of rows to operate over. If NULL , no subsetting is done.
cols	A vector indicating subset of columns to operate over. If NULL , no subsetting is done.
...	Additional arguments passed to specific methods.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set. Only useNames = NA is currently supported, other values are silently ignored.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .

Details

The implementation of this method is optimized for both speed and memory. The method will return [TRUE](#) as soon as a missing value is detected.

Value

Returns [TRUE](#) if a missing value was detected, otherwise [FALSE](#).

Author(s)

Peter Hickey

Peter Hickey

See Also

Starting with R v3.1.0, there is `anyNA()` in the **base**, which provides the same functionality as `anyMissing()`.

Examples

```
# A DelayedMatrix with a 'matrix' seed
dm_matrix <- DelayedArray(matrix(c(rep(1L, 5),
                                as.integer((0:4) ^ 2),
                                seq(-5L, -1L, 1L)),
                                ncol = 3))

# A DelayedMatrix with a 'HDF5ArraySeed' seed
# NOTE: Requires that the HDF5Array package is installed
library(HDF5Array)
dm_HDF5 <- writeHDF5Array(matrix(c(rep(1L, 5),
                                as.integer((0:4) ^ 2),
                                seq(-5L, -1L, 1L)),
                                ncol = 3))

dm_matrix[dm_matrix > 3] <- NA
colAnyNAs(dm_matrix)
dm_HDF5[dm_HDF5 > 3] <- NA
rowAnyNAs(dm_HDF5)
```

 colAvsPerRowSet,DelayedMatrix-method

Calculates for each row (column) a summary statistic for equally sized subsets of columns (rows)

Description

Calculates for each row (column) a summary statistic for equally sized subsets of columns (rows).

Usage

```
## S4 method for signature 'DelayedMatrix'
colAvsPerRowSet(
  X,
  W = NULL,
  cols = NULL,
  S,
  FUN = colMeans,
  ...,
```

```

    force_block_processing = FALSE,
    na.rm = NA,
    tFUN = FALSE
  )

## S4 method for signature 'DelayedMatrix'
rowAvsPerColSet(
  X,
  W = NULL,
  rows = NULL,
  S,
  FUN = rowMeans,
  ...,
  force_block_processing = FALSE,
  na.rm = NA,
  tFUN = FALSE
)

```

Arguments

X	A NxM DelayedMatrix .
W	An optional numeric NxM matrix of weights.
cols	A vector indicating the subset (and/or columns) to operate over. If NULL , no subsetting is done.
S	An integer KxJ matrix that specifying the J subsets. Each column hold K column (row) indices for the corresponding subset. The range of values is [1, M] ([1,N]).
FUN	A row-by-row (column-by-column) summary statistic function. It is applied to each column (row) subset of X that is specified by S.
...	Additional arguments passed to specific methods.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary <code>base::array</code> .
na.rm	(logical) Argument passed to FUN() as <code>na.rm = na.rm</code> . If NA (default), then <code>na.rm = TRUE</code> is used if X or S holds missing values, otherwise <code>na.rm = FALSE</code> .
tFUN	If TRUE, X is transposed before it is passed to FUN.
rows	A vector indicating the subset (and/or columns) to operate over. If NULL , no subsetting is done.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowAvsPerColSet` / `matrixStats::colAvsPerRowSet`.

Value

Returns a numeric $J \times N$ ($M \times J$) matrix.

Author(s)

Peter Hickey

See Also

- `matrixStats::rowAvgPerColSet()` and `matrixStats::colAvgPerRowSet()` which are used when the input is a matrix or numeric vector.

Examples

```
# A DelayedMatrix with a 'DataFrame' seed
dm_DF <- DelayedArray(S4Vectors::DataFrame(C1 = rep(1L, 5),
                                           C2 = as.integer((0:4) ^ 2),
                                           C3 = seq(-5L, -1L, 1L)))
colAvgPerRowSet(dm_DF, S = matrix(1:2, ncol = 2))

rowAvgPerColSet(dm_DF, S = matrix(1:2, ncol = 1))
```

colCollapse,DelayedMatrix-method

Extract one cell from each row (column) of a matrix-like object

Description

Extract one cell from each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colCollapse(
  x,
  idxs,
  cols = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)

## S4 method for signature 'DelayedMatrix'
rowCollapse(
  x,
  idxs,
  rows = NULL,
```

```

    force_block_processing = FALSE,
    ...,
    useNames = NA
  )

```

Arguments

x	A NxK DelayedMatrix .
idxs	An index vector with the position to extract. It is recycled to match the number of rows (column)
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
...	Additional arguments passed to specific methods.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set. Only useNames = NA is currently supported, other values are silently ignored.
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowCollapse / matrixStats::colCollapse`.

Value

Returns a [numeric vector](#) of length N (K).

Author(s)

Peter Hickey

See Also

- `matrixStats::rowCollapse()` and `matrixStats::colCollapse()` which are used when the input is a [matrix](#) or [numeric vector](#).

Examples

```

# A DelayedMatrix with a 'matrix' seed
dm_matrix <- DelayedArray(matrix(c(rep(1L, 5),
                                as.integer((0:4) ^ 2),
                                seq(-5L, -1L, 1L)),
                                ncol = 3))

# A DelayedMatrix with a 'HDF5ArraySeed' seed
# NOTE: Requires that the HDF5Array package is installed
library(HDF5Array)
dm_HDF5 <- writeHDF5Array(matrix(c(rep(1L, 5),
                                as.integer((0:4) ^ 2),
                                seq(-5L, -1L, 1L)),
                                ncol = 3))

# Extract the 4th row as a vector
# NOTE: An ordinary vector is returned regardless of the backend of
#       the DelayedMatrix object
colCollapse(dm_matrix, 4)
colCollapse(dm_HDF5, 4)

# Extract the 2nd column as a vector
# NOTE: An ordinary vector is returned regardless of the backend of
#       the DelayedMatrix object
rowCollapse(dm_matrix, 2)
rowCollapse(dm_HDF5, 2)

```

colCounts,DelayedMatrix-method

Count how often an element in a row (column) of a matrix-like object is equal to a value

Description

Count how often an element in a row (column) of a matrix-like object is equal to a value.

Usage

```

## S4 method for signature 'DelayedMatrix'
colCounts(
  x,
  rows = NULL,
  cols = NULL,
  value = TRUE,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)

```

```
## S4 method for signature 'DelayedMatrix'
rowCounts(
  x,
  rows = NULL,
  cols = NULL,
  value = TRUE,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)
```

Arguments

x	A NxK DelayedMatrix .
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
value	The value to search for.
na.rm	If TRUE , NAs are excluded first, otherwise not.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
...	Additional arguments passed to specific methods.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set. Only useNames = NA is currently supported, other values are silently ignored.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowCounts/matrixStats::colCounts`.

Value

Returns a [integer vector](#) of length N (K).

Author(s)

Peter Hickey

See Also

- `matrixStats::rowCounts()` and `matrixStats::colCounts()` which are used when the input is a matrix or numeric vector.
- For checks if any element is equal to a value, see `rowAnys()`. To check if all elements are equal, see `rowAlls()`.

Examples

```
# A DelayedMatrix with a 'matrix' seed
dm_matrix <- DelayedArray(matrix(c(rep(1L, 5),
                                as.integer((0:4) ^ 2),
                                seq(-5L, -1L, 1L)),
                                ncol = 3))

# A DelayedMatrix with a 'DataFrame' seed
dm_DF <- DelayedArray(S4Vectors::DataFrame(C1 = rep(1L, 5),
                                           C2 = as.integer((0:4) ^ 2),
                                           C3 = seq(-5L, -1L, 1L)))

colCounts(dm_matrix, value = 1)
# Only count those in the first 4 rows
colCounts(dm_matrix, rows = 1:4, value = 1)

rowCounts(dm_DF, value = 5)
# Only count those in the odd-numbered rows of the 2nd column
rowCounts(dm_DF, rows = seq(1, nrow(dm_DF), 2), cols = 2, value = 5)
```

colCummaxs,DelayedMatrix-method

Calculates the cumulative maxima for each row (column) of a matrix-like object

Description

Calculates the cumulative maxima for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colCummaxs(
  x,
  rows = NULL,
  cols = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)

## S4 method for signature 'DelayedMatrix'
```

```
colCummins(  
  x,  
  rows = NULL,  
  cols = NULL,  
  force_block_processing = FALSE,  
  ...,  
  useNames = NA  
)  
  
## S4 method for signature 'DelayedMatrix'  
colCumprods(  
  x,  
  rows = NULL,  
  cols = NULL,  
  force_block_processing = FALSE,  
  ...,  
  useNames = NA  
)  
  
## S4 method for signature 'DelayedMatrix'  
colCumsums(  
  x,  
  rows = NULL,  
  cols = NULL,  
  force_block_processing = FALSE,  
  ...,  
  useNames = NA  
)  
  
## S4 method for signature 'DelayedMatrix'  
rowCummaxs(  
  x,  
  rows = NULL,  
  cols = NULL,  
  force_block_processing = FALSE,  
  ...,  
  useNames = NA  
)  
  
## S4 method for signature 'DelayedMatrix'  
rowCummins(  
  x,  
  rows = NULL,  
  cols = NULL,  
  force_block_processing = FALSE,  
  ...,  
  useNames = NA  
)
```

```
## S4 method for signature 'DelayedMatrix'
rowCumprods(
  x,
  rows = NULL,
  cols = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)

## S4 method for signature 'DelayedMatrix'
rowCumsums(
  x,
  rows = NULL,
  cols = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)
```

Arguments

x	A NxK DelayedMatrix .
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
...	Additional arguments passed to specific methods.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set. Only <code>useNames = NA</code> is currently supported, other values are silently ignored.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowCummaxs / matrixStats::colCummaxs`.

Value

Returns a [numeric matrix](#) with the same dimensions as x.

Author(s)

Peter Hickey

Peter Hickey

Peter Hickey

Peter Hickey

See Also

- `matrixStats::rowCummaxs()` and `matrixStats::colCummaxs()` which are used when the input is a matrix or numeric vector.
- For single maximum estimates, see `rowMaxs()`.
- `base::cummax()`.

Examples

```
# A DelayedMatrix with a 'matrix' seed
dm_matrix <- DelayedArray(matrix(c(rep(1L, 5),
                                as.integer((0:4) ^ 2),
                                seq(-5L, -1L, 1L)),
                                ncol = 3))

# A DelayedMatrix with a 'Matrix' seed
dm_Matrix <- DelayedArray(Matrix::Matrix(c(rep(1L, 5),
                                          as.integer((0:4) ^ 2),
                                          seq(-5L, -1L, 1L)),
                                          ncol = 3))

colCummaxs(dm_matrix)

colCummins(dm_matrix)

colCumprods(dm_matrix)

colCumsums(dm_matrix)

# Only use rows 2-4
rowCummaxs(dm_Matrix, rows = 2:4)

# Only use rows 2-4
rowCummins(dm_Matrix, rows = 2:4)

# Only use rows 2-4
rowCumprods(dm_Matrix, rows = 2:4)

# Only use rows 2-4
rowCumsums(dm_Matrix, rows = 2:4)
```

`colDiffs,DelayedMatrix-method`

Calculates the difference between each element of a row (column) of a matrix-like object

Description

Calculates the difference between each element of a row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colDiffs(
  x,
  rows = NULL,
  cols = NULL,
  lag = 1L,
  differences = 1L,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)
```

```
## S4 method for signature 'DelayedMatrix'
rowDiffs(
  x,
  rows = NULL,
  cols = NULL,
  lag = 1L,
  differences = 1L,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)
```

Arguments

<code>x</code>	A $N \times K$ DelayedMatrix .
<code>rows</code>	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
<code>cols</code>	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
<code>lag</code>	An integer specifying the lag.
<code>differences</code>	An integer specifying the order of difference.

force_block_processing FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on `\link[DelayedArray]{getAutoBlockSize}()`) columns (`colFoo()`) or rows (`rowFoo()`) into memory as an ordinary `base::array`.

... Additional arguments passed to specific methods.

useNames If `NA`, the default behavior of the function about naming support is remained. If `FALSE`, no naming support is done. Else if `TRUE`, names attributes of result are set. **Only useNames = NA is currently supported, other values are silently ignored.**

Details

The S4 methods for `x` of type `matrix`, `array`, or `numeric` call `matrixStats::rowDiffs/matrixStats::colDiffs`.

Value

Returns a `numeric matrix` with one column (row) less than `x`: $N \times (K - 1)$ or $(N - 1) \times K$.

Author(s)

Peter Hickey

See Also

- `matrixStats::rowDiffs()` and `matrixStats::colDiffs()` which are used when the input is a `matrix` or `numeric vector`.
- `base::diff()`.

Examples

```
# A DelayedMatrix with a 'matrix' seed
dm_matrix <- DelayedArray(matrix(c(rep(1L, 5),
                                as.integer((0:4) ^ 2),
                                seq(-5L, -1L, 1L)),
                              ncol = 3))

# A DelayedMatrix with a 'HDF5ArraySeed' seed
# NOTE: Requires that the HDF5Array package is installed
library(HDF5Array)
dm_HDF5 <- writeHDF5Array(matrix(c(rep(1L, 5),
                                  as.integer((0:4) ^ 2),
                                  seq(-5L, -1L, 1L)),
                                ncol = 3))

colDiffs(dm_matrix)

rowDiffs(dm_HDF5)
# In reverse column order
rowDiffs(dm_HDF5, cols = seq(ncol(dm_HDF5), 1, -1))
```

`colIQRDiffs,DelayedMatrix-method`

Calculates the interquartile range of the difference between each element of a row (column) of a matrix-like object

Description

Calculates the interquartile range of the difference between each element of a row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colIQRDiffs(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  diff = 1L,
  trim = 0,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)
```

```
## S4 method for signature 'DelayedMatrix'
colMadDiffs(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  diff = 1L,
  trim = 0,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)
```

```
## S4 method for signature 'DelayedMatrix'
colSdDiffs(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  diff = 1L,
  trim = 0,
  force_block_processing = FALSE,
```

```
    ...,
    useNames = NA
  )

## S4 method for signature 'DelayedMatrix'
colVarDiffs(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  diff = 1L,
  trim = 0,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)

## S4 method for signature 'DelayedMatrix'
rowIQRDiffs(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  diff = 1L,
  trim = 0,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)

## S4 method for signature 'DelayedMatrix'
rowMadDiffs(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  diff = 1L,
  trim = 0,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)

## S4 method for signature 'DelayedMatrix'
rowSdDiffs(
  x,
  rows = NULL,
  cols = NULL,
```

```

    na.rm = FALSE,
    diff = 1L,
    trim = 0,
    force_block_processing = FALSE,
    ...,
    useNames = NA
)

## S4 method for signature 'DelayedMatrix'
rowVarDiffs(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  diff = 1L,
  trim = 0,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)

```

Arguments

x	A NxK DelayedMatrix .
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , NAs are excluded first, otherwise not.
diff	An integer specifying the order of difference.
trim	A double in [0,1/2] specifying the fraction of observations to be trimmed from each end of (sorted) x before estimation.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
...	Additional arguments passed to specific methods.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set. Only useNames = NA is currently supported, other values are silently ignored.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowIQRDiffs / matrixStats::colIQRDiffs`.

Value

Returns a [numeric vector](#) of length N (K).

Author(s)

Peter Hickey

Peter Hickey

Peter Hickey

Peter Hickey

See Also

- `matrixStats::rowIQRDiffs()` and `matrixStats::colIQRDiffs()` which are used when the input is a matrix or numeric vector.
- For the direct interquartile range see also [rowIQRs](#).

Examples

```
# A DelayedMatrix with a 'Matrix' seed
dm_Matrix <- DelayedArray(Matrix::Matrix(c(rep(1L, 5),
                                         as.integer((0:4) ^ 2),
                                         seq(-5L, -1L, 1L)),
                                         ncol = 3))

# A DelayedMatrix with a 'SolidRleArraySeed' seed
dm_Rle <- RleArray(Rle(c(rep(1L, 5),
                        as.integer((0:4) ^ 2),
                        seq(-5L, -1L, 1L))),
                  dim = c(5, 3))

colIQRDiffs(dm_Matrix)

colMadDiffs(dm_Matrix)

colSdDiffs(dm_Matrix)

colVarDiffs(dm_Matrix)

# Only using rows 2-4
rowIQRDiffs(dm_Rle, rows = 2:4)

# Only using rows 2-4
rowMadDiffs(dm_Rle, rows = 2:4)

# Only using rows 2-4
rowSdDiffs(dm_Rle, rows = 2:4)

# Only using rows 2-4
rowVarDiffs(dm_Rle, rows = 2:4)
```

 colIQRs,DelayedMatrix-method

Calculates the interquartile range for each row (column) of a matrix-like object

Description

Calculates the interquartile range for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colIQRs(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)

## S4 method for signature 'DelayedMatrix'
rowIQRs(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)
```

Arguments

x	A NxK DelayedMatrix .
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , NAs are excluded first, otherwise not.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .

... Additional arguments passed to specific methods.

useNames If `NA`, the default behavior of the function about naming support is remained. If `FALSE`, no naming support is done. Else if `TRUE`, names attributes of result are set. **Only useNames = NA is currently supported, other values are silently ignored.**

Details

The S4 methods for `x` of type `matrix`, `array`, or `numeric` call `matrixStats::rowIQRs/matrixStats::colIQRs`.

Value

Returns a `numeric vector` of length `N (K)`.

Author(s)

Peter Hickey

See Also

- `matrixStats::rowIQRs()` and `matrixStats::colIQRs()` which are used when the input is a `matrix` or `numeric vector`.
- For a non-robust analog, see `rowSds()`. For a more robust version see `rowMads()`
- `stats::IQR()`.

Examples

```
# A DelayedMatrix with a 'matrix' seed
dm_matrix <- DelayedArray(matrix(c(rep(1L, 5),
                                as.integer((0:4) ^ 2),
                                seq(-5L, -1L, 1L)),
                                ncol = 3))

# A DelayedMatrix with a 'Matrix' seed
dm_Matrix <- DelayedArray(Matrix::Matrix(c(rep(1L, 5),
                                           as.integer((0:4) ^ 2),
                                           seq(-5L, -1L, 1L)),
                                           ncol = 3))

colIQRs(dm_matrix)

# Only using rows 2-4
rowIQRs(dm_matrix, rows = 2:4)
```

 colLogSumExps,DelayedMatrix-method

Accurately calculates the logarithm of the sum of exponentials for each row (column) of a matrix-like object

Description

Accurately calculates the logarithm of the sum of exponentials for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colLogSumExps(
  lx,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)
```

```
## S4 method for signature 'DelayedMatrix'
rowLogSumExps(
  lx,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)
```

Arguments

lx	A NxK DelayedMatrix . Typically, lx are $\log(x)$ values.
rows	A vector indicating the subset (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , NAs are excluded first, otherwise not.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads

one or more (depending on `\link[DelayedArray]{getAutoBlockSize}()`) columns (`colFoo()`) or rows (`rowFoo()`) into memory as an ordinary `base::array`.

... Additional arguments passed to specific methods.

`useNames` If `NA`, the default behavior of the function about naming support is remained. If `FALSE`, no naming support is done. Else if `TRUE`, names attributes of result are set. **Only** `useNames = NA` is currently supported, other values are silently ignored.

Details

The S4 methods for `x` of type `matrix`, `array`, or `numeric` call `matrixStats::rowLogSumExps / matrixStats::colLogSumExps`.

Value

Returns a `numeric vector` of length `N (K)`.

Author(s)

Peter Hickey

See Also

- `matrixStats::rowLogSumExps()` and `matrixStats::colLogSumExps()` which are used when the input is a `matrix` or `numeric vector`.
- `rowSums2()`

Examples

```
x <- DelayedArray(matrix(runif(10), ncol = 2))
colLogSumExps(log(x))
rowLogSumExps(log(x))
```

colMads,DelayedMatrix-method

Calculates the median absolute deviation for each row (column) of a matrix-like object

Description

Calculates the median absolute deviation for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colMads(
  x,
  rows = NULL,
  cols = NULL,
  center = NULL,
  constant = 1.4826,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)

## S4 method for signature 'DelayedMatrix'
colSds(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  center = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)

## S4 method for signature 'DelayedMatrix'
rowMads(
  x,
  rows = NULL,
  cols = NULL,
  center = NULL,
  constant = 1.4826,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)

## S4 method for signature 'DelayedMatrix'
rowSds(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  center = NULL,
  force_block_processing = FALSE,
  ...,

```

```

    useNames = NA
  )

```

Arguments

x	A NxK DelayedMatrix .
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
center	(optional) the center, defaults to the row means
constant	A scale factor. See <code>stats::mad()</code> for details.
na.rm	If TRUE , NAs are excluded first, otherwise not.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary <code>base::array</code> .
...	Additional arguments passed to specific methods.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set. Only useNames = NA is currently supported, other values are silently ignored.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowMads/matrixStats::colMads`.

Value

Returns a [numeric vector](#) of length N (K).

Author(s)

Peter Hickey
Peter Hickey

See Also

- `matrixStats::rowMads()` and `matrixStats::colMads()` which are used when the input is a `matrix` or `numeric` vector.
- For mean estimates, see `rowMeans2()` and `rowMeans()`.
- For non-robust standard deviation estimates, see `rowSds()`.

Examples

```
# A DelayedMatrix with a 'data.frame' seed
dm_df <- DelayedArray(data.frame(C1 = rep(1L, 5),
                                C2 = as.integer((0:4) ^ 2),
                                C3 = seq(-5L, -1L, 1L)))

# A DelayedMatrix with a 'Dataframe' seed
dm_DF <- DelayedArray(S4Vectors::DataFrame(C1 = rep(1L, 5),
                                           C2 = as.integer((0:4) ^ 2),
                                           C3 = seq(-5L, -1L, 1L)))

colMads(dm_df)

colSds(dm_df)

rowMads(dm_DF)

rowSds(dm_DF)
```

colMeans2,DelayedMatrix-method

Calculates the mean for each row (column) of a matrix-like object

Description

Calculates the mean for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colMeans2(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)

## S4 method for signature 'Matrix'
colMeans2(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

## S4 method for signature 'SolidRleArraySeed'
colMeans2(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

## S4 method for signature 'DelayedMatrix'
rowMeans2(
  x,
```

```

    rows = NULL,
    cols = NULL,
    na.rm = FALSE,
    force_block_processing = FALSE,
    ...,
    useNames = NA
)

## S4 method for signature 'Matrix'
rowMeans2(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

```

Arguments

x	A NxK DelayedMatrix .
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , NAs are excluded first, otherwise not.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
...	Additional arguments passed to specific methods.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set. Only useNames = NA is currently supported, other values are silently ignored.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowMeans2/matrixStats::colMeans2`.

Value

Returns a [numeric vector](#) of length N (K).

Author(s)

Peter Hickey

See Also

- `matrixStats::rowMeans2()` and `matrixStats::colMeans2()` which are used when the input is a [matrix](#) or [numeric vector](#).
- See also [rowMeans\(\)](#) for the corresponding function in base R.

- For variance estimates, see `rowVars()`.
- See also the base R version `base::rowMeans()`.

Examples

```
# A DelayedMatrix with a 'matrix' seed
dm_matrix <- DelayedArray(matrix(c(rep(1L, 5),
                                as.integer((0:4) ^ 2),
                                seq(-5L, -1L, 1L)),
                                ncol = 3))

# A DelayedMatrix with a 'SolidRleArraySeed' seed
dm_Rle <- RleArray(Rle(c(rep(1L, 5),
                          as.integer((0:4) ^ 2),
                          seq(-5L, -1L, 1L))),
                  dim = c(5, 3))

colMeans2(dm_matrix)

# NOTE: Temporarily use verbose output to demonstrate which method is
#       which method is being used
options(DelayedMatrixStats.verbose = TRUE)
# By default, this uses a seed-aware method for a DelayedMatrix with a
# 'SolidRleArraySeed' seed
rowMeans2(dm_Rle)
# Alternatively, can use the block-processing strategy
rowMeans2(dm_Rle, force_block_processing = TRUE)
options(DelayedMatrixStats.verbose = FALSE)
```

colMedians,DelayedMatrix-method

Calculates the median for each row (column) of a matrix-like object

Description

Calculates the median for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colMedians(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)
```

```
## S4 method for signature 'DelayedMatrix'
rowMedians(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)
```

Arguments

x	A NxK DelayedMatrix .
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , NAs are excluded first, otherwise not.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
...	Additional arguments passed to specific methods.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set. Only <code>useNames = NA</code> is currently supported, other values are silently ignored.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowMedians / matrixStats::colMedians`.

Value

Returns a [numeric vector](#) of length N (K).

Author(s)

Peter Hickey

See Also

- `matrixStats::rowMedians()` and `matrixStats::colMedians()` which are used when the input is a [matrix](#) or [numeric vector](#).
- For mean estimates, see `rowMeans2()` and `rowMeans()`.

Examples

```
# A DelayedMatrix with a 'Matrix' seed
dm_Matrix <- DelayedArray(Matrix::Matrix(c(rep(1L, 5),
                                           as.integer((0:4) ^ 2),
                                           seq(-5L, -1L, 1L)),
                                           ncol = 3))

colMedians(dm_Matrix)

rowMedians(dm_Matrix)
```

colOrderStats,DelayedMatrix-method

Calculates an order statistic for each row (column) of a matrix-like object

Description

Calculates an order statistic for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colOrderStats(
  x,
  rows = NULL,
  cols = NULL,
  which,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)

## S4 method for signature 'DelayedMatrix'
rowOrderStats(
  x,
  rows = NULL,
  cols = NULL,
  which,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)
```

Arguments

x A NxK [DelayedMatrix](#).

rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
which	An integer index in [1,K] ([1,N]) indicating which order statistic to be returned
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
...	Additional arguments passed to specific methods.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set. Only useNames = NA is currently supported, other values are silently ignored.

Details

The S4 methods for `x` of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowOrderStats / matrixStats::colOrderStats`.

Value

Returns a [numeric vector](#) of length `N` (`K`).

Author(s)

Peter Hickey

See Also

- `matrixStats::rowOrderStats()` and `matrixStats::colOrderStats()` which are used when the input is a [matrix](#) or [numeric vector](#).

Examples

```
# A DelayedMatrix with a 'Matrix' seed
dm_Matrix <- DelayedArray(Matrix::Matrix(c(rep(1L, 5),
                                         as.integer((0:4) ^ 2),
                                         seq(-5L, -1L, 1L)),
                                         ncol = 3))

# Only using columns 2-3
colOrderStats(dm_Matrix, cols = 2:3, which = 1)

# Different algorithms, specified by `which`, may give different results
rowOrderStats(dm_Matrix, which = 1)
rowOrderStats(dm_Matrix, which = 2)
```

`colProds,DelayedMatrix-method`*Calculates the product for each row (column) of a matrix-like object*

Description

Calculates the product for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colProds(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  method = c("direct", "expSumLog"),
  force_block_processing = FALSE,
  ...,
  useNames = NA
)

## S4 method for signature 'SolidRleArraySeed'
colProds(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  method = c("direct", "expSumLog"),
  ...,
  useNames = NA
)

## S4 method for signature 'DelayedMatrix'
rowProds(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  method = c("direct", "expSumLog"),
  force_block_processing = FALSE,
  ...,
  useNames = NA
)
```

Arguments

x	A NxK DelayedMatrix .
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , NAs are excluded first, otherwise not.
method	A character vector of length one that specifies the how the product is calculated. Note, that this is not a generic argument and not all implementation have to provide it.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
...	Additional arguments passed to specific methods.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set. Only useNames = NA is currently supported, other values are silently ignored.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowProds/matrixStats::colProds`.

Value

Returns a [numeric vector](#) of length N (K).

Author(s)

Peter Hickey

See Also

- `matrixStats::rowProds()` and `matrixStats::colProds()` which are used when the input is a [matrix](#) or [numeric vector](#).
- For sums across rows (columns), see `rowSums2()` (`colSums2()`)
- `base::prod()`.

Examples

```
# A DelayedMatrix with a 'matrix' seed
dm_matrix <- DelayedArray(matrix(c(rep(1L, 5),
                                as.integer((0:4) ^ 2),
                                seq(-5L, -1L, 1L)),
```

```

                                ncol = 3))
# A DelayedMatrix with a 'HDF5ArraySeed' seed
# NOTE: Requires that the HDF5Array package is installed
library(HDF5Array)
dm_HDF5 <- writeHDF5Array(matrix(c(rep(1L, 5),
                                as.integer((0:4) ^ 2),
                                seq(-5L, -1L, 1L)),
                                ncol = 3))

colProds(dm_matrix)

rowProds(dm_matrix)

```

colQuantiles,DelayedMatrix-method

Calculates quantiles for each row (column) of a matrix-like object

Description

Calculates quantiles for each row (column) of a matrix-like object.

Usage

```

## S4 method for signature 'DelayedMatrix'
colQuantiles(
  x,
  rows = NULL,
  cols = NULL,
  probs = seq(from = 0, to = 1, by = 0.25),
  na.rm = FALSE,
  type = 7L,
  force_block_processing = FALSE,
  ...,
  useNames = NA,
  drop = TRUE
)

```

```

## S4 method for signature 'DelayedMatrix'
rowQuantiles(
  x,
  rows = NULL,
  cols = NULL,
  probs = seq(from = 0, to = 1, by = 0.25),
  na.rm = FALSE,
  type = 7L,
  force_block_processing = FALSE,
  ...,
  useNames = NA,
)

```

```

    drop = TRUE
  )

```

Arguments

x	A NxK DelayedMatrix .
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
probs	A numeric vector of J probabilities in [0, 1].
na.rm	If TRUE , NAs are excluded first, otherwise not.
type	An integer specifying the type of estimator. See <code>stats::quantile()</code> . for more details.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary <code>base::array</code> .
...	Additional arguments passed to specific methods.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set. Only useNames = NA is currently supported, other values are silently ignored.
drop	If TRUE a vector is returned if J == 1.

Details

The S4 methods for x of type `matrix`, `array`, or `numeric` call `matrixStats::rowQuantiles / matrixStats::colQuantiles`.

Value

a `numeric` NxJ (KxJ) `matrix`, where N (K) is the number of rows (columns) for which the J values are calculated.

Author(s)

Peter Hickey

See Also

- `matrixStats::rowQuantiles()` and `matrixStats::colQuantiles()` which are used when the input is a `matrix` or `numeric` vector.
- `stats::quantile`

Examples

```
# A DelayedMatrix with a 'data.frame' seed
dm_df <- DelayedArray(data.frame(C1 = rep(1L, 5),
                                C2 = as.integer((0:4) ^ 2),
                                C3 = seq(-5L, -1L, 1L)))

# colnames, if present, are preserved as rownames on output
colQuantiles(dm_df)

# Input has no rownames so output has no rownames
rowQuantiles(dm_df)
```

```
colRanks,DelayedMatrix-method
```

Calculates the rank of the elements for each row (column) of a matrix-like object

Description

Calculates the rank of the elements for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colRanks(
  x,
  rows = NULL,
  cols = NULL,
  ties.method = c("max", "average", "first", "last", "random", "max", "min", "dense"),
  preserveShape = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = useNames
)

## S4 method for signature 'DelayedMatrix'
rowRanks(
  x,
  rows = NULL,
  cols = NULL,
  ties.method = c("max", "average", "first", "last", "random", "max", "min", "dense"),
  force_block_processing = FALSE,
  ...,
  useNames = NA
)
```

Arguments

x	A NxK DelayedMatrix .
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
ties.method	A character string specifying how ties are treated. Note that the default specifies fewer options than the original matrixStats package.
preserveShape	If TRUE the output matrix has the same shape as the input x. Note, that this is not a generic argument and not all implementation of this function have to provide it.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary <code>base::array</code> .
...	Additional arguments passed to specific methods.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set. Only useNames = NA is currently supported, other values are silently ignored.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowRanks/matrixStats::colRanks`.

The `matrixStats::rowRanks()` function can handle a lot of different values for the `ties.method` argument. Users of the generic function should however only rely on `max` and `average` because the other ones are not guaranteed to be implemented:

`max` for values with identical values the maximum rank is returned

`average` for values with identical values the average of the ranks they cover is returned. Note, that in this case the return value is of type `numeric`.

Value

a matrix of type [integer](#) is returned unless `ties.method = "average"`. It has dimensions `N x J` (`K x J`) [matrix](#), where N (K) is the number of rows (columns) of the input x.

Author(s)

Peter Hickey

See Also

- `matrixStats::rowRanks()` and `matrixStats::colRanks()` which are used when the input is a [matrix](#) or [numeric](#) vector.
- [base::rank](#)

Examples

```
# A DelayedMatrix with a 'Matrix' seed
dm_Matrix <- DelayedArray(Matrix::Matrix(c(rep(1L, 5),
                                           as.integer((0:4) ^ 2),
                                           seq(-5L, -1L, 1L)),
                                           ncol = 3))

colRanks(dm_Matrix)

rowRanks(dm_Matrix)
```

colSums2,DelayedMatrix-method

Calculates the sum for each row (column) of a matrix-like object

Description

Calculates the sum for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colSums2(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)

## S4 method for signature 'Matrix'
colSums2(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

## S4 method for signature 'SolidRleArraySeed'
colSums2(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = NA)

## S4 method for signature 'DelayedMatrix'
rowSums2(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)
```

```
)

## S4 method for signature 'Matrix'
rowSums2(x, rows = NULL, cols = NULL, na.rm = FALSE, ..., useNames = useNames)
```

Arguments

x	A NxK DelayedMatrix .
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , NAs are excluded first, otherwise not.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
...	Additional arguments passed to specific methods.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set. Only useNames = NA is currently supported, other values are silently ignored.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowSums2/matrixStats::colSums2`.

Value

Returns a [numeric vector](#) of length N (K).

Author(s)

Peter Hickey

See Also

- `matrixStats::rowSums2()` and `matrixStats::colSums2()` which are used when the input is a [matrix](#) or [numeric vector](#).
- For mean estimates, see `rowMeans2()` and `rowMeans()`.
- `base::sum()`.

Examples

```

# A DelayedMatrix with a 'matrix' seed
dm_matrix <- DelayedArray(matrix(c(rep(1L, 5),
                                as.integer((0:4) ^ 2),
                                seq(-5L, -1L, 1L)),
                                ncol = 3))

# A DelayedMatrix with a 'Matrix' seed
dm_Matrix <- DelayedArray(Matrix::Matrix(c(rep(1L, 5),
                                           as.integer((0:4) ^ 2),
                                           seq(-5L, -1L, 1L)),
                                           ncol = 3))

colSums2(dm_matrix)

# NOTE: Temporarily use verbose output to demonstrate which method is
#       which method is being used
options(DelayedMatrixStats.verbose = TRUE)
# By default, this uses a seed-aware method for a DelayedMatrix with a
# 'SolidRleArraySeed' seed
rowSums2(dm_Matrix)
# Alternatively, can use the block-processing strategy
rowSums2(dm_Matrix, force_block_processing = TRUE)
options(DelayedMatrixStats.verbose = FALSE)

```

colTabulates,DelayedMatrix-method

Tabulates the values in a matrix-like object by row (column)

Description

Tabulates the values in a matrix-like object by row (column).

Usage

```

## S4 method for signature 'DelayedMatrix'
colTabulates(
  x,
  rows = NULL,
  cols = NULL,
  values = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)

## S4 method for signature 'DelayedMatrix'
rowTabulates(
  x,

```

```

rows = NULL,
cols = NULL,
values = NULL,
force_block_processing = FALSE,
...,
useNames = NA
)

```

Arguments

x	A NxK DelayedMatrix .
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
values	the values to search for.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
...	Additional arguments passed to specific methods.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set. Only <code>useNames = NA</code> is currently supported, other values are silently ignored.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowTabulates / matrixStats::colTabulates`.

Value

a [numeric](#) NxJ (KxJ) [matrix](#), where N (K) is the number of rows (columns) for which the J values are calculated.

Author(s)

Peter Hickey

See Also

- `matrixStats::rowTabulates()` and `matrixStats::colTabulates()` which are used when the input is a [matrix](#) or [numeric](#) vector.
- `base::table()`

Examples

```
# A DelayedMatrix with a 'DataFrame' seed
dm_DF <- DelayedArray(S4Vectors::DataFrame(C1 = rep(1L, 5),
                                           C2 = as.integer((0:4) ^ 2),
                                           C3 = seq(-5L, -1L, 1L)))

colTabulates(dm_DF)

rowTabulates(dm_DF)
```

colVars,DelayedMatrix-method

Calculates the variance for each row (column) of a matrix-like object

Description

Calculates the variance for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colVars(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  center = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)

## S4 method for signature 'DelayedMatrix'
rowVars(
  x,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  center = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)
```

Arguments

x	A NxK DelayedMatrix .
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , NAs are excluded first, otherwise not.
center	(optional) the center, defaults to the row means.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
...	Additional arguments passed to specific methods.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set. Only useNames = NA is currently supported, other values are silently ignored.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowVars/matrixStats::colVars`.

Value

Returns a [numeric vector](#) of length N (K).

Author(s)

Peter Hickey

See Also

- `matrixStats::rowVars()` and `matrixStats::colVars()` which are used when the input is a [matrix](#) or [numeric vector](#).
- For mean estimates, see `rowMeans2()` and `rowMeans()`.
- For standard deviation estimates, see `rowSds()`.
- `stats::var()`.

Examples

```
# A DelayedMatrix with a 'matrix' seed
dm_matrix <- DelayedArray(matrix(c(rep(1L, 5),
                                as.integer((0:4) ^ 2),
                                seq(-5L, -1L, 1L)),
```

```

                                ncol = 3))
# A DelayedMatrix with a 'HDF5ArraySeed' seed
# NOTE: Requires that the HDF5Array package is installed
library(HDF5Array)
dm_HDF5 <- writeHDF5Array(matrix(c(rep(1L, 5),
                                as.integer((0:4) ^ 2),
                                seq(-5L, -1L, 1L)),
                                ncol = 3))

colVars(dm_matrix)

rowVars(dm_matrix)

```

colWeightedMads,DelayedMatrix-method

Calculates the weighted median absolute deviation for each row (column) of a matrix-like object

Description

Calculates the weighted median absolute deviation for each row (column) of a matrix-like object.

Usage

```

## S4 method for signature 'DelayedMatrix'
colWeightedMads(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  constant = 1.4826,
  center = NULL,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)

## S4 method for signature 'DelayedMatrix'
rowWeightedMads(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  constant = 1.4826,
  center = NULL,
  force_block_processing = FALSE,

```

```

    ...,
    useNames = NA
  )

```

Arguments

x	A NxK DelayedMatrix .
w	A numeric vector of length K (N) that specifies by how much each element is weighted.
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , NAs are excluded first, otherwise not.
constant	A scale factor. See <code>stats::mad()</code> for details.
center	(optional) the center, defaults to the row means
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
...	Additional arguments passed to specific methods.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set. Only useNames = NA is currently supported, other values are silently ignored.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowWeightedMads / matrixStats::colWeightedMads`.

Value

Returns a [numeric vector](#) of length N (K).

Author(s)

Peter Hickey

See Also

- `matrixStats::rowWeightedMads()` and `matrixStats::colWeightedMads()` which are used when the input is a matrix or numeric vector.
- See also [rowMads](#) for the corresponding unweighted function.

Examples

```
# A DelayedMatrix with a 'matrix' seed
dm_matrix <- DelayedArray(matrix(c(rep(1L, 5),
                                as.integer((0:4) ^ 2),
                                seq(-5L, -1L, 1L)),
                                ncol = 3))

colWeightedMads(dm_matrix, w = 1:5)

rowWeightedMads(dm_matrix, w = 3:1)
```

colWeightedMeans,DelayedMatrix-method

Calculates the weighted mean for each row (column) of a matrix-like object

Description

Calculates the weighted mean for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colWeightedMeans(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)

## S4 method for signature 'DelayedMatrix'
rowWeightedMeans(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)
```

Arguments

x	A NxK DelayedMatrix .
w	A numeric vector of length K (N) that specifies by how much each element is weighted.
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , NAs are excluded first, otherwise not.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
...	Additional arguments passed to specific methods.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set. Only useNames = NA is currently supported, other values are silently ignored.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowWeightedMeans` / `matrixStats::colWeightedMeans`.

Value

Returns a [numeric vector](#) of length N (K).

Author(s)

Peter Hickey

See Also

- `matrixStats::rowWeightedMeans()` and `matrixStats::colWeightedMeans()` which are used when the input is a matrix or numeric vector.
- See also [rowMeans2](#) for the corresponding unweighted function.

Examples

```
# A DelayedMatrix with a 'Matrix' seed
dm_Matrix <- DelayedArray(Matrix::Matrix(c(rep(1L, 5),
                                           as.integer((0:4) ^ 2),
                                           seq(-5L, -1L, 1L)),
                                           ncol = 3))
```

```
colWeightedMeans(dm_Matrix)
# Specifying weights inversely proportional to rowwise variances
colWeightedMeans(dm_Matrix, w = 1 / rowVars(dm_Matrix))
rowWeightedMeans(dm_Matrix, w = 1:3)
```

colWeightedMedians,DelayedMatrix-method

Calculates the weighted median for each row (column) of a matrix-like object

Description

Calculates the weighted median for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colWeightedMedians(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)

## S4 method for signature 'DelayedMatrix'
rowWeightedMedians(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)
```

Arguments

x A NxK [DelayedMatrix](#).

w A [numeric](#) vector of length K (N) that specifies by how much each element is weighted.

rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , NAs are excluded first, otherwise not.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary base::array .
...	Additional arguments passed to specific methods.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set. Only <code>useNames = NA</code> is currently supported, other values are silently ignored.

Details

The S4 methods for `x` of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowWeightedMedians / matrixStats::colWeightedMedians`.

Value

Returns a [numeric vector](#) of length `N (K)`.

Author(s)

Peter Hickey

See Also

- `matrixStats::rowWeightedMedians()` and `matrixStats::colWeightedMedians()` which are used when the input is a [matrix](#) or [numeric vector](#).
- See also [rowMedians](#) for the corresponding unweighted function.

Examples

```
# A DelayedMatrix with a 'SolidRleArraySeed' seed
dm_Rle <- RleArray(Rle(c(rep(1L, 5),
                        as.integer((0:4) ^ 2),
                        seq(-5L, -1L, 1L))),
                  dim = c(5, 3))

# Specifying weights inversely proportional to rowwise MADs
colWeightedMedians(dm_Rle, w = 1 / rowMads(dm_Rle))
```

colWeightedSds,DelayedMatrix-method

Calculates the weighted standard deviation for each row (column) of a matrix-like object

Description

Calculates the weighted standard deviation for each row (column) of a matrix-like object.

Usage

```
## S4 method for signature 'DelayedMatrix'
colWeightedSds(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)
```

```
## S4 method for signature 'DelayedMatrix'
colWeightedVars(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)
```

```
## S4 method for signature 'DelayedMatrix'
rowWeightedSds(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)
```

```
## S4 method for signature 'DelayedMatrix'
rowWeightedVars(
  x,
  w = NULL,
  rows = NULL,
  cols = NULL,
  na.rm = FALSE,
  force_block_processing = FALSE,
  ...,
  useNames = NA
)
```

Arguments

x	A NxK DelayedMatrix .
w	A numeric vector of length K (N) that specifies by how much each element is weighted.
rows	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
cols	A vector indicating the subset of rows (and/or columns) to operate over. If NULL , no subsetting is done.
na.rm	If TRUE , NAs are excluded first, otherwise not.
force_block_processing	FALSE (the default) means that a seed-aware, optimised method is used (if available). This can be overridden to use the general block-processing strategy by setting this to TRUE (typically not advised). The block-processing strategy loads one or more (depending on <code>\link[DelayedArray]{getAutoBlockSize}()</code>) columns (<code>colFoo()</code>) or rows (<code>rowFoo()</code>) into memory as an ordinary <code>base::array</code> .
...	Additional arguments passed to specific methods.
useNames	If NA , the default behavior of the function about naming support is remained. If FALSE , no naming support is done. Else if TRUE , names attributes of result are set. Only useNames = NA is currently supported, other values are silently ignored.

Details

The S4 methods for x of type [matrix](#), [array](#), or [numeric](#) call `matrixStats::rowWeightedSds / matrixStats::colWeightedSds`.

Value

Returns a [numeric vector](#) of length N (K).

Author(s)

Peter Hickey
Peter Hickey

See Also

- `matrixStats::rowWeightedSds()` and `matrixStats::colWeightedSds()` which are used when the input is a matrix or numeric vector.
- See also `rowSds` for the corresponding unweighted function.

Examples

```
# A DelayedMatrix with a 'SolidRleArraySeed' seed
dm_Rle <- RleArray(Rle(c(rep(1L, 5),
                        as.integer((0:4) ^ 2),
                        seq(-5L, -1L, 1L))),
                  dim = c(5, 3))

colWeightedSds(dm_Rle, w = 1 / rowMeans2(dm_Rle))

# Specifying weights inversely proportional to rowwise means
colWeightedVars(dm_Rle, w = 1 / rowMeans2(dm_Rle))

# Specifying weights inversely proportional to columnwise means
rowWeightedSds(dm_Rle, w = 1 / colMeans2(dm_Rle))

# Specifying weights inversely proportional to columnwise means
rowWeightedVars(dm_Rle, w = 1 / colMeans2(dm_Rle))
```

DelayedMatrixStats	<i>DelayedMatrixStats: Functions that apply to rows and columns of DelayedMatrix objects.</i>
--------------------	---

Description

DelayedMatrixStats is a part of the **matrixStats** API to work with *DelayedMatrix* objects from the **DelayedArray** package. High-performing functions operating on rows and columns of *DelayedMatrix* objects, e.g. `colMedians()` / `rowMedians()`, `colRanks()` / `rowRanks()`, and `colSds()` / `rowSds()`. Functions optimized per data type and for subsetted calculations such that both memory usage and processing time is minimized.

subset_by_Nindex	subset_by_Nindex
------------------	------------------

Description

`subset_by_Nindex()` is an internal generic function not aimed to be used directly by the user. It is basically an S4 generic for `DelayedArray:::subset_by_Nindex`.

Usage

```
subset_by_Nindex(x, Nindex)
```

Arguments

x	An array-like object.
Nindex	An unnamed list of subscripts as positive integer vectors, one vector per dimension in x. Empty and missing subscripts (represented by <code>integer(0)</code> and <code>NULL</code> list elements, respectively) are allowed. The subscripts can contain duplicated indices. They cannot contain NAs or non-positive values.

Details

`subset_by_Nindex(x, Nindex)` conceptually performs the operation `x[Nindex[1], ..., Nindex[length(Nindex)]]`. `subset_by_Nindex()` methods need to support empty and missing subscripts, e.g., `subset_by_Nindex(x, list(NULL, integer(0)))` must return an $M \times 0$ object of class `class(x)` and `subset_by_Nindex(x, list(integer(0), integer(0)))` a 0×0 object of class `class(x)`.

Also, subscripts are allowed to contain duplicate indices so things like `subset_by_Nindex(x, list(c(1:3, 3:1), 2L))` need to be supported.

Value

A object of class `class(x)` of the appropriate type (e.g., integer, double, etc.). For example, if x is a [data.frame](#) representing an $M \times N$ matrix of integers, `subset_by_Nindex(x, list(NULL, 2L))` must return its 2nd column as a [data.frame](#) with M rows and 1 column of type integer.

Index

all, [4](#)
array, [4](#), [8](#), [10](#), [12](#), [15](#), [18](#), [21](#), [24](#), [26](#), [28](#), [30](#),
[32](#), [34](#), [36](#), [38](#), [40](#), [42](#), [44](#), [46](#), [48](#), [50](#),
[52](#), [54](#)

base::array, [4](#), [6](#), [8](#), [10](#), [12](#), [15](#), [18](#), [21](#), [23](#),
[26](#), [28](#), [30](#), [32](#), [34](#), [36](#), [38](#), [40](#), [42](#), [44](#),
[46](#), [48](#), [50](#), [52](#), [54](#)
base::rank, [40](#)

colAlls, [4](#)
colAlls, DelayedMatrix-method, [2](#)
colAnyMissings, [5](#)
colAnyMissings, DelayedMatrix-method
(colAnyMissings), [5](#)
colAnyNAs, DelayedMatrix-method
(colAnyMissings), [5](#)
colAnys, DelayedMatrix-method
(colAlls, DelayedMatrix-method),
[2](#)
colAvgPerRowSet, [9](#)
colAvgPerRowSet, DelayedMatrix-method,
[7](#)
colCollapse, [10](#)
colCollapse, DelayedMatrix-method, [9](#)
colCounts, [13](#)
colCounts, DelayedMatrix-method, [11](#)
colCummaxs, [16](#)
colCummaxs, DelayedMatrix-method, [13](#)
colCummins, DelayedMatrix-method
(colCummaxs, DelayedMatrix-method),
[13](#)
colCumprods, DelayedMatrix-method
(colCummaxs, DelayedMatrix-method),
[13](#)
colCumsums, DelayedMatrix-method
(colCummaxs, DelayedMatrix-method),
[13](#)
colDiffs, [18](#)
colDiffs, DelayedMatrix-method, [17](#)

colIQRDiffs, [22](#)
colIQRDiffs, DelayedMatrix-method, [19](#)
colIQRs, [24](#)
colIQRs, DelayedMatrix-method, [23](#)
colLogSumExps, [26](#)
colLogSumExps, DelayedMatrix-method, [25](#)
colMadDiffs, DelayedMatrix-method
(colIQRDiffs, DelayedMatrix-method),
[19](#)
colMads, [28](#)
colMads, DelayedMatrix-method, [26](#)
colMeans2, [30](#)
colMeans2, DelayedMatrix-method, [29](#)
colMeans2, Matrix-method
(colMeans2, DelayedMatrix-method),
[29](#)
colMeans2, SolidRleArraySeed-method
(colMeans2, DelayedMatrix-method),
[29](#)
colMedians, [32](#)
colMedians, DelayedMatrix-method, [31](#)
colOrderStats, [34](#)
colOrderStats, DelayedMatrix-method, [33](#)
colProds, [36](#)
colProds, DelayedMatrix-method, [35](#)
colProds, SolidRleArraySeed-method
(colProds, DelayedMatrix-method),
[35](#)
colQuantiles, [38](#)
colQuantiles, DelayedMatrix-method, [37](#)
colRanks, [40](#)
colRanks, DelayedMatrix-method, [39](#)
colSdDiffs, DelayedMatrix-method
(colIQRDiffs, DelayedMatrix-method),
[19](#)
colSds, DelayedMatrix-method
(colMads, DelayedMatrix-method),
[26](#)
colSums2, [42](#)

- colSums2(), [36](#)
- colSums2,DelayedMatrix-method, [41](#)
- colSums2,Matrix-method
(colSums2,DelayedMatrix-method),
[41](#)
- colSums2,SolidRleArraySeed-method
(colSums2,DelayedMatrix-method),
[41](#)
- colTabulates, [44](#)
- colTabulates,DelayedMatrix-method, [43](#)
- colVarDiffs,DelayedMatrix-method
(colIQRDiffs,DelayedMatrix-method),
[19](#)
- colVars, [46](#)
- colVars,DelayedMatrix-method, [45](#)
- colWeightedMads, [48](#)
- colWeightedMads,DelayedMatrix-method,
[47](#)
- colWeightedMeans, [50](#)
- colWeightedMeans,DelayedMatrix-method,
[49](#)
- colWeightedMedians, [52](#)
- colWeightedMedians,DelayedMatrix-method,
[51](#)
- colWeightedSds, [55](#)
- colWeightedSds,DelayedMatrix-method,
[53](#)
- colWeightedVars,DelayedMatrix-method
(colWeightedSds,DelayedMatrix-method),
[53](#)
- cummax, [16](#)
- data.frame, [56](#)
- DelayedMatrix, [4](#), [6](#), [8](#), [10](#), [12](#), [15](#), [17](#), [21](#), [23](#),
[25](#), [28](#), [30](#), [32](#), [33](#), [36](#), [38](#), [40](#), [42](#), [44](#),
[46](#), [48](#), [50](#), [51](#), [54](#)
- DelayedMatrixStats, [55](#)
- diff, [18](#)
- FALSE, [4](#), [6](#), [10](#), [12](#), [15](#), [18](#), [21](#), [24](#), [26](#), [28](#), [30](#),
[32](#), [34](#), [36](#), [38](#), [40](#), [42](#), [44](#), [46](#), [48](#), [50](#),
[52](#), [54](#)
- integer, [8](#), [12](#), [40](#)
- IQR, [24](#)
- logical, [4](#)
- mad, [28](#), [48](#)
- matrix, [4](#), [8](#), [10](#), [12](#), [15](#), [18](#), [21](#), [24](#), [26](#), [28](#), [30](#),
[32](#), [34](#), [36](#), [38](#), [40](#), [42](#), [44](#), [46](#), [48](#), [50](#),
[52](#), [54](#)
- NA, [4](#), [6](#), [10](#), [12](#), [15](#), [18](#), [21](#), [23–26](#), [28](#), [30](#), [32](#),
[34](#), [36](#), [38](#), [40](#), [42](#), [44](#), [46](#), [48](#), [50](#), [52](#),
[54](#)
- NULL, [4](#), [6](#), [8](#), [10](#), [12](#), [15](#), [17](#), [21](#), [23](#), [25](#), [28](#), [30](#),
[32](#), [34](#), [36](#), [38](#), [40](#), [42](#), [44](#), [46](#), [48](#), [50](#),
[52](#), [54](#)
- numeric, [4](#), [8](#), [10](#), [12](#), [15](#), [18](#), [21](#), [22](#), [24](#), [26](#),
[28](#), [30](#), [32](#), [34](#), [36](#), [38](#), [40](#), [42](#), [44](#), [46](#),
[48](#), [50–52](#), [54](#)
- prod, [36](#)
- quantile, [38](#)
- rowAlls, [4](#), [13](#)
- rowAlls,DelayedMatrix-method
(colAlls,DelayedMatrix-method),
[2](#)
- rowAnyMissings (colAnyMissings), [5](#)
- rowAnyMissings,DelayedMatrix-method
(colAnyMissings), [5](#)
- rowAnyNAs,DelayedMatrix-method
(colAnyMissings), [5](#)
- rowAnys, [4](#), [13](#)
- rowAnys,DelayedMatrix-method
(colAlls,DelayedMatrix-method),
[2](#)
- rowAvgPerColSet, [9](#)
- rowAvgPerColSet,DelayedMatrix-method
(colAvgPerRowSet,DelayedMatrix-method),
[7](#)
- rowCollapse, [10](#)
- rowCollapse,DelayedMatrix-method
(colCollapse,DelayedMatrix-method),
[9](#)
- rowCounts, [13](#)
- rowCounts,DelayedMatrix-method
(colCounts,DelayedMatrix-method),
[11](#)
- rowCummaxs, [16](#)
- rowCummaxs,DelayedMatrix-method
(colCummaxs,DelayedMatrix-method),
[13](#)
- rowCummins,DelayedMatrix-method
(colCummaxs,DelayedMatrix-method),
[13](#)

- rowCumprods, DelayedMatrix-method
(colCummaxs, DelayedMatrix-method),
[13](#)
- rowCumsums, DelayedMatrix-method
(colCummaxs, DelayedMatrix-method),
[13](#)
- rowDiffs, [18](#)
- rowDiffs, DelayedMatrix-method
(colDiffs, DelayedMatrix-method),
[17](#)
- rowIQRDiffs, [22](#)
- rowIQRDiffs, DelayedMatrix-method
(colIQRDiffs, DelayedMatrix-method),
[19](#)
- rowIQRs, [22](#), [24](#)
- rowIQRs, DelayedMatrix-method
(colIQRs, DelayedMatrix-method),
[23](#)
- rowLogSumExps, [26](#)
- rowLogSumExps, DelayedMatrix-method
(colLogSumExps, DelayedMatrix-method),
[25](#)
- rowMadDiffs, DelayedMatrix-method
(colIQRDiffs, DelayedMatrix-method),
[19](#)
- rowMads, [28](#), [48](#)
- rowMads(), [24](#)
- rowMads, DelayedMatrix-method
(colMads, DelayedMatrix-method),
[26](#)
- rowMaxs, [16](#)
- rowMeans, [28](#), [30–32](#), [42](#), [46](#)
- rowMeans2, [28](#), [30](#), [32](#), [42](#), [46](#), [50](#)
- rowMeans2, DelayedMatrix-method
(colMeans2, DelayedMatrix-method),
[29](#)
- rowMeans2, Matrix-method
(colMeans2, DelayedMatrix-method),
[29](#)
- rowMedians, [32](#), [52](#)
- rowMedians, DelayedMatrix-method
(colMedians, DelayedMatrix-method),
[31](#)
- rowOrderStats, [34](#)
- rowOrderStats, DelayedMatrix-method
(colOrderStats, DelayedMatrix-method),
[33](#)
- rowProds, [36](#)
- rowProds, DelayedMatrix-method
(colProds, DelayedMatrix-method),
[35](#)
- rowQuantiles, [38](#)
- rowQuantiles, DelayedMatrix-method
(colQuantiles, DelayedMatrix-method),
[37](#)
- rowRanks, [40](#)
- rowRanks, DelayedMatrix-method
(colRanks, DelayedMatrix-method),
[39](#)
- rowSdDiffs, DelayedMatrix-method
(colIQRDiffs, DelayedMatrix-method),
[19](#)
- rowSds, [24](#), [28](#), [46](#), [55](#)
- rowSds, DelayedMatrix-method
(colMads, DelayedMatrix-method),
[26](#)
- rowSums2, [36](#), [42](#)
- rowSums2(), [26](#)
- rowSums2, DelayedMatrix-method
(colSums2, DelayedMatrix-method),
[41](#)
- rowSums2, Matrix-method
(colSums2, DelayedMatrix-method),
[41](#)
- rowTabulates, [44](#)
- rowTabulates, DelayedMatrix-method
(colTabulates, DelayedMatrix-method),
[43](#)
- rowVarDiffs, DelayedMatrix-method
(colIQRDiffs, DelayedMatrix-method),
[19](#)
- rowVars, [31](#), [46](#)
- rowVars, DelayedMatrix-method
(colVars, DelayedMatrix-method),
[45](#)
- rowWeightedMads, [48](#)
- rowWeightedMads, DelayedMatrix-method
(colWeightedMads, DelayedMatrix-method),
[47](#)
- rowWeightedMeans, [50](#)
- rowWeightedMeans, DelayedMatrix-method
(colWeightedMeans, DelayedMatrix-method),
[49](#)
- rowWeightedMedians, [52](#)
- rowWeightedMedians, DelayedMatrix-method
(colWeightedMedians, DelayedMatrix-method),

51
rowWeightedSds, 55
rowWeightedSds, DelayedMatrix-method
(colWeightedSds, DelayedMatrix-method),
53
rowWeightedVars, DelayedMatrix-method
(colWeightedSds, DelayedMatrix-method),
53

stats::quantile, 38
subset_by_Nindex, 55
sum, 42

table, 44
TRUE, 4, 6, 10, 12, 15, 18, 21, 23–26, 28, 30,
32, 34, 36, 38, 40, 42, 44, 46, 48, 50,
52, 54

var, 46
vector, 4, 6, 8, 10, 12, 15, 17, 21–26, 28, 30,
32, 34, 36, 38, 40, 42, 44, 46, 48, 50,
52, 54