

# Package ‘INSPEcT’

October 27, 2015

**Type** Package

**Title** Analysis of 4sU-seq and RNA-seq time-course data

**Version** 1.0.0

**Date** 2014-12-20

**Author** Stefano de Pretis

**Maintainer** Stefano de Pretis <ste.depo@gmail.com>

**Description** INSPEcT (INference of Synthesis, Processing and dEgradation rates in Time-Course experiments) analyses 4sU-seq and RNA-seq time-course data in order to evaluate synthesis, processing and degradation rates and asses via modeling the rates that determines changes in mature mRNA levels.

**License** GPL-2

**Depends** R (>= 3.2), methods, Biobase, GenomicFeatures, GenomicRanges, IRanges

**Imports** pROC, deSolve, rootSolve, compiler, BiocParallel, preprocessCore

**Suggests** BiocStyle, knitr, TxDb.Mmusculus.UCSC.mm9.knownGene

**SystemRequirements** python (>= 2.5), HTSeq

**VignetteBuilder** knitr

**biocViews** Sequencing, RNASeq, GeneRegulation, TimeCourse, SystemsBiology

**NeedsCompilation** no

## R topics documented:

AIC-INSPEcT-method . . . . .	2
chisqmodel . . . . .	3
chisqtest . . . . .	4
combine . . . . .	4
dim,INSPEcT-method . . . . .	5
Extract . . . . .	6
featureNames,INSPEcT-method . . . . .	7
geneClass . . . . .	7
getModel . . . . .	8
inHeatmap . . . . .	9

INSPEcT	10
INSPEcT-class	10
INSPEcT_model-class	12
labeledSF	13
logLik	14
makeExonsGtfFromDb	14
makeModelRates	15
makeRPKMs	16
makeSimDataset	17
makeSimModel	18
modelingParams	19
modelRates	21
modelSelection	22
mycerIds10	24
nCores	25
newINSPEcT	26
nGenes	27
nTpts	28
plotGene	28
ratePvals	29
ratesFirstGuess	30
ratesFirstGuess Var	31
removeModel	31
rocCurve	32
rocThresholds	33
rpkms	34
sfPlot	35
simData1rep	36
simData3rep	36
simRates	36
split	37
totalSF	37
tpts	38
UCSC_mm9_genes_exons	38
UCSC_mm9_genes_introns	39
viewModelRates	39
<b>Index</b>	<b>40</b>

---

AIC-INSPEcT-method	<i>Akaike information criterion calculated for the models evaluated by INSPEcT</i>
--------------------	--

---

## Description

This method is used to retrieve AIC values for all models tested for all genes.

**Usage**

```
## S4 method for signature 'INSPEcT_model'
AIC(object, ..., k = 2)

## S4 method for signature 'INSPEcT'
AIC(object, ..., k = 2)
```

**Arguments**

object	An object of class INSPEcT or INSPEcT_model
...	Additional arguments for the generic
k	Additional parameter for the generic

**Value**

A matrix of AIC values

**Examples**

```
data('mycerIds10', package='INSPEcT')
AIC(mycerIds10)
```

---

chisqmodel

*Retrieve results of chi-squared test for the selected models*


---

**Description**

Retrieve results of chi-squared test for the selected models

This method is used to retrieve the chi-squared test results for the models that have been selected to better represent the behavior of each gene.

**Usage**

```
chisqmodel(object, ...)

## S4 method for signature 'INSPEcT_model'
chisqmodel(object, ...)

## S4 method for signature 'INSPEcT'
chisqmodel(object, ...)
```

**Arguments**

object	An object of class INSPEcT or INSPEcT_model
...	Additional arguments for the generic

**Value**

A vector of chi-squared test results

**Examples**

```
data('mycerIds10', package='INSPEcT')
chisqmodel(mycerIds10)
```

---

chisqtest	<i>Retrieve all results of chi-squared test</i>
-----------	---

---

**Description**

Retrieve all results of chi-squared test

This method is used to retrieve all the chi-squared test results for all models tested for all genes.

**Usage**

```
chisqtest(object, ...)

## S4 method for signature 'INSPEcT_model'
chisqtest(object, ...)

## S4 method for signature 'INSPEcT'
chisqtest(object, ...)
```

**Arguments**

object	An object of class INSPEcT or INSPEcT_model
...	Additional arguments for the generic

**Value**

A matrix of chi-squared test results for all the tested models

**Examples**

```
data('mycerIds10', package='INSPEcT')
chisqtest(mycerIds10)
```

---

combine	<i>Combine different Objects of Class INSPEcT</i>
---------	---

---

**Description**

This method combines the information coming from different Objects of INSPEcT class. Requirements for two or more object to be combined together are:

- they must be either modeled or either not modeled
- they must have the same time points
- they must have the same modeling parameters

**Usage**

```
## S4 method for signature 'INSPEcT,INSPEcT'
combine(x, y, ...)
```

**Arguments**

x                    An object of class INSPEcT  
y                    An object of class INSPEcT  
...                   Additional objects of class INSPEcT

**Details**

In case the same gene is contained in more than one object that the user tries to combine, the information from one object will be used and a warning will be reported

**Value**

An Object of class INSPEcT

**Examples**

```
data('mycerIds10', package='INSPEcT')
mycerIds_2genes <- mycerIds10[1:2]
mycerIds_5genes <- mycerIds10[6:10]
mycerIds_7genes <- combine(mycerIds_2genes, mycerIds_5genes)
```

---

dim,INSPEcT-method      *Dimensions of an Object of Class INSPEcT*

---

**Description**

A method to obtain the dimension of the object of class INSPEcT reported as a vector containing of the genes and the number of time points

**Usage**

```
## S4 method for signature 'INSPEcT'
dim(x)
```

**Arguments**

x                    An object of class INSPEcT

**Value**

A numeric that indicates the number of genes within the object and the number of time points contained the object

**See Also**

[nGenes](#), [nTpts](#)

---

Extract

*Extract Parts of an INSPEcT or an INSPEcT\_model Object*

---

### Description

Operators acting on INSPEcT or INSPEcT\_model objects to extract parts. INSPEcT\_model objects can be subsetted only by gene. INSPEcT objects can be subsetted either by gene id or time point. In case of subsetting an INSPEcT object by time point, the model should be empty.

### Usage

```
## S4 method for signature 'INSPEcT_model,ANY,ANY'
x[i]

## S4 method for signature 'INSPEcT,ANY,ANY'
x[i, j]
```

### Arguments

x	An object of class INSPEcT or INSPEcT_model
i	A numeric, a vector of logicals or a vector of names indicating the features to be extracted
j	A numeric, a vector of logicals indicating the time points to be extracted

### Value

An Object of class INSPEcT

### See Also

removeModel

### Examples

```
data('mycerIds10', package='INSPEcT')
mycerIds_5genes <- mycerIds10[1:5]
## Not run:
## This will turn out into an error:
mycerIds_5genes_5tpts <- mycerIds10[1:5, 1:5]

## End(Not run)
## Before subsetting time points, the model should be removed:
mycerIds_5genes_5tpts <- removeModel(mycerIds10)[1:5, 1:5]
```

---

 featureNames,INSPEcT-method

*Gene Names Associated with an Object of Class INSPEcT*


---

### Description

A method to visualize gene names associated with the object of class INSPEcT

### Usage

```
## S4 method for signature 'INSPEcT'
featureNames(object)

## S4 replacement method for signature 'INSPEcT'
featureNames(object) <- value
```

### Arguments

object	An object of class INSPEcT
value	A character that will replace the current feature names

### Value

A character that contains gene names associated with the object of class INSPEcT

---

geneClass	<i>Retrieve the regulatory class for each gene</i>
-----------	--

---

### Description

Retrieve the regulatory class for each gene

This method returns a factor that summarise the gene class (transcriptional regulatory mechanism) that INSPEcT has assigned to each gene. The classification depends on the chi-squared and Brown's method thresholds, that can be both provided as arguments. If the user decides a different thresholding respect to the default, these new values can be permanently set within the object.

### Usage

```
geneClass(object, bTsh = NULL, cTsh = NULL)

## S4 method for signature 'INSPEcT_model'
geneClass(object, bTsh = NULL, cTsh = NULL)

## S4 method for signature 'INSPEcT'
geneClass(object, bTsh = NULL, cTsh = NULL)
```

**Arguments**

object	An object of class INSPECT or INSPECT_model
bTsh	A numeric representing the p-value threshold for considering a rate as variable. P-values are calculated through <a href="#">ratePvals</a>
cTsh	A numeric representing the threshold for the chi-squared test to consider a model as valid

**Value**

A character containing the regulatory class for each gene

**See Also**

[ratePvals](#)

**Examples**

```
data('mycerIds10', package='INSPECT')
geneClass(mycerIds10)
# see the classification with another threshold for chi-squared test
geneClass(mycerIds10, cTsh=.2)
# set the new threshold permanently within the object
thresholds(mycerIds10)$chisquare <- .2
```

---

getModel

*Get or replace INSPECT\_model object within INSPECT object*

---

**Description**

Get or replace INSPECT\_model object within INSPECT object

A method to get or set the INSPECT\_model object within an INSPECT object. This method is particularly useful to get and set testing parameters of the INSPECT\_model object within the INSPECT object.

**Usage**

```
getModel(object)
```

```
getModel(object) <- value
```

```
## S4 method for signature 'INSPECT'
getModel(object)
```

```
## S4 replacement method for signature 'INSPECT'
getModel(object) <- value
```

**Arguments**

object	An object of class INSPECT
value	An object of class INSPECT model



**Value**

An object of class INSPEcT model

**See Also**

[testingParams](#)

**Examples**

```
data('mycerIds10', package='INSPEcT')
getModel(mycerIds10)
```

---

inHeatmap

*Heatmap that represent the fold changes of all the five features*


---

**Description**

Heatmap that represent the fold changes of all the five features

A method to see as an heatmap the logRatios of synthesis, degradation and processing rates and pre-mRNA and total mRNA concentration of a population of genes, either at the level of estimated or modeled rates.

**Usage**

```
inHeatmap(object, type = "pre-model", breaks = seq(-1, 1, length.out = 51),
  plot_matureRNA = FALSE, absoluteExpression = TRUE, rowLabels = NULL,
  clustering = TRUE, clustIdx = 3:5)
```

```
## S4 method for signature 'INSPEcT'
inHeatmap(object, type = "pre-model", breaks = seq(-1,
  1, length.out = 51), plot_matureRNA = FALSE, absoluteExpression = TRUE,
  rowLabels = NULL, clustering = TRUE, clustIdx = 3:5)
```

**Arguments**

object	An object of class INSPEcT
type	Eiher "pre-model" or "model" to switch between pre-modeled or modeled features
breaks	A vector of breaks for the heatmap
plot_matureRNA	A logical. If set to TRUE, mature-mRNA is displayed instead of total-mRNA (default: FALSE)
absoluteExpression	A logical. If set to FALSE, the plot representing the intensity of expression is omitted. (default=TRUE)
rowLabels	A character that represent the label names that will be shown on the y-axis of the heatmap. If NULL featureNames(object) will be shown (default is NULL)
clustering	A logical. If set to FALSE, it displays genes the order they are, with no clustering (default: TRUE)

`clustIdx` A numeric. Indicates which of the features are used for the clustering. 0=absoluteExpression; 1=total-mRNA/mature-mRNA; 2=preMRNA; 3=synthesis; 4=degradation; 5=processing (default=3:5, meaning that synthesis, degradation and processing are used for the clustering)

### Value

A list of matrices containing the logRatios for total mRNA levels, pre-mRNA levels, synthesis rates, degradation rates and processing rates. Matrices are ordered according to the clustering.

### Examples

```
data('mycerIds10', package='INSPEcT')
inHeatmap(mycerIds10, 'pre-model')
inHeatmap(mycerIds10, 'model')
```

---

INSPEcT

*INSPEcT package*

---

### Description

INSPEcT (INference of Synthesis, Processing and dEgradation rates in Time-coursre experiments) is a package that analyse 4sU-seq and RNA-seq time-course data in order to evaluate synthesis, processing and degradation rates and asses via modeling the rates that determines changes in mature mRNA levels.

It implements two classes ([INSPEcT\\_model](#) and [INSPEcT](#)) and their corresponding methods. To have a detailed description of how the two classes are structured and which methods apply on, type:

```
? 'INSPEcT-class'
? 'INSPEcT_model-class'
```

To see how the typical workflow of INSPEcT works, type:

```
vignette('INSPEcT')
```

Last but not least, to obtain a citation, type:

```
citation('INSPEcT')
```

---

INSPEcT-class

*An S4 class to contain all rates and models generated by INSPEcT*

---

### Description

INSPEcT is a class able to store all the estimated rates and concentrations (slot `ratesFirstGuess`), the modeled rates and concentrations (slot `modelRates`) and the model themselves (slot `model`). Within the class INSPEcT other information regarding the experimental design are stored, such as the time points where experiments were collected (slot `tpts`), the labeling time (slot `tL`) and the normalization scale factors used for RNA- (totalSF) and 4sU-seq libraries (labeledSF). A list of parameters that will be used during the modeling process is stored within the slot `params` and can be accessed by [modelingParams](#). A new instance of the class INSPEcT can be generated by the constructor function [newINSPEcT](#).

**Usage**

```
## S4 method for signature 'INSPEcT'  
show(object)
```

**Arguments**

object            An object of class INSPEcT

**Details**

Methods that apply to INSPEcT class are

```
[  
AIC  
chisqmodel  
chisqtest  
combine  
dim  
featureNames  
geneClass  
getModel<-  
getModel  
inHeatmap  
labeledSF llrtests  
logLik  
makeModelRates  
makeSimModel  
modelingParams<-  
modelingParams  
modelRates  
modelSelection  
nCores<-  
nCores  
nGenes  
nTpts  
plotGene  
ratePvals  
ratesFirstGuessVar  
ratesFirstGuess  
removeModel  
sfPlot  
thresholds  
totalSF  
tpts  
viewModelRates
```

**Value**

Method show for objects of class INSPEcT displays the main features of the slots ratesFirstGuess, model and modelRates

**Slots**

**params** A list of parameters of the modeling part  
**ratesFirstGuess** An object of class ExpressionSet that contains all the rates and concentrations guessed from the first part of INSPEcT analysis (before modeling)  
**model** An object of class INSPEcT\_model that contains the output of the modeling  
**modelRates** An object of class ExpressionSet that contains all modeled the rates and concentrations  
**tpts** A numeric vector of the time-points  
**labeledSF** A numeric vector of the scaling factor used for inter time-point normalization of 4sU-seq libraries  
**totalSF** A numeric vector of the scaling factor used for inter time-point normalization of RNA-seq libraries  
**tL** A numeric containing the length of the 4sU pulse

---

INSPEcT\_model-class    *An S4 class to represent models generated by INSPEcT*

---

**Description**

INSPEcT\_model is a class able to store all the results of the modeling of synthesis, processing and degradation rates made via the method `modelRates` (slot `ratesSpecs`). It also stores the criteria (slot `parameter`) to choose between the many models tested for each gene the one that better describes the data and the results. The slot `simple` is a flag that distinguish wheter the model contains the information of the introns or not. In case not, the flag `simple` is set to TRUE. Also the method `makeSimModel` of class `INSPEcT-class` creates an object of class INSPEcT\_model. This object will be used by `makeSimDataset` to generate a complete simulated data-set, whose classification performance can be tested.

**Usage**

```
## S4 method for signature 'INSPEcT_model'
show(object)
```

**Arguments**

`object`            An object of class INSPEcT\_model

**Details**

Methods that apply to INSPEcT\_model class are

```
[
AIC
chisqmodel
chisqtest
geneClass
llrtests
logLik
makeModelRates
```

```

makeSimDataset
modelSelection
ratePvals
rocCurve
rocThresholds
thresholds

```

### Value

Method show for objects of class INSPEcT\_model returns the number of the genes that have been modeled

### Slots

params A list that defines thresholds and how to perform log likelihood ratio tests

ratesSpecs A list containing the modeling output

simple A logical that indicates whether the mode of INSPEcT is simple (no pre-mRNA and degradation rates) or not.

---

labeledSF

*Accessor to the slot labeledSF of an INSPEcT object*

---

### Description

Accessor to the slot labeledSF of an INSPEcT object

Accessor to obtain the labeledSF slot associated with the object of class INSPEcT

### Usage

```
labeledSF(object)
```

```
## S4 method for signature 'INSPEcT'
labeledSF(object)
```

### Arguments

object An object of class INSPEcT

### Value

A numeric that indicates the scaling factors applied between time points of the data coming from 4sU-seq library (applies directly to synthesis rates and indirectly to degradation rates)

### Examples

```

data('mycerIds10')
labeledSF(mycerIds10)

```

---

logLik	<i>Retrieve results of log likelihood test</i>
--------	--

---

**Description**

Retrieve results of log likelihood test

This method is used to retrieve all the log likelihood ratio test results for all pairs tested for all genes.

**Usage**

```
logLik(object, ...)

## S4 method for signature 'INSPEcT_model'
logLik(object, ...)

## S4 method for signature 'INSPEcT'
logLik(object, ...)
```

**Arguments**

object	An object of class INSPEcT or INSPEcT_model
...	Additional arguments for the generic

**Value**

A matrix of log likelihood test results for all the tested model comparisons

**Examples**

```
data('mycerIds10', package='INSPEcT')
logLik(mycerIds10)
```

---

makeExonsGtfFromDb	<i>Make a GTF file of exonic or intronic features from a TxDb object</i>
--------------------	--

---

**Description**

Make a GTF file of exonic or intronic features from a TxDb object

**Usage**

```
makeExonsGtfFromDb(object, type, filename)

makeIntronsGtfFromDb(object, type, filename)

## S4 method for signature 'TxDb'
makeExonsGtfFromDb(object, type, filename)

## S4 method for signature 'TxDb'
makeIntronsGtfFromDb(object, type, filename)
```

**Arguments**

object	An object of class TxDb
type	Either "gene" or "tx", see details for further information
filename	The name of the GTF file that is created

**Details**

In case type "gene" is chosen, the union of all exons of transcripts associated to a gene is used.

**Value**

None

**Examples**

```
require(TxDb.Mmusculus.UCSC.mm9.knownGene)
txdb <- TxDb.Mmusculus.UCSC.mm9.knownGene
isActiveSeq(txdb) <- c(TRUE, rep(FALSE, length(isActiveSeq(txdb)) - 1))
res <- makeExonsGtfFromDb(txdb, 'gene', 'exons.gtf')
isActiveSeq(txdb) <- rep(TRUE, length(isActiveSeq(txdb)))
```

---

makeModelRates

*Calculate modeled rates and concentrations*


---

**Description**

Calculate modeled rates and concentrations

This function is used to evaluate rates and concentrations after modeling of the rates has been run with `modelRates`. The modeled rates are in functional form and can be evaluated at any time points.

This method can be used to regenerate the rates associated to the modeling, in case some testing parameters has changed.

**Usage**

```
makeModelRates(object, ...)

## S4 method for signature 'INSPECT_model'
makeModelRates(object, ...)

## S4 method for signature 'INSPECT'
makeModelRates(object, ...)
```

**Arguments**

object	An object of class INSPECT_model
...	additional arguments tpts : A vector of time points where rates and concentrations have to be evaluated

**Value**

An object of class ExpressionSet containing the modeled rates and concentrations

**Examples**

```

data('mycerIds10', package='INSPEcT')
tpts <- c(0, 1/6, 1/3, 1/2, 1, 2, 4, 8, 16)
eSet <- makeModelRates(getModel(mycerIds10), tpts=tpts)
exprs(eSet)
data('mycerIds10', package='INSPEcT')
viewModelRates(mycerIds10, 'degradation')
## force every degradation rate to be accepted as variable
thresholds(getModel(mycerIds10))$brown <- c(synthesis=.01, degradation=1, processing=.01)
mycerIds10 <- makeModelRates(mycerIds10)
viewModelRates(mycerIds10, 'degradation')

```

---

makeRPKMs

---

*Calculate RPKM values on introns and exons from sam files*


---

**Description**

Given a vector of time points, paths to sam files of the 4sU-seq and RNA-seq experiments and paths of GTF files, "makeRPKMs" function calculates read counts and RPKM on exonic and intronic features per each gene. Reads that fall where intronic and exonic features overlaps are assigned to exons. This function is based on HTSeq software (<http://www-huber.embl.de/users/anders/HTSeq/doc/overview.html>) which is expected to be pre installed and on the path.

**Usage**

```

makeRPKMs(tpts, sampaths_4su, sampaths_total, exons_gtf_file, introns_gtf_file,
  out_folder = ".")

```

**Arguments**

tpts	A vector of time points corresponding in which experiments have been collected (it admits non-unique values in case of replicates)
sampaths_4su	A vector of paths of 4sU-seq sam files of the same length of tpts
sampaths_total	A vector of paths of RNA-seq sam files of the same length of tpts
exons_gtf_file	A path to the GTF file that defines exon features
introns_gtf_file	A path to the GTF file that defines intron features (if NULL only exons reads are quantified)
out_folder	A path to the output folder (by default the current directory)

**Value**

A list of intron and exon rpkms for both RNA-seq and 4sU-seq



**Examples**

```

exons_gtf_file <- system.file('extdata', 'UCSC_mm9_genes_exons.txt', package="INSPEcT")
introns_gtf_file <- system.file('extdata', 'UCSC_mm9_genes_introns.txt', package="INSPEcT")
samfiles4su <- system.file('extdata', '4sURNA_0h.sam', package="INSPEcT")
samfilesTotal <- system.file('extdata', 'totalRNA_0h.sam', package="INSPEcT")
## Not run:
rpkms <- makeRPkMs(1, samfiles4su, samfilesTotal, exons_gtf_file, introns_gtf_file)
save(rpkms, file='rpkms.rd')

## End(Not run)

```

---

makeSimDataset	<i>Generate synthetic rates and concentrations</i>
----------------	--

---

**Description**

Generate synthetic rates and concentrations

This method generates rates and concentrations where noise is added according to the desired number of replicates that the user set as an arguments from the `INSPEcT_model` object that has been created by the method of the class `INSPEcT` [makeSimModel](#). Rates and concentrations can be generated at the time-points of interest. This method generates an `INSPEcT` object that can be modeled and the performance of the modeling can be tested directly against the `INSPEcT_model` object created by [makeSimModel](#).

**Usage**

```

makeSimDataset(object, tpts, nRep, seed = NULL)

## S4 method for signature 'INSPEcT_model'
makeSimDataset(object, tpts, nRep, seed = NULL)

```

**Arguments**

object	An object of class <code>INSPEcT_model</code> , usually the output of <a href="#">makeSimModel</a>
tpts	A numeric vector of time points where rates and concentrations have to be evaluated
nRep	Number of replicates to simulate
seed	A numeric to obtain reproducible results

**Value**

An object of the class `ExpressionSet` containing rates and concentrations

**See Also**

[makeSimModel](#)

**Examples**

```

## generate a synthtic data-set of 10 genes based on the real data-set
data('rpkm', package='INSPEcT')
tpts <- c(0, 1/6, 1/3, 1/2, 1, 2, 4, 8, 16)
tL <- 1/6
mycerIds <- newINSPEcT(tpts, tL, rpkm$rpkm_4su_exons, rpkm$rpkm_total_exons, rpkm$rpkm_4su_introns, rpkm$rpkm_4su_utr)
simRates <- makeSimModel(mycerIds, 10)
simData <- makeSimDataset(simRates, tpts, 1)
## load simulated datasets
data('simRates', package='INSPEcT')
data('simData3rep', package='INSPEcT')
## measure sensitivity/sensibility of synthesis, degradation and processing
## rates identification
dev.new()
rocCurve(simRates, simData3rep)
## measure classification with a different threshold for the chi-squared
## test acceptance of models
rocCurve(simRates, simData3rep, cTsh=.2)

```

---

makeSimModel

*Build the synthetic rates shaped on a dataset*


---

**Description**

Build the synthetic rates shaped on a dataset

This method allow the creation of synthesis, degradation and processing rates for a certain number of genes. The rates are created according to the distributions of the real data-set which is given as an input of the method. Different proportions of constant varying rates can be set and a new vector of time points can be provided. This method has to be used before the [makeSimDataset](#) method.

**Usage**

```

makeSimModel(object, nGenes, newTpts = NULL, probs = c(constant = 0.5,
  sigmoid = 0.3, impulse = 0.2), na.rm = TRUE, seed = NULL)

## S4 method for signature 'INSPEcT'
makeSimModel(object, nGenes, newTpts = NULL,
  probs = c(constant = 0.5, sigmoid = 0.3, impulse = 0.2), na.rm = TRUE,
  seed = NULL)

```

**Arguments**

object	An object of class INSPEcT
nGenes	A numeric with the number of synthtic genes to be created
newTpts	A numeric verctor with time points of the synthtic dataset, if NULL the time points of the real dataset will be used
probs	A numeric vector wich describes the probability of a rate to be constant, shaped like a sigmoid or like an impulse model
na.rm	A logical that set whether missing values in the real dataset should be removed
seed	A numeric to obtain reproducible results

**Details**

The method `makeSimModel` generates an object of class `INSPEcT_model` that stores the parametric functions to generate clean rates of a time-course. To any of the rates also a noise variance is associated but not used yet. In a typical workflow the output of `makeSimModel` is the input of the method `makeSimDataset`, that build the noisy rates and concentrations, given a specified number of replicates.

**Value**

An object of class `INSPEcT_model` with synthetic rates

**See Also**

[makeSimDataset](#)

**Examples**

```
data('rpkms', package='INSPEcT')
tpts <- c(0, 1/6, 1/3, 1/2, 1, 2, 4, 8, 16)
tL <- 1/6
mycerIds <- newINSPEcT(tpts, tL, rpkms$rpkm_4su_exons, rpkms$rpkm_total_exons, rpkms$rpkm_4su_introns, rpkms$rpkm_4su_utr)
## generate a synthetic data-set of 10 genes based on the real data-set
simRates <- makeSimModel(mycerIds, 10)
simData <- makeSimDataset(simRates, tpts, 1)
## measure sensitivity/sensibility of synthesis, degradation and processing
## rates identification
data('simRates', package='INSPEcT')
data('simData3rep', package='INSPEcT')
rocCurve(simRates, simData3rep)
## measure classification with a different threshold for the chi-squared
## test acceptance of models
rocCurve(simRates, simData3rep, cTsh=.2)
## generate a synthetic data-set of 10 genes based on the real data-set
## with more replicates and more time points
newTpts <- c(0, 1/6, 1/3, 1/2, 1, 1.5, 2, 4, 8, 12, 16, 24)
simRates <- makeSimModel(mycerIds, 10, newTpts=newTpts)
simData <- makeSimDataset(simRates, newTpts, 3)
```

**Description**

Get and set number parameters for the modeling

A method to get and set the parameters that will be used in the modeling of estimated rates and concentrations by the method `modelRates`

**Usage**

```

modelingParams(object)

modelingParams(object) <- value

## S4 method for signature 'INSPEcT'
modelingParams(object)

## S4 replacement method for signature 'INSPEcT'
modelingParams(object) <- value

```

**Arguments**

object	An object of class INSPEcT
value	A list with new parameters

**Value**

List of parameters and their values

- nInit number of optimization to find the best functional representation of each rate (by default 10)
- nIter number of max iteration during optimization (default is 300)
- na.rm A logical wheter missing values should be removed from estimated rates (default is TRUE)
- nCores The number of cores to be used during parallelization (default is 2)
- verbose A logical wheter to be verbose or not (default is TRUE)
- estimateRatesWith Either "int" or "der". With "int" the degradation and processing rates are estimated integrating the system between one time point and the following. With "der" degradation and processing rates are estimated using the derivative of total and pre mRNA. (default is "int")
- useSigmoidFun A logical, whether to choose between sigmoid and impulse function to fit rates and concentrations. In case not, always impulse function is used. (default is TRUE)
- testOnSmooth A logical, wheter models should be tested on smoothed pre-mRNA, total mRNA and synthesis rates or not. (default is TRUE)

**See Also**

[modelRates](#)

**Examples**

```

data('mycerIds10', package='INSPEcT')
modelingParams(mycerIds10)
data('mycerIds10', package='INSPEcT')
mycerIds10 <- removeModel(mycerIds10)
modelingParams(mycerIds10)$useSigmoidFun <- FALSE

```

---

modelRates	<i>Launch the modeling process</i>
------------	------------------------------------

---

### Description

Launch the modeling process with parameters set with [modelingParams](#)

This method model the synthesis, degradation and processign rates after their estimation by the constructor function [newINSPEcT](#). Estimated rates are not guaranteed to optimally describes provided input data yet. To this purpose, modeled rates can be generated and genes can be assigned to a transcriptional regulatory mechanism. Modeled rates can be accessed via the method [viewModelRates](#) and gene classification according to the regulatory mechanism can be accessed by [geneClass](#). The modeling procedure can be set by the user by modyging the parameters via [modelingParams](#)

### Usage

```
modelRates(object, seed = NULL, nCores = NULL, verbose = NULL)
```

```
## S4 method for signature 'INSPEcT'
modelRates(object, seed = NULL, nCores = NULL,
  verbose = NULL)
```

### Arguments

object	An object of class INSPEcT
seed	A numeric, indicatindg the seed to be set for reproducible results
nCores	Either NULL or numeric. If numeric indicates the number of cores to be used for parallelization (if nCores=1 doesn't parallelize). If NULL takes the information from the object (see <a href="#">modelingParams</a> )
verbose	Either NULL or logical. If logical indicates whether to output some text during computation or not, if NULL it takes the information from the object (see <a href="#">modelingParams</a> ) (Default: NULL) used for parallelization (if nCores=1 doesn't parallelize). If NULL takes the information from the object (see <a href="#">modelingParams</a> ) (Default: NULL)

### Details

When modeling many genes, parallelization is strongly suggested to reduce computational time. Since all genes run independently, the computational time is divided by the number of cores used/available. However, when modeling more than 500 genes, it may happen that a single gene returns an error that escapes the try/catch controls of INSPEcT. With the parallel mode, the error will propagate on all genes that have been computed with the same processor (or core). To avoid this, the computation could be splitted in chunks and the whole data set can be obtained by combining the chunks (see Examples).

### Value

An object of class INSPEcT with modeled rates

### See Also

[viewModelRates](#), [geneClass](#), [modelingParams](#)

**Examples**

```

data('rpkm', package='INSPECT')
tpts <- c(0, 1/6, 1/3, 1/2, 1, 2, 4, 8, 16)
tL <- 1/6
mycerIds <- newINSPECT(tpts, tL, rpkm$rpkm_4su_exons, rpkm$rpkm_total_exons,
  rpkm$rpkm_4su_introns, rpkm$rpkm_total_introns)
mycerIdsOneGene <- mycerIds[5]
## View modeling parameters
modelingParams(mycerIdsOneGene)
## Run the modeling in a reproducible way (setting seed)
mycerIdsOneGene <- modelRates(mycerIdsOneGene, seed=1)
## view modeled synthesis rates
viewModelRates(mycerIdsOneGene, 'synthesis')
## view gene classes
geneClass(mycerIdsOneGene)

## Divide a parallel computation into chunks
## Not run:
nCores(mycerIds) <- parallel::detectCores()
chunkSize <- 100
splitIdx <- ceiling(c(1:nGenes(mycerIds))/chunkSize)
chunks <- lapply(split(mycerIds, splitIdx), modelRates)
mycerIdsModeled <- do.call('combine', chunks)

## End(Not run)

```

---

modelSelection

*Get or set parameters for model test and selection*


---

**Description**

With this methods the user can personalize the criteria by which INSPECT selects a rate to be variable or constant. In particular, the model selection criteria can be selected between log-likelihood ratio test and Akaike's information criterion. In case log-likelihood ratio test is selected, the thresholds of chi-squared and Brown's method can be set (see Details section).

**Usage**

```

modelSelection(object)

modelSelection(object) <- value

thresholds(object)

thresholds(object) <- value

llrtests(object)

llrtests(object) <- value

## S4 method for signature 'INSPECT'
modelSelection(object)

```

```

## S4 replacement method for signature 'INSPEcT'
modelSelection(object) <- value

## S4 method for signature 'INSPEcT_model'
modelSelection(object)

## S4 replacement method for signature 'INSPEcT_model'
modelSelection(object) <- value

## S4 method for signature 'INSPEcT'
thresholds(object)

## S4 replacement method for signature 'INSPEcT'
thresholds(object) <- value

## S4 method for signature 'INSPEcT_model'
thresholds(object)

## S4 replacement method for signature 'INSPEcT_model'
thresholds(object) <- value

## S4 method for signature 'INSPEcT'
llrtests(object)

## S4 replacement method for signature 'INSPEcT'
llrtests(object) <- value

## S4 method for signature 'INSPEcT_model'
llrtests(object)

## S4 replacement method for signature 'INSPEcT_model'
llrtests(object) <- value

```

### Arguments

object	An object of class <code>INSPEcT</code> or <code>INSPEcT_model</code>
value	A list or a character that will substitute the set of parameters <ul style="list-style-type: none"> <li>• <code>modelSelection</code>: A character, either "llr" to test whether a rate is varying using log-likelihood testing framework or "aic" to choose the best model via Akaike Information Criterion (Default: "llr").</li> <li>• <code>thresholds</code>: A named list containing the threshold that is used to consider a model as accepted in terms of the chi-squared test and three thresholds (one per each rate) that are used to consider a rate as variable using the Brown's method on the log-likelihood ratio tests</li> <li>• <code>llrtests</code>: A list of three elements that represent, for each rate, the pairs of models that will be compared via log likelihood ratio test to assess whether the rate is variable or not</li> </ul>

## Details

When log-likelihood is chosen as a criterion for model selection, different nested models can be compared to assess whether a single rate is varying or constant. For example, in case we want to establish whether synthesis rate is constant or not we can test the null hypothesis "all the rates are constant" against the alternative hypothesis "synthesis rate is changing". The null hypothesis is a special case of the alternative hypothesis, therefore the models are nested. We can also assess whether synthesis rate is constant or not by comparing the null hypothesis "degradation rate is changing" against the alternative hypothesis "degradation and synthesis are changing". The method `llrtests` set the models that are compared to assess the variability of each rate. Different comparisons will be combined using Brown's method for combining p-values. Models are named with a short notation where synthesis is "a", degradation is "b" and processing is "c". "0" is the model where all genes are kept constant and "ab", for example is the model where synthesis rate and degradation rate are changing. The user can also set the thresholds for Brown's p-value and chi-squared p-value. While the former set the threshold to assess whether a rate is variable or not over time, the latter set the chi-squared threshold for a pair of model to be used via the log-likelihood ratio test. In order for a pair to be used, at least one model of the pair should have a chi-squared p-value (goodness of fit) below the threshold. The construction of a synthetic data-set can help in the choice of the correct parameters for the test (`makeSimModel`, `makeSimDataset`).

## Value

See "value"

## See Also

`makeSimModel`, `makeSimDataset`

## Examples

```
data('mycerIds10', package='INSPEcT')
modelSelection(mycerIds10)
modelSelection(mycerIds10) <- 'aic'
thresholds(mycerIds10)
thresholds(mycerIds10)$chisquare <- 1e-3
thresholds(mycerIds10)$brown['synthesis'] <- 1e-3
llrtests(mycerIds10)
llrtests(mycerIds10)$synthesis <- list(c('0','a'), c('b','ab'))
```

---

mycerIds10

*An INSPEcT object with evaluated and modeled rates and concentrations*

---

## Description

This INSPEcT object contains the evaluated and modeled rates and concentrations of the very first 10 genes of the dataset `rpkm`s

## Format

An INSPEcT object



---

nCores	<i>Get and set number of cores to be used for the modeling</i>
--------	--

---

## Description

Get and set number of cores to be used for the modeling

This method is a fast way to get and set the number of cores that the modeling part will use (method [modelRates](#)). The same task can be achieved using the more general [modelingParams](#) method

## Usage

```
nCores(object, ...)  
  
nCores(object) <- value  
  
## S4 method for signature 'INSPECT'  
nCores(object, ...)  
  
## S4 replacement method for signature 'INSPECT,numeric'  
nCores(object) <- value
```

## Arguments

object	An object of class INSPECT
...	Additional arguments for the generic
value	A numeric value with the number of cores to be used

## Value

Number of cores to be used

## Examples

```
data('mycerIds10', package='INSPECT')  
nCores(mycerIds10)  
## use the more general modelingParams method  
modelingParams(mycerIds10)$nCores  
data('mycerIds10', package='INSPECT')  
mycerIds10 <- removeModel(mycerIds10)  
nCores(mycerIds10) <- detectCores()  
## use the more general modelingParams method  
modelingParams(mycerIds10)$nCores <- detectCores()
```

---

newINSPEcT

*Create a new INSPEcT object*


---

### Description

The function newINSPEcT creates a new instance of the class INSPEcT, provided the intronic and exonic RPKMs of RNA- and 4sU-seq experiments at different time points, the time points, the labeling time and optionally the scaling factor to normalize the libraries. The scaling factor to normalize the 4sU-seq libraries can be calculated by the function itself and this way of calculating the scaling factors gives robustness to the estimation of sythesis, degradation and processing rates. In case only exonic RPKMs are provided, only synthesis and degradation rates can be estimated by the function newINSPEcT and the scaling factors to normalize 4sU-seq libraries cannot be calculated. To provide robustness to the procedure the argument labeledSF is strongly suggested in this case.

### Usage

```
newINSPEcT(tpts, labeling_time, rpkms_4su_exons, rpkms_total_exons,
  rpkms_4su_introns = NULL, rpkms_total_introns = NULL,
  parallelize = TRUE, totalMedianNorm = TRUE, labeledMedianNorm = FALSE,
  totalSF = NULL, labeledSF = NULL, totalQuantileNorm = FALSE,
  labeledQuantileNorm = FALSE, simulatedData = FALSE,
  degDuringPulse = FALSE)
```

### Arguments

tpts	A vector of time points
labeling_time	A number, lenght of the 4sU pulse
rpkms_4su_exons	A matrix containing expression levels of 4su exons
rpkms_total_exons	A matrix containing expression levels of total exons
rpkms_4su_introns	A matrix containing expression levels of 4su introns
rpkms_total_introns	A matrix containing expression levels of total introns
parallelize	A logical, if set to TRUE parallelizes the calculation of rates
totalMedianNorm	A logical to perform median normalization over total RNA exons rpkms, it will apply also on introns
labeledMedianNorm	A logical to perform median normalization over 4sU RNA exons rpkms, it will apply also on introns
totalSF	A vector storing user defined normalization scale over Total RNA exons and introns rpkms
labeledSF	A vector storing user defined normalization scale over 4sU RNA exons and introns rpkms
totalQuantileNorm	A logical to perform to perform median normalization over total RNA exons rpkms, it will apply also on introns

labeledQuantileNorm A logical to perform to perform median normalization over 4sU RNA exons rpkms, it will apply also on introns

simulatedData A logical, set to TRUE in case the analysis is on simulated data

degDuringPulse A logical, set to TRUE in case of a long labelling time. Also degradation of newly synthesized transcripts will be taken into account

### Value

An object of class INSPEcT with rates guessed, rates can be accessed by `ratesFirstGuess` method.

### Examples

```
data('rpkm', package='INSPEcT')
tpts <- c(0, 1/6, 1/3, 1/2, 1, 2, 4, 8, 16)
tL <- 1/6
mycerIds <- newINSPEcT(tpts, tL, rpkm$rpkm_4su_exons, rpkm$rpkm_total_exons, rpkm$rpkm_4su_introns, rpkm$rpkm_total_introns)
```

---

nGenes

*Get the number of genes within the INSPEcT object*

---

### Description

Get the number of genes within the INSPEcT object

A method to obtain the number of the genes associated with the object of class INSPEcT

### Usage

```
nGenes(object)

## S4 method for signature 'INSPEcT'
nGenes(object)
```

### Arguments

object An object of class INSPEcT

### Value

A numeric that indicates the number of genes within the object

### Examples

```
data('mycerIds10')
nGenes(mycerIds10)
```

---

nTpts	<i>Get the number of time points within the INSPEcT object</i>
-------	--

---

**Description**

Get the number of time points within the INSPEcT object

A method to obtain the number of the tpts associated with the object of class INSPEcT

**Usage**

```
nTpts(object)
```

```
## S4 method for signature 'INSPEcT'
nTpts(object)
```

**Arguments**

object            An object of class INSPEcT

**Value**

A numeric that indicates the number of time points contained the object

**Examples**

```
data('mycerIds10')
nTpts(mycerIds10)
```

---

plotGene	<i>Plot the pre-modeled and modeled profiles for one gene</i>
----------	---

---

**Description**

Plot the pre-modeled and modeled profiles for one gene

A method to see the shapes of the estimated synthesis, degradation and processing rates, pre-mRNA and total mRNA concentrations (solid thin lines) their variances (dashed lines) and the modeled rates and concentrations (ticker solid line) of a single gene.

**Usage**

```
plotGene(object, ix, fix.yaxis = FALSE)
```

```
## S4 method for signature 'INSPEcT'
plotGene(object, ix, fix.yaxis = FALSE)
```

**Arguments**

object            An object of class INSPEcT

ix                Either a rowname or a row number to select one single gene

fix.yaxis        A logical, indicating whether the limits for y-axis of degradation and processing rates should be fixed relative to their distributions

**Value**

A list containing total mRNA levels and their confidence interval (levels plus and minus one standard deviation), pre-mRNA levels and their confidence intervals, synthesis rates and their confidence intervals, degradation rates and processing rates of the selected gene.

**Examples**

```
data('mycerIds10', package='INSPEcT')
plotGene(mycerIds10, 1)
```

---

ratePvals

*Retrieve a single p-value for each rate*


---

**Description**

Retrieve a single p-value for each rate

This method is used to retrieve all the p-values combined with Brown's method that combines the results of the log likelihood ratio test results for all pairs tested for each rate and all genes. P-values will change according to the threshold set for the chi-squared test because it influences the model that will be taken into consideration to perform log likelihood ratio tests. To have a sense of the best parameter to choose, a synthetic data-set can be built and tested ([makeSimModel](#), [makeSimDataset](#)) In case 'aic' has been selected via [modelSelection](#) method, this method assigns the chi-squared test result of the model selected by AIC to the respective variable rates

**Usage**

```
ratePvals(object, cTsh = NULL)

## S4 method for signature 'INSPEcT_model'
ratePvals(object, cTsh = NULL)

## S4 method for signature 'INSPEcT'
ratePvals(object, cTsh = NULL)
```

**Arguments**

object	An object of class INSPEcT or INSPEcT_model
cTsh	A numeric representing the threshold for the chi-squared test to consider a model as valid

**Details**

ratePvals retrieve a single p-value for each rate thanks to multiple log likelihood tests performed on nested models that has a chi-squared test below the selected threshold. Among the many p-values that log likelihood ratio test calculate, a single p-value is obtained applying Brown's method for combining dependent p-values.

**Value**

A matrix containing p-values calculated for each rate

**See Also**

[makeSimModel](#), [makeSimDataset](#)

**Examples**

```
data('mycerIds10', package='INSPEcT')
ratePvals(mycerIds10)
# calculate agin the p-values with Brown with a different threshold
# for considering a model valid for the log likelihood ratio test
ratePvals(mycerIds10, cTsh=.2)
# Set permanently the chi-squared threshold at .2 for mycerIds10 object
thresholds(mycerIds10)$chisquare <- .2
```

---

ratesFirstGuess	<i>Retrieve pre-modeling rates and concentrations</i>
-----------------	---

---

**Description**

Retrieve pre-modeling rates and concentrations

This method allow to access to the estimated synthesis, degradation, processing rates and pre mRNA and total mRNA concentrations the way they were calculated by the constructor function [newINSPEcT](#).

**Usage**

```
ratesFirstGuess(object, feature)
```

```
## S4 method for signature 'INSPEcT'
ratesFirstGuess(object, feature)
```

**Arguments**

object	An object of class INSPEcT
feature	A character indicating the feature to retireve, "synthesis", "degradation", "processing" for rates, "total" for total mRNA concentrations or "preMRNA" for premature mRNA concentrations

**Value**

A numeric matrix containing the values for the selected feature

**See Also**

[newINSPEcT](#), [ratesFirstGuessVar](#)

**Examples**

```
data('rpkm', package='INSPEcT')
tpts <- c(0, 1/6, 1/3, 1/2, 1, 2, 4, 8, 16)
tL <- 1/6
mycerIds <- newINSPEcT(tpts, tL, rpkm$rpkm_4su_exons, rpkm$rpkm_total_exons, rpkm$rpkm_4su_introns, rpkm$rpkm_pre_mRNA)
# get estimated synthesis rates
ratesFirstGuess(mycerIds, 'synthesis')
```

---

ratesFirstGuessVar      *Retrieve pre-modeling rates and concentrations variance*

---

### Description

Retrieve pre-modeling rates and concentrations variance

This method allow to access to the estimated variance of synthesis rates and pre mRNA and total mRNA concentrations the way they were calculated by the constructor function [newINSPEcT](#).

### Usage

```
ratesFirstGuessVar(object, feature)
```

```
## S4 method for signature 'INSPEcT'
ratesFirstGuessVar(object, feature)
```

### Arguments

object	An object of class INSPEcT
feature	A character indicating the feature to retireve, "synthesis", "degradation", "processing" for rates, "total" for total mRNA concentrations or "preMRNA" for premature mRNA concentrations

### Value

A numeric vector containing the values for the selected feature

### See Also

[newINSPEcT](#), [ratesFirstGuess](#)

### Examples

```
data('rpkm', package='INSPEcT')
tpts <- c(0, 1/6, 1/3, 1/2, 1, 2, 4, 8, 16)
tL <- 1/6
mycerIds <- newINSPEcT(tpts, tL, rpkm$rpkm_4su_exons, rpkm$rpkm_total_exons, rpkm$rpkm_4su_introns, rpkm$rpkm_4su_5p)
ratesFirstGuessVar(mycerIds, 'synthesis')
```

---

removeModel      *remove modelling information from INSPEcT object*

---

### Description

remove modelling information from INSPEcT object

Remove the model from an INSPEcT object. It is required when subsetting an INSPEcT object per time points because when removing time points the modeling is not valid anymore.

**Usage**

```
removeModel(object)

## S4 method for signature 'INSPEcT'
removeModel(object)
```

**Arguments**

object            An Object of class INSPEcT

**Value**

An Object of class INSPEcT

**Examples**

```
data('mycerIds10', package='INSPEcT')
mycerIds_5genes <- mycerIds10[1:5]

## This will turn out into an error:
## Not run: mycerIds_5genes_5tpts <- mycerIds10[1:5, 1:5]

## Before subsetting time points, the model should be removed:
mycerIds_5genes_5tpts <- removeModel(mycerIds10)[1:5, 1:5]

## Also this will turn out into an error:
## Not run: mycerIds10 <- modelRates(mycerIds10)

## Before running the model again, or changing modeling parameters,
## the previous model should be removed:
mycerIds10_old <- mycerIds10
mycerIds10_new <- removeModel(mycerIds10)
modelingParams(mycerIds10_new)$useSigmoidFun <- FALSE
## Not run: mycerIds10_new <- modelRates(mycerIds10_new)
```

---

rocCurve

*Display rate classification performance*

---

**Description**

Display rate classification performance

A method to visualize the performance in the classification of synthesis, degradation and processing rates based on the comparison of the original simulated rates and the one obtained by the function [modelRates](#). For each rate, classification performance is measured in terms of sensitivity and specificity using a ROC curve analysis. False negatives (FN) represent cases where the rate is identified as constant while it was simulated as varying. False positives (FP) represent cases where INSPEcT identified a rate as varying while it was simulated as constant. On the contrary, true positives (TP) and negatives (TN) are cases of correct classification of varying and constant rates, respectively. Consequently, sensitivity and specificity are computed using increasing thresholds for the brown p-values, and the ability of correctly classifying a rate is measured through the area under the curve (AUC) for each rate.



**Usage**

```
rocCurve(object, object2, cTsh = NULL, plot = TRUE)

## S4 method for signature 'INSPEcT_model,INSPEcT_model'
rocCurve(object, object2, cTsh = NULL,
  plot = TRUE)

## S4 method for signature 'INSPEcT_model,INSPEcT'
rocCurve(object, object2, cTsh = NULL,
  plot = TRUE)
```

**Arguments**

object	An object of class INSPEcT_model, with true rates
object2	An object of class INSPEcT or INSPEcT_model, with modeled rates
cTsh	A numeric representing the threshold for the chi-squared test to consider a model as valid; if NULL the value is taken from the INSPEcT_model object
plot	A logical indicating whether ROC curves should be plotted or not

**Value**

A list of objects of class pROC with summary of each roc curve

**See Also**

[makeSimModel](#), [makeSimDataset](#), [rocThresholds](#)

**Examples**

```
data('simRates', package='INSPEcT')
data('simData3rep', package='INSPEcT')
rocCurve(simRates, simData3rep)
```

---

rocThresholds	<i>Display rate classification performance with thresholds visible at x-axis</i>
---------------	--

---

**Description**

Display rate classification performance with thresholds visible at x-axis

A method to visualize the performance in the classification of synthesis, degradation and processing rates based on the comparison of the original simulated rates and the one obtained by the function [modelRates](#). For each rate, classification performance is measured in terms of sensitivity and specificity using a ROC curve analysis. False negatives (FN) represent cases where the rate is identified as constant while it was simulated as varying. False positives (FP) represent cases where INSPEcT identified a rate as varying while it was simulated as constant. On the contrary, true positives (TP) and negatives (TN) are cases of correct classification of varying and constant rates, respectively. Consequently, at increasing brown p-values different sensitivity and specificity can be achieved.

**Usage**

```
rocThresholds(object, object2, cTsh = NULL, bTsh = NULL, xlim = c(1e-05,
  1))

## S4 method for signature 'INSPEcT_model,INSPEcT_model'
rocThresholds(object, object2,
  cTsh = NULL, bTsh = NULL, xlim = c(1e-05, 1))

## S4 method for signature 'INSPEcT_model,INSPEcT'
rocThresholds(object, object2, cTsh = NULL,
  bTsh = NULL, xlim = c(1e-05, 1))
```

**Arguments**

object	An object of class INSPEcT_model, with true rates
object2	An object of class INSPEcT or INSPEcT_model, with modeled rates
cTsh	A numeric representing the threshold for the chi-squared test to consider a model as valid
bTsh	A numeric representing the threshold for the Brown's method to consider a rate as varying
xlim	A numeric representing limits for the x-axis (default is c(1-e-5,1))

**Value**

None

**See Also**

[makeSimModel](#), [makeSimDataset](#), [rocCurve](#)

**Examples**

```
data('simRates', package='INSPEcT')
data('simData3rep', package='INSPEcT')
rocThresholds(simRates, simData3rep)
# Increase the Brown threshold for all rates (be more relaxed)
thresholds(simData3rep)$brown <- c(alpha=.05, beta=.05, gamma=.05)
rocThresholds(simRates, simData3rep)
```

---

rpkms	<i>intron, exons RPKM values of 500 genes from 4sU-seq and RNA-seq experiments</i>
-------	--

---

**Description**

A dataset containing the values of exonic and intronic RPKMs of 500 genes both in 4sU-seq and RNA-seq experiments. The variables are as follows:

**Format**

A list of 4 matrices with 500 rows and 9 columns

**Details**

- rpkms\_4su\_exons
- rpkms\_4su\_introns
- rpkms\_total\_exons
- rpkms\_total\_introns

---

sfPlot	<i>A nice plot to see scaling factors used for RNA-seq and 4sU-seq libraries</i>
--------	--

---

**Description**

A nice plot to see scaling factors used for RNA-seq and 4sU-seq libraries

This method generates a plot that immediately shows the scaling factors used to scale RNA- and 4sU-seq libraries and the possible relations between them. The ratio between the RNA- and the 4sU-seq scaling can be in fact considered as a yield of the synthesis within the cells.

**Usage**

```
sfPlot(object)

## S4 method for signature 'INSPEcT'
sfPlot(object)
```

**Arguments**

object            An object of class INSPEcT

**Value**

None

**Examples**

```
data('rpkms', package='INSPEcT')
tpts <- c(0, 1/6, 1/3, 1/2, 1, 2, 4, 8, 16)
tL <- 1/6
mycerIds <- newINSPEcT(tpts, tL, rpkms$rpkms_4su_exons, rpkms$rpkms_total_exons, rpkms$rpkms_4su_introns, rpkms$rpkms_total_introns)
sfPlot(mycerIds)
```

---

simData1rep	<i>An INSPEcT object with 1000 simulated rates and concentration and their modeled rates</i>
-------------	--

---

**Description**

A dataset containing the rates and concentrations obtained from the dataset simRates with 1 replicates and time points corresponding to: 0, 1/6, 1/3, 1/2, 1, 2, 4, 8, 16 hours. On this dataset rates and concentrations have been modeled with the method modelRates

**Format**

An INSPEcT object

---

simData3rep	<i>An INSPEcT object with 1000 simulated rates and concentration and their modeled rates</i>
-------------	--

---

**Description**

A dataset containing the rates and concentrations obtained from the dataset simRates with 3 replicates and time points corresponding to: 0, 1/6, 1/3, 1/2, 1, 1.5, 2, 4, 8, 12, 16 and 24 hours. On this dataset rates and concentrations have been modeled with the method modelRates

**Format**

An INSPEcT object

---

simRates	<i>An INSPEcT_model object of 1000 simulated rates</i>
----------	--

---

**Description**

The INSPEcT\_model object contains 1000 simulated rates that were obtained using the dataset rpkm as reference

**Format**

An INSPEcT\_model object

---

split	<i>Divide an INSPEcT Object into groups</i>
-------	---

---

**Description**

Divides the INSPEcT object into the groups defined by 'f',

**Usage**

```
## S4 method for signature 'INSPEcT,ANY'
split(x, f, drop = FALSE, ...)
```

**Arguments**

x	An object of class INSPEcT
f	A vector of length equal to the number of genes in x which defines the groups
drop	A logical belonging to the generic function, useless in this context.
...	Additional arguments to match the generic function

**Value**

A list containing objects of class INSPEcT

**Examples**

```
data('mycerIds10')
splitIdx <- c(1,1,1,2,2,2,3,3,3,4)
mycerIds10Split <- split(mycerIds10, splitIdx)
```

---

totalSF	<i>Accessor to the slot totalSF of an INSPEcT object</i>
---------	--

---

**Description**

Accessor to the slot totalSF of an INSPEcT object

Accessor to obtain the totalSF slot associated with the object of class INSPEcT

**Usage**

```
totalSF(object)
```

```
## S4 method for signature 'INSPEcT'
totalSF(object)
```

**Arguments**

object	An object of class INSPEcT
--------	----------------------------

**Value**

A numeric that indicates the scaling factors applied between time points of the data coming from RNA-seq library (applies to total-mRNAs and pre-mRNAs concentrations)

**Examples**

```
data('mycerIds10')
totalSF(mycerIds10)
```

---

tpts

*Accessor to the slot tpts of an INSPEcT object*

---

**Description**

Accessor to the slot tpts of an INSPEcT object

Accessor to obtain the tpts associated with the object of class INSPEcT

**Usage**

```
tpts(object)

## S4 method for signature 'INSPEcT'
tpts(object)
```

**Arguments**

object            An object of class INSPEcT

**Value**

A numeric that indicates time points contained the object

**Examples**

```
data('mycerIds10')
tpts(mycerIds10)
```

---

UCSC\_mm9\_genes\_exons    *A Gtf file containing exons definition of 100 genes*

---

**Description**

A Gtf file containing exons definition of 100 genes

**Format**

A tab separated file

---

 UCSC\_mm9\_genes\_introns

*A Gtf file containing introns definition of 100 genes*


---

**Description**

A Gtf file containing introns definition of 100 genes

**Format**

A tab separated file

---

 viewModelRates

*Retrieve the modeled rates and concentrations*


---

**Description**

Retrieve the modeled rates and concentrations

A method to access the modeled rates via the method [modelRates](#)

**Usage**

```
viewModelRates(object, feature)
```

```
## S4 method for signature 'INSPECT'
viewModelRates(object, feature)
```

**Arguments**

object            An object of class INSPECT

feature           A character indicating the feature to retrieve, "synthesis", "degradation", "processing" for rates, "total" for total mRNA concentrations or "preMRNA" for premature mRNA concentrations

**Value**

A numeric matrix containing the values for the selected feature

**Examples**

```
data('mycerIds10', package='INSPECT')
viewModelRates(mycerIds10, 'synthesis')
```

# Index

- [, [11](#), [12](#)
- [, INSPECT, ANY, ANY-method (Extract), [6](#)
- [, INSPECT\_model, ANY, ANY-method (Extract), [6](#)
  
- AIC, [11](#), [12](#)
- AIC, INSPECT-method (AIC-INSPECT-method), [2](#)
- AIC, INSPECT\_model-method (AIC-INSPECT-method), [2](#)
- AIC-INSPECT-method, [2](#)
  
- chisqmodel, [3](#), [11](#), [12](#)
- chisqmodel, INSPECT-method (chisqmodel), [3](#)
- chisqmodel, INSPECT\_model-method (chisqmodel), [3](#)
- chisqtest, [4](#), [11](#), [12](#)
- chisqtest, INSPECT-method (chisqtest), [4](#)
- chisqtest, INSPECT\_model-method (chisqtest), [4](#)
- combine, [4](#), [11](#)
- combine, INSPECT, INSPECT-method (combine), [4](#)
  
- dim, [11](#)
- dim, INSPECT-method, [5](#)
  
- Extract, [6](#)
  
- featureNames, [11](#)
- featureNames, INSPECT-method, [7](#)
- featureNames<-, INSPECT-method (featureNames, INSPECT-method), [7](#)
  
- geneClass, [7](#), [11](#), [12](#), [21](#)
- geneClass, INSPECT-method (geneClass), [7](#)
- geneClass, INSPECT\_model-method (geneClass), [7](#)
- getModel, [8](#), [11](#)
- getModel, INSPECT-method (getModel), [8](#)
- getModel<- (getModel), [8](#)
- getModel<-, INSPECT-method (getModel), [8](#)
  
- inHeatmap, [9](#), [11](#)
- inHeatmap, INSPECT-method (inHeatmap), [9](#)
- INSPECT, [10](#), [10](#)
- INSPECT-class, [10](#)
- INSPECT-package (INSPECT), [10](#)
- INSPECT\_model, [10](#)
- INSPECT\_model-class, [12](#)
  
- labeledSF, [11](#), [13](#)
- labeledSF, INSPECT-method (labeledSF), [13](#)
- llrtests, [11](#), [12](#), [24](#)
- llrtests (modelSelection), [22](#)
- llrtests, INSPECT-method (modelSelection), [22](#)
- llrtests, INSPECT\_model-method (modelSelection), [22](#)
- llrtests<- (modelSelection), [22](#)
- llrtests<-, INSPECT-method (modelSelection), [22](#)
- llrtests<-, INSPECT\_model-method (modelSelection), [22](#)
- logLik, [11](#), [12](#), [14](#)
- logLik, INSPECT-method (logLik), [14](#)
- logLik, INSPECT\_model-method (logLik), [14](#)
  
- makeExonsGtfFromDb, [14](#)
- makeExonsGtfFromDb, TxDb-method (makeExonsGtfFromDb), [14](#)
- makeGtfFromDb (makeExonsGtfFromDb), [14](#)
- makeIntronsGtfFromDb (makeExonsGtfFromDb), [14](#)
- makeIntronsGtfFromDb, TxDb-method (makeExonsGtfFromDb), [14](#)
- makeModelRates, [11](#), [12](#), [15](#)
- makeModelRates, INSPECT-method (makeModelRates), [15](#)
- makeModelRates, INSPECT\_model-method (makeModelRates), [15](#)
- makeRPKMs, [16](#)
- makeSimDataset, [12](#), [13](#), [17](#), [18](#), [19](#), [24](#), [29](#), [30](#), [33](#), [34](#)
- makeSimDataset, INSPECT\_model-method (makeSimDataset), [17](#)



- makeSimModel, [11](#), [12](#), [17](#), [18](#), [19](#), [24](#), [29](#), [30](#), [33](#), [34](#)
- makeSimModel, INSPECT-method (makeSimModel), [18](#)
- modelingParams, [10](#), [11](#), [19](#), [21](#), [25](#)
- modelingParams, INSPECT-method (modelingParams), [19](#)
- modelingParams<- (modelingParams), [19](#)
- modelingParams<-, INSPECT-method (modelingParams), [19](#)
- modelRates, [11](#), [12](#), [15](#), [19](#), [20](#), [21](#), [25](#), [32](#), [33](#), [39](#)
- modelRates, INSPECT-method (modelRates), [21](#)
- modelSelection, [11](#), [13](#), [22](#), [29](#)
- modelSelection, INSPECT-method (modelSelection), [22](#)
- modelSelection, INSPECT\_model-method (modelSelection), [22](#)
- modelSelection<- (modelSelection), [22](#)
- modelSelection<-, INSPECT-method (modelSelection), [22](#)
- modelSelection<-, INSPECT\_model-method (modelSelection), [22](#)
- mycerIds10, [24](#)
- nCores, [11](#), [25](#)
- nCores, INSPECT-method (nCores), [25](#)
- nCores<- (nCores), [25](#)
- nCores<- , INSPECT, numeric-method (nCores), [25](#)
- newINSPECT, [10](#), [21](#), [26](#), [30](#), [31](#)
- nGenes, [5](#), [11](#), [27](#)
- nGenes, INSPECT-method (nGenes), [27](#)
- nTpts, [5](#), [11](#), [28](#)
- nTpts, INSPECT-method (nTpts), [28](#)
- plotGene, [11](#), [28](#)
- plotGene, INSPECT-method (plotGene), [28](#)
- ratePvals, [8](#), [11](#), [13](#), [29](#)
- ratePvals, INSPECT-method (ratePvals), [29](#)
- ratePvals, INSPECT\_model-method (ratePvals), [29](#)
- ratesFirstGuess, [11](#), [27](#), [30](#), [31](#)
- ratesFirstGuess, INSPECT-method (ratesFirstGuess), [30](#)
- ratesFirstGuessVar, [11](#), [30](#), [31](#)
- ratesFirstGuessVar, INSPECT-method (ratesFirstGuessVar), [31](#)
- removeModel, [11](#), [31](#)
- removeModel, INSPECT-method (removeModel), [31](#)
- rocCurve, [13](#), [32](#), [34](#)
- rocCurve, INSPECT\_model, INSPECT-method (rocCurve), [32](#)
- rocCurve, INSPECT\_model, INSPECT\_model-method (rocCurve), [32](#)
- rocThresholds, [13](#), [33](#), [33](#)
- rocThresholds, INSPECT\_model, INSPECT-method (rocThresholds), [33](#)
- rocThresholds, INSPECT\_model, INSPECT\_model-method (rocThresholds), [33](#)
- rpkms, [34](#)
- sfPlot, [11](#), [35](#)
- sfPlot, INSPECT-method (sfPlot), [35](#)
- show, INSPECT-method (INSPECT-class), [10](#)
- show, INSPECT\_model-method (INSPECT\_model-class), [12](#)
- simData1rep, [36](#)
- simData3rep, [36](#)
- simRates, [36](#)
- split, [37](#)
- split, INSPECT, ANY-method (split), [37](#)
- testingParams, [9](#)
- testingParams (modelSelection), [22](#)
- thresholds, [11](#), [13](#)
- thresholds (modelSelection), [22](#)
- thresholds, INSPECT-method (modelSelection), [22](#)
- thresholds, INSPECT\_model-method (modelSelection), [22](#)
- thresholds<- (modelSelection), [22](#)
- thresholds<-, INSPECT-method (modelSelection), [22](#)
- thresholds<-, INSPECT\_model-method (modelSelection), [22](#)
- totalSF, [11](#), [37](#)
- totalSF, INSPECT-method (totalSF), [37](#)
- tpts, [11](#), [38](#)
- tpts, INSPECT-method (tpts), [38](#)
- UCSC\_mm9\_genes\_exons, [38](#)
- UCSC\_mm9\_genes\_introns, [39](#)
- viewModelRates, [11](#), [21](#), [39](#)
- viewModelRates, INSPECT-method (viewModelRates), [39](#)