

# Package ‘geuvPack’

April 20, 2016

**Title** summarized experiment with expression data from GEUVADIS

**Version** 1.2.0

**Author** VJ Carey <stvjc@channing.harvard.edu>

**Maintainer** VJ Carey <stvjc@channing.harvard.edu>

**Description** FPKM from GEUVADIS, annotated to gencode regions

**Depends** R (>= 2.10), SummarizedExperiment

**License** Artistic-2.0

**LazyLoad** yes

**biocViews** ExperimentData, Genome, SequencingData, MicroarrayData,  
ArrayExpress

**NeedsCompilation** no

## R topics documented:

geuvPack-package	1
geuFPKM	2
gtpath	3

<b>Index</b>	<b>5</b>
--------------	----------

---

geuvPack-package	<i>summarized experiment with expression data from GEUVADIS</i>
------------------	---

---

## Description

FPKM from GEUVADIS, annotated to gencode regions  
could include more things like miRNA read counts

**Details**

Package: geuvPack  
Version: 0.0.0  
Suggests:  
Depends: GenomicRanges  
License: Private  
LazyLoad: yes  
Built: R 3.1.1; ; 2014-08-22 17:12:50 UTC; unix

gtpath function will get 1000 genomes genotype VCF from Amazon S3; modify if you have local VCF

**Author(s)**

VJ Carey <stvjc@channing.harvard.edu>  
Maintainer: VJ Carey <stvjc@channing.harvard.edu>

---

geuFPKM

*Expression data, gene level FPKM, from GEUVADIS*

---

**Description**

see metadata(geuFPKM)

**Usage**

data("geuFPKM")

**Format**

A [RangedSummarizedExperiment](#) object.

**Details**

FPKM as reported in EBI ArrayExpress E-GEUV-1. Other quantifications may be added in future versions of this package.

"500bffee8e0f770c157e0189e9e50ae" is the output of digest on the txt.gz file of quantifications from which the assay data in the geuFPKM [RangedSummarizedExperiment](#) instance is constructed. This was extracted at Channing Division of Network Medicine on 13 November 2013, and verified to be correct for the contents of the URL below on 11 December 2014.

The README file

[http://www.ebi.ac.uk/arrayexpress/files/E-GEUV-1/GeuvadisRNASeqAnalysisFiles\\_README.txt](http://www.ebi.ac.uk/arrayexpress/files/E-GEUV-1/GeuvadisRNASeqAnalysisFiles_README.txt)

has the following remarks

Quantification file set:

- Sample set + sample size :

QC-passed: All QC-passed samples including replicates: 660 (mRNA) or 480 (miRNA)

QC-passed unique: Nonredundant set of unique samples used in most analyses: 462 (mRNA); 452 (miRNA)

- Normalization:

None: raw read counts

Library depth: Read counts scaled by total number of mapped reads (mRNA), or total number reads mapping to miRNAs (miRNA) per sample, then adjusted to the median of the sample set (45M for mRNA, 1.2M for miRNA)

Library depth and transcript length: RPKM

Library depth & expressed & PEER: Library depth scaling as above, removal of units with 0 counts in >50

- November 5, 2013 update: The file GD462.GeneQuantRPKM.50FN.samplename.resk10.norm.txt.gz that had the normalization as above PLUS an additional transformation of each gene's values to standard normal has been replaced by GD462.GeneQuantRPKM.50FN.samplename.resk10.txt.gz

## Source

[ftp://ftp.ebi.ac.uk/pub/databases/microarray/data/experiment/GEUV/E-GEUV-1/analysis\\_results/GD462.GeneQuantRPKM.50FN.samplename.resk10.txt.gz](ftp://ftp.ebi.ac.uk/pub/databases/microarray/data/experiment/GEUV/E-GEUV-1/analysis_results/GD462.GeneQuantRPKM.50FN.samplename.resk10.txt.gz)

## References

PMID 24037378

## Examples

```
data(geuFPKM)
geuFPKM
sd(assay(geuFPKM)[1,])
## maybe str(geuFPKM) ; plot(geuFPKM) ...
```

---

gtpath

*generate path for a VCF file for 1000 genomes genotypes*

---

## Description

generate path for a VCF file for 1000 genomes genotypes

## Usage

```
gtpath(chrdigit, useS3=TRUE, tmlate)
```

**Arguments**

chrdigit	suffix to 'chr' to get the chromosome id
useS3	logical, if TRUE, returns URL of an Amazon S3 bucket-resident 1000 genomes VCF
tmplate	character string, used only if useS3 is FALSE. The substring "%N%" will be replaced by value of chrdigit

**Details**

A subset of samples in GEUVADIS have genotypes recorded in 1000 genomes. This function creates the URL for the VCF corresponding to a chromosome. [cisAssoc](#) can operate on these genotypes.

**Value**

character string

**Examples**

```
gtpath(1)
gtpath(1, FALSE, "/tmp/my%%N%.vcf.gz")
```

# Index

\*Topic **datasets**

geuFPKM, [2](#)

\*Topic **data**

gtpath, [3](#)

\*Topic **package**

geuvPack-package, [1](#)

cisAssoc, [4](#)

geuFPKM, [2](#)

geuvPack (geuvPack-package), [1](#)

geuvPack-package, [1](#)

gtpath, [3](#)

RangedSummarizedExperiment, [2](#)