

# Package ‘MSstatsBig’

September 19, 2024

**Type** Package

**Title** MSstats Preprocessing for Larger than Memory Data

**Version** 1.3.0

**Description** MSstats package provide tools for preprocessing, summarization and differential analysis of mass spectrometry (MS) proteomics data. Recently, some MS protocols enable acquisition of data sets that result in larger than memory quantitative data. MSstats functions are not able to process such data. MSstatsBig package provides additional converter functions that enable processing larger than memory data sets.

**License** Artistic-2.0

**Encoding** UTF-8

**RoxygenNote** 7.2.3

**Imports** arrow, DBI, dplyr, MSstats, MSstatsConvert, readr, sparklyr, utils

**Suggests** knitr, rmarkdown

**VignetteBuilder** knitr

**biocViews** MassSpectrometry, Proteomics, Software

**git\_url** <https://git.bioconductor.org/packages/MSstatsBig>

**git\_branch** devel

**git\_last\_commit** 4531cf8

**git\_last\_commit\_date** 2024-04-30

**Repository** Bioconductor 3.20

**Date/Publication** 2024-09-18

**Author** Mateusz Staniak [aut, cre],  
Devon Kohler [aut]

**Maintainer** Mateusz Staniak <mtst@mstaniak.pl>

## Contents

bigFragPipetoMSstatsFormat . . . . .	2
bigSpectronautoMSstatsFormat . . . . .	3
MSstatsAddAnnotationBig . . . . .	4
MSstatsPreprocessBig . . . . .	5
<b>Index</b>	<b>7</b>

---

bigFragPipetoMSstatsFormat

*Convert out-of-memory FragPipe files to MSstats format.*

---

## Description

Convert out-of-memory FragPipe files to MSstats format.

## Usage

```
bigFragPipetoMSstatsFormat(
  input_file,
  output_file_name,
  backend,
  max_feature_count = 20,
  filter_unique_peptides = FALSE,
  aggregate_psms = FALSE,
  filter_few_obs = FALSE,
  remove_annotation = FALSE,
  connection = NULL
)
```

## Arguments

input_file	name of the input text file in 10-column MSstats format.
output_file_name	name of an output file which will be saved after pre-processing
backend	"arrow" or "sparklyr". Option "sparklyr" requires a spark installation and connection to spark instance provided in the 'connection' parameter.
max_feature_count	maximum number of features per protein. Features will be selected based on highest average intensity.
filter_unique_peptides	If TRUE, shared peptides will be removed. Please refer to the 'Details' section for additional information.
aggregate_psms	If TRUE, multiple measurements per PSM in a Run will be aggregated (by taking maximum value). Please refer to the 'Details' section for additional information.
filter_few_obs	If TRUE, feature with less than 3 observations across runs will be removed. Please refer to the 'Details' section for additional information.
remove_annotation	If TRUE, columns BioReplicate and Condition will be removed to reduce output file size. These will need to be added manually later before using dataProcess function. Only applicable to sparklyr backend.
connection	Connection to a spark instance created with the 'spark_connect' function from 'sparklyr' package.

**Value**

either arrow object or sparklyr table that can be optionally collected into memory by using `dplyr::collect` function.

**Examples**

```
converted_data <- bigFragPipetoMSstatsFormat(
  system.file("extdata", "fgexample.csv", package = "MSstatsBig"),
  "output_file.csv",
  backend = "arrow")
converted_data <- dplyr::collect(converted_data)
head(converted_data)
```

---

bigSpectronauttoMSstatsFormat

*Convert out-of-memory Spectronaut files to MSstats format.*

---

**Description**

Convert out-of-memory Spectronaut files to MSstats format.

**Usage**

```
bigSpectronauttoMSstatsFormat(
  input_file,
  output_file_name,
  backend,
  filter_by_excluded = FALSE,
  filter_by_identified = FALSE,
  filter_by_qvalue = TRUE,
  qvalue_cutoff = 0.01,
  max_feature_count = 20,
  filter_unique_peptides = FALSE,
  aggregate_psms = FALSE,
  filter_few_obs = FALSE,
  remove_annotation = FALSE,
  connection = NULL
)
```

**Arguments**

<code>input_file</code>	name of the input text file in 10-column MSstats format.
<code>output_file_name</code>	name of an output file which will be saved after pre-processing
<code>backend</code>	"arrow" or "sparklyr". Option "sparklyr" requires a spark installation and connection to spark instance provided in the 'connection' parameter.
<code>filter_by_excluded</code>	if TRUE, will filter by the 'F.ExcludedFromQuantification' column.
<code>filter_by_identified</code>	if TRUE, will filter by the 'EG.Identified' column.

filter_by_qvalue	if TRUE, will filter by EG.Qvalue and PG.Qvalue columns.
qvalue_cutoff	cutoff which will be used for q-value filtering.
max_feature_count	maximum number of features per protein. Features will be selected based on highest average intensity.
filter_unique_peptides	If TRUE, shared peptides will be removed. Please refer to the ‘Details’ section for additional information.
aggregate_psms	If TRUE, multiple measurements per PSM in a Run will be aggregated (by taking maximum value). Please refer to the ‘Details’ section for additional information.
filter_few_obs	If TRUE, feature with less than 3 observations across runs will be removed. Please refer to the ‘Details’ section for additional information.
remove_annotation	If TRUE, columns BioReplicate and Condition will be removed to reduce output file size. These will need to be added manually later before using dataProcess function. Only applicable to sparklyr backend.
connection	Connection to a spark instance created with the ‘spark_connect’ function from ‘sparklyr’ package.

**Value**

either arrow object or sparklyr table that can be optionally collected into memory by using `dplyr::collect` function.

**Examples**

```
converted_data <- bigSpectronauttoMSstatsFormat(
  system.file("extdata", "spectronaut_input.csv", package = "MSstatsBig"),
  "output_file.csv",
  backend="arrow")
converted_data <- dplyr::collect(converted_data)
head(converted_data)
```

---

MSstatsAddAnnotationBig

*Merge annotation to output of MSstatsPreprocessBig*

---

**Description**

Merge annotation to output of MSstatsPreprocessBig

**Usage**

```
MSstatsAddAnnotationBig(input, annotation)
```

**Arguments**

input	output of MSstatsPreprocessBig
annotation	run annotation

**Value**

table of 'input' and 'annotation' merged by Run column.

**Examples**

```
converted_data <- bigFragPipetoMSstatsFormat(
  system.file("extdata", "fgexample.csv", package = "MSstatsBig"),
  "output_file.csv",
  backend = "arrow")
converted_data <- dplyr::collect(converted_data)
head(converted_data)
# Change annotation as an example:
converted_data$Condition <- NULL
converted_data$BioReplicate <- NULL
annot <- data.frame(Run = unique(converted_data[["Run"]]))
annot$BioReplicate <- rep(1:53, times = 2)
annot$Condition <- rep(1:2, each = 53)
head(MSstatsAddAnnotationBig(converted_data, annot))
```

---

MSstatsPreprocessBig	<i>General converter for larger-than-memory csv files in MSstats format 10-column format</i>
----------------------	--

---

**Description**

General converter for larger-than-memory csv files in MSstats format 10-column format

**Usage**

```
MSstatsPreprocessBig(
  input_file,
  output_file_name,
  backend,
  max_feature_count = 20,
  filter_unique_peptides = FALSE,
  aggregate_psms = FALSE,
  filter_few_obs = FALSE,
  remove_annotation = FALSE,
  connection = NULL
)
```

**Arguments**

input_file	name of the input text file in 10-column MSstats format.
output_file_name	name of an output file which will be saved after pre-processing
backend	"arrow" or "sparklyr". Option "sparklyr" requires a spark installation and connection to spark instance provided in the 'connection' parameter.
max_feature_count	maximum number of features per protein. Features will be selected based on highest average intensity.

<code>filter_unique_peptides</code>	If TRUE, shared peptides will be removed. Please refer to the ‘Details’ section for additional information.
<code>aggregate_psms</code>	If TRUE, multiple measurements per PSM in a Run will be aggregated (by taking maximum value). Please refer to the ‘Details’ section for additional information.
<code>filter_few_obs</code>	If TRUE, feature with less than 3 observations across runs will be removed. Please refer to the ‘Details’ section for additional information.
<code>remove_annotation</code>	If TRUE, columns BioReplicate and Condition will be removed to reduce output file size. These will need to be added manually later before using <code>dataProcess</code> function. Only applicable to sparklyr backend.
<code>connection</code>	Connection to a spark instance created with the ‘ <code>spark_connect</code> ’ function from ‘ <code>sparklyr</code> ’ package.

### Details

Filtering and aggregation may be very time consuming and the ability to perform them in a given R session depends on available memory, settings of external packages, etc. Hence, all value of related parameters (‘`filter_unique_peptides`’, ‘`aggregate_psms`’, ‘`filter_few_obs`’) are set to FALSE by default and only feature selection is performed, which saves both computation time and memory. Appropriately configured spark backend provides the most consistent way to perform these operations.

### Value

either arrow object or sparklyr table that can be optionally collected into memory by using `dplyr::collect` function.

### Examples

```
converted_data <- bigFragPipetoMSstatsFormat(
  system.file("extdata", "fgexample.csv", package = "MSstatsBig"),
  "tencol_format.csv",
  backend="arrow")
procd <- MSstatsPreprocessBig("tencol_format.csv", "proc_out.csv", backend = "arrow")
head(dplyr::collect(procd))
```

# Index

bigFragPipetoMSstatsFormat, [2](#)  
bigSpectronautoMSstatsFormat, [3](#)

MSstatsAddAnnotationBig, [4](#)  
MSstatsPreprocessBig, [5](#)