

Package ‘CRISPRseek’

October 15, 2018

Type Package

Title Design of target-specific guide RNAs in CRISPR-Cas9,
genome-editing systems

Version 1.20.0

Date 2018-03-26

Encoding UTF-8

Author Lihua Julie Zhu, Benjamin R. Holmes, Hervé Pagès, Michael Lawrence, Isana Veksler-Lublinsky, Victor Ambros, Neil Aronin and Michael Brodsky

Maintainer Lihua Julie Zhu <julie.zhu@umassmed.edu>

Depends R (>= 3.0.1), BiocGenerics, Biostrings

Imports parallel, data.table, seqinr, S4Vectors (>= 0.9.25), IRanges,
BSgenome, BiocParallel, hash

Suggests RUnit, BiocStyle, BSgenome.Hsapiens.UCSC.hg19,
TxDb.Hsapiens.UCSC.hg19.knownGene, org.Hs.eg.db

Description The package includes functions to find potential guide RNAs for input target sequences, optionally filter guide RNAs without restriction enzyme cut site, or without paired guide RNAs, genome-wide search for off-targets, score, rank, fetch flank sequence and indicate whether the target and off-targets are located in exon region or not. Potential guide RNAs are annotated with total score of the top5 and topN off-targets, detailed topN mismatch sites, restriction enzyme cut sites, and paired guide RNAs. If GeneRfold and GeneR are installed (<http://bioconductor.case.edu/bioconductor/2.8/bioc/html/GeneRfold.html>, <http://bioc.ism.ac.jp/packages/2.8/bioc/html/GeneR.html>), minimum free energy and bracket notation of secondary structure of gRNA and gRNA backbone constant region will be included in the summary file. This package leverages Biostrings and BSgenome packages.

License GPL (>= 2)

LazyLoad yes

biocViews GeneRegulation, SequenceMatching, CRISPR

git_url <https://git.bioconductor.org/packages/CRISPRseek>

git_branch RELEASE_3_7

git_last_commit eef2c5a

git_last_commit_date 2018-04-30

Date/Publication 2018-10-15

R topics documented:

CRISPRseek-package	2
annotateOffTargets	4
buildFeatureVectorForScoring	6
calculategRNAEfficiency	7
compare2Sequences	8
filtergRNAs	13
filterOffTarget	14
findgRNAs	16
foldgRNAs	19
getOfftargetScore	20
isPatternUnique	21
offTargetAnalysis	22
searchHits	27
searchHits2	29
translatePattern	30
uniqueREs	31
writeHits	32
writeHits2	33
Index	36

CRISPRseek-package	<i>Design of target-specific guide RNAs (gRNAs) in CRISPR-Cas9, genome-editing systems</i>
--------------------	--

Description

Design of target-specific gRNAs for the CRISPR-Cas9 system by automatically finding potential gRNAs (paired/not paired), with/without restriction enzyme cut site(s) in a given sequence, searching for off targets with user defined maximum number of mismatches, calculating score of each off target based on mismatch positions in the off target and a penalty weight matrix, filtering off targets with user-defined criteria, and annotating off targets with flank sequences, whether located in exon or not. Summary report is also generated with gRNAs ranked by total topN off target score, annotated with restriction enzyme cut sites, gRNA efficacy and possible paired gRNAs. Detailed paired gRNAs information and restriction enzyme cut sites are stored in separate files in the output directory specified by the user. In total, four tab delimited files are generated in the output directory: OfftargetAnalysis.xls (off target details), Summary.xls (gRNA summary), REcutDetails.xls (restriction enzyme cut sites of each gRNA), and pairedgRNAs.xls (potential paired gRNAs).

Details

Package:	CRISPRseek
Type:	Package
Version:	1.0
Date:	2013-10-04
License:	GPL (>= 2)

Function offTargetAnalysis integrates all steps of off target analysis into one function call

Author(s)

Lihua Julie Zhu and Michael Brodsky Maintainer: julie.zhu@umassmed.edu

References

Mali P, Aach J, Stranges PB, Esvelt KM, Moosburner M, Kosuri S, Yang L, Church GM. CAS9 transcriptional activators for target specificity screening and paired nickases for cooperative genome engineering. *Nat Biotechnol.* 2013. 31(9):833-8
 Patrick D Hsu, David A Scott, Joshua A Weinstein, F Ann Ran, Silvana Konermann, Vineeta Agarwala, Yinqing Li, Eli J Fine, Xuebing Wu, Ophir Shalem, Thomas J Cradick, Luciano A Marraffini, Gang Bao & Feng Zhang. DNA targeting specificity of rNA-guided Cas9 nucleases. *Nat Biotechnol.* 2013. 31:827-834
 Lihua Julie Zhu, Benjamin R. Holmes, Neil Aronin and Michael Brodsky. CRISPRseek: a Bioconductor package to identify target-specific guide RNAs for CRISPR-Cas9 genome-editing systems. *Plos One* Sept 23rd 2014
 Doench JG et al., Optimized sgRNA design to maximize activity and minimize off-target effects of CRISPR-Cas9. *Nature Biotechnology* Jan 18th 2016

See Also

offTargetAnalysis

Examples

```
library(CRISPRseek)
library("BSgenome.Hsapiens.UCSC.hg19")
library(TxDb.Hsapiens.UCSC.hg19.knownGene)
library(org.Hs.eg.db)
outputDir <- getwd()
inputFilePath <- system.file("extdata", "inputseq.fa", package = "CRISPRseek")
REpatternFile <- system.file("extdata", "NEBenzymes.fa", package = "CRISPRseek")
##### Scenario 1. Target and off-target analysis for paired gRNAs with
##### one of the pairs overlap RE sites
results <- offTargetAnalysis(inputFilePath, findgRNAsWithREcutOnly=TRUE,
  REpatternFile =REpatternFile,findPairedgRNAOnly=TRUE,
  BSgenomeName=Hsapiens, txdb=TxDb.Hsapiens.UCSC.hg19.knownGene,
  orgAnn = org.Hs.egSYMBOL,max.mismatch = 1, chromToSearch = "chrX",
  outputDir = outputDir,overwrite = TRUE)

##### Scenario 2. Target and off-target analysis for paired gRNAs with or
##### without RE sites
results <- offTargetAnalysis(inputFilePath, findgRNAsWithREcutOnly = FALSE,
  REpatternFile = REpatternFile,findPairedgRNAOnly = TRUE,
  BSgenomeName = Hsapiens, txdb = TxDb.Hsapiens.UCSC.hg19.knownGene,
  orgAnn = org.Hs.egSYMBOL,max.mismatch = 1, chromToSearch = "chrX",
  outputDir = outputDir, overwrite = TRUE)

##### Scenario 3. Target and off-target analysis for gRNAs overlap RE sites

results <- offTargetAnalysis(inputFilePath, findgRNAsWithREcutOnly = TRUE,
  REpatternFile = REpatternFile,findPairedgRNAOnly = FALSE,
  BSgenomeName = Hsapiens, txdb = TxDb.Hsapiens.UCSC.hg19.knownGene,
  orgAnn = org.Hs.egSYMBOL, max.mismatch = 1, chromToSearch = "chrX",
  outputDir = outputDir, overwrite = TRUE)

##### Scenario 4. Off-target analysis for all potential gRNAs, this will
#####be the slowest among the aforementioned scenarios.
```

```

results <- offTargetAnalysis(inputFilePath, findgRNAsWithREcutOnly = FALSE,
  REpatternFile = REpatternFile, findPairedgRNAOnly = FALSE,
  BSgenomeName = Hsapiens, txdb = TxDb.Hsapiens.UCSC.hg19.knownGene,
  orgAnn = org.Hs.egSYMBOL, max.mismatch = 1, chromToSearch = "chrX",
  outputDir = outputDir, overwrite = TRUE)

##### Scenario 5. Target and off-target analysis for gRNAs input by user.
gRNAFilePath <- system.file("extdata", "testHsap_GATA1_ex2_gRNA1.fa",
  package="CRISPRseek")
results <- offTargetAnalysis(inputFilePath = gRNAFilePath, findgRNAs = FALSE,
  findgRNAsWithREcutOnly = FALSE, REpatternFile = REpatternFile,
  findPairedgRNAOnly = FALSE, BSgenomeName = Hsapiens,
  txdb = TxDb.Hsapiens.UCSC.hg19.knownGene,
  orgAnn = org.Hs.egSYMBOL, max.mismatch = 1, chromToSearch = "chrX",
  outputDir = outputDir, overwrite = TRUE)

##### Scenario 6. Quick gRNA finding without target and off-target analysis
results <- offTargetAnalysis(inputFilePath, findgRNAsWithREcutOnly = TRUE,
  REpatternFile = REpatternFile, findPairedgRNAOnly = TRUE,
  chromToSearch = "", outputDir = outputDir, overwrite = TRUE)

##### Scenario 7. Quick gRNA finding with gRNA efficacy analysis
results <- offTargetAnalysis(inputFilePath, findgRNAsWithREcutOnly = TRUE,
  REpatternFile = REpatternFile, findPairedgRNAOnly = TRUE,
  BSgenomeName = Hsapiens, annotateExon = FALSE,
  max.mismatch = 0, outputDir = outputDir, overwrite = TRUE)

```

annotateOffTargets *annotate off targets*

Description

annotate off targets to indicate whether it is inside an exon or intron, and the gene id if inside the gene.

Usage

```
annotateOffTargets(scores, txdb, orgAnn)
```

Arguments

scores	a data frame output from getOfftargetScore or filterOfftarget. It contains strand (strand of the off target, + for plus and - for minus strand), chrom (chromosome of the off target), chromStart (start position of the off target), chromEnd (end position of the off target), name (gRNA name), gRNAPlusPAM (gRNA sequence with PAM sequence concatenated), OffTargetSequence (the genomic sequence of the off target), n.mismatch (number of mismatches between the off target and the gRNA), forViewInUCSC (string for viewing in UCSC genome browser, e.g., chr14:31665685-31665707), score (score of the off target), mismatch.distance2PAM (a comma separated distances of all mismatches to PAM, e.g., 14,11 means one mismatch is 14 bp away from PAM and the other mismatch is 11 bp away from PAM), alignment (alignment between gRNA and off
--------	---

target, e.g.,G..C..... means that this off target aligns with gRNA except that G and C are mismatches),NGG (this off target contains canonical PAM or not, 1 for yes and 0 for no) mean.neighbor.distance.mismatch (mean distance between neighboring mismatches)

txdb	TxDb object, for creating and using TxDb object, please refer to GenomicFeatures package. For a list of existing TxDb object, please search for annotation package starting with Txdb at http://www.bioconductor.org/packages/release/BiocViews.html#___An such as TxDb.Rnorvegicus.UCSC.rn5.refGene for rat, TxDb.Mmusculus.UCSC.mm10.knownGene for mouse, TxDb.Hsapiens.UCSC.hg19.knownGene for human, TxDb.Dmelanogaster.UCSC.dm3.ensGene for Drosophila and TxDb.Celegans.UCSC.ce6.ensGene for C.elegans
orgAnn	organism annotation mapping such as org.Hs.egSYMBOL in org.Hs.eg.db package for human

Value

a data frame with off target annotation

Author(s)

Lihua Julie Zhu

References

Lihua Julie Zhu, Benjamin R. Holmes, Neil Aronin and Michael Brodsky. CRISPRseek: a Bioconductor package to identify target-specific guide RNAs for CRISPR-Cas9 genome-editing systems. Plos One Sept 23rd 2014

See Also

offTargetAnalysis

Examples

```
library(CRISPRseek)
#library("BSgenome.Hsapiens.UCSC.hg19")
library(TxDb.Hsapiens.UCSC.hg19.knownGene)
library(org.Hs.eg.db)
hitsFile <- system.file("extdata", "hits.txt", package="CRISPRseek")
hits <- read.table(hitsFile, sep = "\t", header = TRUE,
  stringsAsFactors = FALSE)
featureVectors <- buildFeatureVectorForScoring(hits)
scores <- getOfftargetScore(featureVectors)
outputDir <- getwd()
results <- annotateOffTargets(scores,
  txdb = TxDb.Hsapiens.UCSC.hg19.knownGene,
  orgAnn = org.Hs.egSYMBOL)
results
```

```
buildFeatureVectorForScoring
      Build feature vectors
```

Description

Build feature vectors for calculating scores of off targets

Usage

```
buildFeatureVectorForScoring(hits, gRNA.size = 20,
  canonical.PAM = "NGG",
  subPAM.position = c(22,23), PAM.size = 3, PAM.location = "3prime")
```

Arguments

hits	a data frame generated from searchHits, which contains IsMismatch.posX (Indicator variable indicating whether this position X is mismatch or not, 1 means yes and 0 means not, X = 1- gRNA.size) representing all positions in the guide RNA, abbreviated as gRNA),strand (strand of the off target, + for plus and - for minus strand), chrom (chromosome of the off target), chromStart (start position of the off target), chromEnd (end position of the off target),name (gRNA name), gRNAPlusPAM (gRNA sequence with PAM sequence concatenated), OffTargetSequence (the genomic sequence of the off target), n.mismatch (number of mismatches between the off target and the gRNA), forViewInUCSC (string for viewing in UCSC genome browser, e.g., chr14:31665685-31665707), score (set to 100, and will be calculated in getOfftargetScore)
gRNA.size	gRNA size, default 20
canonical.PAM	Canonical PAM, default NGG for spCas9, TTTN for Cpf1
subPAM.position	The start and end positions of the sub PAM to fetch. Default to 22 and 23 for SP with 20bp gRNA and NGG as preferred PAM
PAM.size	Size of PAM, default to 3 for spCas9, 4 for Cpf1
PAM.location	PAM location relative to gRNA. For example, default to 3prime for spCas9 PAM. Please set to 5prime for cpf1 PAM since it's PAM is located on the 5 prime end

Value

A data frame with hits plus features used for calculating scores and for generating report, including IsMismatch.posX (Indicator variable indicating whether this position X is mismatch or not, 1 means yes and 0 means not, X = 1- gRNA.size) representing all positions in the gRNA), strand (strand of the off target, + for plus and - for minus strand),chrom (chromosome of the off target), chromStart (start position of the off target),chromEnd (end position of the off target),name (gRNA name), gRNAPlusPAM (gRNA sequence with PAM sequence concatenated), OffTargetSequence (the genomic sequence of the off target), n.mismatch (number of mismatches between the off target and the gRNA), forViewInUCSC (string for viewing in UCSC genome browser, e.g., chr14:31665685-31665707), score (score of the off target), mismatche.distance2PAM (a comma separated distances of all mismatches to PAM, e.g., 14,11 means one mismatch is 14 bp away from PAM and the other mismatch is 11 bp away from PAM), alignment (alignment between gRNA

and off target, e.g.,G..C..... means that this off target aligns with gRNA except that G and C are mismatches), NGG (this off target contains canonical PAM or not, 1 for yes and 0 for no) mean.neighbor.distance.mismatch (mean distance between neighboring mismatches)

Author(s)

Lihua Julie Zhu

See Also

offTargetAnalysis

Examples

```
hitsFile <- system.file("extdata", "hits.txt", package = "CRISPRseek")
hits <- read.table(hitsFile, sep= "\t", header = TRUE,
  stringsAsFactors = FALSE)
buildFeatureVectorForScoring(hits)
```

calculategRNAEfficiency

Calculate gRNA Efficiency

Description

Calculate gRNA Efficiency for a given set of sequences and feature weight matrix

Usage

```
calculategRNAEfficiency(extendedSequence,
  baseBeforegRNA, featureWeightMatrix, gRNA.size = 20,
  enable.multicore = FALSE, n.cores.max = 6)
```

Arguments

- extendedSequence Sequences containing gRNA plus PAM plus flanking sequences. Each sequence should be long enough for building features specified in the featureWeightMatrix
- baseBeforegRNA Number of bases before gRNA used for calculating gRNA efficiency, default 4
- featureWeightMatrix a data frame with the first column containing significant features and the second column containing the weight of corresponding features. In the following example, DoenchNBT2014 weight matrix is used. Briefly, features include INTERCEPT,GC_LOW (penalty for low GC content in the gRNA sequence), GC_HIGH (penalty for high GC content in the gRNA sequence), G02 (means G at second position of the extendedSequence), GT02 (means GT di-nucleotides starting at 2nd position of the extendedSequence). To understand how is the feature weight matrix is identified, or how to use alternative feature weight matrix file, please see Doench et al., 2014 for details.
- gRNA.size The size of the gRNA, default 20

enable.multicore	Indicate whether enable parallel processing, default FALSE. For super long sequences with lots of gRNAs, suggest set it to TRUE
n.cores.max	Indicating maximum number of cores to use in multi core mode, i.e., parallel processing, default 6. Please set it to 1 to disable multicore processing for small dataset.

Value

DNAStrngSet consists of potential gRNAs that can be input to filtergRNAs function directly

Author(s)

Lihua Julie Zhu

References

Doench JG, Hartenian E, Graham DB, Tothova Z, Hegde M, Smith I, Sullender M, Ebert BL, Xavier RJ, Root DE. Rational design of highly active sgRNAs for CRISPR-Cas9-mediated gene inactivation. Nat Biotechnol. 2014 Sep 3. doi: 10.1038/nbt.3026 <http://www.broadinstitute.org/rnai/public/analysis-tools/sgrna-design>

See Also

offTargetAnalysis

Examples

```

extendedSequence <- c("TGGATTGTATAATCAGCATGGATTGGAAC",
  "TCAACGAGGATATTCTCAGGCTTCAGGTCC",
  "GTTACCTGAATTTGACCTGCTCGGAGGTAA",
  "CTTGGTGTGGCTTCCTTTAAGACATGGAGC",
  "CATACAGGCATTGAAGAAGAATTTAGGCCT",
  "AGTACTATACATTTGGCTTAGATTTGGCGG",
  "TTTTCCAGATAGCCGATCTTGGTGTGGCTT",
  "AAGAAGGGAATTCGCTGGTGATGGAGT"
)
featureWeightMatrixFile <- system.file("extdata", "DoenchNBT2014.csv",
  package = "CRISPRseek")
featureWeightMatrix <- read.csv(featureWeightMatrixFile, header=TRUE)
calculategRNAEfficiency(extendedSequence, baseBeforegRNA = 4,
  featureWeightMatrix, gRNA.size = 20)

```

compare2Sequences	<i>Compare 2 input sequences/sequence sets for possible guide RNAs (gRNAs)</i>
-------------------	--

Description

Generate all possible guide RNAs (gRNAs) for two input sequences, or two sets of sequences and generate scores for potential off-targets in the other sequence.

Usage

```

compare2Sequences(inputFile1Path, inputFile2Path,
  inputNames=c("Seq1", "Seq2"),
  format = c("fasta", "fasta"), header=FALSE, findgRNAsWithREcutOnly = FALSE,
  searchDirection=c("both", "1to2", "2to1"), BSgenomeName,
  REpatternFile=system.file("extdata", "NEBenzymes.fa", package = "CRISPRseek"),
  minREpatternSize = 6, findgRNAs = c(TRUE, TRUE), removegRNADetails = c(FALSE, FALSE),
  exportAllgRNAs = c("no", "all", "fasta", "genbank"), annotatePaired = FALSE,
  overlap.gRNA.positions = c(17, 18), findPairedgRNAOnly = FALSE,
  min.gap = 0, max.gap = 20, gRNA.name.prefix = "_gR", PAM.size = 3,
  gRNA.size = 20, PAM = "NGG", PAM.pattern = "N[A|G]G$",
  allowed.mismatch.PAM = 1, max.mismatch = 3,
  outputDir, upstream = 0, downstream = 0,
  weights = c(0, 0, 0.014, 0, 0, 0.395, 0.317, 0, 0.389, 0.079, 0.445,
  0.508, 0.613, 0.851, 0.732, 0.828, 0.615, 0.804, 0.685, 0.583),
  overwrite = FALSE, baseBeforegRNA = 4,
  baseAfterPAM = 3, featureWeightMatrixFile = system.file("extdata",
  "DoenchNBT2014.csv", package = "CRISPRseek"), foldgRNAs = FALSE,
  gRNA.backbone="GUUUUAGAGCUAGAAAUAGCAAGUUAUUAAUAAGGCUAGUCGUAUCAACUUGAAAAAGUGGCACCGAGUCGGUGCUU
  temperature = 37,
  scoring.method = c("Hsu-Zhang", "CFDscore"),
  subPAM.activity = hash( AA = 0,
    AC = 0,
    AG = 0.259259259,
    AT = 0,
    CA = 0,
    CC = 0,
    CG = 0.107142857,
    CT = 0,
    GA = 0.069444444,
    GC = 0.022222222,
    GG = 1,
    GT = 0.016129032,
    TA = 0,
    TC = 0,
    TG = 0.038961039,
    TT = 0),
  subPAM.position = c(22, 23),
  PAM.location = "3prime",
  mismatch.activity.file = system.file("extdata",
  "NatureBiot2016SuppTable19DoenchRoot.csv",
  package = "CRISPRseek")
)

```

Arguments

<code>inputFile1Path</code>	Sequence input file 1 path that contains one of the two sequences to be searched for potential gRNAs
<code>inputFile2Path</code>	Sequence input file 2 path that contains one of the two sequences to be searched for potential gRNAs
<code>inputNames</code>	Name of the input sequences when <code>inputFile1Path</code> and <code>inputFile2Path</code> are DNAS-tringSet instead of file path

format	Format of the input files, fasta, fastq and bed format are supported, default fasta
header	Indicate whether the input file contains header, default FALSE, only applies to bed format
findgRNAsWithREcutOnly	Indicate whether to find gRNAs overlap with restriction enzyme recognition pattern
searchDirection	Indicate whether perform gRNA in both sequences and off-target search against each other (both) or search gRNA in input1 and off-target analysis in input2 (1to2), or vice versa (2to1)
BSgenomeName	BSgenome object. Please refer to available.genomes in BSgenome package. For example, BSgenome.Hsapiens.UCSC.hg19 for hg19, BSgenome.Mmusculus.UCSC.mm10 for mm10, BSgenome.Celegans.UCSC.ce6 for ce6, BSgenome.Rnorvegicus.UCSC.rn5 for rn5, BSgenome.Drerio.UCSC.danRer7 for Zv9, and BSgenome.Dmelanogaster.UCSC.dm3 for dm3
REpatternFile	File path containing restriction enzyme cut patterns
minREpatternSize	Minimum restriction enzyme recognition pattern length required for the enzyme pattern to be searched for, default 6
findgRNAs	Indicate whether to find gRNAs from the sequences in the input file or skip the step of finding gRNAs, default TRUE for both input sequences. Set it to FALSE if the input file contains user selected gRNAs plus PAM already.
removegRNADetails	Indicate whether to remove the detailed gRNA information such as efficacy file and restriction enzyme cut sites, default false for both input sequences. Set it to TRUE if the input file contains the user selected gRNAs plus PAM already.
exportAllgRNAs	Indicate whether to output all potential gRNAs to a file in fasta format, genbank format or both. Default to no.
annotatePaired	Indicate whether to output paired information, default to FALSE
overlap.gRNA.positions	The required overlap positions of gRNA and restriction enzyme cut site, default 17 and 18
findPairedgRNAOnly	Choose whether to only search for paired gRNAs in such an orientation that the first one is on minus strand called reverse gRNA and the second one is on plus strand called forward gRNA. TRUE or FALSE, default FALSE
min.gap	Minimum distance between two oppositely oriented gRNAs to be valid paired gRNAs. Default 0
max.gap	Maximum distance between two oppositely oriented gRNAs to be valid paired gRNAs. Default 20
gRNA.name.prefix	The prefix used when assign name to found gRNAs, default _gR, short for guided RNA.
PAM.size	PAM length, default 3
gRNA.size	The size of the gRNA, default 20
PAM	PAM sequence after the gRNA, default NGG
PAM.pattern	Regular expression of PAM, default N[AIG]G\$ for spCas9. For cpf1, ^TTTN since it is a 5 prime PAM sequence

allowed.mismatch.PAM	Maximum number of mismatches allowed to the PAM sequence, default to 1 for PAM.pattern N[AIG]G PAM
max.mismatch	Maximum mismatch allowed to search the off targets in the other sequence, default 3
outputDir	the directory where the sequence comparison results will be written to
upstream	upstream offset from the bed input starts to search for gRNA and/or offtargets, default 0
downstream	downstream offset from the bed input ends to search for gRNA and/or offtargets, default 0
weights	numeric vector size of gRNA length, default c(0, 0, 0.014, 0, 0, 0.395, 0.317, 0, 0.389, 0.079, 0.445, 0.508, 0.613, 0.851, 0.732, 0.828, 0.615, 0.804, 0.685, 0.583) which is used in Hsu et al., 2013 cited in the reference section
overwrite	overwrite the existing files in the output directory or not, default TRUE
baseBeforegRNA	Number of bases before gRNA used for calculating gRNA efficiency, default 4 Please note, for PAM located on the 5 prime, need to specify the number of bases before the PAM sequence plus PAM size.
baseAfterPAM	Number of bases after PAM used for calculating gRNA efficiency, default 3 for spCas9 Please note, for PAM located on the 5 prime, need to include the length of the gRNA plus the extended sequence on the 3 prime
featureWeightMatrixFile	Feature weight matrix file used for calculating gRNA efficiency. By default DoenchNBT2014 weight matrix is used. To use alternative weight matrix file, please input a csv file with first column containing significant features and the second column containing the corresponding weights for the features. Please see Doench et al., 2014 for details.
foldgRNAs	Default FALSE. If set to TRUE, summary file will contain minimum free energy of the secondary structure of gRNA with gRNA backbone from GeneRfold package provided that GeneRfold package has been installed.
gRNA.backbone	gRNA backbone constant region sequence. Default to the sequence in Sp gRNA backbone.
temperature	temperature in celsius. Default to 37 celsius.
scoring.method	Indicates which method to use for offtarget cleavage rate estimation, currently two methods are supported, Hsu-Zhang and CFDscore
subPAM.activity	Applicable only when scoring.method is set to CFDscore A hash to represent the cleavage rate for each alternative sub PAM sequence relative to preferred PAM sequence
subPAM.position	Applicable only when scoring.method is set to CFDscore The start and end positions of the sub PAM. Default to 22 and 23 for SP with 20bp gRNA and NGG as preferred PAM
PAM.location	PAM location relative to gRNA. For example, spCas9 PAM is located on the 3 prime (3prime) while cpf1 PAM is located on the 5 prime (5prime)
mismatch.activity.file	Applicable only when scoring.method is set to CFDscore A comma separated (csv) file containing the cleavage rates for all possible types of single nucleotide mismatches at each position of the gRNA. By default, using the supplemental Table 19 from Doench et al., Nature Biotechnology 2016

Value

Return a data frame with all potential gRNAs from both sequences. In addition, a tab delimited file scoresFor2InputSequences.xls is also saved in the outputDir, sorted by scoreDiff descending.

name	name of the gRNA
gRNAPlusPAM	gRNA plus PAM sequence
targetInSeq1	target/off-target sequence including PAM in the 1st input sequence file
targetInSeq2	target/off-target sequence including PAM in the 2nd input sequence file
guideAlignment2Offtarget	alignment of gRNA to the other input sequence (off-target sequence)
offTargetStrand	strand of the other sequence (off-target sequence) the gRNA align to
scoreForSeq1	score for the target sequence in the 1st input sequence file
scoreForSeq2	score for the target sequence in the 1st input sequence file
mismatch.distance2PAM	distances of mismatch to PAM, e.g., 14 means the mismatch is 14 bp away from PAM
n.mismatch	number of mismatches between the off-target and the gRNA
targetSeqName	the name of the input sequence where the target sequence is located
scoreDiff	scoreForSeq1 - scoreForSeq2
bracket.notation	folded gRNA in bracket notation
mfe.sgRNA	minimum free energy of sgRNA
mfe.diff	mfe.sgRNA-mfe.backbone
mfe.backbone	minimum free energy of the gRNA backbone by itself

Author(s)

Lihua Julie Zhu

References

Patrick D Hsu, David A Scott, Joshua A Weinstein, F Ann Ran, Silvana Konermann, Vineeta Agarwala, Yinqing Li, Eli J Fine, Xuebing Wu, Ophir Shalem, Thomas J Cradick, Luciano A Marraffini, Gang Bao & Feng Zhang (2013) DNA targeting specificity of rNA-guided Cas9 nucleases. Nature Biotechnology 31:827-834

See Also

CRISPRseek

Examples

```
library(CRISPRseek)
inputFile1Path <- system.file("extdata", "rs362331T.fa",
                             package = "CRISPRseek")
inputFile2Path <- system.file("extdata", "rs362331C.fa",
                             package = "CRISPRseek")
REpatternFile <- system.file("extdata", "NEBenzymes.fa",
```

```

package = "CRISPRseek")
seqs <- compare2Sequences(inputFile1Path, inputFile2Path,
  outputDir = getwd(),
  REpatternFile = REpatternFile, overwrite = TRUE)
inputFile1Path <- DNASTringSet("TAATATTTTAAAATCGGTGACGTGGGCCCAAAACGAGTGCAGTTCCAAAGGCACCCACCTGTGGCAG")
names(inputFile1Path) <- "seq1"

inputFile2Path <- DNASTringSet("TAATATTTTAAAATCGGTGACGTGGGCCCAAAACGAGTGCAGTTCCAAAGGCACCCACCTGTGGCAG")
names(inputFile2Path) <- "seq2"

seqs <- compare2Sequences(inputFile1Path, inputFile2Path,
  inputNames=c("Seq1", "Seq2"),
  scoring.method = "CFDscore",
  outputDir = getwd(),
  overwrite = TRUE)

```

filtergRNAs

Filter gRNAs

Description

Filter gRNAs containing restriction enzyme cut site

Usage

```

filtergRNAs(all.gRNAs, pairOutputFile = "",
  findgRNAsWithREcutOnly = FALSE,
  REpatternFile = system.file("extdata", "NEBenzymes.fa",
    package = "CRISPRseek"), format = "fasta",
  minREpatternSize = 4, overlap.gRNA.positions = c(17, 18), overlap.allpos = TRUE)

```

Arguments

all.gRNAs	gRNAs as DNASTringSet, such as the output from findgRNAs
pairOutputFile	File path with paired gRNAs
findgRNAsWithREcutOnly	Indicate whether to find gRNAs overlap with restriction enzyme recognition pattern
REpatternFile	File path containing restriction enzyme cut patterns
format	Format of the REpatternFile, default as fasta
minREpatternSize	Minimum restriction enzyme recognition pattern length required for the enzyme pattern to be searched for, default 4
overlap.gRNA.positions	The required overlap positions of gRNA and restriction enzyme cut site, default 17 and 18
overlap.allpos	Default TRUE, meaning that only gRNAs overlap with all the positions are retained FALSE, meaning that gRNAs overlap with one or both of the positions are retained

Value

gRNAs.withRE gRNAs as DNASTringSet that passed the filter criteria
 gRNAREcutDetails
 a data frame that contains a set of gRNAs annotated with restriction enzyme cut details

Author(s)

Lihua Julie Zhu

See Also

offTargetAnalysis

Examples

```
all.gRNAs <- findgRNAs(
  inputFilePath = system.file("extdata", "inputseq.fa",
  package = "CRISPRseek"),
  pairOutputFile = "testpairedgRNAs.xls",
  findPairedgRNAOnly = TRUE)

gRNAs.RE <- filtergRNAs(all.gRNAs = all.gRNAs,
  pairOutputFile = "testpairedgRNAs.xls", minREpatternSize = 6,
  REpatternFile = system.file("extdata", "NEBenzymes.fa",
  package = "CRISPRseek"), overlap.allpos = TRUE)

gRNAs <- gRNAs.RE$gRNAs.withRE
restriction.enzyme.cut.sites <- gRNAs.RE$gRNAREcutDetails
```

filterOffTarget *filter off targets and generate reports.*

Description

filter off targets that meet the criteria set by users such as minimum score, topN. In addition, off target was annotated with flank sequence, gRNA cleavage efficiency and whether it is inside an exon or not if fetchSequence is set to TRUE and annotateExon is set to TRUE

Usage

```
filterOffTarget(scores, min.score = 0.5, topN = 100,
  topN.OfftargetTotalScore = 10,
  annotateExon = TRUE, txdb, orgAnn, outputDir, oneFilePergRNA = FALSE,
  fetchSequence = TRUE, upstream = 200, downstream = 200, BSgenomeName,
  baseBeforegRNA = 4, baseAfterPAM = 3,
  featureWeightMatrixFile = system.file("extdata", "DoenchNBT2014.csv",
  package = "CRISPRseek"))
```

Arguments

scores	a data frame output from getOfftargetScore. It contains strand (strand of the off target, + for plus and - for minus strand), chrom (chromosome of the off target), chromStart (start position of the off target), chromEnd (end position of the off target), name (gRNA name), gRNAPlusPAM (gRNA sequence with PAM sequence concatenated), OffTargetSequence (the genomic sequence of the off target), n.mismatch (number of mismatches between the off target and the gRNA), forViewInUCSC (string for viewing in UCSC genome browser, e.g., chr14:31665685-31665707), score (score of the off target), mismatch.distance.2PAM (a comma separated distances of all mismatches to PAM, e.g., 14,11 means one mismatch is 14 bp away from PAM and the other mismatch is 11 bp away from PAM), alignment (alignment between gRNA and off target, e.g.,G..C..... means that this off target aligns with gRNA except that G and C are mismatches), NGG (this off target contains canonical PAM or not, 1 for yes and 0 for no) mean.neighbor.distance.mismatch (mean distance between neighboring mismatches)
min.score	minimum score of an off target to included in the final output, default 0.5
topN	top N off targets to be included in the final output, default 100
topN.OfftargetTotalScore	top N off target used to calculate the total off target score, default 10
annotateExon	Choose whether or not to indicate whether the off target is inside an exon or not, default TRUE
txdb	TxDb object, for creating and using TxDb object, please refer to GenomicFeatures package. For a list of existing TxDb object, please search for annotation package starting with TxDb at http://www.bioconductor.org/packages/release/BiocViews.html#___Annotation such as TxDb.Rnorvegicus.UCSC.rn5.refGene for rat, TxDb.Mmusculus.UCSC.mm10.knownGene for mouse, TxDb.Hsapiens.UCSC.hg19.knownGene for human, TxDb.Dmelanogaster.UCSC.dm3.ensGene for Drosophila and TxDb.Celegans.UCSC.ce6.ensGene for C.elegans
orgAnn	organism annotation mapping such as org.Hs.egSYMBOL in org.Hs.eg.db package for human
outputDir	the directory where the off target analysis and reports will be written to
oneFilePerGRNA	write to one file for each gRNA or not, default to FALSE
fetchSequence	Fetch flank sequence of off target or not, default TRUE
upstream	upstream offset from the off target start, default 200
downstream	downstream offset from the off target end, default 200
BSgenomeName	BSgenome object. Please refer to available.genomes in BSgenome package. For example, BSgenome.Hsapiens.UCSC.hg19 for hg19, BSgenome.Mmusculus.UCSC.mm10 for mm10, BSgenome.Celegans.UCSC.ce6 for ce6, BSgenome.Rnorvegicus.UCSC.rn5 for rn5, and BSgenome.Dmelanogaster.UCSC.dm3 for dm3
baseBeforegRNA	Number of bases before gRNA used for calculating gRNA efficiency, default 4
baseAfterPAM	Number of bases after PAM used for calculating gRNA efficiency, default 3
featureWeightMatrixFile	Feature weight matrix file used for calculating gRNA efficiency. By default DoenchNBT2014 weight matrix is used. To use alternative weight matrix file, please input a csv file with first column containing significant features and the second column containing the corresponding weights for the features. Please see Doench et al., 2014 for details.

Value

offtargets	a data frame with off target analysis results
summary	a data frame with summary of the off target analysis results

Author(s)

Lihua Julie Zhu

References

Doench JG, Hartenian E, Graham DB, Tothova Z, Hegde M, Smith I, Sullender M, Ebert BL, Xavier RJ, Root DE. Rational design of highly active sgRNAs for CRISPR-Cas9-mediated gene inactivation. Nat Biotechnol. 2014 Sep 3. doi: 10.1038 nbt.3026 Lihua Julie Zhu, Benjamin R. Holmes, Neil Aronin and Michael Brodsky. CRISPRseek: a Bioconductor package to identify target-specific guide RNAs for CRISPR-Cas9 genome-editing systems. Plos One Sept 23rd 2014

See Also

offTargetAnalysis

Examples

```
library(CRISPRseek)
library("BSgenome.Hsapiens.UCSC.hg19")
library(TxDb.Hsapiens.UCSC.hg19.knownGene)
library(org.Hs.eg.db)
hitsFile <- system.file("extdata", "hits.txt", package="CRISPRseek")
hits <- read.table(hitsFile, sep = "\t", header = TRUE,
  stringsAsFactors = FALSE)
featureVectors <- buildFeatureVectorForScoring(hits)
scores <- getOfftargetScore(featureVectors)
outputDir <- getwd()
results <- filterOffTarget(scores, BSgenomeName = Hsapiens,
  txdb = TxDb.Hsapiens.UCSC.hg19.knownGene,
  orgAnn = org.Hs.egSYMBOL, outputDir = outputDir,
  min.score = 0.1, topN = 10, topN.OfftargetTotalScore = 5)
results$offtargets
results$summary
```

findgRNAs

Find potential gRNAs

Description

Find potential gRNAs for an input file containing sequences in fasta format

Usage

```
findgRNAs(inputFilePath, format = "fasta", PAM = "NGG", PAM.size = 3,
  findPairedgRNAOnly = FALSE, annotatePaired = TRUE, enable.multicore = FALSE,
  n.cores.max = 6, gRNA.pattern = "", gRNA.size = 20,
  overlap.gRNA.positions = c(17,18), min.gap = 0, max.gap = 20,
  pairOutputFile, name.prefix = "", featureWeightMatrixFile = system.file("extdata",
    "DoenchNBT2014.csv", package = "CRISPRseek"), baseBeforegRNA = 4,
  baseAfterPAM = 3, calculategRNAEfficacy = FALSE, efficacyFile,
  PAM.location = "3prime")
```

Arguments

<code>inputFilePath</code>	Sequence input file path or a DNASTringSet object that contains sequences to be searched for potential gRNAs
<code>format</code>	Format of the input file, fasta and fastq are supported, default fasta
<code>PAM</code>	protospacer-adjacent motif (PAM) sequence after the gRNA, default NGG
<code>PAM.size</code>	PAM length, default 3
<code>findPairedgRNAOnly</code>	Choose whether to only search for paired gRNAs in such an orientation that the first one is on minus strand called reverse gRNA and the second one is on plus strand called forward gRNA. TRUE or FALSE, default FALSE
<code>annotatePaired</code>	Indicate whether to output paired information, default TRUE
<code>enable.multicore</code>	Indicate whether enable parallel processing, default FALSE. For super long sequences with lots of gRNAs, suggest set it to TRUE
<code>n.cores.max</code>	Indicating maximum number of cores to use in multi core mode, i.e., parallel processing, default 6. Please set it to 1 to disable multicore processing for small dataset.
<code>gRNA.pattern</code>	Regular expression or IUPAC Extended Genetic Alphabet to represent gRNA pattern, default is no restriction. To specify that the gRNA must start with GG for example, then set it to ^GG. Please see help(translatePattern) for a list of IUPAC Extended Genetic Alphabet.
<code>gRNA.size</code>	The size of the gRNA, default 20
<code>overlap.gRNA.positions</code>	The required overlap positions of gRNA and restriction enzyme cut site, default 17 and 18
<code>min.gap</code>	Minimum distance between two oppositely oriented gRNAs to be valid paired gRNAs. Default 0
<code>max.gap</code>	Maximum distance between two oppositely oriented gRNAs to be valid paired gRNAs. Default 20
<code>pairOutputFile</code>	The output file for writing paired gRNA information to
<code>name.prefix</code>	The prefix used when assign name to found gRNAs, default gRNA, short for guided RNA.
<code>baseBeforegRNA</code>	Number of bases before gRNA used for calculating gRNA efficiency, default 4 for spCas9 Please note, for PAM located on the 5 prime, need to specify the number of bases before the PAM sequence plus PAM size.

baseAfterPAM	Number of bases after PAM used for calculating gRNA efficiency, default 3 for spCas9 Please note, for PAM located on the 5 prime, need to include the length of the gRNA plus the extended sequence on the 3 prime
featureWeightMatrixFile	Feature weight matrix file used for calculating gRNA efficiency. By default DoenchNBT2014 weight matrix is used. To use alternative weight matrix file, please input a csv file with first column containing significant features and the second column containing the corresponding weights for the features. Please see Doench et al., 2014 for details.
calculategRNAEfficacy	Default to FALSE, not to calculate gRNA efficacy
efficacyFile	File path to write gRNA efficacies
PAM.location	PAM location relative to gRNA. For example, spCas9 PAM is located on the 3 prime while cpf1 PAM is located on the 5 prime

Details

If users already has a fasta file that contains a set of potential gRNAs, then users can call filtergRNAs directly although the easiest way is to call the one-stop-shopping function OffTargetAnalysis with findgRNAs set to FALSE.

Value

DNAStrngSet consists of potential gRNAs that can be input to filtergRNAs function directly

Note

If the input sequence file contains multiple >300 bp sequences, suggest create one input file for each sequence and run the OffTargetAnalysis separately.

Author(s)

Lihua Julie Zhu

See Also

offTargetAnalysis

Examples

```
findgRNAs(inputFilePath = system.file("extdata",
  "inputseq.fa", package = "CRISPRseek"),
  pairOutputFile = "testpairedgRNAs.xls",
  findPairedgRNAOnly = TRUE)
findgRNAs(inputFilePath = system.file("extdata",
  "cpf1.fa", package = "CRISPRseek"),
  findPairedgRNAOnly=FALSE,
  pairOutputFile = "testpairedgRNAs-cpf1.xls",
  PAM="TTTN", PAM.location = "5prime", PAM.size = 4,
  overlap.gRNA.positions = c(19,23),
  baseBeforegRNA = 8, baseAfterPAM = 23,
  calculategRNAEfficacy= TRUE,
  featureWeightMatrixFile = system.file("extdata",
  "DoenchNBT2014.csv", package = "CRISPRseek"),
```

```
efficacyFile = "testcpf1Efficacy.xls")
```

 foldgRNAs

Fold gRNAs with the gRNA backbone constant region

Description

Fold gRNAs with the gRNA backbone constant region and output minimum free energy and the folded structure in bracket notation using GeneRfold package

Usage

```
foldgRNAs(gRNAs.withoutPAM,
  gRNA.backbone="GUUUUAGAGCUAGAAUAGCAAGUUAAAAUAAGGCUAGUCCGUUAUCAACUUGAAAAAGUGGCACCGAGUCGGUGCUU
  temperature = 37)
```

Arguments

gRNAs.withoutPAM	gRNAs as character, without PAM sequence.
gRNA.backbone	gRNA backbone constant region sequence. Default to the sequence in Sp gRNA backbone.
temperature	temperature in celsius. Default to 37 celsius.

Value

a data frame that contains a set of gRNAs annotated with bracket.notation (folded sgRNA in bracket notation), mfe.sgRNA (minimum free energy of sgRNA:gRNA plus backbone), mfe.diff (mfe.sgRNA-mfe.backbone), mfe.backbone (minimum free energy of the gRNA backbone by itself).

Author(s)

Lihua Julie Zhu

See Also

offTargetAnalysis

Examples

```
gRNAs.withoutPAM <- c("AACCTTGGGGTTACTGAAAG", "ATCCTGGAGCTTAGTCATAG")
mfe <- foldgRNAs(gRNAs.withoutPAM)
```

getOfftargetScore *Calculate score for each off target*

Description

Calculate score for each off target with given feature vectors and weights vector

Usage

```
getOfftargetScore(featureVectors,
  weights = c(0, 0, 0.014, 0, 0, 0.395, 0.317, 0, 0.389, 0.079, 0.445, 0.508,
  0.613, 0.851, 0.732, 0.828, 0.615, 0.804, 0.685, 0.583))
```

Arguments

featureVectors a data frame generated from `buildFeatureVectorForScoring`. It contains `IsMismatch.posX` (Indicator variable indicating whether this position X is mismatch or not, 1 means yes and 0 means not, $X = 1 - \text{gRNA.size}$) representing all positions in the gRNA), `strand` (strand of the off target, + for plus and - for minus strand), `chrom` (chromosome of the off target), `chromStart` (start position of the off target), `chromEnd` (end position of the off target), `name` (gRNA name), `gRNAPlusPAM` (gRNA sequence with PAM sequence concatenated), `OffTargetSequence` (the genomic sequence of the off target), `n.mismatch` (number of mismatches between the off target and the gRNA), `forViewInUCSC` (string for viewing in UCSC genome browser, e.g., `chr14:31665685-31665707`), `score` (score of the off target), `mismatch.distance2PAM` (a comma separated distances of all mismatches to PAM, e.g., `14,11` means one mismatch is 14 bp away from PAM and the other mismatch is 11 bp away from PAM), `alignment` (alignment between gRNA and off target, e.g., `.....G..C.....` means that this off target aligns with gRNA except that G and C are mismatches), `NGG` (this off target contains canonical PAM or not, 1 for yes and 0 for no), `mean.neighbor.distance.mismatch` (mean distance between neighboring mismatches)

weights a numeric vector size of gRNA length, default `c(0, 0, 0.014, 0, 0, 0.395, 0.317, 0, 0.389, 0.079, 0.445, 0.508, 0.613, 0.851, 0.732, 0.828, 0.615, 0.804, 0.685, 0.583)` which is used in Hsu et al., 2013 cited in the reference section

Details

score is calculated using the weights and algorithm by Hsu et al., 2013 cited in the reference section

Value

a data frame containing `strand` (strand of the match, + for plus and - for minus strand), `chrom` (chromosome of the off target), `chromStart` (start position of the off target), `chromEnd` (end position of the off target), `name` (gRNA name), `gRNAPlusPAM` (gRNA sequence with PAM sequence concatenated), `OffTargetSequence` (the genomic sequence of the off target), `n.mismatch` (number of mismatches between the off target and the gRNA), `forViewInUCSC` (string for viewing in UCSC genome browser, e.g., `chr14:31665685-31665707`), `score` (score of the off target), `mismatch.distance2PAM` (a comma separated distances of all mismatches to PAM, e.g., `14,11` means one mismatch is 14 bp away from PAM and the other mismatch is 11 bp away from PAM), `alignment` (alignment between gRNA and off target, e.g., `.....G..C.....` means that this off target aligns

with gRNA except that G and C are mismatches), NGG (this off target contains canonical PAM or not, 1 for yes and 0 for no) mean.neighbor.distance.mismatch (mean distance between neighboring mismatches)

Author(s)

Lihua Julie Zhu

References

Patrick D Hsu, David A Scott, Joshua A Weinstein, F Ann Ran, Silvana Konermann, Vineeta Agarwala, Yinqing Li, Eli J Fine, Xuebing Wu, Ophir Shalem, Thomas J Cradick, Luciano A Marraffini, Gang Bao & Feng Zhang (2013) DNA targeting specificity of rNA-guided Cas9 nucleases. Nature Biotechnology 31:827-834

See Also

offTargetAnalysis

Examples

```
hitsFile <- system.file("extdata", "hits.txt",
  package = "CRISPRseek")
hits <- read.table(hitsFile, sep = "\t", header = TRUE,
  stringsAsFactors = FALSE)
featureVectors <- buildFeatureVectorForScoring(hits)
getOfftargetScore(featureVectors)
```

isPatternUnique

Output whether the input patterns occurs only once in the sequence

Description

Input a sequence and a list of patterns and determine if the patterns occurs only once in the sequence. Used for determining whether a RE site in gRNA also occurs in the flanking region.

Usage

```
isPatternUnique(seq, patterns)
```

Arguments

seq	flanking sequence of a gRNA
patterns	patterns as DNASTringSet, such as a list of RE sites

Value

returns a character vectors containing the uniqueness of each pattern/RE site

Author(s)

Lihua Julie Zhu

Examples

```
seq <- "TGGATTGTATAATCAGCATGGATTTGGAAC"
patterns <- DNASTringSet(c("TGG", "TGA", "TGGATA", "TTGGAAC", ""))
isPatternUnique(seq, patterns)
isPatternUnique(seq)
isPatternUnique(patterns)
```

offTargetAnalysis	<i>Design of target-specific guide RNAs for CRISPR-Cas9 system in one function</i>
-------------------	--

Description

Design of target-specific guide RNAs (gRNAs) for CRISPR-Cas9 system by automatically calling findgRNAs, filtergRNAs, searchHits, buildFeatureVectorForScoring, getOfftargetScore, filterOfftarget, calculating gRNA cleavage efficiency and generate reports.

Usage

```
offTargetAnalysis(inputFilePath, format = "fasta", header = FALSE,
  gRNAoutputName, findgRNAs = TRUE,
  exportAllgRNAs = c("all", "fasta", "genbank", "no"),
  findgRNAsWithREcutOnly = FALSE,
  REpatternFile = system.file("extdata", "NEBenzymes.fa",
    package = "CRISPRseek"), minREpatternSize = 4,
  overlap.gRNA.positions = c(17, 18), findPairedgRNAOnly = FALSE,
  annotatePaired = TRUE, enable.multicore = FALSE, n.cores.max = 6,
  min.gap = 0, max.gap = 20, gRNA.name.prefix = "", PAM.size = 3,
  gRNA.size = 20, PAM = "NGG", BSgenomeName, chromToSearch = "all",
  chromToExclude = c("chr17_ctg5_hap1", "chr4_ctg9_hap1", "chr6_apd_hap1",
"chr6_cox_hap2", "chr6_dbb_hap3", "chr6_mann_hap4", "chr6_mcf_hap5", "chr6_qbl_hap6",
"chr6_ssto_hap7"),
  max.mismatch = 3, PAM.pattern = "N[A|G]G$", allowed.mismatch.PAM = 1,
  gRNA.pattern = "", min.score = 0, topN = 1000,
  topN.OfftargetTotalScore = 10, annotateExon = TRUE,
  txdb, orgAnn, outputDir, fetchSequence = TRUE, upstream = 200, downstream = 200,
  upstream.search = 0, downstream.search = 0,
  weights = c(0, 0, 0.014, 0, 0, 0.395, 0.317, 0, 0.389, 0.079, 0.445, 0.508,
0.613, 0.851, 0.732, 0.828, 0.615, 0.804, 0.685, 0.583),
  baseBeforegRNA = 4, baseAfterPAM = 3,
  featureWeightMatrixFile = system.file("extdata", "DoenchNBT2014.csv",
package = "CRISPRseek"), useScore = TRUE, useEfficacyFromInputSeq = FALSE,
  outputUniqueREs = TRUE, foldgRNAs = FALSE,
  gRNA.backbone="GUUUUAGAGCUAGAAAUAGCAAGUUAAAUAAGGCUAGUCCGUUAUCAACUUGAAAAAGUGGCACCGAGUCGGUGCU
  temperature = 37,
  overwrite = FALSE,
  scoring.method = c("Hsu-Zhang", "CFDscore"),
  subPAM.activity = hash( AA = 0,
    AC = 0,
    AG = 0.259259259,
    AT = 0,
```

```

    CA = 0,
    CC = 0,
    CG = 0.107142857,
    CT = 0,
    GA = 0.069444444,
    GC = 0.022222222,
    GG = 1,
    GT = 0.016129032,
    TA = 0,
    TC = 0,
    TG = 0.038961039,
    TT = 0),
  subPAM.position = c(22, 23),
  PAM.location = "3prime",
  mismatch.activity.file = system.file("extdata",
    "NatureBiot2016SuppTable19DoenchRoot.csv",
    package = "CRISPRseek")
)

```

Arguments

inputFilePath	Sequence input file path or a DNASTringSet object that contains sequences to be searched for potential gRNAs
format	Format of the input file, fasta, fastq and bed are supported, default fasta
header	Indicate whether the input file contains header, default FALSE, only applies to bed format
gRNAoutputName	Specify the name of the gRNA output file when inputFilePath is DNASTringSet object instead of file path
findgRNAs	Indicate whether to find gRNAs from the sequences in the input file or skip the step of finding gRNAs, default TRUE. Set it to FALSE if the input file contains user selected gRNAs plus PAM already.
exportAllgRNAs	Indicate whether to output all potential gRNAs to a file in fasta format, genbank format or both. Default to both.
findgRNAsWithREcutOnly	Indicate whether to find gRNAs overlap with restriction enzyme recognition pattern
REpatternFile	File path containing restriction enzyme cut patterns
minREpatternSize	Minimum restriction enzyme recognition pattern length required for the enzyme pattern to be searched for, default 4
overlap.gRNA.positions	The required overlap positions of gRNA and restriction enzyme cut site, default 17 and 18
findPairedgRNAOnly	Choose whether to only search for paired gRNAs in such an orientation that the first one is on minus strand called reverse gRNA and the second one is on plus strand called forward gRNA. TRUE or FALSE, default FALSE
annotatePaired	Indicate whether to output paired information, default TRUE
min.gap	Minimum distance between two oppositely oriented gRNAs to be valid paired gRNAs. Default 0

enable.multicore	Indicate whether enable parallel processing, default FALSE. For super long sequences with lots of gRNAs, suggest set it to TRUE
n.cores.max	Indicating maximum number of cores to use in multi core mode, i.e., parallel processing, default 6. Please set it to 1 to disable multicore processing for small dataset.
max.gap	Maximum distance between two oppositely oriented gRNAs to be valid paired gRNAs. Default 20
gRNA.name.prefix	The prefix used when assign name to found gRNAs, default gRNA, short for guided RNA.
PAM.size	PAM length, default 3
gRNA.size	The size of the gRNA, default 20
PAM	PAM sequence after the gRNA, default NGG
BSgenomeName	BSgenome object. Please refer to available.genomes in BSgenome package. For example, BSgenome.Hsapiens.UCSC.hg19 for hg19, BSgenome.Mmusculus.UCSC.mm10 for mm10, BSgenome.Celegans.UCSC.ce6 for ce6, BSgenome.Rnorvegicus.UCSC.rm5 for rm5, BSgenome.Drerio.UCSC.danRer7 for Zv9, and BSgenome.Dmelanogaster.UCSC.dm3 for dm3
chromToSearch	Specify the chromosome to search, default to all, meaning search all chromosomes. For example, chrX indicates searching for matching in chromosome X only
chromToExclude	Specify the chromosome not to search. If specified as "", meaning to search chromosomes specified by chromToSearch. By default, to exclude haplotype blocks from offtarget search in hg19, i.e., chromToExclude = c("chr17_ctg5_hap1", "chr4_ctg9_hap1", "chr6_apd_hap1", "chr6_cox_hap2", "chr6_dbb_hap3", "chr6_mann_hap4", "chr6_mcf_hap5", "chr6_ssto_hap7")
max.mismatch	Maximum mismatch allowed in off target search, default 3. Warning: will be considerably slower if set > 3
PAM.pattern	Regular expression of protospacer-adjacent motif (PAM), default N[AIG]G\$ for spCas9. For cpf1, ^TTTN since it is a 5 prime PAM sequence
allowed.mismatch.PAM	Maximum number of mismatches allowed in the PAM sequence, default to 1 for N[AIG]G PAM pattern
gRNA.pattern	Regular expression or IUPAC Extended Genetic Alphabet to represent gRNA pattern, default is no restriction. To specify that the gRNA must start with GG for example, then set it to ^GG. Please see help(translatePattern) for a list of IUPAC Extended Genetic Alphabet.
min.score	minimum score of an off target to included in the final output, default 0
topN	top N off targets to be included in the final output, default 1000
topN.OfftargetTotalScore	top N off target used to calculate the total off target score, default 10
annotateExon	Choose whether or not to indicate whether the off target is inside an exon or not, default TRUE
txdb	TxDb object, for creating and using TxDb object, please refer to GenomicFeatures package. For a list of existing TxDb object, please search for annotation package starting with Txdb at http://www.bioconductor.org/packages/release/BiocViews.html#___An

	such as TxDb.Rnorvegicus.UCSC.rn5.refGene for rat, TxDb.Mmusculus.UCSC.mm10.knownGene for mouse, TxDb.Hsapiens.UCSC.hg19.knownGene for human, TxDb.Dmelanogaster.UCSC.dm3.ensGene for Drosophila and TxDb.Celegans.UCSC.ce6.ensGene for C.elegans
orgAnn	organism annotation mapping such as org.Hs.egSYMBOL in org.Hs.eg.db package for human
outputDir	the directory where the off target analysis and reports will be written to
fetchSequence	Fetch flank sequence of off target or not, default TRUE
upstream	upstream offset from the off target start, default 200
downstream	downstream offset from the off target end, default 200
upstream.search	upstream offset from the bed input starts to search for gRNAs, default 0
downstream.search	downstream offset from the bed input ends to search for gRNAs, default 0
weights	Applicable only when scoring.method is set to Hsu-Zhang a numeric vector size of gRNA length, default c(0, 0, 0.014, 0, 0, 0.395, 0.317, 0, 0.389, 0.079, 0.445, 0.508, 0.613, 0.851, 0.732, 0.828, 0.615, 0.804, 0.685, 0.583) which is used in Hsu et al., 2013 cited in the reference section
baseBeforegRNA	Number of bases before gRNA used for calculating gRNA efficiency, default 4 Please note, for PAM located on the 5 prime, need to specify the number of bases before the PAM sequence plus PAM size.
baseAfterPAM	Number of bases after PAM used for calculating gRNA efficiency, default 3 for spCas9 Please note, for PAM located on the 5 prime, need to include the length of the gRNA plus the extended sequence on the 3 prime
featureWeightMatrixFile	Feature weight matrix file used for calculating gRNA efficiency. By default DoenchNBT2014 weight matrix is used. To use alternative weight matrix file, please input a csv file with first column containing significant features and the second column containing the corresponding weights for the features. Please see Doench et al., 2014 for details.
useScore	Default TRUE, display in gray scale with the darkness indicating the gRNA efficacy. The taller bar shows the Cas9 cutting site. If set to False, efficacy will not show. Instead, gRNAs in plus strand will be colored red and gRNAs in negative strand will be colored green.
useEfficacyFromInputSeq	Default FALSE. If set to TRUE, summary file will contain gRNA efficacy calculated from input sequences instead of from off-target analysis. Set it to TRUE if the input sequence is from a different species than the one used for off-target analysis.
outputUniqueREs	Default TRUE. If set to TRUE, summary file will contain REs unique to the cleavage site within 100 or 200 bases surrounding the gRNA sequence.
foldgRNAs	Default FALSE. If set to TRUE, summary file will contain minimum free energy of the secondary structure of gRNA with gRNA backbone from GeneRfold package provided that GeneRfold package has been installed.
gRNA.backbone	gRNA backbone constant region sequence. Default to the sequence in Sp gRNA backbone.
temperature	temperature in celsius. Default to 37 celsius.
overwrite	overwrite the existing files in the output directory or not, default FALSE

scoring.method	Indicates which method to use for offtarget cleavage rate estimation, currently two methods are supported, Hsu-Zhang and CFDscore
subPAM.activity	Applicable only when scoring.method is set to CFDscore A hash to represent the cleavage rate for each alternative sub PAM sequence relative to preferred PAM sequence
subPAM.position	Applicable only when scoring.method is set to CFDscore The start and end positions of the sub PAM. Default to 22 and 23 for spCas9 with 20bp gRNA and NGG as preferred PAM. For Cpf1, it could be c(1,2).
PAM.location	PAM location relative to gRNA. For example, default to 3prime for spCas9 PAM. Please set to 5prime for cpf1 PAM since it's PAM is located on the 5 prime end
mismatch.activity.file	Applicable only when scoring.method is set to CFDscore A comma separated (csv) file containing the cleavage rates for all possible types of single nucleotide mismatches at each position of the gRNA. By default, using the supplemental Table 19 from Doench et al., Nature Biotechnology 2016

Value

Four tab delimited files are generated in the output directory: OfftargetAnalysis.xls (detailed information of off targets), Summary.xls (summary of the gRNAs), REcutDetails.xls (restriction enzyme cut sites of each gRNA), and pairedgRNAs.xls (potential paired gRNAs)

Author(s)

Lihua Julie Zhu

References

Patrick D Hsu, David A Scott, Joshua A Weinstein, F Ann Ran, Silvana Konermann, Vineeta Agarwala, Yinqing Li, Eli J Fine, Xuebing Wu, Ophir Shalem, Thomas J Cradick, Luciano A Marraffini, Gang Bao & Feng Zhang (2013) DNA targeting specificity of rNA-guided Cas9 nucleases. Nature Biotechnology 31:827-834 Doench JG, Hartenian E, Graham DB, Tothova Z, Hegde M, Smith I, Sullender M, Ebert BL, Xavier RJ, Root DE. Rational design of highly active sgRNAs for CRISPR-Cas9-mediated gene inactivation. Nat Biotechnol. 2014 Sep 3. doi: 10.1038 nbt.3026 Lihua Julie Zhu, Benjamin R. Holmes, Neil Aronin and Michael Brodsky. CRISPRseek: a Bioconductor package to identify target-specific guide RNAs for CRISPR-Cas9 genome-editing systems. Plos One Sept 23rd 2014 Doench JG et al., Optimized sgRNA design to maximize activity and minimize off-target effects of CRISPR-Cas9. Nature Biotechnology Jan 18th 2016

See Also

CRISPRseek

Examples

```
library(CRISPRseek)
library("BSgenome.Hsapiens.UCSC.hg19")
library(TxDb.Hsapiens.UCSC.hg19.knownGene)
library(org.Hs.eg.db)
outputDir <- getwd()
```

```

inputFilePath <- system.file("extdata", "inputseq.fa",
                             package = "CRISPRseek")
REpatternFile <- system.file("extdata", "NEBenzymes.fa",
                              package = "CRISPRseek")
results <- offTargetAnalysis(inputFilePath, findgRNAsWithREcutOnly = TRUE,
                             REpatternFile = REpatternFile, findPairedgRNAOnly = FALSE,
                             annotatePaired = FALSE,
                             BSgenomeName = Hsapiens, chromToSearch = "chrX",
                             txdb = TxDb.Hsapiens.UCSC.hg19.knownGene,
                             orgAnn = org.Hs.egSYMBOL, max.mismatch = 1,
                             outputDir = outputDir, overwrite = TRUE)

##### PAM is on the 5 prime side
results <- offTargetAnalysis(inputFilePath, findgRNAsWithREcutOnly = FALSE,
                             REpatternFile = REpatternFile, findPairedgRNAOnly = FALSE,
                             annotatePaired = FALSE,
                             BSgenomeName = Hsapiens, chromToSearch = "chrX",
                             txdb = TxDb.Hsapiens.UCSC.hg19.knownGene,
                             orgAnn = org.Hs.egSYMBOL, max.mismatch = 4,
                             outputDir = outputDir, overwrite = TRUE, PAM.location = "5prime",
                             PAM = "TGT", PAM.pattern = "^T[A|G]N", allowed.mismatch.PAM = 2,
                             subPAM.position = c(1,2))

```

searchHits

Search for off targets in a sequence as DNAStrng

Description

Search for off targets for given gRNAs, sequence and maximum mismatches

Usage

```

searchHits(gRNAs, seqs, seqname, max.mismatch = 3, PAM.size = 3,
           gRNA.size = 20, PAM = "NGG", PAM.pattern = "NNN$",
           allowed.mismatch.PAM = 2, PAM.location = "3prime",
           outfile)

```

Arguments

gRNAs	DNAStrngSet object containing a set of gRNAs. Please note the sequences must contain PAM appended after gRNAs, e.g., ATCGAAATTCGAGCCAATCCCGG where ATCGAAATTCGAGCCAATCC is the gRNA and CGG is the PAM
seqs	DNAStrng object containing a DNA sequence.
seqname	Specify the name of the sequence
max.mismatch	Maximum mismatch allowed in off target search, default 3. Warning: will be considerably slower if it is set to greater than 3
PAM.size	Size of PAM, default 3
gRNA.size	Size of gRNA, default 20
PAM	PAM as regular expression for appending to the gRNA, default NGG for Sp-Cas9, change to TTTN for cpf1.

PAM.pattern	Regular expression of PAM, default N[AIG]G\$ for spCas9. For cpf1, ^TTTN since it is a 5 prime PAM sequence
allowed.mismatch.PAM	Maximum number of mismatches allowed in the offtargets comparing to the PAM sequence. Default to 2 for NGG PAM
PAM.location	PAM location relative to gRNA. For example, spCas9 PAM is located on the 3 prime while cpf1 PAM is located on the 5 prime
outfile	File path to temporarily store the search results

Value

a data frame contains IsMismatch.posX (indicator variable indicating whether this position X is mismatch or not, 1 means yes and 0 means not, X = 1 to gRNA.size) representing all positions in the gRNA),strand (strand of the match, + for plus and - for minus strand), chrom (chromosome of the off target), chromStart (start position of the off target), chromEnd (end position of the off target),name (gRNA name), gRNAPlusPAM (gRNA sequence with PAM sequence concatenated), OffTargetSequence (the genomic sequence of the off target), n.mismatch (number of mismatches between the off target and the gRNA), forViewInUCSC (string for viewing in UCSC genome browser, e.g., chr14:31665685-31665707), score (set to 100, and will be updated in getOfftargetScore)

Author(s)

Lihua Julie Zhu

See Also

offTargetAnalysis

Examples

```

if(interactive())
{
  all.gRNAs <- findgRNAs(inputFilePath =
    system.file("extdata", "inputseq.fa", package = "CRISPRseek"),
    pairOutputFile = "pairedgRNAs.xls",
    findPairedgRNAOnly = TRUE)

  library("BSgenome.Hsapiens.UCSC.hg19")
  ### for speed reason, use max.mismatch = 0 for finding all targets with
  ### all variants of PAM
  hits <- searchHits(all.gRNAs[1], BSgenomeName = Hsapiens,
    max.mismatch = 0, chromToSearch = "chrX")
  colnames(hits)

  ### test PAM located at 5 prime
  all.gRNAs <- findgRNAs(inputFilePath =
    system.file("extdata", "inputseq.fa", package = "CRISPRseek"),
    pairOutputFile = "pairedgRNAs.xls",
    findPairedgRNAOnly = FALSE,
    PAM = "TGT", PAM.location = "5prime")

  library("BSgenome.Hsapiens.UCSC.hg19")
  ### for speed reason, use max.mismatch = 0 for finding all targets with
  ### all variants of PAM
  hits <- searchHits(all.gRNAs[1], BSgenomeName = Hsapiens, PAM.size = 3,

```

```

        max.mismatch = 0, chromToSearch = "chrX", PAM.location = "5prime",
        PAM = "^T[A|G]N", allowed.mismatch.PAM = 2)
    colnames(hits)
}

```

searchHits2

*Search for off targets***Description**

Search for off targets for given gRNAs, BSgenome and maximum mismatches

Usage

```

searchHits2(gRNAs, BSgenomeName, chromToSearch = "all", chromToExclude = "",
  max.mismatch = 3,
  PAM.size = 3, gRNA.size = 20, PAM = "NGG", PAM.pattern = "N[A|G]G$",
  allowed.mismatch.PAM = 1, PAM.location = "3prime")

```

Arguments

gRNAs	DNAStrngSet object containing a set of gRNAs. Please note the sequences must contain PAM appended after gRNAs, e.g., ATCGAAATTCGAGCCAATC-CCGG where ATCGAAATTCGAGCCAATCC is the gRNA and CGG is the PAM
BSgenomeName	BSgenome object. Please refer to available.genomes in BSgenome package. For example, BSgenome.Hsapiens.UCSC.hg19 for hg19, BSgenome.Mmusculus.UCSC.mm10 for mm10, BSgenome.Celegans.UCSC.ce6 for ce6, BSgenome.Rnorvegicus.UCSC.rn5 for rn5, and BSgenome.Dmelanogaster.UCSC.dm3 for dm3
chromToSearch	Specify the chromosome to search, default to all, meaning search all chromosomes. For example, chrX indicates searching for matching in chromosome X only
chromToExclude	Specify the chromosome not to search, default to none, meaning to search chromosomes specified by chromToSearch. For example, to exclude haplotype blocks from offtarget search in hg19, set chromToExclude to c("chr17_ctg5_hap1", "chr4_ctg9_hap1", "chr6_apd_hap1", "chr6_cox_hap2", "chr6_dbb_hap3", "chr6_mann_hap4", "chr6_mcf_hap5", "chr6_chr6_ssto_hap7")
max.mismatch	Maximum mismatch allowed in off target search, default 3. Warning: will be considerably slower if it is set to greater than 3
PAM.size	Size of PAM, default 3
gRNA.size	Size of gRNA, default 20
PAM	Regular expression of protospacer-adjacent motif (PAM), default NGG for sp-Cas9. For cpf1, ^TTTN
PAM.pattern	Regular expression of PAM, default N[A G]G\$ for spCas9. For cpf1, ^TTTN since it is a 5 prime PAM sequence
allowed.mismatch.PAM	Number of degenerative bases in the PAM sequence, default to 1 for N[A G]G PAM
PAM.location	PAM location relative to gRNA. For example, spCas9 PAM is located on the 3 prime while cpf1 PAM is located on the 5 prime

Value

a data frame contains `IsMismatch.posX` (indicator variable indicating whether this position X is mismatch or not, 1 means yes and 0 means not, X = 1 to `gRNA.size`) representing all positions in the `gRNA`), `strand` (strand of the match, + for plus and - for minus strand), `chrom` (chromosome of the off target), `chromStart` (start position of the off target), `chromEnd` (end position of the off target), `name` (`gRNA` name), `gRNAplusPAM` (`gRNA` sequence with PAM sequence concatenated), `OffTargetSequence` (the genomic sequence of the off target), `n.mismatch` (number of mismatches between the off target and the `gRNA`), `forViewInUCSC` (string for viewing in UCSC genome browser, e.g., `chr14:31665685-31665707`), `score` (set to 100, and will be updated in `getOfftargetScore`)

Author(s)

Lihua Julie Zhu

See Also

`offTargetAnalysis`

Examples

```
all.gRNAs <- findgRNAs(inputFilePath =
  system.file("extdata", "inputseq.fa", package = "CRISPRseek"),
  pairOutputFile = "pairedgRNAs.xls",
  findPairedgRNAOnly = TRUE)

library("BSgenome.Hsapiens.UCSC.hg19")
### for speed reason, use max.mismatch = 0 for finding all targets with
### all variants of PAM
hits <- searchHits2(all.gRNAs[1], BSgenomeName = Hsapiens,
  max.mismatch = 0, chromToSearch = "chrX")
colnames(hits)

### test PAM located at 5 prime
all.gRNAs <- findgRNAs(inputFilePath =
  system.file("extdata", "inputseq.fa", package = "CRISPRseek"),
  pairOutputFile = "pairedgRNAs.xls",
  findPairedgRNAOnly = FALSE,
  PAM = "TGT", PAM.location = "5prime")

library("BSgenome.Hsapiens.UCSC.hg19")
### for speed reason, use max.mismatch = 0 for finding all targets with
### all variants of PAM
hits <- searchHits2(all.gRNAs[1], BSgenomeName = Hsapiens, PAM.size = 3,
  max.mismatch = 0, chromToSearch = "chrX", PAM.location = "5prime",
  PAM = "NGG",
  PAM.pattern = "^T[A|G]N", allowed.mismatch.PAM = 2)
colnames(hits)
```

translatePattern

translate pattern from IUPAC Extended Genetic Alphabet to regular expression

Description

translate pattern containing the IUPAC nucleotide ambiguity codes to regular expression. For example, Y->[C|T], R-> [A|G], S-> [G|C], W-> [A|T], K-> [T|U|G], M-> [A|C], B-> [C|G|T], D-> [A|G|T], H-> [A|C|T], V-> [A|C|G] and N-> [A|C|T|G].

Usage

```
translatePattern(pattern)
```

Arguments

pattern a character vector with the IUPAC nucleotide ambiguity codes

Value

a character vector with the pattern represented as regular expression

Author(s)

Lihua Julie Zhu

Examples

```
pattern1 <- "AACCNWMK"
translatePattern(pattern1)
```

uniqueREs	<i>Output restriction enzymes that recognize only the gRNA cleavage sites</i>
-----------	---

Description

For each identified gRNA, output restriction enzymes that recognize only the gRNA cleavage sites.

Usage

```
uniqueREs(REcutDetails, summary, offTargets, scanUpstream = 100,
          scanDownstream = 100, BSgenomeName)
```

Arguments

REcutDetails REcutDetails stored in the REcutDetails.xls
summary summary stored in the summary.xls
offTargets offTargets stored in the offTargets.xls
scanUpstream upstream offset from the gRNA start, default 100
scanDownstream downstream offset from the gRNA end, default 100
BSgenomeName BSgenome object. Please refer to available.genomes in BSgenome package. For example, BSgenome.Hsapiens.UCSC.hg19 for hg19, BSgenome.Mmusculus.UCSC.mm10 for mm10, BSgenome.Celegans.UCSC.ce6 for ce6, BSgenome.Rnorvegicus.UCSC.rm5 for rm5, BSgenome.Drerio.UCSC.danRer7 for Zv9, and BSgenome.Dmelanogaster.UCSC.dm3 for dm3

Value

returns the RE sites that recognize only the gRNA cleavage sites for each gRNA.

Author(s)

Lihua Julie Zhu

Examples

```
library("BSgenome.Hsapiens.UCSC.hg19")
load(system.file("extdata", "ForTestinguniqueREs.RData",
  package = "CRISPRseek"))
uniqueREs(results$REcutDetails, results$summary, results$offtarget,
scanUpstream = 50,
  scanDownstream = 50, BSgenomeName = Hsapiens)
```

writeHits

Write the hits of sequence search from a sequence to a file

Description

write the hits of sequence search from a sequence instead of BSgenome to a file, internal function used by searchHits

Usage

```
writeHits(gRNA, seqname, matches, strand, file, gRNA.size = 20L,
  PAM = "NGG", PAM.pattern = "N[A|G]G$", max.mismatch = 4L,
  chrom.len, append = FALSE, PAM.location = "3prime",
  PAM.size = 3L, allowed.mismatch.PAM = 1L,
  seqs)
```

Arguments

gRNA	DNAStrng object with gRNA sequence with PAM appended immediately after, e.g., ACGTACGTACGTACTGACGTCGG with 20bp gRNA sequence plus 3bp PAM sequence CGG
seqname	sequence name as character
matches	XStringViews object storing matched chromosome locations
strand	strand of the match, + for plus strand and - for minus strand
file	file path where the hits is written to
gRNA.size	gRNA size, default 20
PAM	PAM as regular expression for appending to the gRNA, default NGG for Sp-Cas9, change to TTTN for cpf1.
PAM.pattern	PAM as regular expression for filtering the hits, default N[A G]G\$ for spCas9. For cpf1, ^TTTN since it is a 5 prime PAM sequence.
max.mismatch	maximum mismatch allowed within the gRNA (excluding PAM portion) for filtering the hits, default 4
chrom.len	length of the matched chromosome

append	TRUE if append to existing file, false if start a new file
PAM.location	PAM location relative to gRNA. For example, spCas9 PAM is located on the 3 prime while cpf1 PAM is located on the 5 prime
PAM.size	Size of PAM, default 3
allowed.mismatch.PAM	Maximum number of mismatches allowed in the offtargets comparing to the PAM sequence. Default to 1 for NGG PAM
seqs	DNAStrng object containing a DNA sequence.

Value

results are saved in the file specified by file

Author(s)

Lihua Julie Zhu

References

<http://bioconductor.org/packages/2.8/bioc/vignettes/BSgenome/inst/doc/GenomeSearching.pdf>

See Also

offTargetAnalysis

Examples

```
if(interactive())
{
  gRNAPlusPAM <- DNAStrng("ACGTACGTACGTACTGACGTCGG")
  x <- DNAStrng("AAGCGGATATGACGTACGTACGTACTGACGTCGG")
  chrom.len <- nchar(as.character(x))
  m <- matchPattern(gRNAPlusPAM, x)
  names(m) <- "testing"
  writeHits(gRNA = gRNAPlusPAM, seqname = "chr1",
            matches = m, strand = "+", file = "exampleWriteHits.txt",
            chrom.len = chrom.len, append = FALSE)
}
```

writeHits2

Write the hits of sequence search to a file

Description

write the hits of sequence search to a file, internal function used by searchHits

Usage

```
writeHits2(gRNA, seqname, matches, strand, file, gRNA.size = 20,
           PAM = "NGG", PAM.pattern = "N[A|G]G$",
           max.mismatch = 4, chrom.len, append = FALSE,
           PAM.location = "3prime", PAM.size = 3,
           allowed.mismatch.PAM = 1L,
           BSgenomeName)
```

Arguments

gRNA	DNASTring object with gRNA sequence with PAM appended immediately after, e.g., ACGTACGTACGTACTGACGTCGG with 20bp gRNA sequence plus 3bp PAM sequence CGG
seqname	chromosome name as character, e.g., chr1
matches	XStringViews object storing matched chromosome locations
strand	strand of the match, + for plus strand and - for minus strand
file	file path where the hits is written to
gRNA.size	gRNA size, default 20
PAM	PAM as regular expression for filtering the hits, default NGG for spCas9. For cpf1, TTTN.
PAM.pattern	Regular expression of protospacer-adjacent motif (PAM), default N[AIG]G\$ for spCas9. For cpf1, ^TTTN since it is a 5 prime PAM sequence
max.mismatch	maximum mismatch allowed within the gRNA (excluding PAM portion) for filtering the hits, default 4
chrom.len	length of the matched chromosome
append	TRUE if append to existing file, false if start a new file
PAM.location	PAM location relative to gRNA. For example, spCas9 PAM is located on the 3 prime while cpf1 PAM is located on the 5 prime
PAM.size	Size of PAM, default 3
allowed.mismatch.PAM	Number of degenerative bases in the PAM sequence, default to 1 for N[AIG]G PAM
BSgenomeName	BSgenome object. Please refer to available.genomes in BSgenome package. For example, BSgenome.Hsapiens.UCSC.hg19 for hg19, BSgenome.Mmusculus.UCSC.mm10 for mm10, BSgenome.Celegans.UCSC.ce6 for ce6, BSgenome.Rnorvegicus.UCSC.rm5 for rm5, BSgenome.Drerio.UCSC.danRer7 for Zv9, and BSgenome.Dmelanogaster.UCSC.dm3 for dm3

Value

results are saved in the file specified by file

Author(s)

Lihua Julie Zhu

References

<http://bioconductor.org/packages/2.8/bioc/vignettes/BSgenome/inst/doc/GenomeSearching.pdf>

See Also

offTargetAnalysis

Examples

```
library("BSgenome.Hsapiens.UCSC.hg19")
gRNAPlusPAM <- DNASTring("ACGTACGTACGTACTGACGTCGG")
x <- DNASTring("AAGCGGATATGACGTACGTACGTACTGACGTCGG")
chrom.len <- nchar(as.character(x))
m <- matchPattern(gRNAPlusPAM, x)
names(m) <- "testing"
writeHits2(gRNA = gRNAPlusPAM, seqname = "chr1",
           PAM = "NGG", PAM.pattern = "NNN$", allowed.mismatch.PAM = 2,
           matches = m, strand = "+", file = "exampleWriteHits.txt",
           chrom.len = chrom.len, append = FALSE, BSgenomeName = Hsapiens)
```

Index

*Topic **misc**

- annotateOffTargets, 4
- buildFeatureVectorForScoring, 6
- calculategRNAEfficiency, 7
- compare2Sequences, 8
- filtergRNAs, 13
- filterOffTarget, 14
- findgRNAs, 16
- foldgRNAs, 19
- getOfftargetScore, 20
- isPatternUnique, 21
- offTargetAnalysis, 22
- searchHits, 27
- searchHits2, 29
- translatePattern, 30
- uniqueREs, 31
- writeHits, 32
- writeHits2, 33

- uniqueREs, 31

- writeHits, 32

- writeHits2, 33

*Topic **package**

- CRISPRseek-package, 2

- annotateOffTargets, 4

- buildFeatureVectorForScoring, 6

- calculategRNAEfficiency, 7

- compare2Sequences, 8

- CRISPRseek (CRISPRseek-package), 2

- CRISPRseek-package, 2

- filtergRNAs, 13

- filterOffTarget, 14

- findgRNAs, 16

- foldgRNAs, 19

- getOfftargetScore, 20

- isPatternUnique, 21

- offTargetAnalysis, 22

- searchHits, 27

- searchHits2, 29

- translatePattern, 30