

Package ‘affycomp’

April 15, 2019

Version 1.58.0

Title Graphics Toolbox for Assessment of Affymetrix Expression Measures

Author Rafael A. Irizarry <rafa@jhu.edu> and Zhijin Wu <zwu@stat.brown.edu> with contributions from Simon Cawley <simon_cawley@affymetrix.com>

Maintainer Rafael A. Irizarry <rafa@jhu.edu>

Depends R (>= 2.13.0), methods, Biobase (>= 2.3.3)

Suggests splines, affycompData

Description The package contains functions that can be used to compare expression measures for Affymetrix Oligonucleotide Arrays.

License GPL (>= 2)

biocViews OneChannel, Microarray, Preprocessing

git_url <https://git.bioconductor.org/packages/affycomp>

git_branch RELEASE_3_8

git_last_commit 99607b2

git_last_commit_date 2018-10-30

Date/Publication 2019-04-15

R topics documented:

affycomp.compfigs.auxiliary	2
affycomp.figures.auxiliary	3
affycompPlot	5
affycompTable	6
assessAll	8
assessDilution	8
assessSD	9
assessSpikeIn	10
assessSpikeIn2	11
dilution.phenodata	12
exprset.log	12
hgu133a.spikein.phenodata	13
hgu133a.spikein.xhyb	13

mas5.assessment	14
readin	14
remove.hgu133a.xhyb	15
SD	15
spikein.phenodata	16

Index	17
--------------	-----------

affycomp.compfigs.auxiliary

Auxiliary functions to create comparative Figures

Description

These functions are auxiliary function to [affycompPlot](#). These Figures are used to compare expression measures. They take lists with components created by the [assessDilution](#) and [assessSpikeIn](#) functions.

Usage

```
affycomp.compfig2(l, method.names = as.character(1:length(l)),
  add.legend = TRUE, main = "Figure 2")
```

```
affycomp.compfig3(l, method.names = as.character(1:length(l)),
  main = "Figure 3")
```

```
affycomp.compfig4a(l, method.names = as.character(1:length(l)),
  add.legend = TRUE, main = "Figure 4a")
```

```
affycomp.compfig4b(l, method.names = as.character(1:length(l)),
  add.legend = TRUE, main = "Figure 4b")
```

```
affycomp.compfig4c(l, method.names = as.character(1:length(l)),
  add.legend = TRUE, rotate=TRUE, main = "Figure 4c")
```

```
affycomp.compfig5a(l, method.names = as.character(1:length(l)),
  add.legend = TRUE, main = "Figure 5a", maxfp=100)
```

```
affycomp.compfig5b(l, method.names = as.character(1:length(l)),
  add.legend = TRUE, main = "Figure 5b", maxfp=100)
```

```
affycomp.compfig5cde(l, method.names = as.character(1:length(l)),
  add.legend = TRUE, main = "Figure 5c", maxfp=100,
  type=c("low", "med", "high"))
```

```
affycomp.compfig5c(l, method.names = as.character(1:length(l)),
  add.legend = TRUE, main = "Figure 5c", maxfp=100)
```

```
affycomp.compfig5d(l, method.names = as.character(1:length(l)),
  add.legend = TRUE, main = "Figure 5d", maxfp=100)
```

```
affycomp.compfig5e(l, method.names = as.character(1:length(l)),
```

```
add.legend = TRUE, main = "Figure 5e", maxfp=100)
```

Arguments

l	a list of lists with the necessary components to create the Figure. See details.
method.names	a character vector with the names of the expression measures methodologies being compared.
add.legend	logical. If TRUE a legend is added.
main	title of the Figure.
rotate	in the case of compfig4c one can either show the actual local slopes or the bias (local slope minus 1).
maxfp	range of the false positives in ROC will be from 0 to maxfp
type	compfig5cdef is the engine for 5c, 5d, and 5e. type tells is which of these 4 to run.

Details

These are similar to the functions defined in [affycomp.figures.auxiliary](#). Main difference is that here you send lists with the result of the assessment functions as components.

Value

Figures are produced.

Author(s)

Rafael A. Irizarry

Examples

```
library(affycompData)
data(rma.assessment)
data(mas5.assessment)
affycomp.compfig2(list(rma.assessment$Dilution,mas5.assessment$Dilution))
affycomp.compfig3(list(rma.assessment$Dilution,mas5.assessment$Dilution))
affycomp.compfig4a(list(rma.assessment$Signal,mas5.assessment$Signal))
affycomp.compfig4b(list(rma.assessment$Dilution,mas5.assessment$Dilution))
affycomp.compfig5a(list(rma.assessment$FC,mas5.assessment$FC))
affycomp.compfig5b(list(rma.assessment$FC2,mas5.assessment$FC2))
```

affycomp.figures.auxiliary

Auxiliary functions to create Figures

Description

These functions are auxiliary function to [affycompPlot](#). These Figures are used to assess an expression measure. They take components created by the [assessDilution](#) and [assessSpikeIn](#) functions.

Usage

```

affycomp.figure1(l,main="Figure 1",xlim=NULL,ylim=NULL)
affycomp.figure1b(l,main="Figure 1b",xlim=NULL,ylim=NULL,cex=0.85,all=FALSE)
affycomp.figure2(l,main="Figure 2")
affycomp.figure2b(l,main="Figure 2b")
affycomp.figure3(l, main = "Figure 3")
affycomp.figure4a(l, main = "Figure 4a",equal.lims=FALSE)
affycomp.figure4b(l, main = "Figure 4b")
affycomp.figure4c(l, rotate=TRUE, main = "Figure 4c")
affycomp.figure5a(l, main = "Figure 5a",maxfp=100)
affycomp.figure5b(l, main = "Figure 5b",maxfp=100)
affycomp.figure5c(l, main = "Figure 5c",maxfp=100)
affycomp.figure5d(l, main = "Figure 5d",maxfp=100)
affycomp.figure5e(l, main = "Figure 5e",maxfp=100)
affycomp.figure6a(l, main = "Figure 6a",xlim = NULL, ylim = NULL)
affycomp.figure6b(l, main = "Figure 6b",xlim = NULL, ylim = NULL)

```

Arguments

l	A list with the necessary components to create the Figure. See details.
main	Title for the Figure.
maxfp	range of the false positives in ROC will be from 0 to maxfp
xlim	x-axis limits.
ylim	y-axis limits.
cex	size of numbers in figure 1b.
all	logical. If TRUE all spikeins are shown. Otherwise, only those resulting in smaller, realistic, fold changes are shown.
equal.lims	logical. If TRUE the limits of x-axis and y-axis will have same range.
rotate	in the case of compfig4c one can either show the actual local slopes or the bias (local slope minus 1).

Details

Read the vignette for more details on what each Figure is. You can read [assessSpikeIn](#) and [assessDilution](#) to see which assessments are needed.

Value

Figures are produced.

Author(s)

Rafael A. Irizarry

Examples

```

library(affycompData)
data(rma.assessment)
affycomp.figure1(rma.assessment$MA)

```

```

affycomp.figure2(rma.assessment$Dilution)
affycomp.figure3(rma.assessment$Dilution)
affycomp.figure4a(rma.assessment$Signal)
affycomp.figure4b(rma.assessment$Dilution)
affycomp.figure5a(rma.assessment$FC)
affycomp.figure5b(rma.assessment$FC2)
affycomp.figure6a(rma.assessment$FC)
affycomp.figure6b(rma.assessment$FC)

```

affycompPlot

Assessment Plots

Description

Function that makes assessment plot

Usage

```

affycompPlot(...,assessment.list=NULL,method.names=NULL,
             figure1.xlim=c(-4,15),figure1.ylim=c(-10,12),
             figure1b.xlim=c(-2,14),figure1b.ylim=c(-6,5),
             figure6a.xlim=c(-12,12),figure6a.ylim=c(-12,12),
             figure6b.xlim=c(-3,3),figure6b.ylim=c(-6,6))

affycomp.compfigs(l, method.names = NULL, figure1.xlim = c(-4, 15),
                 figure1.ylim = c(-10, 12), figure1b.xlim = c(-4, 15),
                 figure1b.ylim = c(-4, 4), figure6a.xlim = c(-12, 12),
                 figure6a.ylim = c(-12, 12), figure6b.xlim = c(-3, 3),
                 figure6b.ylim = c(-6, 6))

affycomp.figures(l)
affycomp.figure.calls(what)
affycomp.compfigs.calls(what)

```

Arguments

... lists produced by the assessment functions (one for each method) separated by commas.

assessment.list Alternatively, one can also send a list of lists produced by one of the assessment functions.

method.names A character vector with the names of the expression measure methodology.

figure1.xlim x-axis lim used for the plots in Figure 1.

figure1.ylim y-axis lim used for the plots in Figure 1.

figure1b.xlim x-axis lim used for the plots in Figure 1b.

figure1b.ylim y-axis lim used for the plots in Figure 1b.

figure6a.xlim x-axis lim used for the plots in Figure 6a.

figure6a.ylim y-axis lim used for the plots in Figure 6a.

figure6b.xlim x-axis lim used for the plots in Figure 6b.

figure6b.ylim y-axis lim used for the plots in Figure 6b.

l list with assessment lists as components.

what a dummy variable to know what function call to create.

Details

Read the vignette for more details on what each Figure is. Once an assessment is used this function knows what to do. You can call any of the assessment functions described in [assessSpikeIn](#), [assessDilution](#) and [assessSD](#).

affycomp.figures, affycomp.figure.calls, affycomp.compfigs.calls are auxiliary functions.

Value

Figures are produced.

Author(s)

Rafael A. Irizarry

Examples

```
library(affycompData)
data(rma.assessment)
data(mas5.assessment)
affycompPlot(rma.assessment,mas5.assessment)
affycompPlot(rma.assessment$FC)
affycompPlot(rma.assessment$Dilution,mas5.assessment$Dilution)
affycompPlot(rma.assessment$Dilution,mas5.assessment$Dilution)
affycompPlot(rma.assessment$Signal,mas5.assessment$Signal)
affycompPlot(rma.assessment$Dilution,mas5.assessment$Dilution)
affycompPlot(rma.assessment$FC2,mas5.assessment$FC2)
```

affycompTable

Expression Assessment Table

Description

These functions take as an argument the output of the assessment functions.

Usage

```
affycompTable(...,Table=NULL,assessment.list=NULL,method.names=NULL)

tableAll(...,assessment.list=NULL,method.names=NULL)

tableDilution(l, method.names=NULL)

tableFC(l, method.names=NULL)

tableFC2(l, method.names=NULL)

tableSignal(l, method.names=NULL)

tableLS(l, method.names=NULL)
```

```

tableSpikeInSD(1, method.names=NULL)

tableMA2(1, method.names=NULL)

tableOverallSNR(...,assessment.list=NULL,method.names=NULL,ngenes=12626)

tableRanks(...,assessment.list=NULL,method.names=NULL,ngenes=12626,rank=TRUE)

```

Arguments

<code>...</code>	lists produced by the assessment functions
<code>Table</code>	If <code>TableAll</code> was used one can send it through this argument
<code>assessment.list</code>	Alternatively, one can also send a list of lists produced by <code>tableAll</code> .
<code>method.names</code>	A character vector with the names of the epxression measure methodology.
<code>l</code>	list of assessments.
<code>rank</code>	if TRUE <code>tableRanks</code> will present ranks instead of local slopes.
<code>ngenes</code>	when computing ranks, out of how many genes should we do it?

Details

Read the vignette for more details on what the entries of the table are. `affycompTable` has a few entries per graph. `tableAll` has more entries. Once an assessment is used this function knows what to do. You can call any of the assessment functions described in [assessSpikeIn](#), [assessDilution](#), [assessSD](#), [assessLS](#), [assessMA2](#), and [assessSpikeInSD](#).

Note `tableRanks` and `tableOverallSNR` work on the results from [assessSpikeIn2](#).

Value

A matrix. One column per each method and one row for each comparison. `tableOverallSNR` is an exception. Where rows represnt methods.

Author(s)

Rafael A. Irizarry

Examples

```

library(affycompData)
data(rma.assessment) ##this was produced with affycomp.assess
data(mas5.assessment) ##this one too
tmp <- affycompTable(mas5.assessment,rma.assessment)
format(tmp,digit=2)

```

assessAll *Assessment functions*

Description

Assessment functions. Takes a couple of [ExpressionSet](#), one for spike in another for the dilution and returns a list with necessary information to create assessment plots.

Usage

```
assessAll(d,s,method.name=NULL,verbose=TRUE)
```

```
affycomp(d,s,method.name=NULL,verbose=TRUE,return.it=TRUE)
```

Arguments

d	An ExpressionSet containing the expression measures for the Gene Logic's dilution experiment.
s	An ExpressionSet containing expression measures for the Affymetrix's spike-in experiment.
method.name	Name of expression measure being assessed.
verbose	verbosity flag.
return.it	if TRUE returns assessment lists.

Details

assessAll performs assessments for Figures 1-6. It is a wrapper for assessDilution and assessSpikeIn. affycomp is a wrapper that does it all... including the plotting and creation of table.

Value

Lists with the necessary information to make the Figures.

Author(s)

Rafael A. Irizarry

assessDilution *Assessment functions for Dilution Data*

Description

Assessment function. Takes an [ExpressionSet](#) and returns a list with necessary information to create assessment plots.

Usage

```
assessDilution(exprset,method.name=NULL)
```


Arguments

exprset	An ExpressionSet containing expression measures for GeneLogic's dilution experiment.
method.name	Name of expression measure being assessed.

Details

assessDilution performs the assessment for the plots related to Dilution (Figures 2, 3, 4b)

Value

Lists with the necessary information to make the Figures.

Author(s)

Rafael A. Irizarry

assessSD

SD Assessment functions

Description

Assessment function for standard deviation estimates. Takes a dilution data [ExpressionSet](#) and returns a list with necessary information to create assessment plot.

Usage

```
assessSD(exprset, method.name=NULL, logx=FALSE)
```

Arguments

exprset	An ExpressionSet containing expression measures for Affymetrix's dilution experiment.
method.name	Name of expression measure being assessed.
logx	Logical indicating whether the average expression being computed should be logged, default no. See details.

Details

assessSD does the assessment for Figure 7. This requires the [ExpressionSet](#) to have standard error estimates for the expression measure. Some expression measures (e.g. dChip) will have SEs in original scale, where others (e.g. RMA) will have them in log scale. For the former, use logx=TRUE.

Value

Lists with the necessary information to make the Figures.

Author(s)

Rafael A. Irizarry

assessSpikeIn	<i>Assessment functions for Spike In Data</i>
---------------	---

Description

These functions are assessment functions. Each takes an [ExpressionSet](#) and returns a list with necessary information to create assessment plots.

Usage

```
assessSpikeIn(s,method.name=NULL,verbose=TRUE)

assessMA(exprset,method.name=NULL)
assessSignal(exprset,method.name=NULL)
assessFC(exprset,method.name=NULL)
assessFC2(exprset,method.name=NULL)
```

Arguments

s	An ExpressionSet containing expression measures for Affymetrix's spike-in experiment.
exprset	An ExpressionSet containing expression measures for Affymetrix's spike-in experiment.
method.name	Name of expression measure being assessed.
verbose	logical. If TRUE show messages.

Details

assessMA performs the assessment for the MA-plot (Figure 1), assessSignal performs the assessment for signal detection plot (Figure 4a), assessFC performs assessments used by fold-change related plots (Figures 5a, 6a, 6b). assessFC2 is for the ROC for genes with nominal fold changes of 2 (Figure 5b). assessSpikeIn is a wrapper for all these and returns a list of lists.

Value

Lists with the necessary information to make the Figures.

Author(s)

Rafael A. Irizarry

assessSpikeIn2	<i>New Assessment functions for Spike In Data</i>
----------------	---

Description

These functions are assessment functions. Each takes an [ExpressionSet](#) and returns a list with necessary information to create assessment plots.

Usage

```
assessSpikeIn2(s, method.name=NULL, verbose=TRUE)
assessSpikeInSD(exprset, method.name=NULL, span=1/3)
assessLS(exprset, method.name=NULL)
assessMA2(exprset, method.name=NULL)
```

Arguments

s	An ExpressionSet containing expression measures for Affymetrix's spike-in experiment.
exprset	An ExpressionSet containing expression measures for Affymetrix's spike-in experiment.
method.name	Name of expression measure being assessed.
verbose	logical. If TRUE show messages.
span	span used in call to loess.

Details

assessMA2 performs the assessment for the second MA-plot (Figure 1b), and assessLS performs the assessment for signal detection plot (Figure 4c). assessMA2 also performs assessments used by fold-change related plots (Figures 5a,b) and the ROC plots (Figures 5c,d,e). assessSpikeInSD is for the standard deviation assessment in Figure 2b. assessSpikeIn2 is a wrapper for all these and returns a list of lists.

Value

Lists with the necessary information to make the Figures.

Author(s)

Rafael A. Irizarry

dilution.phenodata *Phenotypic Information for Dilution Study*

Description

This object is of class `phenoData` with necessary information for the assessemnts.

Usage

```
data(dilution.phenodata)
```

Format

An object of class `phenoData`

Source

Two sources of cRNA A (human liver tissue) and B (Central Nervous System cell line) have been hybridized to human array (HGU95Av2) in a range of proportions and dilutions. This object described these.

For more information see Irizarry, R.A., et al. (2001) <http://www.biostat.jhsph.edu/~ririzarr/papers/index.html>

exprset.log *Take log base 2 of Expression*

Description

Take log base 2 of the expression matrix in an `ExpressionSet`

Usage

```
exprset.log(exprset)
```

Arguments

exprset `ExpressionSet`

Details

This functions takes log base 2 of the expression matrix in an `ExpressionSet`. Negatives are converted to the smallest non-negative entry.

Value

An `ExpressionSet`

Author(s)

Rafael A. Irizarry

hgu133a.spikein.phenodata

phenotypic information for HGU133A spike in study

Description

This object is of class `phenoData` with necessary information for the assesemnts.

Usage

```
data(hgu133a.spikein.phenodata)
```

Format

An object of class `phenoData`

Source

This comes from an experiments where 16 different cRNA fragments have been added to the hybridization mixture of the GeneChip arrays at different pM concentrations. For more information see Irizarry, R.A., et al. (2001) <http://www.biostat.jhsph.edu/~ririzarr/papers/index.html>

hgu133a.spikein.xhyb *Cross hybridizers*

Description

Probe Sets likely to crosshybridize to spiked-in probesets in the Affymetrix HGU133A spike in.

This object is list. Each component of the list contains probeset names of possible crosshybridizers. The sequences of each spiked-in clone were collected and blasted against all HG-U133A target sequences. Target sequences are the ~600bp regions from which probes were selected. Thresholds of 100, 150 and 200bp were used and define the three components of the list.

Usage

```
data(hgu133a.spikein.xhyb)
```

Format

A list

Source

Simon Cawley <simon_cawley@affymetrix.com>

mas5.assessment	<i>Example of the result of assessments</i>
-----------------	---

Description

The Dilution and both (HGU95 and HGU133) types of Spike-in data were processed with Affymetrix MAS 5.0 software, yielding three "MAS 5.0" [ExpressionSet](#)'s. (These are available, in csv-format, at <http://affycomp.jhsph.edu/AFFY2/rafa@jhu.edu/030424.1033/>.) Then various assessment functions from the affycomp package (most recently, version 1.28.0) were applied. `mas5.assessment` resulted from `assessAll` on Dilution and HGU95. See `mas5.assessment` in `affycompData` for results of other assessments.

Usage

```
data(mas5.assessment)
```

Format

A list of list.

readin	<i>Read Expression Date Sets</i>
--------	----------------------------------

Description

Reads a comma-delimited file containing the expression values of the dilution and spike-in data sets and creates a [ExpressionSet](#)

Usage

```
read.dilution(filename)
read.spikein(filename, cdfName=c("hgu95a", "hgu133a"), remove.xhyb=TRUE)
read.newspikein(filename)
```

Arguments

<code>filename</code>	character containing the filename to be read.
<code>cdfName</code>	are we reading data from the hgu95a or hgu133a spike-in experiment?
<code>remove.xhyb</code>	logical. If TRUE possible cross hybridizers are removed from the HGU133A spikein. See remove.hgu133a.xhyb .

Details

The file to be read must be comma-delimited with the first row containing the cel filenames (case sensitive). The first column must be the Affymetrix gene identifiers. `read.dilution` will put things in the right place.

`read.newspikein` is a wrapper to read results from the hgu133a spikein experiment.

Value

An [ExpressionSet](#).

Author(s)

Rafael A. Irizarry

remove.hgu133a.xhyb	<i>Remove crosshybridizers</i>
---------------------	--------------------------------

Description

This functions removes possible cross hybridizers from Affymetrix HGU133A spike-in experiment

Usage

```
remove.hgu133a.xhyb(s, bp = c("200", "150", "100"))
```

Arguments

s	an ExpressionSet containing the HGU133A spike-in
bp	number of base pair matches needed to define a possible cross hybridizer

Details

Some details are contained in the help file for [hgu133a.spikein.xhyb](#)

Value

An ExpressionSet with probeset removed

See Also

[hgu133a.spikein.xhyb](#)

SD	<i>SD Assessment Functions</i>
----	--------------------------------

Description

These functions create assessments, figures, and tables for expression standard errors

Usage

```
affycomp.figure7(l,main="Figure 7")
affycomp.compfig7(l,method.names=as.character(1:length(l)),
                  main="Figure 7")
tableSD(l,method.names=NULL)
```

Arguments

l	a list of lists with the necessary components to create the Figure. See details.
method.names	a character vector with the names of the expression measures methodologies being compared.
main	title of the Figure.

Details

This uses the dilution data. The exprsets need to have standard error estimates in the assayDataElement(exprset, "se. Read the vignette for more details. The functions work similarly to those assessing expression measures.

All these files need the result of [assessSD](#)

Value

Depends on the call.

Author(s)

Rafael A. Irizarry

Examples

```
library(affycompData)
data(rma.sd.assessment) ##this was produced with affycomp.assess
data(lw.sd.assessment) ##this one too
affycomp.comfig7(list(rma.sd.assessment,lw.sd.assessment))
affycomp.figure7(rma.sd.assessment)
```

spikein.phenodata *phenotypic information for spike in study*

Description

This object is of class [phenoData](#) with necessary information for the assessemnts.

Usage

```
data(spikein.phenodata)
```

Format

An object of class [phenoData](#)

Source

This comes from an experiments where 16 different cRNA fragments have been added to the hybridization mixture of the GeneChip arrays at different pM concentrations. For more information see Irizarry, R.A., et al. (2001) <http://www.biostat.jhsph.edu/~ririzarr/papers/index.html>

Index

*Topic **datasets**

- dilution.phenodata, 12
- hgu133a.spikein.phenodata, 13
- hgu133a.spikein.xhyb, 13
- mas5.assessment, 14
- spikein.phenodata, 16

*Topic **hplot**

- affycomp.compfigs.auxiliary, 2
- affycomp.figures.auxiliary, 3
- affycompPlot, 5

*Topic **manip**

- affycompTable, 6
- assessAll, 8
- assessDilution, 8
- assessSD, 9
- assessSpikeIn, 10
- assessSpikeIn2, 11
- exprset.log, 12
- readin, 14
- remove.hgu133a.xhyb, 15
- SD, 15

affycomp (assessAll), 8

affycomp.compfig2
(affycomp.compfigs.auxiliary),
2

affycomp.compfig2b
(affycomp.compfigs.auxiliary),
2

affycomp.compfig3
(affycomp.compfigs.auxiliary),
2

affycomp.compfig4a
(affycomp.compfigs.auxiliary),
2

affycomp.compfig4b
(affycomp.compfigs.auxiliary),
2

affycomp.compfig4c
(affycomp.compfigs.auxiliary),
2

affycomp.compfig5a
(affycomp.compfigs.auxiliary),
2

affycomp.compfig5b
(affycomp.compfigs.auxiliary),
2

affycomp.compfig5c
(affycomp.compfigs.auxiliary),
2

affycomp.compfig5cde
(affycomp.compfigs.auxiliary),
2

affycomp.compfig5d
(affycomp.compfigs.auxiliary),
2

affycomp.compfig5e
(affycomp.compfigs.auxiliary),
2

affycomp.compfig7 (SD), 15

affycomp.compfigs (affycompPlot), 5

affycomp.compfigs.auxiliary, 2

affycomp.figure.calls (affycompPlot), 5

affycomp.figure1
(affycomp.figures.auxiliary), 3

affycomp.figure1b
(affycomp.figures.auxiliary), 3

affycomp.figure2
(affycomp.figures.auxiliary), 3

affycomp.figure2b
(affycomp.figures.auxiliary), 3

affycomp.figure3
(affycomp.figures.auxiliary), 3

affycomp.figure4a
(affycomp.figures.auxiliary), 3

affycomp.figure4b
(affycomp.figures.auxiliary), 3

affycomp.figure4c
(affycomp.figures.auxiliary), 3

affycomp.figure5a
(affycomp.figures.auxiliary), 3

affycomp.figure5b
(affycomp.figures.auxiliary), 3

affycomp.figure5c
(affycomp.figures.auxiliary), 3

affycomp.figure5d
(affycomp.figures.auxiliary), 3

affycomp.figure5e
 (affycomp.figures.auxiliary), 3
affycomp.figure6a
 (affycomp.figures.auxiliary), 3
affycomp.figure6b
 (affycomp.figures.auxiliary), 3
affycomp.figure7 (SD), 15
affycomp.figures (affycompPlot), 5
affycomp.figures.auxiliary, 3, 3
affycompPlot, 2, 3, 5
affycompTable, 6
assessAll, 8, 14
assessDilution, 2–4, 6, 7, 8
assessFC (assessSpikeIn), 10
assessFC2 (assessSpikeIn), 10
assessLS, 7
assessLS (assessSpikeIn2), 11
assessMA (assessSpikeIn), 10
assessMA2, 7
assessMA2 (assessSpikeIn2), 11
assessSD, 6, 7, 9, 16
assessSignal (assessSpikeIn), 10
assessSpikeIn, 2–4, 6, 7, 10
assessSpikeIn2, 7, 11
assessSpikeInSD, 7
assessSpikeInSD (assessSpikeIn2), 11

dilution.phenodata, 12

ExpressionSet, 8–12, 14, 15
exprset.log, 12

hgu133a.spikein.phenodata, 13
hgu133a.spikein.xhyb, 13, 15

mas5.assessment, 14, 14

phenoData, 12, 13, 16

read.dilution (readin), 14
read.newspikein (readin), 14
read.spikein (readin), 14
readin, 14
remove.hgu133a.xhyb, 14, 15

SD, 15
spikein.phenodata, 16

tableAll, 7
tableAll (affycompTable), 6
tableDilution (affycompTable), 6
tableFC (affycompTable), 6
tableFC2 (affycompTable), 6
tableLS (affycompTable), 6
tableMA2 (affycompTable), 6
tableOverallSNR (affycompTable), 6
tableRanks (affycompTable), 6
tableSD (SD), 15
tableSignal (affycompTable), 6
tableSpikeInSD (affycompTable), 6