

Package ‘flowWorkspace’

April 16, 2019

Type Package

Title Infrastructure for representing and interacting with gated and ungated cytometry data sets.

Version 3.30.2

Date 2011-06-10

Author Greg Finak, Mike Jiang

Maintainer Greg Finak <gfinak@fhcrc.org>, Mike Jiang <wjjiang2@fhcrc.org>

Description This package is designed to facilitate comparison of automated gating methods against manual gating done in flowJo. This package allows you to import basic flowJo workspaces into BioConductor and replicate the gating from flowJo using the flowCore functionality. Gating hierarchies, groups of samples, compensation, and transformation are performed so that the output matches the flowJo analysis.

License Artistic-2.0

LazyLoad yes

Imports Biobase, BiocGenerics, graph, graphics, grDevices, lattice, methods, stats, stats4, utils, RBGL, XML, tools, gridExtra, Rgraphviz, data.table, dplyr, latticeExtra, Rcpp, RColorBrewer, stringr, scales, flowViz, matrixStats

Collate 'AllGenerics.R' 'AllClasses.R' 'GatingHierarchy_Methods.R' 'GatingSet_Methods.R' 'GatingSetList_Methods.R' 'RcppExports.R' 'filterObject_Methods.R' 'add_Methods.R' 'flowJoWorkspace_Methods.R' 'flow_trans.R' 'getDescendants.R' 'getSingleCellExpression.R' 'getStats.R' 'merge_GatingSet.R' 'moveNode.R' 'setGate_Methods.R' 'updateIndices.R' 'utils.R' 'zzz.R'

Depends R (>= 2.16.0), flowCore (>= 1.45.14), ncdfFlow (>= 2.25.4)

biocViews ImmunoOncology, FlowCytometry, DataImport, Preprocessing, DataRepresentation

Suggests testthat, flowWorkspaceData, knitr, ggcyto, parallel

LinkingTo Rcpp, BH (>= 1.62.0-1), RProtoBufLib (>= 1.3.7), cytolib (>= 1.3.2)

VignetteBuilder knitr

SystemRequirements xml2, GNU make, C++11

RoxygenNote 6.0.1

git_url <https://git.bioconductor.org/packages/flowWorkspace>

git_branch RELEASE_3_8

git_last_commit eac7b2d

git_last_commit_date 2019-01-04

Date/Publication 2019-04-15

R topics documented:

flowWorkspace-package	4
add,GatingSet,list-method	4
asinhtGml2_trans	7
asinh_Gml2	8
booleanFilter-class	9
checkRedundantNodes	10
clone	11
compensate,GatingSet,ANY-method	11
compute_timestep	12
dropRedundantChannels	13
dropRedundantNodes	13
estimateLogicle.GatingHierarchy	14
extract_cluster_pop_name_from_node	15
filterObject,rectangleGate-method	15
fix_channel_slash	16
flowData,GatingSet-method	16
flowJo.fasinh	17
flowJo.flog	18
flowJoTrans	19
flowJoWorkspace-class	19
flowJo_biexp_trans	20
flowJo_fasinh_trans	21
flowWorkspace.par.init	21
flowWorkspace.par.set	22
flow_breaks	22
flow_trans	23
GatingHierarchy-class	24
GatingSet,character,character-method	24
GatingSet-class	25
GatingSetList-class	27
getCompensationMatrices,GatingHierarchy-method	29
getCompensationObj	30
getData,GatingHierarchy,missing-method	30
getDescendants	31
getFJWSubsetIndices	32
getGate,GatingHierarchy,character-method	32
getIndiceMat	33
getIndices,GatingHierarchy,character-method	34
getIndices,GatingSet,name-method	35
getKeywords,flowJoWorkspace,character-method	35
getLogLevel	36
getMergedStats	37

getNode, GatingSet-method	37
getParent, GatingSet, character-method	38
getProp, GatingHierarchy, character-method	39
getSampleGroups, flowJoWorkspace-method	41
getSamples, flowJoWorkspace-method	41
getSingleCellExpression, GatingSetList, character-method	42
getStats	44
getTransformations, GatingHierarchy-method	45
gh_check_cluster_node	46
gh_get_cluster_labels	47
groupByChannels	47
groupByTree	48
insertGate	48
isGated	49
isNcdf	50
keyword, GatingHierarchy, character-method	50
lapply, GatingSet-method	51
length, GatingSet-method	52
logicGml2_trans	52
logic_trans	53
logtGml2_trans	54
markernames, GatingHierarchy-method	54
mkformula	56
moveNode	56
ncFlowSet	57
openWorkspace, character-method	57
parseWorkspace, flowJoWorkspace-method	58
pData, GatingHierarchy-method	60
plot, GatingSet, missing-method	61
plotGate	62
plotPopCV, GatingHierarchy-method	64
plot_diff_tree	65
pop.MFI	66
prettyAxis	66
recompute, GatingSet-method	67
sampleNames, GatingHierarchy-method	68
save_gs	68
set.count.xml	70
setGate, GatingHierarchy, character, filter-method	70
setNode, GatingHierarchy, character, character-method	71
standardize-GatingSet	72
subset.GatingSet	73
transform, GatingSet-method	73
transformerList	74
updateChannels	75
updateIndices, GatingHierarchy, character, logical-method	76

flowWorkspace-package *Import and replicate flowJo workspaces and gating schemes using flowCore.*

Description

Import flowJo workspaces into R. Generate the flowJo gating hierarchy and gates using flowCore functionality. Transform and compensate data in accordance with flowJo settings. Plot gates, gating hierarchies, population statistics, and compare flowJo vs flowCore population summaries.

Details

Package:	flowWorkspace
Type:	Package
Version:	0.5.40
Date:	2011-03-04
License:	Artistic 2.0
LazyLoad:	yes
Depends:	R (>= 2.16.0),Rcpp (>= 0.9.9)

Author(s)

Greg Finak, Mike Jiang

References

<http://www.rglab.org/>

add,GatingSet,list-method

Create a GatingSet and add/remove the flowCore gate(or population) to/from a GatingHierarchy/GatingSet.

Description

GatingSet method creates a gatingset from a flowSet with the ungated data as the root node. add method add the flowCore gate to a GatingHierarchy/GatingSet. setGate method update the gate of one population node in GatingHierarchy/GatingSet. Rm method Remove the population node from a GatingHierarchy/GatingSet. They are equivalent to the workFlow,add and Rm methods in flowCore package. recompute method does the actual gating after the gate is added,i.e. calculating the event indices according to the gate definition.

Usage

```
## S4 method for signature 'GatingSet,list'  
add(wf, action, ...)  
  
## S4 method for signature 'GatingSetList,list'  
add(wf, action, ...)  
  
## S4 method for signature 'GatingSet,filtersList'  
add(wf, action, ...)  
  
## S4 method for signature 'GatingSet,filterList'  
add(wf, action, validityCheck = TRUE, ...)  
  
## S4 method for signature 'GatingSetList,filterList'  
add(wf, action, ...)  
  
## S4 method for signature 'GatingSetList,filtersList'  
add(wf, action, ...)  
  
## S4 method for signature 'GatingSet,filter'  
add(wf, action, ...)  
  
## S4 method for signature 'GatingSet,filters'  
add(wf, action, ...)  
  
## S4 method for signature 'GatingSetList,filter'  
add(wf, action, ...)  
  
## S4 method for signature 'GatingSetList,filters'  
add(wf, action, ...)  
  
## S4 method for signature 'GatingHierarchy,filter'  
add(wf, action, ...)  
  
## S4 method for signature 'GatingHierarchy,filters'  
add(wf, action, names = NULL, ...)  
  
## S4 method for signature 'GatingHierarchy,quadGate'  
add(wf, action, names = NULL, ...)  
  
## S4 method for signature 'GatingHierarchy,logical'  
add(wf, action, parent, name, recompute,  
    cluster_method_name = NULL, ...)  
  
## S4 method for signature 'GatingHierarchy,factor'  
add(wf, action, name = NULL, ...)  
  
## S4 method for signature 'GatingHierarchy,logicalFilterResult'  
add(wf, action, ...)  
  
## S4 method for signature 'GatingHierarchy,multipleFilterResult'  
add(wf, action, name = NULL,
```

```

... )

## S4 method for signature 'character,GatingSet,character'
Rm(symbol, envir, subSymbol, ...)

## S4 method for signature 'character,GatingSetList,character'
Rm(symbol, envir, subSymbol, ...)

## S4 method for signature 'character,GatingHierarchy,character'
Rm(symbol, envir, subSymbol,
    ...)

```

Arguments

wf	A GatingHierarchy or GatingSet
action	A filter or a list of filters to be added to the GatingHierarchy or GatingSet.
...	some other arguments to specify how the gates are added to the gating tree. <ul style="list-style-type: none"> negated: a logical scalar to specify whether the gate is negated, which means the the population outside of the gate will be kept as the result population. It is FALSE by default.
validityCheck	logical whether to check the consistency of tree structure across samples. default is TRUE. Can be turned off when speed is preferred to the robustness.
names	a character vector of length four, which specifies the population names resulted by adding a quadGate.
parent	a character scalar to specify the parent node name where the new gate to be added to, by default it is NULL, which indicates the root node
name	a character scalar to specify the node name of population that is generated by the gate to be added.
recompute	a logical flag The order of the names is clock-wise starting from the top left quadrant population.
symbol	A character identifies the population node in a GatingHierarchy or GatingSet to remove
envir	A GatingHierarchy or GatingSet
subSymbol	Not used.

Value

GatingSet method returns a GatingSet object with just root node. add method returns a population node ID (or four population node IDs when adding a quadGate) that uniquely identify the population node within a GatingHierarchy.

See Also

[GatingSet-class](#)

Examples

```

## Not run:
  data(GvHD)
#select raw flow data

```

```

fs<-GvHD[1:3]

#transform the raw data
tf <- transformList(colnames(fs[[1]])[3:6], asinh, transformationId="asinh")
fs_trans<-transform(fs,tf)

#add transformed data to a gatingset
gs <- GatingSet(fs_trans)
gs
getNodeIDs(gs[[1]]) #only contains root node

#add one gate
rg <- rectangleGate("FSC-H"=c(200,400), "SSC-H"=c(250, 400),
  filterId="rectangle")

nodeID<-add(gs, rg)#it is added to root node by default if parent is not specified
nodeID
getNodeIDs(gs[[1]]) #the second population is named after filterId of the gate

#add a quadGate
qg <- quadGate("FL1-H"=2, "FL2-H"=4)
nodeIDs<-add(gs,qg,parent="rectangle")
nodeIDs #quadGate produces four population nodes
getNodeIDs(gs[[1]]) #population names are named after dimensions of gate if not specified

#add a boolean Gate
bg<-booleanFilter(`CD15 FITC-CD45 PE+`|`CD15 FITC+CD45 PE-`)
bg
nodeID2<-add(gs,bg,parent="rectangle")
nodeID2
getNodeIDs(gs[[1]])
#do the actual gating
recompute(gs)

#plot one gate for one sample
plotGate(gs[[1]],"rectangle")
plotGate(gs[[1]],nodeIDs) #may be smoothed automatically if there are not enough events after gating

#plot gates across samples using lattice plot
plotGate(gs,nodeID)
#plot all gates for one sample
plotGate(gs[[1]])#boolean gate is skipped by default
plotGate(gs[[1]],bool=TRUE)

#plot the gating hierarchy
require(Rgraphviz)
plot(gs[[1]])
#remove one node causing the removal of all the descendants
Rm('rectangle', gs)
getNodeIDs(gs[[1]])

## End(Not run)

```

Description

Used to construct inverse hyperbolic sine transform object.

Usage

```
asinhtGml2_trans(..., n = 6, equal.space = FALSE)
```

Arguments

... parameters passed to asinh_Gml2
 n desired number of breaks (the actual number will be different depending on the data range)
 equal.space whether breaks at equal-spaced intervals

Value

asinhtGml2 transformation object

Examples

```
trans.obj <- asinhtGml2_trans(equal.space = TRUE)
data <- 1:1e3
brks.func <- trans.obj[["breaks"]]
brks <- brks.func(data)
brks # fasin space displayed at raw data scale

#transform it to verify it is equal-spaced at transformed scale
trans.func <- trans.obj[["transform"]]
brks.trans <- trans.func(brks)
brks.trans
```

asinh_Gml2	<i>inverse hyperbolic sine transform function generator (GatingML 2.0 version)</i>
------------	--

Description

hyperbolic sine/inverse hyperbolic sine transform function constructor. It is simply a special form of flowJo.fasinh with length set to 1 and different default values for parameters t, m, a.

Usage

```
asinh_Gml2(T = 262144, M = 4.5, A = 0, inverse = FALSE)
```

Arguments

T numeric the maximum value of input data
 M numeric the full width of the transformed display in asymptotic decades
 A numeric Additional negative range to be included in the display in asymptotic decades
 inverse whether to return the inverse function

Value

fasinh/fsinh transform function

Examples

```
trans <- asinh_Gml2()
data.raw <- c(1,1e2,1e3)
data.trans <- trans(data.raw)
data.trans

inverse.trans <- asinh_Gml2(inverse = TRUE)
inverse.trans(data.trans)
```

booleanFilter-class *A class describing logical operation (& or |) of the reference populations*

Description

booleanFilter class inherits class [expressionFilter](#) and exists for the purpose of methods dispatching.

booleanFilter is a constructor from an expression

char2booleanFilter is a constructor from a character string

Usage

```
booleanFilter(expr, ..., filterId = "defaultBooleanFilter")

char2booleanFilter(expr, ..., filterId = "defaultBooleanFilter")

## S4 method for signature 'booleanFilter'
show(object)
```

Arguments

expr	expression
...	further arguments to the expression
filterId	character identifier
object	booleanFilter

See Also

[addGatingHierarchy](#)

Examples

```
# "4+/TNFa+" and "4+/IL2+" are two existing gates
#note: no spaces between node names and & , ! operators
booleanFilter(`4+/TNFa+&!4+/IL2+`)

#programmatically
n1 <- "4+/TNFa+"
n2 <- "4+/IL2+"
exprs <- paste0(n1, "&!", n2)
call <- substitute(booleanFilter(v), list(v = as.symbol(exprs)))
eval(call)
```

checkRedundantNodes	<i>try to determine the redundant terminal(or leaf) nodes that can be removed</i>
---------------------	---

Description

These leaf nodes make the gating trees to be different from one another and can be removed by the subsequent convenient call [dropRedundantNodes](#).

Usage

```
checkRedundantNodes(x, path = "auto", ...)
```

Arguments

x	GatingSet or list of groups(each group is a list of 'GatingSet'). When it is a list, it is usually the outcome from groupByTree .
path	argumented passed to getNode s. The default value is "auto".
...	other arguments passed to getNode s.

Value

a list of the character vectors indicating the nodes that are considered to be redundant for each group of GatingSets.

Examples

```
## Not run:
gslist <- list(gs1, gs2, gs3, gs4, gs5)
gs_groups <- groupByTree(gslist)
toRm <- checkRedundantNodes(gs_groups)

## End(Not run)
```

clone	<i>clone a GatingSet</i>
-------	--------------------------

Description

clone a GatingSet

Usage

```
clone(x, ...)
```

Arguments

x	A GatingSet
...	ncdfFile = NULL: see clone.ncdfFlowSet

Details

Note that the regular R assignment operation on a GatingSet object does not return the copy as one would normally expect because the GatingSet contains environment slots (and external pointer for GatingSet), which require deep-copying. So make sure to use this clone method in order to make a copy of existing object.

Value

A copy of a given GatingSet.

Examples

```
## Not run:
  #G is a GatingSet
  G1<-clone(G)

## End(Not run)
```

compensate,GatingSet,ANY-method	<i>compensate the flow data associated with the GatingSet</i>
---------------------------------	---

Description

The compensation is saved in the GatingSet and can be retrieved by [getCompensationMatrices](#).

Usage

```
## S4 method for signature 'GatingSet,ANY'
compensate(x, spillover)

## S4 method for signature 'GatingSetList,ANY'
compensate(x, spillover)
```

Arguments

x GatingSet or GatingSetList
 spillover compensation object or a list of compensation objects

Value

a GatingSet or GatingSetList object with the underlying flow data compensated.

Examples

```
## Not run:

cfile <- system.file("extdata","compdata","compmatrix", package="flowCore")
comp.mat <- read.table(cfile, header=TRUE, skip=2, check.names = FALSE)
## create a compensation object
comp <- compensation(comp.mat,compensationId="comp1")
#add it to GatingSet
gs <- compensate(gs, comp)

## End(Not run)
```

compute_timestep	<i>compute time step from fcs keyword</i>
------------------	---

Description

compute time step from fcs keyword

Usage

```
compute_timestep(kw, unit.range, timestep.source = c("Timestep", "BTIM"))
```

Arguments

kw list of keywords
 unit.range the actual measured time unit range
 timestep.source either "Timestep" or "BTIM". prefer to \$Timestep keyword when it is non
 NULL

dropRedundantChannels *Remove the channels from flow data that are not used by gates*

Description

Removing these redundant channels can help standardize the channels across different GatingSet objects and make them mergable.

Usage

```
dropRedundantChannels(gs, ...)
```

Arguments

gs	a GatingSet
...	other arguments passed to getNodes method

Value

a new GatingSet object that has redundant channels removed. Please note that this new object shares the same reference (or external pointers) with the original GatingSets.

Examples

```
## Not run:
gs_new <- dropRedundantChannels(gs)

## End(Not run)
```

dropRedundantNodes *Remove the terminal leaf nodes that make the gating trees to be different from one another.*

Description

It is usually called after [groupByTree](#) and [checkRedundantNodes](#). The operation is done in place through external pointers which means all the original GatingSets are modified.

Usage

```
dropRedundantNodes(x, toRemove)
```

Arguments

x	GatingSet or list of groups(each group is a list of 'GatingSet'). When it is a list, it is usually the outcome from groupByTree .
toRemove	list of the node sets to be removed. its length must equals to the length of 'x'. When x is a list, toRemove is usually the outcome from checkRedundantNodes .

Examples

```
## Not run:
gslist <- list(gs1, gs2, gs3, gs4, gs5)
gs_groups <- groupByTree(gslist)
toRm <- checkRedundantNodes(gs_groups)
dropRedundantNodes(gs_groups, toRm)

#Now they can be merged into a single GatingSetList.
#Note that the original gs objects are all modified in place.
GatingSetList(gslist)

## End(Not run)
```

```
estimateLogicle.GatingHierarchy
```

Compute logicle transformation from the flowData associated with a GatingHierarchy

Description

See details in [estimateLogicle](#)

Usage

```
## S3 method for class 'GatingHierarchy'
estimateLogicle(x, channels, ...)
```

Arguments

x	a GatingHierarchy
channels	channels or markers for which the logicle transformation is to be estimated.
...	other arguments

Value

transformerList object

Examples

```
## Not run:
# gs is a GatingSet
trans.list <- estimateLogicle(gs[[1]], c("CD3", "CD4", "CD8"))
# trans.list is a transformerList that can be directly applied to GatingSet
gs <- transform(gs, trans.list)

## End(Not run)
```

```
extract_cluster_pop_name_from_node
```

Extract the population name from the node path It strips the parent path and cluster method name.

Description

Extract the population name from the node path It strips the parent path and cluster method name.

Usage

```
extract_cluster_pop_name_from_node(node, cluster_method_name)
```

Arguments

```
node           population node path
cluster_method_name
                the name of the clustering method
```

Examples

```
extract_cluster_pop_name_from_node("cd3/flowClust_pop1", "flowClust")
#returns "pop1"
```

```
filterObject,rectangleGate-method
```

convert flowCore filter to a list It convert the flowCore gate to a list whose structure can be understood by underlying c++ data structure.

Description

convert flowCore filter to a list

It convert the flowCore gate to a list whose structure can be understood by underlying c++ data structure.

Usage

```
## S4 method for signature 'rectangleGate'
filterObject(x)

## S4 method for signature 'polygonGate'
filterObject(x)

## S4 method for signature 'booleanFilter'
filterObject(x)

## S4 method for signature 'ellipsoidGate'
filterObject(x)

## S4 method for signature 'logical'
filterObject(x)
```

Arguments

x filter a flowCore gate. Currently supported gates are: "rectangleGate", "polygonGate", "ellipsoidGate" and "booleanFilter"

Value

a list

fix_channel_slash toggle the channel names between '/' and '_' character

Description

FlowJoX tends to replace '/' in the original channel names with '_' in gates and transformations. We need to do the same to the flow data but also need to change it back during the process since the channel names of the flowSet can't be modified until the data is fully compensated.

Usage

```
fix_channel_slash(chnls, slash_loc = NULL)
```

Arguments

chnls the channel names

slash_loc a list that records the locations of the original slash character within each channel name so that when restoring slash it won't tamper the the original '_' character.

Value

the toggled channel names

flowData,GatingSet-method
Fetch or replace the flowData object associated with a GatingSet .

Description

Accessor method that gets or replaces the flowset/ncdfFlowSet object in a GatingSet or GatingHierarchy

Usage

```
## S4 method for signature 'GatingSet'
flowData(x)

## S4 replacement method for signature 'GatingSet'
flowData(x) <- value
```


Arguments

x	A GatingSet
value	The replacement flowSet or ncdfFlowSet object

Details

Accessor method that sets or replaces the ncdfFlowSet object in the GatingSet or GatingHierarchy.

Value

the object with the new flowSet in place.

flowJo.fasinh	<i>inverse hyperbolic sine transform function</i>
---------------	---

Description

hyperbolic sine/inverse hyperbolic sine (flowJo-version) transform function constructor

Usage

```
flowJo.fasinh(m = 4, t = 12000, a = 0.7, length = 256)
```

```
flowJo.fsinh(m = 4, t = 12000, a = 0.7, length = 256)
```

Arguments

m	numeric the full width of the transformed display in asymptotic decades
t	numeric the maximum value of input data
a	numeric Additional negative range to be included in the display in asymptotic decades
length	numeric the maximum value of transformed data

Value

fasinh/fsinh transform function

Examples

```
trans <- flowJo.fasinh()
data.raw <- c(1,1e2,1e3)
data.trans <- trans(data.raw)
data.trans
```

```
inverse.trans <- flowJo.fsinh()
inverse.trans(data.trans)
```

flowJo.flog	<i>flog transform function</i>
-------------	--------------------------------

Description

flog transform function constructor. It is different from flowCore version of [logtGml2](#) in the way that it reset negative input so that no NAN will be returned.

Usage

```
flowJo.flog(decade = 4.5, offset = 1, max_val = 262144, min_val = 0,  
            scale = 1, inverse = FALSE)
```

Arguments

decade	number of decades
offset	offset to the original input
max_val	top of scale value
min_val	lower bound of scaled value (where negative raw value gets truncated at)
scale	the linear scale factor
inverse	whether return the inverse function

Value

flog(or its inverse) transform function

Examples

```
trans <- flowJo.flog()  
data.raw <- c(1,1e2,1e3)  
data.trans <- trans(data.raw)  
data.trans  
  
inverse.trans <- flowJo.flog(inverse = TRUE)  
inverse.trans(data.trans)  
  
#negative input  
data.raw <- c(-10,1e2,1e3)  
data.trans <- trans(data.raw)  
data.trans  
inverse.trans(data.trans)#we lose the original value at lower end since flog can't restore negative value  
  
#different  
trans <- flowJo.flog(decade = 3, max_val = 1e3)  
data.trans <- trans(data.raw)  
data.trans  
inverse.trans <- flowJo.flog(decade = 3, max_val = 1e3, inverse = TRUE)  
inverse.trans(data.trans)
```

flowJoTrans	<i>construct the flowJo-type biexponential transformation function</i>
-------------	--

Description

Normally it was parsed from flowJo xml workspace. This function provides the alternate way to construct the flowJo version of logicle transformation function within R.

Usage

```
flowJoTrans(channelRange = 4096, maxValue = 262144, pos = 4.5, neg = 0,
  widthBasis = -10, inverse = FALSE)
```

Arguments

channelRange	numeric the maximum value of transformed data
maxValue	numeric the maximum value of input data
pos	numeric the full width of the transformed display in asymptotic decades
neg	numeric Additional negative range to be included in the display in asymptotic decades
widthBasis	numeric unkown.
inverse	logical whether to return the inverse transformation function.

Examples

```
trans <- flowJoTrans()
data.raw <- c(-1, 1e3, 1e5)
data.trans <- trans(data.raw)
round(data.trans)
inv <- flowJoTrans(inverse = TRUE)
round(inv(data.trans))
```

flowJoWorkspace-class *An R representation of a flowJo workspace.*

Description

Objects can be created by calls of the form `new("flowJoWorkspace.xml", ...)`.

Slots

version: Object of class "character". The version of the XML workspace.
file: Object of class "character". The file name.
.cache: Object of class "environment". An environment for internal use.
path: Object of class "character". The path to the file.
doc: Object of class "XMLInternalDocument". The XML document object.
options: Object of class "integer". The XML parsing options passed to [xmlTreeParse](#).

See Also

[GatingSet GatingHierarchy](#)

Examples

```
require(flowWorkspaceData)
d<-system.file("extdata",package="flowWorkspaceData")
wsfile<-list.files(d,pattern="A2004Analysis.xml",full=TRUE)
ws <- openWorkspace(wsfile);
ws
getSamples(ws)
```

flowJo_biexp_trans *flowJo biexponential transformation.*

Description

Used for constructing biexponential transformation object.

Usage

```
flowJo_biexp_trans(..., n = 6, equal.space = FALSE)
```

Arguments

...	parameters passed to flowJoTrans
n	desired number of breaks (the actual number will be different depending on the data range)
equal.space	whether breaks at equal-spaced intervals

Value

biexponential transformation object

Examples

```
data(GvHD)
fr <- GvHD[[1]]
data.raw <- exprs(fr)[, "FL1-H"]
trans.obj <- flowJo_biexp_trans(equal.space = TRUE)
brks.func <- trans.obj[["breaks"]]
brks <- brks.func(data.raw)
brks # biexp space displayed at raw data scale

#transform it to verify it is equal-spaced at transformed scale
trans.func <- trans.obj[["transform"]]

print(trans.func(brks))
```

flowJo_fasinh_trans *flowJo inverse hyperbolic sine transformation.*

Description

Used to construct the inverse hyperbolic sine transform object.

Usage

```
flowJo_fasinh_trans(..., n = 6, equal.space = FALSE)
```

Arguments

...	parameters passed to flowJo.fasinh
n	desired number of breaks (the actual number will be different depending on the data range)
equal.space	whether breaks at equal-spaced intervals

Value

fasinh transformation object

Examples

```
trans.obj <- flowJo_fasinh_trans(equal.space = TRUE)
data <- 1:1e3
brks.func <- trans.obj[["breaks"]]
brks <- brks.func(data)
brks # fasinh space displayed at raw data scale

#transform it to verify it is equal-spaced at transformed scale
trans.func <- trans.obj[["transform"]]
round(trans.func(brks))
```

flowWorkspace.par.init

workspace version is parsed from xml node '/Workspace/version' in flowJo workspace and matched with this list to dispatch to the one of the three workspace parsers

Description

workspace version is parsed from xml node '/Workspace/version' in flowJo workspace and matched with this list to dispatch to the one of the three workspace parsers

Usage

```
flowWorkspace.par.init()
```

`flowWorkspace.par.set` *flowWorkspace.par.set sets a set of parameters in the flowWorkspace package namespace.*

Description

`flowWorkspace.par.set` sets a set of parameters in the `flowWorkspace` package namespace.
`flowWorkspace.par.get` gets a set of parameters in the `flowWorkspace` package namespace.

Usage

```
flowWorkspace.par.set(name, value)

flowWorkspace.par.get(name = NULL)
```

Arguments

<code>name</code>	The name of a parameter category to get or set.
<code>value</code>	A named list of values to set for category name or a list of such lists if name is missing.

Details

It is currently used to add/remove the support for a specific flowJo versions (parsed from xml node `'/Workspace/version'` in flowJo workspace)

Examples

```
#get the flowJo versions currently supported
old <- flowWorkspace.par.get("flowJo_versions")

#add the new version
old[["win"]] <- c(old[["win"]], "1.7")
flowWorkspace.par.set("flowJo_versions", old)

flowWorkspace.par.get("flowJo_versions")
```

`flow_breaks`

Generate the breaks that makes sense for flow data visualization

Description

It is mainly used as helper function to construct breaks function used by `'trans_new'`.

Usage

```
flow_breaks(x, n = 6, equal.space = FALSE, trans.fun, inverse.fun)
```

Arguments

x	the raw data values
n	desired number of breaks (the actual number will be different depending on the data range)
equal.space	whether breaks at equal-spaced intervals
trans.fun	the transform function (only needed when equal.space is TRUE)
inverse.fun	the inverse function (only needed when equal.space is TRUE)

Value

either 10^n intervals or equal-spaced(after transformed) intervals in raw scale.

Examples

```
data(GvHD)
fr <- GvHD[[1]]
data.raw <- exprs(fr)[, "FL1-H"]
flow_breaks(data.raw)

trans <- logicleTransform()
inv <- inverseLogicleTransform(trans = trans)
myBrks <- flow_breaks(data.raw, equal.space = TRUE, trans = trans, inv = inv)
round(myBrks)
#to verify it is equally spaced at transformed scale
print(trans(myBrks))
```

flow_trans	<i>helper function to generate a trans objects Used by other specific trans constructor</i>
------------	---

Description

helper function to generate a trans objects Used by other specific trans constructor

Usage

```
flow_trans(name, trans.fun, inverse.fun, equal.space = FALSE, n = 6)
```

Arguments

name	transformation name
trans.fun	the transform function (only needed when equal.space is TRUE)
inverse.fun	the inverse function (only needed when equal.space is TRUE)
equal.space	whether breaks at equal-spaced intervals
n	desired number of breaks (the actual number will be different depending on the data range)

GatingHierarchy-class *Class GatingHierarchy*

Description

GatingHierarchy is a class for representing the gating hierarchy, which can be either imported from a flowJo workspace or constructed in R.

Details

There is a one-to-one correspondence between GatingHierarchy objects and FCS files in the flowJo workspace. Each sample (FCS file) is associated with its own GatingHierarchy. It is also more space efficient by storing gating results as logical/bit vector instead of copying the raw data.

Given a GatingHierarchy, one can extract the data associated with any subpopulation, extract gates, plot gates, and extract population proportions. This facilitates the comparison of manual gating methods with automated gating algorithms.

See Also

[GatingSet](#)

Examples

```
require(flowWorkspaceData)
d<-system.file("extdata",package="flowWorkspaceData")
wsfile<-list.files(d,pattern="A2004Analysis.xml",full=TRUE)
ws <- openWorkspace(wsfile);
G<-try(parseWorkspace(ws,path=d,name=1));
  gh <- G[[1]]
  getPopStats(gh);
  plotPopCV(gh)
  nodes <- getNodes(gh)
  thisNode <- nodes[4]
  plotGate(gh,thisNode);
  getGate(gh,thisNode);
  getData(gh,thisNode)
```

GatingSet,character,character-method

constructors for GatingSet

Description

construct object from xml workspace file and a list of sampleIDs (not intended to be called by user.)

construct a gatingset with empty trees (just root node)

construct object from existing gating hierarchy(gating template) and flow data

Usage

```
## S4 method for signature 'character,character'
GatingSet(x, y, guides, includeGates = FALSE,
  sampNloc = "keyword", xmlParserOption, wsType)

## S4 method for signature 'flowSet,ANY'
GatingSet(x)

## S4 method for signature 'GatingHierarchy,character'
GatingSet(x, y, path = ".", ...)
```

Arguments

x	character or flowSet or GatingHierarchy
y	character or missing
guides	character vectors to uniquely identify each sample (Sometime FCS file names alone may not be unique)
includeGates	logical whether to parse the gates or just simply extract the flowJo stats
sampNloc	character scalar indicating where to get sampleName(or FCS filename) within xml workspace. It is either from "keyword" or "sampleNode".
xmlParserOption	integer option passed to xmlTreeParse
wsType	character workspace type, can be value of "win", "macII", "vX", "macIII".
path	character specifies the path to the flow data (FCS files)
...	other arguments. see parseWorkspace

Examples

```
## Not run:
#fdata could be a flowSet or ncdfFlowSet
gs <- GatingSet(fdata)

## End(Not run)
```

GatingSet-class	<i>Class "GatingSet"</i>
-----------------	--------------------------

Description

GatingSet holds a set of GatingHierarchy objects, representing a set of samples and the gating scheme associated with each.

[subsets a GatingSet or GatingSetList using the familiar bracket notation

[[extract a GatingHierarchy object from a GatingSet or GatingSetList

Usage

```
## S4 method for signature 'GatingSet,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'GatingSet,numeric'
x[[i, j, ...]]

## S4 method for signature 'GatingSetList,ANY'
x[i, j, ..., drop = TRUE]
```

Arguments

x	GatingSet or GatingSetList
i	numeric or logical or character used as sample index
j	not used
...	not used
drop	not used

Details

Objects stores a collection of GatingHierarchies and represent a group in a flowJo workspace. A GatingSet can have two “states”. After a call to `parseWorkspace(...,execute=FALSE)`, the workspace is imported but the data is not. Setting `execute` to `TRUE` is needed in order to load, transform, compensate, and gate the associated data. Whether or not a GatingHierarchy has been applied to data is encoded in the `flag` slot. Some methods will warn the user, or may not function correctly if the GatingHierarchy has not been executed. This mechanism is in place, largely for the purpose of speed when working with larger workspaces. It allows the use to load a workspace and subset desired samples before proceeding to load the data.

Slots

`FCSPath`: deprecated

`data`: Object of class "flowSet". flow data associated with this GatingSet

`flag`: Object of class "logical". A flag indicating whether the gates, transformations, and compensation matrices have been applied to data, or simply imported.

`axis`: Object of class "list". stores the axis information used for `plotGate`.

`pointer`: Object of class "externalptr". points to the gating hierarchy stored in C data structure.

`guid`: Object of class "character". the unique identifier for GatingSet object.

`transformation`: Object of class "list". a list of transformation objects used by GatingSet.

`compensation`: Object of class "ANY". compensation objects.

See Also

[GatingHierarchy](#) [flowJoWorkspace](#) [parseWorkspace](#)

Examples

```
require(flowWorkspaceData)
d<-system.file("extdata",package="flowWorkspaceData")
wsfile<-list.files(d,pattern="A2004Analysis.xml",full=TRUE)
ws <- openWorkspace(wsfile);
G<-try(parseWorkspace(ws,execute=TRUE,path=d,name=1));
plotPopCV(G);
```

GatingSetList-class *Class "GatingSetList"*

Description

A list of of GatingSet objects. This class exists for method dispatching.
 use GatingSetList constructor to create a GatingSetList from a list of GatingSet

Usage

```
GatingSetList(x, samples = NULL)

## S4 method for signature 'GatingSetList,missing'
rbind2(x, y = "missing", ...)
```

Arguments

x	a list of GatingSet
samples	character vector specifying the order of samples. if not specified, the samples are ordered as the underlying stored order.
y	missing not used.
...	other arguments passed to rbind2 method for ncdfflowList

Details

Objects store a collection of GatingSets, which usually has the same gating trees and markers. Most GatingSets methods can be applied to GatingSetList.

See Also

[GatingSet](#) [GatingHierarchy](#)

Examples

```
## Not run:
#load several GatingSets from disk
gs_list<-lapply(list.files("../gs_toMerge",full=T) ,function(this_folder){
  load_gs(this_folder)
})

#gs_list is a list
gs_groups <- merge(gs_list)
```

```

#returns a list of GatingSetList objects
gslist2 <- gs_groups[[2]]
#gslist2 is a GatingSetList that contains multiple GatingSets and they share the same gating and data structure
gslist2
class(gslist2)
sampleNames(gslist2)

#reference a GatingSet by numeric index
gslist2[[1]]
#reference a GatingSet by character index
gslist2[["30104.fcs"]]

#loop through all GatingSets within GatingSetList
lapply(gslist2,sampleNames)

#subset a GatingSetList by [
sampleNames(gslist2[c(4,1)])
sampleNames(gslist2[c(1,4)])
gslist2[c("30104.fcs")]

#get flow data from it
getData(gslist2)
#get gated flow data from a particular population
getData(gslist2, "3+")

#extract the gates associated with one population
getGate(gslist2,"3+")
getGate(gslist2,5)

#extract the pheno data
pData(gslist2[3:1])
#modify the pheno data
pd <- pData(gslist2)
pd$id <- 1:nrow(pd)
pData(gslist2) <- pd
pData(gslist2[3:2])

#plot the gate
plotGate(gslist2[1:2],5,smooth=T)
plotGate_labkey(gslist2[3:4],4,x="<APC Cy7-A>",y="<PE Tx RD-A>",smooth=T)

#remove cerntain gates by loop through GatingSets
getNodes(gslist2[[1]])
lapply(gslist2,function(gs)Rm("Excl",gs))

#extract the stats
getPopStats(gslist2)
#extract statistics by using getQASStats defined in QUALIFIER package
res<-getQASStats(gslist2[c(4,2)],isMFI=F,isSpike=F,nslaves=1)

#archive the GatingSetList
save_gslist(gslist2, path = "~/rglab/workspace/flowIncubator/output/gslist",overwrite=T)
gslist2 <- load_gslist(path = "~/rglab/workspace/flowIncubator/output/gslist")

#convert GatingSetList into one GatingSet by rbind2
gs_merged2 <- rbind2(gslist2,ncdfFile=path.expand(tempfile(tmpdir="~/rglab/workspace/flowIncubator/output/gs_merged2

```

```
## End(Not run)

## Not run:
samleNames(gsA) # return A1, A2
samleNames(gsB) # return B1, B2
gs.list <- list(gsA, gsB)
gslist<- GatingSetList(gs.list)
sampleNames(gslist) #return A1,A2,B1,B2

#set different order when create the GatingSetList
gslist<- GatingSetList(gs.list, samples = c("A1","B1", "A2", "B2"))
sampleNames(gslist) #return A1,B1,A2,B2

## End(Not run)
```

getCompensationMatrices,GatingHierarchy-method

Retrieve the compensation matrices from a GatingHierarchy

Description

Retrieve the compensation matrices from a GatingHierarchy.

Usage

```
## S4 method for signature 'GatingHierarchy'
getCompensationMatrices(x)
```

Arguments

x A GatingHierarchy object.

Details

Return all the compensation matrices in a GatingHierarchy.

Value

A list of matrix representing the spillover matrix in GatingHierarchy

Examples

```
## Not run:
#Assume gh is a GatingHierarchy
getCompensationMatrices(gh);

## End(Not run)
```

`getCompensationObj` *extract compensation object from GatingSet*

Description

extract compensation object from GatingSet

Usage

```
getCompensationObj(gs, sampleName)
```

Arguments

<code>gs</code>	GatingSet
<code>sampleName</code>	sample name

`getData,GatingHierarchy,missing-method`
get gated flow data from a GatingHierarchy/GatingSet/GatingSetList

Description

get gated flow data from a GatingHierarchy/GatingSet/GatingSetList

Usage

```
## S4 method for signature 'GatingHierarchy,missing'
getData(obj, y, ...)

## S4 method for signature 'GatingHierarchy,character'
getData(obj, y, ...)

## S4 method for signature 'GatingSet,missing'
getData(obj, y, ...)

## S4 method for signature 'GatingSet,character'
getData(obj, y, ...)

## S4 method for signature 'GatingSetList,ANY'
getData(obj, y, ...)
```

Arguments

<code>obj</code>	A GatingHierarchy, GatingSet or GatingSetList object.
<code>y</code>	character the node name or full(/partial) gating path. If not specified, will return the complete flowFrame/flowSet at the root node.
<code>...</code>	arguments passed to <code>ncdfFlow::[]</code>

Details

Returns a flowFrame/flowSet containing the events in the gate defined at node y. Subset membership can be obtained using getIndices. Population statistics can be obtained using getPop and getPopStats. When calling getData on a GatingSet, the trees representing the GatingHierarchy for each sample in the GatingSet are presumed to have the same structure. To update the data, use flowData method.

Value

A flowFrame object if obj is a GatingHierarchy. A flowSet or ncdfFlowSet if a GatingSet. A ncdfFlowList if a GatingSetList.

See Also

[flowData](#) [getIndices](#) [getPopStats](#)

Examples

```
## Not run:
#G is a GatingSet
geData(G,3) #get a flowSet constructed from the third node / population in the tree.
geData(G,"cd4")

#gh is a GatingHierarchy
getData(gh)

## End(Not run)
```

getDescendants	<i>get all the descendant nodes for the given ancestor</i>
----------------	--

Description

get all the descendant nodes for the given ancestor

Usage

```
getDescendants(gh, node, ...)
```

Arguments

gh	GatingHierarchy
node	the node path
...	passed to getNode call

Examples

```
library(flowWorkspace)
dataDir <- system.file("extdata",package="flowWorkspaceData")
suppressMessages(gs <- load_gs(list.files(dataDir, pattern = "gs_manual",full = TRUE)))
getDescendants(gs[[1]], "CD4")
getDescendants(gs[[1]], "CD8", path = "auto")
```

getFJWSubsetIndices *Fetch the indices for a subset of samples in a flowJo workspace, based on a keyword value pair*

Description

This function will calculate the indices of a subset of samples in a flowJoWorkspace, based on a keyword/value filter. It is applied to a specific group of samples in the workspace. The output is meant to be passed to the subset= argument of parseWorkspace.

Usage

```
getFJWSubsetIndices(ws, key = NULL, value = NULL, group,
  requiregates = TRUE)
```

Arguments

ws	flowJoWorkspace object
key	character The name of the keyword.
value	character The value of the keyword.
group	numeric The group of samples to subset.
requiregates	TRUE or FALSE, specifying whether we include only samples that have gates attached or whether we include any sample in the workspace.

Details

Returns an index vector into the samples in a flowJo workspace for use with parseWorkspace(subset=), based on a keyword/value filter in a specific group of samples.

Value

A numeric vector of indices.

See Also

[parseWorkspace](#)

getGate,GatingHierarchy,character-method
Return the flowCore gate definition associated with a node in a GatingHierarchy/GatingSet.

Description

Return the flowCore gate definition object associated with a node in a GatingHierarchy or GatingSet object.

Usage

```
## S4 method for signature 'GatingHierarchy,character'
getGate(obj, y)

## S4 method for signature 'GatingSet,character'
getGate(obj, y)

## S4 method for signature 'GatingSetList,character'
getGate(obj, y)
```

Arguments

obj A GatingHierrarchy or GatingSet
y A character the name or full(/partial) gating path of the node of interest.

Value

A gate object from flowCore. Usually a polygonGate, but may be a rectangleGate. Boolean gates are represented by a "BooleanGate" S3 class. This is a list boolean gate definition that references populations in the GatingHierarchy and how they are to be combined logically. If obj is a GatingSet, assuming the trees associated with each GatingHierarchy are identical, then this method will return a list of gates, one for each sample in the GatingSet corresponding to the same population indexed by y.

See Also

[getData](#) [getNode](#)s

Examples

```
## Not run: #gh is a GatingHierarchy
getGate(gh, "CD3") #return the gate for the fifth node in the tree, but fetch it by name.
#G is a GatingSet
getGate(G, "CD3") #return a list of gates for the fifth node in each tree

## End(Not run)
```

getIndiceMat

Return the single-cell matrix of 1/0 dichotomized expression

Description

Return the single-cell matrix of 1/0 dichotomized expression

Usage

```
getIndiceMat(gh, y)
```

Arguments

gh GatingHierarchy object
y character node name

getIndices,GatingHierarchy,character-method

Get the membership indices for each event with respect to a particular gate in a GatingHierarchy

Description

Returns a logical vector that describes whether each event in a sample is included or excluded by this gate.

Usage

```
## S4 method for signature 'GatingHierarchy,character'
getIndices(obj, y)
```

Arguments

obj	A GatingHierarchy representing a sample.
y	A character giving the name or full(/partial) gating path of the population / node of interest.

Details

Returns a logical vector that describes whether each event in the data file is included in the given gate of this GatingHierarchy. The indices are for all events in the file, and do not reflect the population counts relative to the parent but relative to the root. To get population frequencies relative to the parent one cross-tabulate the indices of y with the indices of its parent.

Value

A logical vector of length equal to the number of events in the FCS file that determines whether each event is or is not included in the current gate.

Note

Generally you should not need to use getIndices but the more convenient methods getProp and getPopStats which return population frequencies relative to the parent node. The indices returned reference all events in the file and are not directly suitable for computing population statistics, unless subsets are taken with respect to the parent populations.

See Also

[getPopStats](#)

Examples

```
## Not run:
#G is a gating hierarchy
#Return the indices for population 5 (topological sort)
getIndices(G,getNodes(G,tsort=TRUE)[5]);

## End(Not run)
```

getIndices,GatingSet,name-method

routine to return the indices by specify boolean combination of reference nodes:

Description

It adds the boolean gates and does the gating on the fly, and return the indices associated with that bool gate, and remove the bool gate the typical use case would be extracting any-cytokine-expressed cells

Usage

```
## S4 method for signature 'GatingSet,name'
getIndices(obj, y)
```

Arguments

obj	GatingSet
y	a quoted expression.

Examples

```
## Not run:

getIndices(gs,quote(`4+/TNFa+|4+/IL2+`))

## End(Not run)
```

getKeywords,flowJoWorkspace,character-method

Get Keywords

Description

Retrieve keywords associated with a workspace

Usage

```
## S4 method for signature 'flowJoWorkspace,character'
getKeywords(obj, y, ...)
```

```
## S4 method for signature 'flowJoWorkspace,numeric'
getKeywords(obj, y, ...)
```

Arguments

obj A flowJoWorkspace
 y ccharacter or numeric specifying the sample name or sample ID
 ... other arguments sampNloc a character the location where the sample name is specified. See parseWorkspace for more details.

Details

Retrieve a list of keywords from a flowJoWorkspace

Value

A list of keyword - value pairs.

Examples

```
require(flowWorkspaceData)
d<-system.file("extdata",package="flowWorkspaceData")
wsfile<-list.files(d,pattern="manual.xml",full=TRUE)
ws <- openWorkspace(wsfile);

getSamples(ws)
res <- try(getKeywords(ws,"CytoTrol_CytoTrol_1.fcs"), silent = TRUE)
print(res[[1]])
getKeywords(ws, 1)
```

getLogLevel	<i>get/set the log level</i>
-------------	------------------------------

Description

It is helpful sometime to get more detailed print out for the purpose of trouble shooting

Usage

```
getLogLevel()

setLogLevel(level = "none")
```

Arguments

level a character that represents the log level , can be value of c("none", "GatingSet", "GatingHierarchy", "Population", "gate") default is "none" , which does not print any information from C parser.

Value

a character that represents the internal log level

Examples

```
getLogLevel()
setLogLevel("Population")
getLogLevel()
```

getMergedStats

Get Cell Population Statistics and Sample Metadata

Description

Get Cell Population Statistics and Sample Metadata

Usage

```
getMergedStats(object, ...)
```

Arguments

object	a GatingSet or GatingSetList
...	additional arguments passed to getPopStats

Value

a data.table of merged population statistics with sample metadata.

Examples

```
## Not run:
#G is a GatingSetList
stats = getMergedStats(G)

## End(Not run)
```

getNodes, GatingSet-method

Get the names of all nodes from a gating hierarchy.

Description

getNodes returns a character vector of names of the nodes (populations) in the GatingSet.

Usage

```
## S4 method for signature 'GatingSet'
getNodes(x, y = NULL, order = "regular",
  path = "full", showHidden = FALSE, ...)
```

Arguments

x	A GatingSet Assuming the gating hierarchy are identical within the GatingSet, the Gating tree of the first sample is used to query the node information.
y	A character not used.
order	order=c("regular", "tsort", "bfs") returns the nodes in regular, topological or breadth-first sort order. "regular" is default.
path	A character or numeric scalar. when numeric, it specifies the fixed length of gating path (length 1 displays terminal name). When character, it can be either 'full' (full path, which is default) or 'auto' (display the shortest unique gating path from the bottom of gating tree).
showHidden	logical whether to include the hidden nodes
...	Additional arguments.

Details

integer indices of nodes are based on regular order,so whenever need to map from character node name to integer node ID,make sure to use default order which is regular.

Value

getNode returns a character vector of node/population names, ordered appropriately.

getParent,GatingSet,character-method

Return the name of the parent population or a list of child populations of the current population in the GatingHierarchy

Description

Returns the name of the parent population or a character/numeric vector of all the children of the current population in the given GatingHierarchy

Usage

```
## S4 method for signature 'GatingSet,character'
getParent(obj, y, ...)
```

```
## S4 method for signature 'GatingSet,character'
getChildren(obj, y, showHidden = TRUE, ...)
```

Arguments

obj	A GatingHierarchy
y	a character/numeric the name or full(/partial) gating path or node indices of the node / population.
...	other arguments passed to getNode methods
showHidden	logical whether to include the hidden children nodes.

Value

getParent returns a character vector, the name of the parent population. getChildren returns a character or numeric vector of the node names or node indices of the child nodes of the current node. An empty vector if the node has no children.

See Also

[getNode](#)s

Examples

```
## Not run:
#G is a gatinghierarchy
#return the name of the parent of the fifth node in the hierarchy.
getParent(G,getNode(G[[1]][5]))
n<-getNode(G,tsort=T)[4];
getChildren(G,n);#Get the names of the child nodes of the 4th node in this gating hierarchy.
getChildren(G,4);#Get the ids of the child nodes

## End(Not run)
```

getProp,GatingHierarchy,character-method

Return a table of population statistics for all populations in a GatingHierarchy/GatingSet or the population proportions or the total number of events of a node (population) in a GatingHierarchy

Description

getProp calculates the population proportion (events in the gate / events in the parent population) associated with a node in the GatingHierarchy. getPopStats is more useful than getPop. Returns a table of population statistics for all populations in a GatingHierarchy/GatingSet. Includes the xml counts, openCyto counts and frequencies. getTotal returns the total number of events in the gate defined in the GatingHierarchy object

Usage

```
## S4 method for signature 'GatingHierarchy,character'
getProp(x, y, xml = FALSE)

## S4 method for signature 'GatingHierarchy,character'
getTotal(x, y, xml = FALSE)

## S4 method for signature 'GatingHierarchy'
getPopStats(x, path = "auto", ...)

## S4 method for signature 'GatingSet'
getPopStats(x, statistic = c("freq", "count"),
  xml = FALSE, subpopulations = NULL, format = c("long", "wide"),
  path = "auto", ...)

## S4 method for signature 'GatingSetList'
getPopStats(x, format = c("long", "wide"), ...)
```

Arguments

x	A GatingHierarchy or GatingSet
y	character node name or path
xml	logical indicating whether the statistics come from xml (if parsed from xml workspace) or from openCyto.
path	character see getNode s
...	Additional arguments passed to getNode s
statistic	character specifies the type of population statistics to extract.(only valid when format is "wide"). Either "freq" or "count" is currently supported.
subpopulations	character vector to specify a subset of populations to return. (only valid when format is "long")
format	character value of c("wide", "long") specifying whether to organize the output in long or wide format

Details

getPopStats returns a table population statistics for all populations in the gating hierarchy. The output is useful for verifying that the import was successful, if the xml and openCyto derived counts don't differ much (i.e. if they have a small coefficient of variation.) for a GatingSet, returns a matrix of proportions for all populations and all samples getProp returns the proportion of cells in the gate, relative to its parent. getTotal returns the total number of events included in this gate. The contents of "thisTot" variable in the "metadata" environment of the nodeData element associated with the gating tree and gate / population.

Value

getPopStats returns a data.frame with columns for the population name, xml derived counts, openCyto derived counts, and the population proportions (relative to their parent population). getProp returns a population frequency numeric. getTotal returns a numeric value of the total number of elements in the population.

See Also

[getNode](#)s

Examples

```
## Not run:
#gh is a GatingHierarchy
getPopStats(gh);
#proportion for the fifth population
getProp(gh,getNode(gh)[5])
getTotal(gh,getNode(gh,tsort=T)[5])

#gs is a GatingSet
getPopStats(gs)
#optionally output in long format as a data.table
getPopStats(gs, format = "long", path = "auto")
#only get stats for a subset of populations
getPopStats(gs, format = "long", subpopulations = getNode(gs)[4:6])

## End(Not run)
```

getSampleGroups, flowJoWorkspace-method

Get a table of sample groups from a flowJo workspace

Description

Return a data frame of sample group information from a flowJo workspace

Usage

```
## S4 method for signature 'flowJoWorkspace'  
getSampleGroups(x)
```

Arguments

x A flowJoWorkspace object.

Details

Returns a table of samples and groups defined in the flowJo workspace

Value

A data.frame containing the groupName, groupID, and sampleID for each sample in the workspace. Each sample may be associated with multiple groups.

See Also

[flowJoWorkspace-class](#) [openWorkspace](#)

Examples

```
## Not run:  
#ws is a flowJoWorkspace  
getSampleGroups(ws);  
  
## End(Not run)
```

getSamples, flowJoWorkspace-method

Get a list of samples from a flowJo workspace

Description

Return a data frame of samples contained in a flowJo workspace

Usage

```
## S4 method for signature 'flowJoWorkspace'  
getSamples(x, sampNloc = "keyword")
```

Arguments

x A flowJoWorkspace
 sampNloc character either "keyword" or "sampleNode". see [parseWorkspace](#)

Details

Returns a data.frame of samples in the flowJoWorkspace, including their sampleID, name, and compID (compensation matrix ID).

Value

A data.frame with columns sampleID, name, and compID if x is a flowJoWorkspace.

Examples

```
## Not run:
#ws is a flowJoWorkspace
getSamples(ws);

## End(Not run)
```

getSingleCellExpression,GatingSetList,character-method

Return the cell events data that express in any of the single populations defined in y

Description

Returns a list of matrix containing the events that expressed in any one of the populations defined in y

Usage

```
## S4 method for signature 'GatingSetList,character'
getSingleCellExpression(x, nodes, ...)

## S4 method for signature 'GatingSet,character'
getSingleCellExpression(x, nodes, ...)

getSingleCellExpressionByGate(...)
```

Arguments

x A GatingSet or GatingSetList object .
 nodes character vector specifying different cell populations
 ... other arguments
 other.markers character vector specifying the extra markers/channels to be returned besides the ones derived from "nodes" and "map" argument.It is only valid when threshold is set to FALSE.
 swap logical indicates whether channels and markers of flow data are swapped.

threshold logical indicates whether to threshold the flow data by setting intensity value to zero when it is below the gate threshold.

marginal logical indicates whether the gate is treated as 1d marginal gate. Default is TRUE, which means markers are determined either by node name or by 'map' argument explained below. When FALSE, the markers are determined by the gate dimensions. and node name and 'map' argument are ignored.

map a named list providing the mapping between node names (as specified in the gating hierarchy of the gating set) and channel names (as specified in either the desc or name columns of the parameters of the associated flowFrames in the GatingSet). see examples.

ignore.case whether to ignore case when match the marker names. Default is FALSE.

mc.cores passed to mclapply. Default is 1, which means the process runs in serial mode. When it is larger than 1, parallel mode is enabled.

Value

A list of numeric matrices

Author(s)

Mike Jiang <wjiang2@fhcrc.org>

See Also

[getIndices](#) [getPopStats](#)

Examples

```
## Not run:
#G is a GatingSet
nodes <- c("4+/TNFa+", "4+/IL2+")
res <- getSingleCellExpression(gs, nodes)
res[[1]]

# if it fails to match the given nodes to the markers, then try to provide the mapping between node and marker
res <- getSingleCellExpression(gs, nodes , map = list("4+/TNFa+" = "TNFa", "4+/IL2+" = "IL2"))

# It can also operate on the 2d gates by setting marginal to FALSE
# The markers are no longer deduced from node names or supplied by map
# Instead, it retrieves the markers that are associated with the gates
nodes <- c("4+/TNFa+IFNg+", "4+/IL2+IL3+")
res <- getSingleCellExpression(gs, nodes, marginal = FALSE)
#or simply call convenient wrapper
getSingleCellExpressionByGate(gs, nodes)

## End(Not run)
```

getStats

Exact MFI from populations(or nodes) for all the markers

Description

It calculates the MFI for each marker.

Usage

```
getStats(x, ...)

## S3 method for class 'GatingSetList'
getStats(x, ...)

## S3 method for class 'GatingSet'
getStats(x, ...)

## S3 method for class 'GatingHierarchy'
getStats(x, nodes = NULL, type = "count",
         inverse.transform = FALSE, stats.fun.arg = list(), ...)
```

Arguments

x	a GatingSet or GatingHierarchy
...	arguments passed to getNode s method.
nodes	the character vector specifies the populations of interest. default is all available nodes
type	the character vector specifies the type of pop stats or a function used to compute population stats. when character, it is expected to be either "count" or "percent". Default is "count" (total number of events in the populations). when a function, it takes a flowFrame object through 'fr' argument and return the stats as a named vector.
inverse.transform	logical flag . Whether inverse transform the data before computing the stats.
stats.fun.arg	a list of arguments passed to 'type' when 'type' is a function.

Value

a data.table that contains MFI values for each marker per column along with 'pop' column and 'sample' column (when used on a 'GatingSet')

Examples

```
## Not run:
dataDir <- system.file("extdata", package="flowWorkspaceData")
suppressMessages(gs <- load_gs(list.files(dataDir, pattern = "gs_manual", full = TRUE)))

# get stats all nodes
dt <- getStats(gs) #default is "count"

nodes <- c("CD4", "CD8")
```

```

getStats(gs, nodes, "percent")

# pass a build-in function
getStats(gs, nodes, type = pop.MFI)

# compute the stats based on the raw data scale
getStats(gs, nodes, type = pop.MFI, inverse.transform = TRUE)

# supply user-defined stats fun
pop.quantiles <- function(fr){
  chnls <- colnames(fr)
  res <- matrixStats::colQuantiles(exprs(fr), probs = 0.75)
  names(res) <- chnls
  res
}
getStats(gs, nodes, type = pop.quantiles)

## End(Not run)

```

```
getTransformations,GatingHierarchy-method
```

Return a list of transformations or a transformation in a GatingHierarchy

Description

Return a list of all the transformations or a transformation in a GatingHierarchy

Usage

```

## S4 method for signature 'GatingHierarchy'
getTransformations(x, channel = NULL,
  inverse = FALSE, only.function = TRUE, ...)

```

Arguments

x	A GatingHierarchy object
channel	character channel name
inverse	logical whether to return the inverse transformation function. Valid when only.funtion is TRUE
only.function	logical whether to return the function or the entire transformer object(see scales package) that contains transform and inverse and breaks function.
...	other arguments equal.spaced logical passed to the breaks functio to determine whether to break at 10^n or equally spaced intervals

Details

Returns a list of the transformations or a transformation in the flowJo workspace. The list is of length L, where L is the number of distinct transformations applied to samples in the flowJoWorkspace. Each element of L is itself a list of length M, where M is the number of parameters that were transformed for a sample or group of samples in a flowJoWorkspace. For example, if a sample has 10

parameters, and 5 are transformed during analysis, using two different sets of transformations, then L will be of length 2, and each element of L will be of length 5. The elements of L represent channel- or parameter-specific transformation functions that map from raw intensity values to channel-space used by flowJo.

Value

lists of functions(or transform objects when only.function is FALSE), with each element of the list representing a transformation applied to a specific channel/parameter of a sample.

Examples

```
## Not run:
#Assume gh is a GatingHierarchy
getTransformations(gh); # return a list transformation functions
getTransformations(gh, inverse = TRUE); # return a list inverse transformation functions
getTransformations(gh, channel = "FL1-H") # only return the transformation associated with given channel
getTransformations(gh, channel = "FL1-H", only.function = FALSE) # return the entire transform object

## End(Not run)
```

gh_check_cluster_node *check if a node is clustering node*

Description

check if a node is clustering node

Usage

```
gh_check_cluster_node(gh, node)
```

Arguments

gh	GatingHierarchy
node	the population/node name or path

Value

the name of the clustering method. If it is not cluster node, returns NULL

gh_get_cluster_labels *Retrieve the cluster labels from the cluster nodes*

Description

Clustering results are stored as individual gated nodes. This helper function collect all the gating indices from the same clustering run (identified by 'parent' node and 'cluster_method_name" and merge them as a single factor.

Usage

```
gh_get_cluster_labels(gh, parent, cluster_method_name)
```

Arguments

gh	GatingHierarchy
parent	the parent population/node name or path
cluster_method_name	the name of the clustering method

groupByChannels *split GatingSets into groups based on their flow channels*

Description

Sometime it is gates are defined on the different dimensions across different GatingSets, (e.g. 'FSC-W' or 'SSC-H' may be used for Y axis for cytokines) These difference in dimensions may not be critical since they are usually just used for visualization(istead of thresholding events) But this prevents the gs from merging because they may not be collected across batces Thus we have to separate them if we want to visualize the gates.

Usage

```
groupByChannels(x)
```

Arguments

x	a list of GatingSets
---	----------------------

Examples

```
## Not run:
gslist <- list(gs1, gs2, gs3, gs4, gs5)
gs_groups <- groupByChannels(gslist)

## End(Not run)
```

groupByTree	<i>split GatingSets into groups based on their gating schemes Be careful that the splitted resluts still points to the original data set!!</i>
-------------	--

Description

It allows isomorphism in Gating tree and ignore difference in hidden nodes i.e. tree is considered to be the same as long as `getNode(gh, path = "auto", showHidden = F)` returns the same set

Usage

```
groupByTree(x)
```

Arguments

x a list of GatingSets or one GatingSet

Value

when x is a GatingSet, this function returns a list of sub-GatingSets When x is a list of GatingSets, it returns a list of list, each list itself is a list of GatingSets, which share the same gating tree.

Examples

```
## Not run:
gslist <- list(gs1, gs2, gs3, gs4, gs5)
gs_groups <- groupByTree(gslist)

## End(Not run)
```

insertGate	<i>insert a dummy gate to the GatingSet</i>
------------	---

Description

Is is useful trick to make the tree structure of GatingSet same with other so that they can be combined into a 'GatingSetList' object. (deprecated by 'moveNode')

Usage

```
insertGate(gs, gate, parent, children)
```

Arguments

gs	GatingSet to work with
gate	filter a dummy gate to be inserted, its 'filterId' will be used as the population name
parent	character full path of parent node where the new dummy gate to be added to
children	character full path of children nodes that the new dummy gate to be parent of

Value

a new GatingSet object with the new gate added but share the same flow data with the input 'GatingSet'

Examples

```
## Not run:
#construct a dummy singlet gate
dummyGate <- rectangleGate("FSC-A" = c(-Inf, Inf), "FSC-H" = c(-Inf, Inf), filterId = "singlets")
#insert it between the 'not debris' node and "lymph" node
gs_clone <- insertGate(gs, dummyGate, "not debris", "lymph")

## End(Not run)
```

isGated	<i>The flags of gate nodes isGated checks if a node is already gated isNegated checks if a node is negated. isHidden checks if a node is hidden.</i>
---------	--

Description

The flags of gate nodes isGated checks if a node is already gated isNegated checks if a node is negated. isHidden checks if a node is hidden.

Usage

```
isGated(obj, y, ...)
```

S4 method for signature 'GatingHierarchy,character'

```
isGated(obj, y)
```

```
isNegated(obj, y, ...)
```

S4 method for signature 'GatingHierarchy,character'

```
isNegated(obj, y)
```

```
isHidden(obj, y, ...)
```

S4 method for signature 'GatingHierarchy,character'

```
isHidden(obj, y)
```

Arguments

obj	GatingHierarchy
y	node/gating path
...	not used

isNcdf	<i>determine the flow data associated with a Gating Hierarchy is based on 'ncdfFlowSet' or 'flowSet'</i>
--------	--

Description

determine the flow data associated with a Gating Hierarchy is based on 'ncdfFlowSet' or 'flowSet'

Usage

```
isNcdf(x)
```

Arguments

x	GatingHierarchy object
---	------------------------

Value

logical

keyword,GatingHierarchy,character-method	<i>Retrieve a specific keyword for a specific sample in a GatingHierarchy or or set of samples in a GatingSet or GatingSetList</i>
--	--

Description

Retrieve a specific keyword for a specific sample in a GatingHierarchy or or set of samples in a GatingSet or GatingSetList

Usage

```
## S4 method for signature 'GatingHierarchy,character'  
keyword(object, keyword)
```

```
## S4 method for signature 'GatingHierarchy,missing'  
keyword(object, keyword = "missing", ...)
```

```
## S4 method for signature 'GatingSet,missing'  
keyword(object, keyword = "missing", ...)
```

```
## S4 method for signature 'GatingSet,character'  
keyword(object, keyword)
```

```
## S4 method for signature 'GatingSetList,missing'  
keyword(object, keyword = "missing", ...)
```

```
## S4 method for signature 'GatingSetList,character'  
keyword(object, keyword)
```

Arguments

object	GatingHierarchy or GatingSet or GatingSetList
keyword	character specifying keyword name. When missing, extract all keywords.
...	other arguments passed to keyword-methods

Details

See keyword in Package 'flowCore'

See Also

[keyword-methods](#)

Examples

```
## Not run:
# get all the keywords from all samples
keyword(G)
# get all the keywords from one sample
keyword(G[[1]])
# filter the instrument setting
keyword(G[[1]], compact = TRUE)
# get single keyword from all samples
keyword(G, "FILENAME")
# get single keyword from one sample
keyword(G[[1], "FILENAME"])

## End(Not run)
```

lapply,GatingSet-method

apply FUN to each sample (i.e. GatingHierarchy)

Description

sample names are used for names of the returned list

Usage

```
## S4 method for signature 'GatingSet'
lapply(X, FUN, ...)
```

Arguments

X	GatingSet
FUN	function to be applied to each sample in 'GatingSet'
...	other arguments to be passed to 'FUN'

length, GatingSet-method

Methods to get the length of a GatingSet

Description

Return the length of a GatingSet or GatingSetList object (number of samples).

Usage

```
## S4 method for signature 'GatingSet'
length(x)
```

```
## S4 method for signature 'GatingSet'
show(object)
```

Arguments

x	GatingSet
object	object

logicleGml2_trans *GatingML2 version of logicle transformation.*

Description

The only difference from [logicle_trans](#) is it is scaled to c(0,1) range.

Usage

```
logicleGml2_trans(T = 262144, M = 4.5, W = 0.5, A = 0, n = 6,
  equal.space = FALSE)
```

Arguments

T, M, W, A	see logicletGml2
n	desired number of breaks (the actual number will be different depending on the data range)
equal.space	whether breaks at equal-spaced intervals

Value

a logicleGml2 transformation object

Examples

```

trans.obj <- logicleGm12_trans(equal.space = TRUE)
data <- 1:1e3
brks.func <- trans.obj[["breaks"]]
brks <- brks.func(data)
brks # logicle space displayed at raw data scale
#transform it to verify the equal-spaced breaks at transformed scale
print(trans.obj[["transform"]](brks))

```

logicle_trans	<i>logicle transformation.</i>
---------------	--------------------------------

Description

Used for construct logicle transform object.

Usage

```
logicle_trans(..., n = 6, equal.space = FALSE)
```

Arguments

...	arguments passed to logicleTransform.
n	desired number of breaks (the actual number will be different depending on the data range)
equal.space	whether breaks at equal-spaced intervals

Value

a logicle transformation object

Examples

```

trans.obj <- logicle_trans(equal.space = TRUE)
data <- 1:1e3
brks.func <- trans.obj[["breaks"]]
brks <- brks.func(data)
brks # logicle space displayed at raw data scale
#transform it to verify the equal-spaced breaks at transformed scale
print(trans.obj[["transform"]](brks))

```

logtGml2_trans	<i>Gating-ML 2.0 Log transformation.</i>
----------------	--

Description

Used to construct flog transformer object. (which uses a specialized [flowJo.flog](#))

Usage

```
logtGml2_trans(M = 4.5, T = 262144, n = 6, equal.space = FALSE)
```

Arguments

M	number of decades
T	top scale value
n	desired number of breaks (the actual number will be different depending on the data range)
equal.space	whether breaks at equal-spaced intervals

Value

logtGml2 transformation object

Examples

```
trans.obj <- logtGml2_trans(M = 1, T = 1e3, equal.space = TRUE)
data <- 1:1e3
brks.func <- trans.obj[["breaks"]]
brks <- brks.func(data)
brks # fsinh space displayed at raw data scale

#transform it to verify it is equal-spaced at transformed scale
trans.func <- trans.obj[["transform"]]
brks.trans <- trans.func(brks)
brks.trans
```

markernames,GatingHierarchy-method	<i>Get/set the column(channel) or marker names</i>
------------------------------------	--

Description

It simply calls the methods for the underlying flow data (flowSet/ncdfFlowSet/ncdfFlowList).

Usage

```
## S4 method for signature 'GatingHierarchy'
markernames(object)

## S4 replacement method for signature 'GatingHierarchy'
markernames(object) <- value

## S4 method for signature 'GatingHierarchy'
colnames(x, do.NULL = "missing",
  prefix = "missing")

## S4 replacement method for signature 'GatingHierarchy'
colnames(x) <- value

## S4 method for signature 'GatingSet'
markernames(object)

## S4 replacement method for signature 'GatingSet'
markernames(object) <- value

## S4 method for signature 'GatingSet'
colnames(x, do.NULL = "missing", prefix = "missing")

## S4 replacement method for signature 'GatingSet'
colnames(x) <- value
```

Arguments

value	named character vector for markernames<-, regular character vector for colnames<-
x, object	GatingHierarchy/GatingSet/GatingSetList
do.NULL, prefix	not used.

Examples

```
## Not run:

markers.new <- c("CD4", "CD8")
chnls <- c("<B710-A>", "<R780-A>")
names(markers.new) <- chnls
markernames(gs) <- markers.new

chnls <- colnames(gs)
chnls.new <- chnls
chnls.new[c(1,4)] <- c("fsc", "ssc")
colnames(gs) <- chnls.new

## End(Not run)
```

mkformula	<i>make a formula from a character vector</i>
-----------	---

Description

construct a valid formula to be used by flowViz::xyplot

Usage

```
mkformula(dims, isChar = FALSE)
```

Arguments

dims	a character vector that contains y , x axis, if it is unnamed, then treated as the order of c(y,x)
isChar	logical flag indicating whehter to return a formula or a pasted string

Value

when isChar is TRUE, return a character, otherwise coerce it as a formula

Examples

```
all.equal(mkformula(c("SSC-A", "FSC-A"), `SSC-A` ~ `FSC-A`)#unnamed vecotr
all.equal(mkformula(c(x = "SSC-A", y = "FSC-A"), `FSC-A` ~ `SSC-A`)#named vector
```

moveNode	<i>move a node along with all of its descendant nodes to the given ancestor</i>
----------	---

Description

move a node along with all of its descendant nodes to the given ancestor

Usage

```
moveNode(gh, node, to)
```

Arguments

gh	GatingHierarchy
node	the node to be moved
to	the new parent node under which the node will be moved to

Examples

```

library(flowWorkspace)
dataDir <- system.file("extdata",package="flowWorkspaceData")
suppressMessages(gs <- load_gs(list.files(dataDir, pattern = "gs_manual",full = TRUE)))
gh <- gs[[1]]
old.parent <- getParent(gh, "CD4")
new.parent <- "singlets"
moveNode(gh, "CD4", new.parent)
getParent(gh, "CD4")

```

ncFlowSet

*Fetch the flowData object associated with a GatingSet.***Description**

Deprecated by flowData method

Deprecated by flowData method

openWorkspace, character-method

*Open/Close a flowJo workspace***Description**

Open a flowJo workspace and return a flowJoWorkspace object. Close a flowJoWorkspace, destroying the internal representation of the XML document, and freeing the associated memory.

Usage

```

## S4 method for signature 'character'
openWorkspace(file, options = 0, ...)

## S4 method for signature 'flowJoWorkspace'
closeWorkspace(workspace)

```

Arguments

file	Full path to the XML flowJo workspace file.
options	xml parsing options passed to xmlTreeParse
...	other arguments passed to xmlTreeParse
workspace	A flowJoWorkspace

Details

Open an XML flowJo workspace file and return a flowJoWorkspace object. The workspace is represented using a XMLInternalDocument object. Close a flowJoWorkspace after finishing with it. This is necessary to explicitly clean up the C-based representation of the XML tree. (See the XML package).

Value

a flowJoWorkspace object.

Examples

```
## Not run:
file<-"myworkspace.xml"
ws<-openWorkspace(file);
class(ws); #flowJoWorkspace
closeWorkspace(ws);

## End(Not run)
```

parseWorkspace, flowJoWorkspace-method

Parse a flowJo Workspace

Description

Function to parse a flowJo Workspace, generate a GatingHierarchy or GatingSet object, and associated flowCore gates. The data are not loaded or acted upon until an explicit call to recompute() is made on the GatingHierarchy objects in the GatingSet.

Usage

```
## S4 method for signature 'flowJoWorkspace'
parseWorkspace(obj, ...)
```

Arguments

- | | |
|-----|--|
| obj | A flowJoWorkspace to be parsed. |
| ... | <ul style="list-style-type: none"> • name numeric or character. The name or index of the group of samples to be imported. If NULL, the groups are printed to the screen and one can be selected interactively. Usually, multiple groups are defined in the flowJo workspace file. • execute TRUE FALSE a logical specifying if the gates, transformations, and compensation should be immediately calculated after the flowJo workspace have been imported. TRUE by default. • isNcdf TRUE FALSE logical specifying if you would like to use netcdf to store the data, or if you would like to keep all the flowFrames in memory. For a small data set, you can safely set this to FALSE, but for larger data, we suggest using netcdf. You will need the netcdf C library installed. • subset numeric vector specifying the subset of samples in a group to import. Or a character specifying the FCS filenames to be imported. Or an expression to be passed to 'subset' function to filter samples by 'pData' (Note that the columns referred by the expression must also be explicitly specified in 'keywords' argument) • requiregates logical Should samples that have no gates be included? • includeGates logical Should gates be imported, or just the data with compensation and transformation? |

- path either a character scalar or data.frame. When character, it is a path to the fcs files that are to be imported. The code will search recursively, so you can point it to a location above the files. When it is a data.frame, it is expected to contain two columns: 'sampleID' and 'file', which is used as the mapping between 'sampleID' and FCS file (absolute) path. When such mapping is provided, the file system searching is avoided.
- sampNloc a character scalar indicating where to get sampleName(or FCS filename) within xml workspace. It is either from "keyword" or "sampleNode".
- compensation=NULL: a compensation or a list of compensations that allow the customized compensation matrix to be used instead of the one specified in flowJo workspace.
- options=0: a integer option passed to [xmlTreeParse](#)
- channel.ignore.case a logical flag indicates whether the colnames(channel names) matching needs to be case sensitive (e.g. compensation, gating..)
- extend_val numeric the threshold that determine whether the gates need to be extended. default is 0. It is triggered when gate coordinates are below this value.
- extend_to numeric the value that gate coordinates are extended to. Default is -4000. Usually this value will be automatically detected according to the real data range. But when the gates needs to be extended without loading the raw data (i.e. execute is set to FALSE), then this hard-coded value is used.
- leaf.bool a logical whether to compute the leaf boolean gates. Default is TRUE. It helps to speed up parsing by turning it off when the statistics of these leaf boolean gates are not important for analysis. (e.g. COMPASS package will calculate them by itself.) If needed, they can be calculated by calling recompute method at later stage.
- additional.keys character vector: The keywords (parsed from FCS header) to be combined(concatenated with "_") with FCS filename to uniquely identify samples. Default is '\$TOT' (total number of cells) and more keywords can be added to make this GUID.
- keywords character vector specifying the keywords to be extracted as pData of GatingSet
- keywords.source character the place where the keywords are extracted from, can be either "XML" or "FCS"
- keyword.ignore.case a logical flag indicates whether the keywords matching needs to be case sensitive.
- ...: Additional arguments to be passed to [read.ncdfFlowSet](#) or [read.flowSet](#).

Details

A flowJoWorkspace is generated with a call to `openWorkspace()`, passing the name of the xml workspace file. This returns a `flowJoWorkspace`, which can be parsed using the `parseWorkspace()` method. The function can be called non-interactively by passing the index or name of the group of samples to be imported via `parseWorkspace(obj,name=x)`, where `x` is either the numeric index, or the name. The `subset` argument allows one to select a set of files from the chosen sample group. The routine will take the intersection of the files in the sample group, the files specified in `subset` and the files available on disk, and import them.

Value

a GatingSet, which is a wrapper around a list of GatingHierarchy objects, each representing a single sample in the workspace. The GatingHierarchy objects contain graphNEL trees that represent the gating hierarchy of each sample. Each node in the GatingHierarchy has associated data, including the population counts from flowJo, the parent population counts, the flowCore gates generated from the flowJo workspace gate definitions. Data are not yet loaded or acted upon at this stage. To execute the gating of each data file, a call to execute() must be made on each GatingHierarchy object in the GatingSet. This is done automatically by default, and there is no more reason to set this argument to FALSE.

See Also

[getSampleGroups,GatingSet](#)

Examples

```
## Not run:
#f is a xml file name of a flowJo workspace
ws <- openWorkspace(f)
#parse the second group
gs <- parseWorkspace(ws, name = 2); #assume that the fcs files are under the same folder as workspace

gs <- parseWorkspace(ws, name = 4
  , path = dataDir      #specify the FCS path
  , subset = "CytoTrol_CytoTrol_1.fcs"  #subset the parsing by FCS filename
  , isNcdf = FALSE)#turn off cdf storage mode (normally you don't want to do this for parsing)

gs <- parseWorkspace(ws, path = dataDir, name = 4
  , keywords = c("PATIENT ID", "SAMPLE ID", "$TOT", "EXPERIMENT NAME") #tell the parser to
  , keywords.source = "XML" # keywords are extracted from xml workspace (alternatively can
  , additional.keys = c("PATIENT ID") #use additional keywords together with FCS filename t
  , execute = F) # parse workspace without the actual gating (can save time if just want to

#subset by pData (extracted from keywords)
gs <- parseWorkspace(ws, path = dataDir, name = 4
  , subset = `TUBE NAME` %in% c("CytoTrol_1", "CytoTrol_2")
  , keywords = "TUBE NAME")

#override the default compensation defined in xml with the customized compensations
gs <- parseWorkspace(ws, name = 2, compensation = comps); #comp is either a compensation object or a list of c

## End(Not run)
```

pData,GatingHierarchy-method

*read/set pData of flow data associated with GatingSet or
GatingSetList*

Description

Accessor method that gets or replaces the pData of the flowset/ncdfFlowSet object in a GatingSet or GatingSetList

Usage

```
## S4 method for signature 'GatingHierarchy'
pData(object)

## S4 method for signature 'GatingSet'
pData(object)

## S4 replacement method for signature 'GatingSet,data.frame'
pData(object) <- value

## S4 replacement method for signature 'GatingSetList,data.frame'
pData(object) <- value
```

Arguments

object	GatingSet or GatingSetList
value	data.frame The replacement of pData for flowSet or ncdfFlowSet object

Value

a data.frame

plot,GatingSet,missing-method
plot a gating tree

Description

Plot a tree/graph representing the GatingHierarchy

Usage

```
## S4 method for signature 'GatingSet,missing'
plot(x, y, ...)

## S4 method for signature 'GatingSet,character'
plot(x, y, ...)
```

Arguments

x	GatingHierarchy or GatingSet. If GatingSet, the first sample will be used to extract gating tree.
y	missing or character specifies.
...	other arguments:

- boolean: TRUE | FALSE logical specifying whether to plot boolean gate nodes. Defaults to FALSE.
- showHidden: TRUE | FALSE logical whether to show hidden nodes
- layout: See [layoutGraph](#) in package Rgraphviz
- width: See [layoutGraph](#) in package Rgraphviz
- height: See [layoutGraph](#) in package Rgraphviz
- fontsize: See [layoutGraph](#) in package Rgraphviz
- labelfontsize: See [layoutGraph](#) in package Rgraphviz
- fixedsize: See [layoutGraph](#) in package Rgraphviz

Examples

```
## Not run:
#gs is a GatingSet
plot(gs) # the same as plot(gs[[1]])
#plot a subtree rooted from 'CD4'
plot(gs, "CD4")

## End(Not run)
```

plotGate	<i>Plot gates and associated cell population contained in a GatingHierarchy or GatingSet</i>
----------	--

Description

When applied to a GatingHierarchy, arrange is set as TRUE, then all the gates associated with it are plotted as different panel on the same page. If arrange is FALSE, then it plots one gate at a time. By default ,merge is set as TRUE, plot multiple gates on the same plot when they share common parent population and axis. When applied to a GatingSet, if lattice is TRUE, it plots one gate (multiple samples) per page , otherwise, one sample (with multiple gates) per page.

Usage

```
plotGate(x, y, ...)

## S4 method for signature 'GatingHierarchy,numeric'
plotGate(x, y, ...)

## S4 method for signature 'GatingSet,missing'
plotGate(x, y, ...)

## S4 method for signature 'GatingSetList,character'
plotGate(x, y, ...)
```

Arguments

- x [GatingSet](#) or [GatingHierarchy](#) object
- y character the node name or full(/partial) gating path or numeric representing the node index in the [GatingHierarchy](#). or missing which will plot all gates and one gate per page. It is useful for generating plots in a multi-page pdf. Nodes can be accessed with [getNode](#).
- ...
- `bool` logical specifying whether to plot boolean gates.
 - `arrange.main` character The title of the main page of the plot. Default is the sample name. Only valid when x is [GatingHierarchy](#)
 - `arrange` logical indicating whether to arrange different populations/nodes on the same page via `arrangeGrob` call.
 - `merge` logical indicating whether to draw multiple gates on the same plot if these gates share the same parent population and same x,y dimensions/parameters;
 - `projections` list of character vectors used to customize x,y axis. By default, the x,y axis are determined by the respective gate parameters. The elements of the list are named by the population name or path (see y). Each element is a pair of named character specifying the channel name(or marker name) for x, y axis. Short form of channel or marker names (e.g. "APC" or "CD3") can be used as long as they can be uniquely matched to the dimensions of flow data. For example, `projections = list("lymph" = c(x = "SSC-A", y = "FSC-A"), "CD3" = c(x = "CD3", y = "SSC-A"))`
 - `par.settings` list of graphical parameters passed to [lattice](#);
 - `gpar` list of grid parameters passed to [grid.layout](#);
 - `lattice` logical deprecated;
 - `formula` formula a formula passed to `xyplot` function of `flowViz`, by default it is NULL, which means the formula is generated according to the x,y parameters associated with gate.
 - `cond` character the conditioning variable to be passed to `lattice` plot.
 - `overlayNode` names. These populations are plotted on top of the existing gates(defined by y argument) as the overlaid dots.
 - `overlay.symbol` A named (`lattice` graphic parameter) list that defines the symbol color and size for each overlaid population. If not given, we automatically assign the colors.
 - `keyLattice` legend parameter for overlay symbols.
 - `default.y` character specifying y channel for `xyplot` when plotting a 1d gate. Default is "SSC-A" and session-wise setting can be stored by `'flowWorkspace.par.set("plotGate", list(default.y = "FSC-A"))'`
 - `type` character either "xyplot" or "densityplot". Default is "xyplot" and session-wise setting can be stored by `'flowWorkspace.par.set("plotGate", list(type = "xyplot"))'`
 - `fitGate` used to disable behavior of plotting the gate region in 1d densityplot. Default is FALSE and session-wise setting can be stored by `'flowWorkspace.par.set("plotGate", list(fitGate = FALSE))'`
 - `strip.ligcal` specifies whether to show pop name in strip box, only valid when x is [GatingHierarchy](#)
 - `strip.text` either "parent" (the parent population name) or "gate" (the gate name).

- raw.scale logical whether to show the axis in raw(untransformed) scale. Default is TRUE and can be stored as session-wise setting by 'flowWorkspace.par.set("plotGate", list(raw.scale = TRUE))'
- xlim, ylim character can be either "instrument" or "data" which determines the x, y axis scale either by instrument measurement range or the actual data range. or numeric which specifies customized range. They can be stored as session-wise setting by 'flowWorkspace.par.set("plotGate", list(xlim = "instrument"))'
- ...
path A character or numeric scalar passed to `getNodePath` method (used to control how the gating/node path is displayed)
... The other additional arguments to be passed to `xyplot`.

Value

a trellis object if arrange is FALSE,

References

<http://www.rglab.org/>

Examples

```
## Not run:
projections <- list("cd3" = c(x = "cd3", y = "AViD")
  , "cd4" = c(x = "cd8", y = "cd4")
  , "cd4/IL2" = c(x = "IL2", y = "IFNg")
  , "cd4/IFNg" = c(x = "IL2", y = "IFNg")
)
plotGate(gh, c("cd3", "cd4", "cd4/IL2", "cd4/IFNg"), path = "auto", projections = projections, gpar = c(nrow

## End(Not run)
## Not run:
#G is a GatingHierarchy
plotGate(G,getNodePath(G)[5]);#plot the gate for the fifth node

## End(Not run)
```

plotPopCV,GatingHierarchy-method

Plot the coefficient of variation between xml and openCyto population statistics for each population in a gating hierarchy.

Description

This function plots the coefficient of variation calculated between the xml population statistics and the openCyto population statistics for each population in a gating hierarchy extracted from a xml Workspace.

Usage

```
## S4 method for signature 'GatingHierarchy'
plotPopCV(x, m = 2, n = 2, path = "auto", ...)

## S4 method for signature 'GatingSet'
plotPopCV(x, scales = list(x = list(rot = 90)),
  path = "auto", ...)
```

Arguments

x	A GatingHierarchy from or a GatingSet.
m	numeric The number of rows in the panel plot. Now deprecated, uses lattice.
n	numeric The number of columns in the panel plot. Now deprecated, uses lattice.
path	character see getNode s
...	Additional arguments to the barplot methods.
scales	list see barchart

Details

The CVs are plotted as barplots across panels on a grid of size m by n.

Value

Nothing is returned.

See Also

[getPopStats](#)

Examples

```
## Not run:
#G is a GatingHierarchy
plotPopCV(G,4,4);

## End(Not run)
```

plot_diff_tree

visualize the tree structure difference among the GatingSets

Description

visualize the tree structure difference among the GatingSets

Usage

```
plot_diff_tree(x, path = "auto", ...)
```

Arguments

x list of groups(each group is a list of 'GatingSet'). it is usually the outcome from [groupByTree](#).

Examples

```
## Not run:
gslist <- list(gs1, gs2, gs3, gs4, gs5)
gs_groups <- groupByTree(gslist)
plot_diff_tree(gs_groups)

## End(Not run)
```

pop.MFI *built-in stats functions.*

Description

pop.MFI computes and returns the median fluorescence intensity for each marker. They are typically used as the arguments passed to `getStats` method to perform the sample-wise population stats calculations.

Usage

```
pop.MFI(fr)
```

Arguments

fr a flowFrame represents a gated population

Value

a named numeric vector

prettyAxis *Determine tick mark locations and labels for a given channel axis*

Description

Determine tick mark locations and labels for a given channel axis

Usage

```
prettyAxis(gh, channel)
```

Arguments

gh GatingHierarchy
channel character channel name

Value

when there is transformation function associated with the given channel, it returns a list of that contains positions and labels to draw on the axis other wise returns NULL

Examples

```
## Not run:
prettyAxis(gh, "<B710-A>")

## End(Not run)
```

```
recompute,GatingSet-method
```

Compute the cell events by the gates stored within the gating tree.

Description

Compute each cell event to see if it falls into the gate stored within the gating tree and store the result as cell count.

Usage

```
## S4 method for signature 'GatingSet'
recompute(x, y = "root", alwaysLoadData = FALSE, ...)

## S4 method for signature 'GatingSetList'
recompute(x, ...)
```

Arguments

x	GatingSet
y	character node name or node path. Default "root". Optional.
alwaysLoadData	logical. Specifies whether to load the flow raw data for gating boolean gates. Default 'FALSE'. Optional. Sometime it is more efficient to skip loading the raw data if all the reference nodes and parent are already gated. 'FALSE' will check the parent node and reference to determine whether to load the data. This check may not be sufficient since the further upstream ancestor nodes may not be gated yet. In that case, we allow the gating to fail and prompt user to recompute those nodes explicitly. When TRUE, then it forces data to be loaded to guarantee the gating process to be uninterrupted at the cost of unnecessary data IO.
...	other arguments leaf.bool whether to compute the leaf boolean gate, default is TRUE

Details

It is usually used immediately after [add](#) or [setGate](#) calls.

sampleNames,GatingHierarchy-method
Get/update sample names in a GatingSet

Description

Return a sample names contained in a GatingSet

Usage

```
## S4 method for signature 'GatingHierarchy'
sampleNames(object)

## S4 method for signature 'GatingSet'
sampleNames(object)

## S4 replacement method for signature 'GatingSet'
sampleNames(object) <- value
```

Arguments

object	or a GatingSet
value	character new sample names

Details

The sample names comes from pdata of fs.

Value

A character vector of sample names

Examples

```
## Not run:
#G is a GatingSet
sampleNames(G)

## End(Not run)
```

save_gs	<i>save/load a GatingSet/GatingSetList to/from disk.</i>
---------	--

Description

Save/load a GatingSet/GatingSetList which is the gated flow data including gates and populations to/from the disk. The GatingSet object The internal C data structure (gating tree),ncdfFlowSet object(if applicable)

Usage

```
save_gs(G, path, overwrite = FALSE, cdf = c("copy", "move", "skip",
      "symlink", "link"), ...)
```

```
load_gs(path)
```

```
save_gslist(gelist, path, ...)
```

```
load_gslist(path)
```

Arguments

G	A GatingSet
path	A character scalar giving the path to save/load the GatingSet to/from.
overwrite	A logical scalar specifying whether to overwrite the existing folder.
cdf	a character scalar. The valid options are : "copy", "move", "skip", "symlink", "link" specifying what to do with the cdf data file. Sometime it is more efficient to move or create a link of the existing cdf file to the archived folder. It is useful to "skip" archiving cdf file if raw data has not been changed.
...	other arguments: not used.
gslist	A GatingSetList

Value

load_gs returns a GatingSet object load_gslist returns a GatingSetList object

See Also

[GatingSet-class](#), [GatingSetList-class](#)

Examples

```
## Not run:
#G is a GatingSet
save_gs(G,path="tempFolder")
G1<-load_gs(path="tempFolder")

#G is a GatingSet

save_gslist(gelist1,path="tempFolder")
gslist2<-load_gslist(path="tempFolder")

## End(Not run)
```

set.count.xml	<i>save the event counts parsed from xml into c++ tree structure</i>
---------------	--

Description

It is for internal use by the diva parser

Usage

```
set.count.xml(gh, node, count)
```

Arguments

gh	GatingHierarchy
node	the unique gating path that uniquely identifies a population node
count	integer number that is events count for the respective gating node directly parsed from xml file

Examples

```
## Not run:
set.count.xml(gh, "CD3", 10000)

## End(Not run)
```

setGate,GatingHierarchy,character,filter-method	<i>update the gate</i>
---	------------------------

Description

update the population node with a flowCore-compatible gate object

Usage

```
## S4 method for signature 'GatingHierarchy,character,filter'
setGate(obj, y, value,
        negated = FALSE, ...)

## S4 method for signature 'GatingSet,character,list'
setGate(obj, y, value, ...)

## S4 method for signature 'GatingSet,character,filterList'
setGate(obj, y, value, ...)
```

Arguments

obj	GatingHierarchy or GatingSet
y	character node name or path
value	filter or filterList or list of filter objects
negated	logical see add
...	other arguments

Details

Usually [recompute](#) is followed by this call since updating a gate doesn't re-calculating the cell events within the gate automatically. see [filterObject](#) for the gate types that are currently supported.

Examples

```
## Not run:
rg1 <- rectangleGate("FSC-H"=c(200,400), "SSC-H"=c(250, 400), filterId="rectangle")
rg2 <- rectangleGate("FSC-H"=c(200,400), "SSC-H"=c(250, 400), filterId="rectangle")
flist <- list(rg1,rg2)
names(flist) <- sampleNames(gs[1:2])
setGate(gs[1:2], "lymph", flist)
recompute(gs[1:2], "lymph")

## End(Not run)
```

setNode,GatingHierarchy,character,character-method

Update the name of one node in a gating hierarchy/GatingSet.

Description

setNode update the name of one node in a gating hierarchy/GatingSet.

hide/unhide a node

Usage

```
## S4 method for signature 'GatingHierarchy,character,character'
setNode(x, y, value)
```

```
## S4 method for signature 'GatingHierarchy,character,logical'
setNode(x, y, value)
```

```
## S4 method for signature 'GatingSet,character,ANY'
setNode(x, y, value)
```

Arguments

x	GatingHierarchy object
y	character node name or path
value	A character the name of the node. or logical to indicate whether to hide a node

Examples

```

## Not run:
#G is a gating hierarchy
getNode(G[[1]])#return node names
setNode(G,"L","lymph")

## End(Not run)
## Not run:
setNode(gh, 4, FALSE) # hide a node
setNode(gh, 4, TRUE) # unhide a node

## End(Not run)

```

standardize-GatingSet *The tools to standardize the tree structures and channel names.*

Description

```

groupByTree(x)
groupByChannels(x)
checkRedundantNodes(x)
dropRedundantNodes(x, toRemove)
dropRedundantChannels(gs)
updateChannels(gs, map, all = TRUE)
insertGate(gs, gate, parent, children)
setNode(x, y, FALSE)

```

Details

In order to merge multiple GatingSets into single [GatingSetList](#), the gating trees and channel names must be consistent. These functions help removing the discrepancies and standardize the GatingSets so that they are mergable.

[groupByTree](#) splits the GatingSets into groups based on the gating tree structures.

[groupByChannels](#) split GatingSets into groups based on their flow channels.

[checkRedundantNodes](#) returns the terminal(or leaf) nodes that makes the gating trees to be different among GatingSets and thus can be considered to remove as redundant nodes.

[dropRedundantNodes](#) removes the terminal(or leaf) nodes that are detected as redundant by [checkRedundantNodes](#).

[dropRedundantChannels](#) remove the redundant channels that are not used by any gate defined in the GatingSet.

[updateChannels](#) modifies the channel names in place. (Usually used to standardize the channels among GatingSets due to the letter case discrepancies or typo).

[insertGate](#) inserts a dummy gate to the GatingSet. Is is useful trick to deal with the extra non-leaf node in some GatingSets that can not be simply removed by [dropRedundantNodes](#)

[setNode](#) hide a node/gate in a GatingSet. It is useful to deal with the non-leaf node that causes the tree structure discrepancy.

subset.GatingSet *subset the GatingSet/GatingSetList based on 'pData'*

Description

subset the GatingSet/GatingSetList based on 'pData'

Usage

```
## S3 method for class 'GatingSet'
subset(x, subset, ...)
```

Arguments

x	GatingSet or GatingSetList
subset	logical expression(within the context of pData) indicating samples to keep. see subset
...	other arguments. (not used)

Value

a codeGatingSet or GatingSetList object

transform,GatingSet-method
transform the flow data associated with the GatingSet

Description

The transformation functions are saved in the GatingSet and can be retrieved by [getTransformations](#). Currently only flowJo-type biexponential transformation(either returned by [getTransformations](#) or constructed by [flowJoTrans](#)) is supported.

Usage

```
## S4 method for signature 'GatingSet'
transform(`_data`, translist, ...)

## S4 method for signature 'GatingSetList'
transform(`_data`, ...)
```

Arguments

_data	GatingSet or GatingSetList
translist	expect a transformList object or a list of transformList objects(with names matched to sample names)
...	other arguments passed to 'transform' method for 'ncdfFlowSet'.(e.g. 'ncdf-File')

Value

a GatingSet or GatingSetList object with the underlying flow data transformed.

Examples

```
## Not run:
data(GvHD)
fs <- GvHD[1:2]
gs <- GatingSet(fs)

#construct biexponential transformation function
biexpTrans <- flowJo_biexp_trans(channelRange=4096, maxValue=262144, pos=4.5, neg=0, widthBasis=-10)

#make a transformerList object
chnls <- c("FL1-H", "FL2-H")
transList <- transformerList(chnls, biexpTrans)

#add it to GatingSet
gs_trans <- transform(gs, transList)

## End(Not run)
```

transformerList	<i>Constructor for transformerList object</i>
-----------------	---

Description

Similar to transformList function, it constructs a list of transformer objects generated by trans_new method from scales so that the inverse and breaks functions are also included.

Usage

```
transformerList(from, trans)
```

Arguments

from	channel names
trans	a trans object or a list of trans objects constructed by trans_new method.

Examples

```
library(scales)
#create transformer object from scratch
trans <- logicleTransform(w = 0.5, t = 262144, m = 4.5, a = 0)
inv <- inverseLogicleTransform(trans = trans)
trans.obj <- flow_trans("logicle", trans, inv, n = 5, equal.space = FALSE)

#or simply use convenient constructor
#trans.obj <- logicle_trans(n = 5, equal.space = FALSE, w = 0.5, t = 262144, m = 4.5, a = 0)

transformerList(c("FL1-H", "FL2-H"), trans.obj)
```

```
#use different transformer for each channel
trans.obj2 <- asinhtGml2_trans()
transformerList(c("FL1-H", "FL2-H"), list(trans.obj, trans.obj2))
```

updateChannels

Update the channel information of a GatingSet (c++ part)

Description

It updates the channels stored in gates, compensations and transformations based on given mapping between the old and new channel names.

Usage

```
updateChannels(gs, map, all = TRUE)
```

Arguments

gs	a GatingSet object
map	data.frame contains the mapping from old (case insensitive) to new channel names Note: Make sure to remove the '<' or '>' characters from 'old' name because the API tries to only look at the raw channel name so that the gates with both prefixed and non-prefixed names could be updated.
all	logical whether to update the flow data as well

Value

when 'all' is set to TRUE, it returns a new GatingSet but it still shares the same underlying c++ tree structure with the original GatingSet otherwise it returns nothing (less overhead.)

Examples

```
## Not run:
  ##this will update both "Qdot 655-A" and "<Qdot 655-A>"
  gs <- updateChannels(gs, map = data.frame(old = c("Qdot 655-A")
                                           , new = c("<Qdot 655-A")
                                           )
                      )
## End(Not run)
```

updateIndices,GatingHierarchy,character,logical-method
directly update event indices without changing gates

Description

It is useful when we want to alter the population at events level yet without removing or adding the existing gates.

Usage

```
## S4 method for signature 'GatingHierarchy,character,logical'
updateIndices(obj, y, z)
```

Arguments

obj	GatingHierarchy object
y	character node name or path
z	logical vector as local event indices relative to node y

Examples

```
library(flowWorkspace)
dataDir <- system.file("extdata",package="flowWorkspaceData")
suppressMessages(gs <- load_gs(list.files(dataDir, pattern = "gs_manual",full = TRUE)))
gh <- gs[[1]]
#get pop counts
pop.stats <- getStats(gh, nodes = c("CD3+", "CD4", "CD8"))
pop.stats

# subsample 30% cell events at CD3+ node
total.cd3 <- pop.stats[pop == "CD3+", count]
gInd <- seq_len(total.cd3) #create integer index for cd3
gInd <- sample.int(total.cd3, size = total.cd3 * 0.3) #randomly select 30%
#convert it to logical index
gInd.logical <- rep(FALSE, total.cd3)
gInd.logical[gInd] <- TRUE
#replace the original index stored at GatingHierarchy
updateIndices(gh, "CD3+", gInd.logical)
#check the updated pop counts
getStats(gs[[1]], nodes = c("CD3+", "CD4", "CD8")) #note that CD4, CD8 are not updated
#update all the descendants of CD3+
nodes <- getDescendants(gh, "CD3+")
for (node in nodes) suppressMessages(recompute(gh, node))
getStats(gs[[1]], nodes = c("CD3+", "CD4", "CD8")) #now all are update to date
```

Index

- [, GatingSet, ANY-method
(GatingSet-class), 25
- [, GatingSetList, ANY-method
(GatingSet-class), 25
- [[, GatingSet, character-method
(GatingSet-class), 25
- [[, GatingSet, logical-method
(GatingSet-class), 25
- [[, GatingSet, numeric-method
(GatingSet-class), 25

- add, 9, 67, 71
- add (add, GatingSet, list-method), 4
- add, GatingHierarchy, factor-method
(add, GatingSet, list-method), 4
- add, GatingHierarchy, filter-method
(add, GatingSet, list-method), 4
- add, GatingHierarchy, filters-method
(add, GatingSet, list-method), 4
- add, GatingHierarchy, logical-method
(add, GatingSet, list-method), 4
- add, GatingHierarchy, logicalFilterResult-method
(add, GatingSet, list-method), 4
- add, GatingHierarchy, multipleFilterResult-method
(add, GatingSet, list-method), 4
- add, GatingHierarchy, quadGate-method
(add, GatingSet, list-method), 4
- add, GatingSet, filter-method
(add, GatingSet, list-method), 4
- add, GatingSet, filterList-method
(add, GatingSet, list-method), 4
- add, GatingSet, filters-method
(add, GatingSet, list-method), 4
- add, GatingSet, filtersList-method
(add, GatingSet, list-method), 4
- add, GatingSet, list-method, 4
- add, GatingSetList, filter-method
(add, GatingSet, list-method), 4
- add, GatingSetList, filterList-method
(add, GatingSet, list-method), 4
- add, GatingSetList, filters-method
(add, GatingSet, list-method), 4
- add, GatingSetList, filtersList-method
(add, GatingSet, list-method), 4

- add, GatingSetList, list-method
(add, GatingSet, list-method), 4
- asinh_Gml2, 8
- asinhtGml2_trans, 7

- barchart, 65
- booleanFilter (booleanFilter-class), 9
- booleanFilter-class, 9

- char2booleanFilter
(booleanFilter-class), 9
- checkRedundantNodes, 10, 13, 72
- clone, 11
- clone, GatingSet-method (clone), 11
- clone-methods (clone), 11
- clone.ncdfFlowSet, 11
- closeWorkspace
(openWorkspace, character-method),
57
- closeWorkspace, flowJoWorkspace-method
(openWorkspace, character-method),
57
- colnames, GatingHierarchy-method
(markernames, GatingHierarchy-method),
54
- colnames, GatingSet-method
(markernames, GatingHierarchy-method),
54
- colnames<-, GatingHierarchy-method
(markernames, GatingHierarchy-method),
54
- colnames<-, GatingSet-method
(markernames, GatingHierarchy-method),
54
- compensate, GatingSet, ANY-method, 11
- compensate, GatingSetList, ANY-method
(compensate, GatingSet, ANY-method),
11
- compute_timestep, 12

- dropRedundantChannels, 13, 72
- dropRedundantNodes, 10, 13, 72

- estimateLogicle, 14

- estimateLogicle.GatingHierarchy, [14](#)
- expressionFilter, [9](#)
- extract_cluster_pop_name_from_node, [15](#)
- filterObject, [71](#)
- filterObject
 - (filterObject, rectangleGate-method), [15](#)
- filterObject, booleanFilter-method
 - (filterObject, rectangleGate-method), [15](#)
- filterObject, ellipsoidGate-method
 - (filterObject, rectangleGate-method), [15](#)
- filterObject, logical-method
 - (filterObject, rectangleGate-method), [15](#)
- filterObject, polygonGate-method
 - (filterObject, rectangleGate-method), [15](#)
- filterObject, rectangleGate-method, [15](#)
- fix_channel_slash, [16](#)
- flow_breaks, [22](#)
- flow_trans, [23](#)
- flowData, [31](#)
- flowData (flowData, GatingSet-method), [16](#)
- flowData, GatingSet-method, [16](#)
- flowData<- (flowData, GatingSet-method), [16](#)
- flowData<- , GatingSet-method
 - (flowData, GatingSet-method), [16](#)
- flowJo.fasinh, [17](#)
- flowJo.flog, [18](#), [54](#)
- flowJo.fsinh (flowJo.fasinh), [17](#)
- flowJo_biexp_trans, [20](#)
- flowJo_fasinh_trans, [21](#)
- flowJoTrans, [19](#), [20](#), [73](#)
- flowJoWorkspace, [26](#)
- flowJoWorkspace-class, [19](#)
- flowWorkspace (flowWorkspace-package), [4](#)
- flowWorkspace-package, [4](#)
- flowWorkspace.par.get
 - (flowWorkspace.par.set), [22](#)
- flowWorkspace.par.init, [21](#)
- flowWorkspace.par.set, [22](#)
- GatingHierarchy, [9](#), [20](#), [26](#), [27](#), [63](#)
- GatingHierarchy-class, [24](#)
- GatingSet, [20](#), [24](#), [27](#), [60](#), [63](#)
- GatingSet
 - (GatingSet, character, character-method), [24](#)
 - GatingSet, character, character-method, [24](#)
 - GatingSet, flowSet, ANY-method
 - (GatingSet, character, character-method), [24](#)
 - GatingSet, GatingHierarchy, character-method
 - (GatingSet, character, character-method), [24](#)
 - GatingSet-class, [25](#)
 - GatingSetList, [72](#)
 - GatingSetList (GatingSetList-class), [27](#)
 - GatingSetList-class, [27](#)
 - getChildren
 - (getParent, GatingSet, character-method), [38](#)
 - getChildren, GatingSet, character-method
 - (getParent, GatingSet, character-method), [38](#)
 - getCompensationMatrices, [11](#)
 - getCompensationMatrices
 - (getCompensationMatrices, GatingHierarchy-method), [29](#)
 - getCompensationMatrices, GatingHierarchy-method, [29](#)
 - getCompensationObj, [30](#)
 - getData, [33](#)
 - getData
 - (getData, GatingHierarchy, missing-method), [30](#)
 - getData, GatingHierarchy, character-method
 - (getData, GatingHierarchy, missing-method), [30](#)
 - getData, GatingHierarchy, missing-method, [30](#)
 - getData, GatingSet, character-method
 - (getData, GatingHierarchy, missing-method), [30](#)
 - getData, GatingSet, missing-method
 - (getData, GatingHierarchy, missing-method), [30](#)
 - getData, GatingSetList, ANY-method
 - (getData, GatingHierarchy, missing-method), [30](#)
 - getDescendants, [31](#)
 - getFJWSubsetIndices, [32](#)
 - getGate
 - (getGate, GatingHierarchy, character-method), [32](#)
 - getGate, GatingHierarchy, character-method, [32](#)
 - getGate, GatingSet, character-method
 - (getGate, GatingHierarchy, character-method), [32](#)

- 32
- getGate, GatingSetList, character-method
(getGate, GatingHierarchy, character-method), 32
- getIndiceMat, 33
- getIndices, 31, 43
- getIndices
(getIndices, GatingHierarchy, character-method), 34
- getIndices, GatingHierarchy, character-method, 34
- getIndices, GatingSet, name-method, 35
- getKeywords
(getKeywords, flowJoWorkspace, character-method), 35
- getKeywords, flowJoWorkspace, character-method, 35
- getKeywords, flowJoWorkspace, numeric-method
(getKeywords, flowJoWorkspace, character-method), 35
- getLogLevel, 36
- getMergedStats, 37
- getNodes, 10, 33, 38–40, 44, 63–65
- getNodes (getNodes, GatingSet-method), 37
- getNodes, GatingSet-method, 37
- getParent
(getParent, GatingSet, character-method), 38
- getParent, GatingSet, character-method, 38
- getPopStats, 31, 34, 43, 65
- getPopStats
(getProp, GatingHierarchy, character-method), 39
- getPopStats, GatingHierarchy-method
(getProp, GatingHierarchy, character-method), 39
- getPopStats, GatingSet-method
(getProp, GatingHierarchy, character-method), 39
- getPopStats, GatingSetList-method
(getProp, GatingHierarchy, character-method), 39
- getProp
(getProp, GatingHierarchy, character-method), 39
- getProp, GatingHierarchy, character-method, 39
- getSampleGroups, 60
- getSampleGroups
(getSampleGroups, flowJoWorkspace-method), 41
- getSampleGroups, flowJoWorkspace-method, 41
- getSamples
(getSamples, flowJoWorkspace-method), 41
- getSamples, flowJoWorkspace-method, 41
- getSingleCellExpression
(getSingleCellExpression, GatingSetList, character-method), 42
- getSingleCellExpression, GatingSet, character-method
(getSingleCellExpression, GatingSetList, character-method), 42
- getSingleCellExpression, GatingSetList, character-method, 42
- getSingleCellExpressionByGate
(getSingleCellExpression, GatingSetList, character-method), 42
- getStats, 44
- getTotal
(getProp, GatingHierarchy, character-method), 39
- getTotal, GatingHierarchy, character-method
(getProp, GatingHierarchy, character-method), 39
- getTransformations, 73
- getTransformations
(getTransformations, GatingHierarchy-method), 45
- getTransformations, GatingHierarchy-method, 45
- gh_check_cluster_node, 46
- gh_get_cluster_labels, 47
- grid.layout, 63
- groupByChannels, 47, 72
- groupByTree, 10, 13, 48, 66, 72
- insertGate, 48, 72
- isGated, 49
- isGated, GatingHierarchy, character-method
(isGated), 49
- isHidden (isGated), 49
- isHidden, GatingHierarchy, character-method
(isGated), 49
- isNcdf, 50
- isNegated (isGated), 49
- isNegated, GatingHierarchy, character-method
(isGated), 49
- keyword
(keyword, GatingHierarchy, character-method), 50
- keyword, GatingHierarchy, character-method, 50

- keyword,GatingHierarchy,missing-method
(keyword,GatingHierarchy,character-method),
50
- keyword,GatingSet,character-method
(keyword,GatingHierarchy,character-method),
50
- keyword,GatingSet,missing-method
(keyword,GatingHierarchy,character-method),
50
- keyword,GatingSetList,character-method
(keyword,GatingHierarchy,character-method),
50
- keyword,GatingSetList,missing-method
(keyword,GatingHierarchy,character-method),
50
- lapply,GatingSet-method, 51
- lattice, 63
- layoutGraph, 62
- length(length,GatingSet-method), 52
- length,GatingSet-method, 52
- load_gs(save_gs), 68
- load_gslist(save_gs), 68
- logicle_trans, 52, 53
- logicleGml2_trans, 52
- logicletGml2, 52
- logtGml2, 18
- logtGml2_trans, 54
- markernames,GatingHierarchy-method, 54
- markernames,GatingSet-method
(markernames,GatingHierarchy-method),
54
- markernames<- ,GatingHierarchy-method
(markernames,GatingHierarchy-method),
54
- markernames<- ,GatingSet-method
(markernames,GatingHierarchy-method),
54
- merge-GatingSet
(standardize-GatingSet), 72
- mkformula, 56
- moveNode, 56
- ncFlowSet, 57
- ncFlowSet,GatingSet-method(ncFlowSet),
57
- ncFlowSet<- (ncFlowSet), 57
- ncFlowSet<- ,GatingSet-method
(ncFlowSet), 57
- openWorkspace, 41
- openWorkspace
(openWorkspace,character-method),
57
- openWorkspace,character-method, 57
- parseWorkspace, 25, 26, 32, 42
- parseWorkspace
(parseWorkspace,flowJoWorkspace-method),
58
- parseWorkspace,flowJoWorkspace-method,
58
- pData(pData,GatingHierarchy-method), 60
- pData,GatingHierarchy-method, 60
- pData,GatingSet-method
(pData,GatingHierarchy-method),
60
- pData<- (pData,GatingHierarchy-method),
60
- pData<- ,GatingSet,data.frame-method
(pData,GatingHierarchy-method),
60
- pData<- ,GatingSetList,data.frame-method
(pData,GatingHierarchy-method),
60
- plot(plot,GatingSet,missing-method), 61
- plot,GatingSet,character-method
(plot,GatingSet,missing-method),
61
- plot,GatingSet,missing-method, 61
- plot_diff_tree, 65
- plotGate, 62
- plotGate,GatingHierarchy,character-method
(plotGate), 62
- plotGate,GatingHierarchy,missing-method
(plotGate), 62
- plotGate,GatingHierarchy,numeric-method
(plotGate), 62
- plotGate,GatingSet,character-method
(plotGate), 62
- plotGate,GatingSet,missing-method
(plotGate), 62
- plotGate,GatingSet,numeric-method
(plotGate), 62
- plotGate,GatingSetList,character-method
(plotGate), 62
- plotGate-methods(plotGate), 62
- plotPopCV
(plotPopCV,GatingHierarchy-method),
64
- plotPopCV,GatingHierarchy-method, 64
- plotPopCV,GatingSet-method
(plotPopCV,GatingHierarchy-method),
64

- pop.MFI, 66
- prettyAxis, 66
- rbind2, GatingSetList, missing-method
(GatingSetList-class), 27
- read.flowSet, 59
- read.ncdfFlowSet, 59
- recompute, 71
- recompute (recompute, GatingSet-method),
67
- recompute, GatingSet-method, 67
- recompute, GatingSetList-method
(recompute, GatingSet-method),
67
- Rm (add, GatingSet, list-method), 4
- Rm, character, GatingHierarchy, character-method
(add, GatingSet, list-method), 4
- Rm, character, GatingSet, character-method
(add, GatingSet, list-method), 4
- Rm, character, GatingSetList, character-method
(add, GatingSet, list-method), 4
- sampleNames
(sampleNames, GatingHierarchy-method),
68
- sampleNames, GatingHierarchy-method, 68
- sampleNames, GatingSet-method
(sampleNames, GatingHierarchy-method),
68
- sampleNames<-
(sampleNames, GatingHierarchy-method),
68
- sampleNames<-, GatingSet, ANY-method
(sampleNames, GatingHierarchy-method),
68
- sampleNames<-, GatingSet-method
(sampleNames, GatingHierarchy-method),
68
- save_gs, 68
- save_gslist (save_gs), 68
- set.count.xml, 70
- setGate, 67
- setGate
(setGate, GatingHierarchy, character, filter-method),
70
- setGate, GatingHierarchy, character, filter-method,
70
- setGate, GatingSet, character, filterList-method
(setGate, GatingHierarchy, character, filter-method),
70
- setGate, GatingSet, character, list-method
(setGate, GatingHierarchy, character, filter-method),
70
- setLogLevel (getLogLevel), 36
- setNode, 72
- setNode
(setNode, GatingHierarchy, character, character-me
71
- setNode, GatingHierarchy, character, character-method,
71
- setNode, GatingHierarchy, character, logical-method
(setNode, GatingHierarchy, character, character-me
71
- setNode, GatingSet, character, ANY-method
(setNode, GatingHierarchy, character, character-me
71
- show, booleanFilter-method
(booleanFilter-class), 9
- show, flowJoWorkspace-method
(flowJoWorkspace-class), 19
- show, GatingHierarchy-method
(GatingHierarchy-class), 24
- show, GatingSet-method
(length, GatingSet-method), 52
- standardize-GatingSet, 72
- subset, 73
- subset.GatingSet, 73
- transform, GatingSet-method, 73
- transform, GatingSetList-method
(transform, GatingSet-method),
73
- transformerList, 74
- updateChannels, 72, 75
- updateIndices, GatingHierarchy, character, logical-method,
76
- xmlTreeParse, 19, 25, 57, 59
- xyplot, 64