

Package ‘AnVIL’

January 13, 2025

Title Bioconductor on the AnVIL compute environment

Version 1.18.2

Description The AnVIL is a cloud computing resource developed in part by the National Human Genome Research Institute. The AnVIL package provides end-user and developer functionality. For the end-user, AnVIL provides fast binary package installation, utilities for working with Terra / AnVIL table and data resources, and convenient functions for file movement to and from Google cloud storage. For developers, AnVIL provides programatic access to the Terra, Leonardo, Rawls, and Dockstore RESTful programming interface, including helper functions to transform JSON responses to formats more amenable to manipulation in R.

License Artistic-2.0

Encoding UTF-8

Depends R (>= 3.6), dplyr, AnVILBase

Imports stats, utils, methods, futile.logger, jsonlite, httr, rapiclient (>= 0.1.3), yaml, tibble, tidyselect, tidyr, rlang, shiny, DT, miniUI, htmltools, BiocManager, BiocBaseUtils

Suggests parallel, knitr, rmarkdown, testthat, withr, readr, BiocStyle, devtools, AnVILAz, AnVILGCP, lifecycle

Collate utilities.R authenticate.R api.R AnVIL-package.R Service.R Services.R Leonardo.R Terra.R Rawls.R Dockstore.R TDR.R gcloud_sdk.R gcloud.R gsutil.R localize.R drs.R av.R avworkflow.R avworkflow_configuration.R AnVIL-defunct.R gadgets.R zzz.R

VignetteBuilder knitr

biocViews Infrastructure

RoxygenNote 7.3.2

Roxygen list(markdown = TRUE)

Date 2024-10-28

git_url <https://git.bioconductor.org/packages/AnVIL>

git_branch RELEASE_3_20

git_last_commit fb82d00

git_last_commit_date 2024-12-18

Repository Bioconductor 3.20

Date/Publication 2025-01-13

Author Marcel Ramos [aut, cre] (<<https://orcid.org/0000-0002-3242-0582>>),
 Martin Morgan [aut] (<<https://orcid.org/0000-0002-5874-8148>>),
 Kayla Interdonato [aut],
 Yubo Cheng [aut],
 Nitesh Turaga [aut],
 BJ Stubbs [ctb],
 Vincent Carey [ctb],
 Sehyun Oh [ctb],
 Sweta Gopaulakrishnan [ctb],
 Valerie Obenchain [ctb]

Maintainer Marcel Ramos <marcel.ramos@sph.cuny.edu>

Contents

AnVIL-package	2
.gadget_run	3
AnVIL-defunct	4
av-deprecated	5
avworkflows-deprecated	10
avworkflow_config-deprecated	14
avworkspace_gadget	18
drs-deprecated	19
gcloud-deprecated	21
gsutil-deprecated	22
localize-deprecated	25
Service	26
Services	27
utilities	29
Index	30

AnVIL-package

AnVIL: Bioconductor on the AnVIL compute environment

Description

The AnVIL is a cloud computing resource developed in part by the National Human Genome Research Institute. The AnVIL package provides end-user and developer functionality. For the end-user, AnVIL provides fast binary package installation, utilities for working with Terra / AnVIL table and data resources, and convenient functions for file movement to and from Google cloud storage. For developers, AnVIL provides programatic access to the Terra, Leonardo, Rawls, and Dockstore RESTful programming interface, including helper functions to transform JSON responses to formats more amenable to manipulation in R.

Author(s)

Maintainer: Marcel Ramos <marcel.ramos@sph.cuny.edu> ([ORCID](#))

Authors:

- Martin Morgan ([ORCID](#))
- Kayla Interdonato
- Yubo Cheng
- Nitesh Turaga

Other contributors:

- BJ Stubbs [contributor]
- Vincent Carey [contributor]
- Sehyun Oh [contributor]
- Sweta Gopaulakrishnan [contributor]
- Valerie Obenchain [contributor]

.gadget_run

Functions to implement AnVIL gadget interfaces

Description

Functions documented on this page are primarily intended for package developers wishing to implement gadgets (graphical interfaces) to navigating AnVIL-generated tables.

`.gadget_run()` presents the user with a tibble-navigating gadget, returning the value of `DONE_FUN` if a row of the tibble is selected, or `NULL`.

Usage

```
.gadget_run(title, tibble, DONE_FUN)
```

Arguments

<code>title</code>	character(1) (required) title to appear at the base of the gadget, e.g., "AnVIL Workspaces".
<code>tibble</code>	a tibble or <code>data.frame</code> to be displayed in the gadget.
<code>DONE_FUN</code>	a function of two arguments, <code>tibble</code> and <code>row_selected</code> . The tibble is the tibble provided as an argument to <code>.gadget_run()</code> . <code>row_selected</code> is the row selected in the gadget by the user. The function is only invoked when the user selects a valid row.

Value

`.gadget_run()` returns the result of `DONE_FUN()` if a row has been selected by the user, or `NULL` if no row is selected (the user presses `Cancel`, or `Done` prior to selecting any row).

Examples

```
## Not run:
tibble <- avworkspaces()
DONE_FUN <- function(tibble, row_selected) {
  selected <- slice(tibble, row_selected)
  with(selected, paste0(namespace, "/", name))
}
.gadget_run("AnVIL Example", tibble, DONE_FUN)

## End(Not run)
```

AnVIL-defunct

Defunct AnVIL functionality

Description

`repository_stats()`: summarize binary packages compatible with the Bioconductor or Terra container in use.

Usage

```
repository_stats(
  version = BiocManager::version(),
  binary_base_url = BINARY_BASE_URL
)

## S3 method for class 'repository_stats'
print(x, ...)
```

Arguments

<code>version</code>	character(1) or <code>package_version</code> Bioconductor version, e.g., "3.12".
<code>binary_base_url</code>	character(1) host and base path for binary package 'CRAN-style' repository; not usually required by the end-user.
<code>x</code>	the object returned by <code>repository_stats()</code> .
<code>...</code>	additional arguments (not used).

Value

`repository_stats()` returns a list of class `repository_stats` with the following fields:

- `container`: character(1) container label, e.g., `bioconductor_docker`, or NA if not evaluated on a supported container
- `bioconductor_version`: `package_version` the Bioconductor version provided by the user.
- `repository_exists`: logical(1) TRUE if a binary repository exists for the container and Bioconductor Version version.
- `bioconductor_binary_repository`: character(1) repository location, if available, or NA if the repository does not exist.
- `n_software_packages`: integer(1) number of software packages in the Bioconductor source repository.

- `n_binary_packages`: integer(1) number of binary packages available. When a binary repository exists, this number is likely to be larger than the number of source software packages, because it includes the binary version of the source software packages, as well as the (possibly CRAN) dependencies of the binary packages
- `n_binary_software_packages`: integer(1) number of binary packages derived from Bioconductor source packages. This number is less than or equal to `n_software_packages`.
- `missing_binaries`: integer(1) the number of Bioconductor source software packages that are not present in the binary repository.
- `out_of_date_binaries`: integer(1) the number of Bioconductor source software packages that are newer than their binary counterpart. A newer source software package might occur when the main Bioconductor build system has updated a package after the most recent run of the binary build system.

Functions

- `print(repository_stats)`: Print a summary of package availability in binary repositories.

av-deprecated

TABLE, DATA, files, bucket, runtime, and disk elements

Description

[Deprecated]

`avtable_import_status()` queries for the status of an 'asynchronous' table import.

`avdata()` returns key-value tables representing the information visualized under the DATA tab, 'REFERENCE DATA' and 'OTHER DATA' items. `avdata_import()` updates (modifies or creates new, but does not delete) rows in 'REFERENCE DATA' or 'OTHER DATA' tables.

`avbucket()` returns the workspace bucket, i.e., the google bucket associated with a workspace. Bucket content can be visualized under the 'DATA' tab, 'Files' item.

`avfiles_ls()` returns the paths of files in the workspace bucket. `avfiles_backup()` copies files from the compute node file system to the workspace bucket. `avfiles_restore()` copies files from the workspace bucket to the compute node file system. `avfiles_rm()` removes files or directories from the workspace bucket.

`avruntimes()` returns a tibble containing information about runtimes (notebooks or RStudio instances, for example) that the current user has access to.

`avruntime()` returns a tibble with the runtimes associated with a particular google project and account number; usually there is a single runtime satisfying these criteria, and it is the runtime active in AnVIL.

'`avdisks()`' returns a tibble containing information about persistent disks associated with the current user.

Usage

```
avtable_paged(
  table,
  n = Inf,
  page = 1L,
```

```
    pageSize = 1000L,  
    sortField = "name",  
    sortDirection = c("asc", "desc"),  
    filterTerms = character(),  
    filterOperator = c("and", "or"),  
    namespace = avworkspace_namespace(),  
    name = avworkspace_name(),  
    na = c("", "NA")  
  )  
  
  avtable_import_status(  
    job_status,  
    namespace = avworkspace_namespace(),  
    name = avworkspace_name()  
  )  
  
  avdata(namespace = avworkspace_namespace(), name = avworkspace_name())  
  
  avdata_import(  
    .data,  
    namespace = avworkspace_namespace(),  
    name = avworkspace_name()  
  )  
  
  avbucket(  
    namespace = avworkspace_namespace(),  
    name = avworkspace_name(),  
    as_path = TRUE  
  )  
  
  avfiles_ls(  
    path = "",  
    full_names = FALSE,  
    recursive = FALSE,  
    namespace = avworkspace_namespace(),  
    name = avworkspace_name()  
  )  
  
  avfiles_backup(  
    source,  
    destination = "",  
    recursive = FALSE,  
    parallel = TRUE,  
    namespace = avworkspace_namespace(),  
    name = avworkspace_name()  
  )  
  
  avfiles_restore(  
    source,  
    destination = ".",  
    recursive = FALSE,  
    parallel = TRUE,
```

```

    namespace = avworkspace_namespace(),
    name = avworkspace_name()
  )

avfiles_rm(
  source,
  recursive = FALSE,
  parallel = TRUE,
  namespace = avworkspace_namespace(),
  name = avworkspace_name()
)

avruntimes()

avruntime(project = gcloud_project(), account = gcloud_account())

avdisks()

```

Arguments

table	character(1) table name as returned by, e.g., avtables().
n	numeric(1) maximum number of rows to return
page	integer(1) first page of iteration
pageSize	integer(1) number of records per page. Generally, larger page sizes are more efficient.
sortField	character(1) field used to sort records when determining page order. Default is the entity field.
sortDirection	character(1) direction to sort entities ("asc"ending or "desc"ending) when paging.
filterTerms	character(1) string literal to select rows with an exact (substring) matches in column.
filterOperator	character(1) operator to use when multiple terms in filterTerms=, either "and" (default) or "or".
namespace	character(1) AnVIL workspace namespace as returned by, e.g., avworkspace_namespace()
name	character(1) AnVIL workspace name as returned by, eg., avworkspace_name().
na	in avtable() and avtable_paged(), character() of strings to be interpreted as missing values. In avtable_import() character(1) value to use for representing NA_character_. See Details.
job_status	tibble() of job identifiers, returned by avtable_import() and avtable_import_set().
.data	A tibble or data.frame for import as an AnVIL table.
as_path	logical(1) when TRUE (default) return bucket with prefix gs:// (for avbucket()) or gs://<bucket-id> (for avfiles_ls()).
path	For avfiles_ls(), the character(1) file or directory path to list. For avfiles_rm(), the character() (perhaps with length greater than 1) of files or directory
full_names	logical(1) return names relative to path (FALSE, default) or root of the workspace bucket?
recursive	logical(1) list files recursively?

source	character() file paths. for <code>avfiles_backup()</code> , source can include directory names when <code>recursive = TRUE</code> .
destination	character(1) a google bucket (<code>gs://<bucket-id>/...</code>) to write files. The default is the workspace bucket.
parallel	logical(1) backup files using parallel transfer? See <code>?gsutil_cp()</code> .
project	character(1) project (billing account) name, as returned by, e.g., <code>gcloud_project()</code> or <code>avworkspace_namespace()</code> .
account	character(1) google account (email address associated with billing account), as returned by <code>gcloud_account()</code> .

Details

`avfiles_backup()` can be used to back-up individual files or entire directories, recursively. When `recursive = FALSE`, files are backed up to the bucket with names approximately `paste0(destination, "/", basename(source))`. When `recursive = TRUE` and `source` is a directory path `/to/foo/`, files are backed up `"/", dir(basename(source), full.names = TRUE)`. Naming conventions are described in detail in `gsutil_help("cp")`.

`avfiles_restore()` behaves in a manner analogous to `avfiles_backup()`, copying files from the workspace bucket to the compute node file system.

Value

`avtable_paged()`: a tibble of data corresponding to the AnVIL table `table` in the specified workspace.

`avdata()` returns a tibble with five columns: `"type"` represents the origin of the data from the 'REFERENCE' or 'OTHER' data menus. `"table"` is the table name in the REFERENCE menu, or 'workspace' for the table in the 'OTHER' menu, the key used to access the data element, the value label associated with the data element and the value (e.g., google bucket) of the element.

`avdata_import()` returns, invisibly, the subset of the input table used to update the AnVIL tables.

`avbucket()` returns a character(1) bucket identifier, prefixed with `gs://` if `as_path = TRUE`.

`avfiles_ls()` returns a character vector of files in the workspace bucket.

`avfiles_backup()` returns, invisibly, the status code of the `gsutil_cp()` command used to back up the files.

`avfiles_rm()` on success, returns a list of the return codes of `gsutil_rm()`, invisibly.

`avruntimes()` returns a tibble with columns

- `id`: integer() runtime identifier.
- `googleProject`: character() billing account.
- `tool`: character() e.g., "Jupyter", "RStudio".
- `status`: character() e.g., "Stopped", "Running".
- `creator`: character() AnVIL account, typically "user@gmail.com".
- `createdDate`: character() creation date.
- `destroyedDate`: character() destruction date, or NA.
- `dateAccessed`: character() date of (first?) access.
- `runtimeName`: character().
- `clusterServiceAccount`: character() service ('pet') account for this runtime.

- `masterMachineType` character() It is unclear which 'tool' populates which of the `machineType` columns).
- `workerMachineType` character().
- `machineType` character().
- `persistentDiskId` integer() identifier of persistent disk (see `avdisks()`), or NA.

`avruntime()` returns a tibble with the same structure as the return value of `avruntimes()`.

`avdisks()` returns a tibble with columns

- `id` character() disk identifier.
- `googleProject`: character() billing account.
- `status`, e.g. "Ready"
- `size` integer() in GB.
- `diskType` character().
- `blockSize` integer().
- `creator` character() AnVIL account, typically "user@gmail.com".
- `createdDate` character() creation date.
- `destroyedDate` character() destruction date, or NA.
- `dateAccessed` character() date of (first?) access.
- `zone` character() e.g.. "us-central1-a".
- `name` character().

Examples

```
library(AnVILBase)
library(AnVILGCP)
if (has_avworkspace(strict = TRUE, platform = gcp())) {
  ## from within AnVIL
  data <- avdata()
  data
}

## Not run:
avdata_import(data)

## End(Not run)

if (has_avworkspace(strict = TRUE, platform = gcp()))
  ## From within AnVIL...
  bucket <- avstorage() # discover bucket

## Not run:
path <- file.path(bucket, "mtcars.tab")
gsutil_ls(dirname(path)) # no 'mtcars.tab'...
write.table(mtcars, gsutil_pipe(path, "w")) # write to bucket
gsutil_stat(path) # yep, there!
read.table(gsutil_pipe(path, "r")) # read from bucket

## End(Not run)
if (has_avworkspace(strict = TRUE, platform = gcp()))
  avfiles_ls()
```

```

## Not run:
## backup all files in the current directory
## default buckets are gs://<bucket-id>/<file-names>
avfiles_backup(dir())
## backup working directory, recursively
## default buckets are gs://<bucket-id>/<basename(getwd())>/...
avfiles_backup(getwd(), recursive = TRUE)

## End(Not run)

if (gcloud_exists())
  ## from within AnVIL
  avruntimes()

if (gcloud_exists())
  ## from within AnVIL
  avdisks()

```

avworkflows-deprecated

Workflow submissions and file outputs

Description

[Deprecated]

avworkflows() returns a tibble summarizing available workflows.

avworkflow_files() returns a tibble containing information and file paths to workflow outputs.

avworkflow_localize() creates or synchronizes a local copy of files with files stored in the workspace bucket and produced by the workflow.

avworkflow_run() submits and runs the workflow of the configuration.

avworkflow_stop() stops the most recently submitted workflow job from running.

avworkflow_info() returns a tibble containing workflow information, including workflowName, status, start and end time, inputs and outputs.

Usage

```
avworkflows(namespace = avworkspace_namespace(), name = avworkspace_name())
```

```

avworkflow_files(
  submissionId = NULL,
  workflowId = NULL,
  bucket = avbucket(),
  namespace = avworkspace_namespace(),
  name = avworkspace_name()
)

```

```

avworkflow_localize(
  submissionId = NULL,
  workflowId = NULL,

```

```

    destination = NULL,
    type = c("control", "output", "all"),
    bucket = avbucket(),
    dry = TRUE
  )

avworkflow_run(
  config,
  entityName,
  entityType = config$rootEntityType,
  deleteIntermediateOutputFiles = FALSE,
  useCallCache = TRUE,
  useReferenceDisks = FALSE,
  namespace = avworkspace_namespace(),
  name = avworkspace_name(),
  dry = TRUE
)

avworkflow_stop(
  submissionId = NULL,
  namespace = avworkspace_namespace(),
  name = avworkspace_name(),
  dry = TRUE
)

avworkflow_info(
  submissionId = NULL,
  namespace = avworkspace_namespace(),
  name = avworkspace_name()
)

```

Arguments

namespace	character(1) AnVIL workspace namespace as returned by, e.g., <code>avworkspace_namespace()</code>
name	character(1) AnVIL workspace name as returned by, e.g., <code>avworkspace_name()</code> .
submissionId	a character() of workflow submission ids, or a tibble with column <code>submissionId</code> , or <code>NULL</code> / missing. See 'Details'.
workflowId	a character(1) of internal identifier associated with one workflow in the submission, or <code>NULL</code> / missing.
bucket	character(1) DEPRECATED (ignored in the current release) name of the google bucket in which the workflow products are available, as <code>gs://...</code> . Usually the bucket of the active workspace, returned by <code>avbucket()</code> .
destination	character(1) file path to the location where files will be synchronized. For directories in the current working directory, be sure to prepend with <code>"/"</code> . When <code>NULL</code> , the <code>submissionId</code> is used as the destination. <code>destination</code> may also be a google bucket, in which case the workflow files are synchronized from the workspace to a second bucket.
type	character(1) copy "control" (default), "output", or "all" files produced by a workflow.
dry	logical(1) when <code>TRUE</code> (default), report the consequences but do not perform the action requested. When <code>FALSE</code> , perform the action.

config	a avworkflow_configuration object of the workflow that will be run. Only entityType and method configuration name and namespace are used from config; other configuration values must be communicated to AnVIL using avworkflow_configuration_set
entityName	character(1) or NULL name of the set of samples to be used when running the workflow. NULL indicates that no sample set will be used.
entityType	character(1) or NULL type of root entity used for the workflow. NULL means that no root entity will be used.
deleteIntermediateOutputFiles	logical(1) whether or not to delete intermediate output files when the workflow completes.
useCallCache	logical(1) whether or not to read from cache for this submission.
useReferenceDisks	logical(1) whether or not to use pre-built disks for common genome references. Default: FALSE.

Details

For avworkflow_files(), the submissionId is the identifier associated with the submission of one (or more) workflows, and is present in the return value of avworkflow_jobs(); the example illustrates how the first row of avworkflow_jobs() (i.e., the most recently completed workflow) can be used as input to avworkflow_files(). When submissionId is not provided, the return value is for the most recently submitted workflow of the namespace and name of avworkspace().

avworkflow_localize(). type = "control" files summarize workflow progress; they can be numerous but are frequently small and quickly synchronized. type = "output" files are the output products of the workflow stored in the workspace bucket. Depending on the workflow, outputs may be large, e.g., aligned reads in bam files. See gsutil_cp() to copy individual files from the bucket to the local drive.

avworkflow_localize() treats submissionId= in the same way as avworkflow_files(): when missing, files from the most recent workflow job are candidates for localization.

avworkflow_run() invisibly returns a slightly modified config object. The new config object has an added LastSubmissionId value that identifies the submitted job.

Value

avworkflows() returns a tibble. Each workflow is in a 'namespace' and has a 'name', as illustrated in the example. Columns are

- name: workflow name.
- namespace: workflow namespace (often the same as the workspace namespace).
- rootEntityType: name of the avtable() used to retrieve inputs.
- methodRepoMethod.methodUri: source of the method, e.g., a dockstore URI.
- methodRepoMethod.sourceRepo: source repository, e.g., dockstore.
- methodRepoMethod.methodPath: path to method, e.g., a dockerstore method might reference a github repository.
- methodRepoMethod.methodVersion: the version of the method, e.g., 'main' branch of a github repository.

avworkflow_files() returns a tibble with columns

- file: character() 'base name' of the file in the bucket.

- workflow: character() name of the workflow the file is associated with.
- task: character() name of the task in the workflow that generated the file.
- path: character() full path to the file in the google bucket.
- submissionId: character() internal identifier associated with the submission the files belong to.
- workflowId: character() internal identifier associated with each workflow (e.g., row of an avtable() used as input) in the submission.
- submissionRoot: character() path in the workspace bucket to the root of files created by this submission.
- namespace: character() AnVIL workspace namespace (billing account) associated with the submissionId.
- name: character(1) AnVIL workspace name associated with the submissionId.

avworkflow_localize() prints a message indicating the number of files that are (if dry = FALSE) or would be localized. If no files require localization (i.e., local files are not older than the bucket files), then no files are localized. avworkflow_localize() returns a tibble of file name and bucket path of files to be synchronized.

avworkflow_run() returns config, invisibly. Note that config has an added LastSubmissionId value for the submission ID of the last run workflow.

avworkflow_stop() returns (invisibly) TRUE on successfully requesting that the workflow stop, FALSE if the workflow is already aborting, aborted, or done.

avworkflow_info() returns a tibble with columns: submissionId, workflowId, workflowName, status, start, end, inputs and outputs.

Examples

```
library(AnVILBase)
library(AnVILGCP)
if (has_avworkspace(strict = TRUE, platform = gcp()))
  ## from within AnVIL
  avworkflows() |> select(namespace, name)

if (has_avworkspace(strict = TRUE, platform = gcp())) {
  ## e.g., from within AnVIL
  avworkflow_jobs() |>
  ## select most recent workflow
  head(1) |>
  ## find paths to output and log files on the bucket
  avworkflow_files()
}

if (has_avworkspace(strict = TRUE, platform = gcp())) {
  avworkflow_localize(dry = TRUE)
}

## Not run:
entityName <- avtable("participant_set") |>
  pull(participant_set_id) |>
  head(1)
avworkflow_run(new_config, entityName)

## End(Not run)
```

```

## Not run:
avworkflow_stop()

## End(Not run)

if (has_avworkspace(strict = TRUE, platform = gcp()))
  avworkflow_info()

```

avworkflow_config-deprecated

Workflow configuration

Description

[Deprecated]

Functions on this help page facilitate getting, updating, and setting workflow configuration parameters. See ?avworkflows for additional relevant functionality.

avworkflow_namespace() and avworkflow_name() are utility functions to record the workflow namespace and name required when working with workflow configurations. avworkflow() provides a convenient way to provide workflow namespace and name in a single command, namespace/name.

avworkflow_configuration_get() returns a list structure describing an existing workflow configuration.

avworkflow_configuration_inputs() returns a data.frame template for the inputs defined in a workflow configuration. This template can be used to provide custom inputs for a configuration.

avworkflow_configuration_outputs() returns a data.frame template for the outputs defined in a workflow configuration. This template can be used to provide custom outputs for a configuration.

avworkflow_configuration_update() returns a list structure describing a workflow configuration with updated inputs and / or outputs.

avworkflow_configuration_set() updates an existing configuration in Terra / AnVIL, e.g., changing inputs to the workflow.

avworkflow_configuration_template() returns a template for defining workflow configurations. This template can be used as a starting point for providing a custom configuration.

Usage

```
avworkflow_namespace(workflow_namespace = NULL)
```

```
avworkflow_name(workflow_name = NULL)
```

```
avworkflow(workflow = NULL)
```

```

avworkflow_configuration_get(
  workflow_namespace = avworkflow_namespace(),
  workflow_name = avworkflow_name(),
  namespace = avworkspace_namespace(),
  name = avworkspace_name()
)

```

```

avworkflow_configuration_inputs(config)

avworkflow_configuration_outputs(config)

avworkflow_configuration_update(
  config,
  inputs = avworkflow_configuration_inputs(config),
  outputs = avworkflow_configuration_outputs(config)
)

avworkflow_configuration_set(
  config,
  namespace = avworkspace_namespace(),
  name = avworkspace_name(),
  dry = TRUE
)

avworkflow_configuration_template()

## S3 method for class 'avworkflow_configuration'
print(x, ...)

```

Arguments

workflow_namespace	character(1) AnVIL workflow namespace, as returned by, e.g., the namespace column of avworkflows().
workflow_name	character(1) AnVIL workflow name, as returned by, e.g., the name column of avworkflows().
workflow_namespace	character(1) representing the combined workflow namespace and name, as namespace/name.
namespace	character(1) AnVIL workspace namespace as returned by, e.g., avworkspace_namespace().
name	character(1) AnVIL workspace name as returned by, e.g., avworkspace_name().
config	a named list describing the full configuration, e.g., created from editing the return value of avworkflow_configuration_set() or avworkflow_configuration_template().
inputs	the new inputs to be updated in the workflow configuration. If none are specified, the inputs from the original configuration will be used and no changes will be made.
outputs	the new outputs to be updated in the workflow configuration. If none are specified, the outputs from the original configuration will be used and no changes will be made.
dry	logical(1) when TRUE (default), report the consequences but do not perform the action requested. When FALSE, perform the action.
x	Object of class avworkflow_configuration.
...	additional arguments to print(); unused.

Details

The exact format of the configuration is important.

One common problem is that a scalar character vector "bar" is interpreted as a json 'array' ["bar"] rather than a json string "bar". Enclose the string with jsonlite::unbox("bar") in the configuration list if the length 1 character vector in R is to be interpreted as a json string.

A second problem is that an unquoted unboxed character string `unbox("foo")` is required by AnVIL to be quoted. This is reported as a `warning()` about invalid inputs or outputs, and the solution is to provide a quoted string `unbox(' "foo"')`.

Value

`avworkflow_namespace()`, and `avworkflow_name()` return `character(1)` identifiers. `avworkflow()` returns the `character(1)` concatenated namespace and name. The value returned by `avworkflow_name()` will be percent-encoded (e.g., spaces " " replaced by "%20").

`avworkflow_configuration_get()` returns a list structure describing the configuration. See `avworkflow_configuration_get()` for the structure of a typical workflow.

`avworkflow_configuration_inputs()` returns a `data.frame` providing a template for the configuration inputs, with the following columns:

- `inputType`
- `name`
- `optional`
- `attribute`

The only column of interest to the user is the `attribute` column, this is the column that should be changed for customization.

`avworkflow_configuration_outputs()` returns a `data.frame` providing a template for the configuration outputs, with the following columns:

- `name`
- `outputType`
- `attribute`

The only column of interest to the user is the `attribute` column, this is the column that should be changed for customization.

`avworkflow_configuration_update()` returns a list structure describing the updated configuration.

`avworkflow_configuration_set()` returns an object describing the updated configuration. The return value includes invalid or unused elements of the config input. Invalid or unused elements of config are also reported as a warning.

`avworkflow_configuration_template()` returns a list providing a template for configuration lists, with the following structure:

- `namespace` `character(1)` configuration namespace.
- `name` `character(1)` configuration name.
- `rootEntityType` `character(1)` or missing. the name of the table (from `avtables()`) containing the entities referenced in inputs, etc., by the keyword 'this.'
- `prerequisites` named list (possibly empty) of prerequisites.
- `inputs` named list (possibly empty) of inputs. Form of input depends on method, and might include, e.g., a reference to a field in a table referenced by `avtables()` or a character string defining an input constant.
- `outputs` named list (possibly empty) of outputs.
- `methodConfigVersion` `integer(1)` identifier for the method configuration.

- methodRepoMethod named list describing the method, with character(1) elements described in the return value for avworkflows().
 - methodUri
 - sourceRepo
 - methodPath
 - methodVersion. The REST specification indicates that this has type integer, but the documentation indicates either integer or string.
- deleted logical(1) of uncertain purpose.

See Also

The help page `?avworkflows` for discovering, running, stopping, and retrieving outputs from workflows.

Examples

```
library(AnVILBase)
library(AnVILGCP)
if (has_avworkspace(strict = TRUE, platform = gcp())) {
  ## discover available workflows in the workspace
  avworkflows()

  ## what workflows are available?
  available_workflows <- avworkflows()

  ## retrieve the current configuration
  config <- avworkflow_configuration_get()
  config

  ## what are the inputs and outputs?
  inputs <- avworkflow_configuration_inputs(config)
  inputs

  outputs <- avworkflow_configuration_outputs(config)
  outputs

  ## update inputs or outputs, e.g., this input can be anything...
  inputs <-
    inputs |>
    mutate(attribute = ifelse(
      name == "salmon.transcriptome_index_name",
      "new_index_name",
      attribute
    ))
  new_config <- avworkflow_configuration_update(config, inputs)
  new_config

  ## set the new configuration in AnVIL; use dry = FALSE to actually
  ## update the configuration
  avworkflow_configuration_set(config)
}

## avworkflow_configuration_template() is a utility function that may
## help understanding what the inputs and outputs should be
avworkflow_configuration_template() |>
```

```

str()
avworkflow_configuration_template()

```

avworkspace_gadget *Graphical user interfaces for common AnVIL operations*

Description

workspace() allows choice of workspace for subsequent use. It is the equivalent of displaying workspaces with avworkspaces(), and setting the selected workspace with avworkspace().

browse_workspace() uses browseURL() to open a browser window pointing to the Terra workspace.

table() allows choice of table in the current workspace (selected by avworkspace() or workspace()) to be returned as a tibble. It is equivalent to invoking avtables() to show available tables, and avtable() to retrieve the selected table.

workflow() allows choice of workflow for retrieval. It is the equivalent of avworkflows() for listing available workflows, and avworkflow_configuration_get() for retrieving the workflow.

Usage

```

avworkspace_gadget()

browse_workspace(use_avworkspace = TRUE)

avtable_gadget()

avworkflow_gadget()

```

Arguments

use_avworkspace
logical(1) when TRUE (default), use the selected workspace (via workspace() or avworkspace()) if available. If FALSE or no workspace is currently selected, use workspace() to allow the user to select the workspace.

Value

workspace() returns the selected workspace as a character(1) using the format namespace/name, or character(0) if no workspace is selected.

browse_workspace() returns the status of a system() call to launch the browser, invisibly.

table() returns a tibble representing the selected AnVIL table.

workflow() returns an avworkflow_configuration object representing the inputs and outputs of the selected workflow. This can be edited and updated as described in the "Running an AnVIL workflow within R" vignette.

Examples

```
## Not run:
workspace()
browse_workspace(use_avworkspace = FALSE)
tbl <- table()
wkflw <- avworkflow_gadget()

## End(Not run)
```

 drs-deprecated

DRS (Data Repository Service) URL management

Description

`drs_stat()` resolves zero or more DRS URLs to their google bucket location.

`drs_access_url()` returns a vector of 'signed' URLs that allow access to restricted resources via standard https protocols.

`drs_cp()` copies 0 or more DRS URIs to a google bucket or local folder

Usage

```
drs_stat(source = character(), region = "US")
```

```
drs_access_url(source = character(), region = "US")
```

```
drs_cp(source, destination, ..., overwrite = FALSE)
```

Arguments

source	character() DRS URLs (beginning with 'drs://') to resources managed by the 'martha' DRS resolution server.
region	character(1) Google cloud 'region' in which the DRS resource is located. Most data is located in "US" (the default); in principle "auto" allows for discovery of the region, but sometimes fails. Regions are enumerated at https://cloud.google.com/storage/docs/locations#available-locations .
destination	character(1), google cloud bucket or local file system destination path.
...	additional arguments, passed to <code>gsutil_cp()</code> for file copying.
overwrite	logical(1) indicating that source fileNames present in destination should downloaded again.

Details

`drs_stat()` sends requests in parallel to the DRS server, using 8 forked processes (by default) to speed up queries. Use `options(mc.cores = 16L)`, for instance, to set the number of processes to use.

`drs_stat()` uses the AnVIL 'pet' account associated with a runtime. The pet account is discovered by default when evaluated on an AnVIL runtime (e.g., in RStudio or a Jupyter notebook in the AnVIL), or can be found in the return value of `avruntimes()`.

Errors reported by the DRS service are communicated to the user, but can be cryptic. The DRS service itself is called 'martha'. Errors mentioning martha might commonly involve a mal-formed DRS uri. Martha uses a service called 'bond' to establish credentials with registered third party entities such as Kids First. Errors mentioning bond might involve absence of credentials, within Terra, to access the resource; check that, in the Terra / AnVIL graphical user interface, the user profiles 'External Entities' includes the organization to which the DRS uri is being resolved.

Value

`drs_stat()` returns a tbl with the following columns:

- `fileName`: `character()` (resolver sometimes returns null).
- `size`: `integer()` (resolver sometimes returns null).
- `contentType`: `character()` (resolver sometimes returns null).
- `gsUri`: `character()` (resolver sometimes returns null).
- `timeCreated`: `character()` (the time created formatted using ISO 8601; resolver sometimes returns null).
- `timeUpdated`: `character()` (the time updated formatted using ISO 8601; resolver sometimes returns null).
- `bucket`: `character()` (resolver sometimes returns null).
- `name`: `character()` (resolver sometimes returns null).
- `googleServiceAccount`: `list()` (null unless the DOS url belongs to a Bond supported host).
- `hashes`: `list()` (contains the hashes type and their checksum value; if unknown. it returns null)

`drs_access_url()` returns a vector of https URLs corresponding to the vector of DRS URIs provided as inputs to the function.

`drs_cp()` returns a tibble like `drs_stat()`, but with additional columns

- `simple`: `logical()` value indicating whether resolution used a simple signed URL (TRUE) or auxilliary service account.
- `destination`: `character()` full path to retrieved object(s)

Examples

```
drs <- c(
  vcf = "drs://dg.ANV0/6f633518-f2de-4460-aaa4-a27ee6138ab5",
  tbi = "drs://dg.ANV0/4fb9e77f-c92a-4deb-ac90-db007dc633aa"
)

library(AnVILGCP)
if (gcloud_exists() && startsWith(gcloud_account(), "pet-")) {
  ## from within AnVIL
  tbl <- drs_stat(uri)
  urls <- drs_access_url(uri)
  ## library(VariantAnnotation)
  ## vcffile <- VcfFile(urls[["vcf"]], urls[["tbi"]])
  ##
  ## header <- scanVcfHeader(vcffile)
  ## meta(header)[["contig"]]
}
```

gcloud-deprecated *gcloud command line utility interface*

Description

[Deprecated]

These functions invoke the gcloud command line utility. See [gsutil](#) for details on how gcloud is located.

`gcloud_exists()` tests whether the `gcloud()` command can be found on this system. After finding the binary location, it runs `gcloud version` to identify potentially misconfigured installations. See 'Details' section of `gsutil` for where the application is searched.

`gcloud_account()`: report the current gcloud account via `gcloud config get-value account`.

`gcloud_project()`: report the current gcloud project via `gcloud config get-value project`.

`gcloud_help()`: queries gcloud for help for a command or sub-command via `gcloud help ...`

`gcloud_cmd()` allows arbitrary gcloud command execution via `gcloud ...`. Use pre-defined functions in preference to this.

`gcloud_storage()` allows arbitrary gcloud storage command execution via `gcloud storage ...`. Typically used for bucket management commands such as `rm` and `cp`.

`gcloud_storage_buckets()` provides an interface to the `gcloud storage buckets` command. This command can be used to create a new bucket via `gcloud storage buckets create ...`

Usage

`gcloud_exists()`

`gcloud_account(account = NULL)`

`gcloud_project(project = NULL)`

`gcloud_help(...)`

`gcloud_cmd(cmd, ...)`

`gcloud_storage(cmd, ...)`

`gcloud_storage_buckets(bucket_cmd = "create", bucket, ...)`

Arguments

<code>account</code>	character(1) Google account (e.g., <code>user@gmail.com</code>) to use for authentication.
<code>project</code>	character(1) billing project name.
<code>...</code>	Additional arguments appended to gcloud commands.
<code>cmd</code>	character(1) representing a command used to evaluate <code>gcloud cmd ...</code>
<code>bucket_cmd</code>	character(1) representing a buckets command typically used to create a new bucket. It can also be used to <code>add-iam-policy-binding</code> or <code>remove-iam-policy-binding</code> to a bucket.
<code>bucket</code>	character(1) representing a unique bucket name to be created or modified.

Value

`gcloud_exists()` returns TRUE when the gcloud application can be found, FALSE otherwise.

`gcloud_account()` returns a character(1) vector containing the active gcloud account, typically a gmail email address.

`gcloud_project()` returns a character(1) vector containing the active gcloud project.

`gcloud_help()` returns an unquoted character() vector representing the text of the help manual page returned by `gcloud help . . .`

`gcloud_cmd()` returns a character() vector representing the text of the output of `gcloud cmd . . .`

Examples

```
library(AnVILGCP)
gcloud_exists()

if (gcloud_exists())
  gcloud_account()

if (gcloud_exists())
  gcloud_help()
```

gsutil-deprecated *gsutil command line utility interface*

Description

These functions invoke the gsutil command line utility. See the "Details:" section if you have gsutil installed but the package cannot find it.

`gsutil_requesterpays()`: does the google bucket require that the requester pay for access?

`gsutil_ls()`: List contents of a google cloud bucket or, if source is missing, all Cloud Storage buckets under your default project ID

`gsutil_exists()`: check if the bucket or object exists.

`gsutil_stat()`: print, as a side effect, the status of a bucket, directory, or file.

`gsutil_cp()`: copy contents of source to destination. At least one of source or destination must be Google cloud bucket; source can be a character vector with length greater than 1. Use `gsutil_help("cp")` for gsutil help.

`gsutil_rm()`: remove contents of a google cloud bucket.

`gsutil_rsync()`: synchronize a source and a destination. If the destination is on the local file system, it must be a directory or not yet exist (in which case a directory will be created).

`gsutil_cat()`: concatenate bucket objects to standard output

`gsutil_help()`: print 'man' page for the gsutil command or subcommand. Note that only commandes documented on this R help page are supported.

`gsutil_pipe()`: create a pipe to read from or write to a google bucket object.

Usage

```

gsutil_requesterpays(source)

gsutil_ls(source = character(), ..., recursive = FALSE)

gsutil_exists(source)

gsutil_stat(source)

gsutil_cp(source, destination, ..., recursive = FALSE, parallel = TRUE)

gsutil_rm(source, ..., force = FALSE, recursive = FALSE, parallel = TRUE)

gsutil_rsync(
  source,
  destination,
  ...,
  exclude = NULL,
  dry = TRUE,
  delete = FALSE,
  recursive = FALSE,
  parallel = TRUE
)

gsutil_cat(source, ..., header = FALSE, range = integer())

gsutil_help(cmd = character(0))

gsutil_pipe(source, open = "r", ...)

```

Arguments

source	character(1), (character() for gsutil_requesterpays(), gsutil_ls(), gsutil_exists(), gsutil_cp()) paths to a google storage bucket, possibly with wild-cards for file-level pattern matching.
...	additional arguments passed as-is to the gsutil subcommand.
recursive	logical(1); perform operation recursively from source?. Default: FALSE.
destination	character(1), google cloud bucket or local file system destination path.
parallel	logical(1), perform parallel multi-threaded / multi-processing (default is TRUE).
force	logical(1): continue silently despite errors when removing multiple objects. Default: FALSE.
exclude	character(1) a python regular expression of bucket paths to exclude from synchronization. E.g., '.*(\\\.png \\\.txt)\$' excludes '.png' and '.txt' files.
dry	logical(1), when TRUE (default), return the consequences of the operation without actually performing the operation.
delete	logical(1), when TRUE, remove files in destination that are not in source. Exercise caution when you use this option: it's possible to delete large amounts of data accidentally if, for example, you erroneously reverse source and destination.
header	logical(1) when TRUE annotate each

range	(optional) integer(2) vector used to form a range from-to of bytes to concatenate. NA values signify concatenation from the start (first position) or to the end (second position) of the file.
cmd	character() (optional) command name, e.g., "ls" for help.
open	character(1) either "r" (read) or "w" (write) from the bucket.

Details

The gsutil system command is required. The search for gsutil starts with environment variable GCLLOUD_SDK_PATH providing a path to a directory containing a bin directory containingin gsutil, gcloud, etc. The path variable is searched for first as an option() and then system variable. If no option or global variable is found, Sys.which() is tried. If that fails, gsutil is searched for on defined paths. On Windows, the search tries to find Google\Cloud SDK\google-cloud-sdk\bin\gsutil.cmd in the LOCAL APP DATA, Program Files, and Program Files (x86) directories. On linux/macOS, the search continues with ~/google-cloud-sdk.

gsutil_rsync(): To make "gs://mybucket/data" match the contents of the local directory "data" you could do:

```
gsutil_rsync("data", "gs://mybucket/data", delete = TRUE)
```

To make the local directory "data" the same as the contents of gs://mybucket/data:

```
gsutil_rsync("gs://mybucket/data", "data", delete = TRUE)
```

If destination is a local path and does not exist, it will be created.

Value

gsutil_requesterpays(): named logical() vector TRUE when requester-pays is enabled.

gsutil_ls(): character() listing of source content.

gsutil_exists(): logical(1) TRUE if bucket or object exists.

gsutil_stat(): tibble() summarizing status of each bucket member.

gsutil_cp(): exit status of gsutil_cp(), invisibly.

gsutil_rm(): exit status of gsutil_rm(), invisibly.

gsutil_rsync(): exit status of gsutil_rsync(), invisibly.

gsutil_cat() returns the content as a character vector.

gsutil_help(): character() help text for subcommand cmd.

gsutil_pipe() an unopened R pipe(); the mode is *not* specified, and the pipe must be used in the appropriate context (e.g., a pipe created with open = "r" for input as read.csv())

Examples

```
src <- "gs://genomics-public-data/1000-genomes/other/sample_info/sample_info.csv"
library(AnVILGCP)
if (gcloud_exists())
  gsutil_requesterpays(src) # FALSE -- no cost download

if (gcloud_exists()) {
  gsutil_exists(src)
  gsutil_stat(src)
  gsutil_ls(dirname(src))
}
```



```

if (gcloud_exists()) {
  gsutil_cp(src, tempdir())
  ## gsutil_*() commands work with spaces in the source or destination
  destination <- file.path(tempdir(), "foo bar")
  gsutil_cp(src, destination)
  file.exists(destination)
}

if (gcloud_exists())
  gsutil_help("ls")

if (gcloud_exists()) {
  df <- read.csv(gsutil_pipe(src), 5L)
  class(df)
  dim(df)
  head(df)
}

```

localize-deprecated *Copy packages, folders, or files to or from google buckets*

Description

[Deprecated]

`localize()`: recursively synchronizes files from a Google storage bucket (source) to the local file system (destination). This command acts recursively on the source directory, and does not delete files in destination that are not in 'source'.

`delocalize()`: synchronize files from a local file system (source) to a Google storage bucket (destination). This command acts recursively on the source directory, and does not delete files in destination that are not in source.

Usage

```
localize(source, destination, dry = TRUE)
```

```
delocalize(source, destination, unlink = FALSE, dry = TRUE)
```

Arguments

source	character(1), a google storage bucket or local file system directory location.
destination	character(1), a google storage bucket or local file system directory location.
dry	logical(1), when TRUE (default), return the consequences of the operation without actually performing the operation.
unlink	logical(1) remove (unlink) the file or directory in source. Default: FALSE.

Value

`localize()`: exit status of function `gsutil_rsync()`.

`delocalize()`: exit status of function `gsutil_rsync()`

Service

RESTful service constructor

Description

RESTful service constructor

Usage

```
Service(
  service,
  host,
  config = httr::config(),
  authenticate = TRUE,
  api_url = character(),
  package = "AnVIL",
  schemes = "https",
  api_reference_url = api_url,
  api_reference_md5sum = character(),
  api_reference_version = character(),
  api_reference_headers = NULL
)
```

Arguments

service	character(1) The Service class name, e.g., "terra".
host	character(1) host name that provides the API resource, e.g., "leonardo.dsde-prod.broadinstitute.org".
config	httr::config() curl options
authenticate	logical(1) use credentials from authentication service file 'auth.json' in the specified package?
api_url	optional character(1) url location of OpenAPI .json or .yaml service definition.
package	character(1) (default AnVIL) The package where 'api.json' yaml and (optionally) 'auth.json' files are located.
schemes	character(1) (default 'https') Specifies the transfer protocol supported by the API service.
api_reference_url	character(1) path to reference API. See Details.
api_reference_md5sum	character(1) the result of tools::md5sum() applied to the reference API.
api_reference_version	character(1) the version of the reference API. This is used to check that the version of the service matches the version of the reference API. It is usually set by the service generation function, e.g., AnVIL::Rawls().
api_reference_headers	character() header(s) to be used (e.g., c(Authorization = paste("Bearer", token))) when retrieving the API reference for validation.

Details

This function creates a RESTful interface to a service provided by a host, e.g., "leonardo.dsde-prod.broadinstitute.org". The function requires an OpenAPI .json or .yaml specification as well as an (optional) .json authentication token. These files are located in the source directory of a package, at <package>/inst/service/<service>/api.json and <package>/inst/service/<service>/auth.json or at api_url.

When provided, the api_reference_md5sum is used to check that the file described at api_reference_url has the same checksum as an author-validated version.

The service is usually a singleton, created at the package level during .onLoad().

Value

An object of class Service.

Examples

```
.MyService <- setClass("MyService", contains = "Service")

MyService <- function() {
  .MyService(Service("my_service", host="my.api.org"))
}
```

 Services

RESTful services useful for AnVIL developers

Description

RESTful services useful for AnVIL developers

Usage

```
empty_object

operations(x, ..., .deprecated = FALSE)

## S4 method for signature 'Service'
operations(x, ..., auto_unbox = FALSE, .deprecated = FALSE)

schemas(x)

tags(x, .tags, .deprecated = FALSE)

## S4 method for signature 'Service'
x$name

Leonardo()

Terra()

Rawls()
```

Dockstore()

TDR()

Arguments

x	A Service instance, usually a singleton provided by the package and documented on this page, e.g., leonardo or terra.
...	additional arguments passed to methods or, for operations, Service-method, to the internal get_operation() function.
.deprecated	optional logical(1) include deprecated operations?
auto_unbox	logical(1) If FALSE (default) do not automatically 'unbox' R scalar values from JSON arrays to JSON scalars.
.tags	optional character() of tags to use to filter operations.
name	A symbol representing a defined operation, e.g., leonardo\$listRuntimes().

Details

Note the services Terra(), Rawls(), and Leonardo() require the AnVILGCP package for authentication to the Google Cloud Platform. See ?AnVILGCP::gcloud_access_token() for details.

When using \$ to select a service, some arguments appear in 'body' of the REST request. Specify these using the .__body__= argument, as illustrated for createBillingProjectFull(), below.

Value

empty_object returns a representation to be used as arguments in function calls expecting the empty json object {}.

Leonardo() creates the API of the Leonardo container deployment service at <https://leonardo.dsde-prod.broadinstitute.org/api-docs.yaml>.

Terra() creates the API of the Terra cloud computational environemnt at <https://api.firecloud.org/>.

Rawls() creates the API of the Rawls cloud computational environemnt at <https://rawls.dsde-prod.broadinstitute.org>.

Dockstore() represents the API of the Dockstore platform to share Docker-based tools in CWL or WDL or Nextflow at <https://dockstore.org>

TDR() creates the API of the Terra Data Repository to work with snapshot data in the Terra Data Repository at <https://data.terra.bio>.

Examples

```
empty_object

library(AnVILGCP)
if (gcloud_exists()) {
  ## Arguments to be used as the 'body' (`.__body__=`) of a REST query
  Terra()$createBillingProjectFull # 6 arguments...
  args(Terra()$createBillingProjectFull) # ... passed as `.__body__ = list(...)`
}
library(AnVILGCP)
if (gcloud_exists())
```

```
Leonardo()

library(AnVILGCP)
if (gcloud_exists()) {
  tags(Terra())
  tags(Terra(), "Billing")
}

library(AnVILGCP)
if (gcloud_exists()) {
  tags(Rawls())
  tags(Rawls(), "billing")
}

Dockstore()

library(AnVILGCP)
if (gcloud_exists())
  TDR()
```

utilities

Utilities for managing library paths

Description

`add_libpaths()`: Add local library paths to `.libPaths()`.

Usage

```
add_libpaths(paths)
```

Arguments

`paths` `character()`: vector of directories to add to `.libPaths()`. Paths that do not exist will be created.

Value

`add_libpaths()`: updated `.libPaths()`, invisibly.

Examples

```
## Not run: add_libpaths("/tmp/host-site-library")
```

Index

- * **datasets**
 - Services, 27
 - * **internal**
 - AnVIL-package, 2
 - .DollarNames.Service (Services), 27
 - .gadget_run, 3
 - \$.Service-method (Services), 27
 - add_libpaths (utilities), 29
 - AnVIL (AnVIL-package), 2
 - AnVIL-defunct, 4
 - AnVIL-package, 2
 - av-deprecated, 5
 - avbucket (av-deprecated), 5
 - avdata (av-deprecated), 5
 - avdata_import (av-deprecated), 5
 - avdisks (av-deprecated), 5
 - avfiles_backup (av-deprecated), 5
 - avfiles_ls (av-deprecated), 5
 - avfiles_restore (av-deprecated), 5
 - avfiles_rm (av-deprecated), 5
 - avruntime (av-deprecated), 5
 - avruntimes (av-deprecated), 5
 - avtable_gadget (avworkspace_gadget), 18
 - avtable_import_status (av-deprecated), 5
 - avtable_paged (av-deprecated), 5
 - avworkflow
 - (avworkflow_config-deprecated), 14
 - avworkflow_config-deprecated, 14
 - avworkflow_configuration_get
 - (avworkflow_config-deprecated), 14
 - avworkflow_configuration_inputs
 - (avworkflow_config-deprecated), 14
 - avworkflow_configuration_outputs
 - (avworkflow_config-deprecated), 14
 - avworkflow_configuration_set
 - (avworkflow_config-deprecated), 14
 - avworkflow_configuration_template
 - (avworkflow_config-deprecated), 14
 - avworkflow_configuration_update
 - (avworkflow_config-deprecated), 14
 - avworkflow_configurations
 - (avworkflow_config-deprecated), 14
 - avworkflow_files
 - (avworkflows-deprecated), 10
 - avworkflow_gadget (avworkspace_gadget), 18
 - avworkflow_info
 - (avworkflows-deprecated), 10
 - avworkflow_localize
 - (avworkflows-deprecated), 10
 - avworkflow_name
 - (avworkflow_config-deprecated), 14
 - avworkflow_namespace
 - (avworkflow_config-deprecated), 14
 - avworkflow_run
 - (avworkflows-deprecated), 10
 - avworkflow_stop
 - (avworkflows-deprecated), 10
 - avworkflows (avworkflows-deprecated), 10
 - avworkflows-deprecated, 10
 - avworkspace_gadget, 18
- browse_workspace (avworkspace_gadget), 18
 - delocalize (localize-deprecated), 25
 - Dockstore (Services), 27
 - Dockstore-class (Services), 27
 - drs-deprecated, 19
 - drs_access_url (drs-deprecated), 19
 - drs_cp (drs-deprecated), 19
 - drs_stat (drs-deprecated), 19
 - empty_object (Services), 27
 - gcloud (gcloud-deprecated), 21
 - gcloud-deprecated, 21

- gcloud_account (gcloud-deprecated), 21
- gcloud_cmd (gcloud-deprecated), 21
- gcloud_exists (gcloud-deprecated), 21
- gcloud_help (gcloud-deprecated), 21
- gcloud_project (gcloud-deprecated), 21
- gcloud_storage (gcloud-deprecated), 21
- gcloud_storage_buckets (gcloud-deprecated), 21
- gsutil, 21
- gsutil (gsutil-deprecated), 22
- gsutil-deprecated, 22
- gsutil_cat (gsutil-deprecated), 22
- gsutil_cp (gsutil-deprecated), 22
- gsutil_exists (gsutil-deprecated), 22
- gsutil_help (gsutil-deprecated), 22
- gsutil_ls (gsutil-deprecated), 22
- gsutil_pipe (gsutil-deprecated), 22
- gsutil_requesterpays (gsutil-deprecated), 22
- gsutil_rm (gsutil-deprecated), 22
- gsutil_rsync (gsutil-deprecated), 22
- gsutil_stat (gsutil-deprecated), 22

- Leonardo (Services), 27
- Leonardo-class (Services), 27
- localize (localize-deprecated), 25
- localize-deprecated, 25

- operations (Services), 27
- operations, Dockstore-method (Services), 27
- operations, Leonardo-method (Services), 27
- operations, Rawls-method (Services), 27
- operations, Service-method (Services), 27
- operations, TDR-method (Services), 27
- operations, Terra-method (Services), 27

- print.avworkflow_configuration (avworkflow_config-deprecated), 14
- print.repository_stats (AnVIL-defunct), 4

- Rawls (Services), 27
- Rawls-class (Services), 27
- repository_stats (AnVIL-defunct), 4

- schemas (Services), 27
- schemas, Rawls-method (Services), 27
- schemas, Service-method (Services), 27
- schemas, Terra-method (Services), 27
- Service, 26
- Service-class (Services), 27
- Services, 27
- show, Service-method (Services), 27

- tags (Services), 27
- TDR (Services), 27
- TDR-class (Services), 27
- Terra (Services), 27
- Terra-class (Services), 27

- utilities, 29