

Package ‘fedup’

January 20, 2025

Title Fisher's Test for Enrichment and Depletion of User-Defined Pathways

Version 1.14.0

Date 2021-02-17

Depends R (>= 4.1)

Description An R package that tests for enrichment and depletion of user-defined pathways using a Fisher's exact test. The method is designed for versatile pathway annotation formats (eg. gmt, txt, xlsx) to allow the user to run pathway analysis on custom annotations. This package is also integrated with Cytoscape to provide network-based pathway visualization that enhances the interpretability of the results.

biocViews GeneSetEnrichment, Pathways, NetworkEnrichment, Network

Imports openxlsx, tibble, dplyr, data.table, ggplot2, ggthemes, forcats, RColorBrewer, RCy3, utils, stats

Suggests biomaRt, tidyr, testthat, knitr, rmarkdown, devtools, covr

LazyData false

Encoding UTF-8

Language en-US

License MIT + file LICENSE

VignetteBuilder knitr

URL <https://github.com/rosscm/fedup>

BugReports <https://github.com/rosscm/fedup/issues>

RoxygenNote 7.1.1

git_url <https://git.bioconductor.org/packages/fedup>

git_branch RELEASE_3_20

git_last_commit f3b116a

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2025-01-20

Author Catherine Ross [aut, cre]

Maintainer Catherine Ross <catherinem.ross@mail.utoronto.ca>

Contents

geneDouble	2
geneMulti	3
geneSingle	3
pathwaysGMT	4
pathwaysTXT	4
pathwaysXLSX	5
plotDotPlot	5
plotFemap	7
prepInput	8
readPathways	9
runFedup	10
writeFemap	11
writePathways	12
Index	13

geneDouble	<i>Example list of a background set and two sets of test genes to use for enrichment analysis.</i>
------------	--

Description

Raw Excel data file (Sup Tab 2) is available from <https://www.ncbi.nlm.nih.gov/pmc/articles/PMC7566881/>

Usage

```
data(geneDouble)
```

Format

a named list with three vector elements, one common background gene vector and two test gene vectors.

Details

```
Script to prepare data system.file("script", "genes.R", package = "fedup")
```

geneMulti

Example list of a background set and multiple sets of test genes to use for enrichment analysis.

Description

Raw Excel data file (Sup Tab 2) is available from <https://www.ncbi.nlm.nih.gov/pmc/articles/PMC7566881/>

Usage

```
data(geneMulti)
```

Format

a named list with thirteen vector elements, one common background gene vector and twelve test gene vectors.

Details

```
Script to prepare data system.file("script", "genes.R", package = "fedup")
```

geneSingle

Example list of a background set and single set of test genes to use for enrichment analysis.

Description

Raw Excel data file (Sup Tab 2) is available from <https://www.ncbi.nlm.nih.gov/pmc/articles/PMC7566881/>

Usage

```
data(geneSingle)
```

Format

a named list with two vector elements, one common background gene vector and one test gene vector.

Details

```
Script to prepare data system.file("script", "genes.R", package = "fedup")
```

pathwaysGMT

Named list of human pathway annotations obtained from a GMT file.

Description

GMT file is available from http://download.baderlab.org/EM_Genesets/November_17_2020/Human/symbol

Usage

```
data(pathwaysGMT)
```

Format

a named list of 1437 vectors

Details

Raw data location `system.file("extdata", "Human_Reactome_November_17_2020_symbol.gmt", package = "fedup")` Script to prepare data `system.file("script", "pathwaysGMT.R", package = "fedup")`

pathwaysTXT

Example list of SAFE terms obtained from a TXT file.

Description

Raw data file (S5) is available from <https://boonelab.ccb.utoronto.ca/supplement/costanzo2016/>

Usage

```
data(pathwaysTXT)
```

Format

a named list of 317 vectors

Details

Raw data location `system.file("extdata", "SAFE_terms.txt", package = "fedup")`

Script to prepare data `system.file("script", "pathwaysTXT.R", package = "fedup")`

`pathwaysXLSX`*Example list of SAFE terms obtained from a XLSX file.*

Description

Raw data file (S5) is available from <https://boonelab.ccb.utoronto.ca/supplement/costanzo2016/>

Usage

```
data(pathwaysXLSX)
```

Format

a named list of 317 vectors

Details

Raw data location `system.file("extdata", "SAFE_terms.xlsx", package = "fedup")`

Script to prepare data `system.file("script", "pathwaysXLSX.R", package = "fedup")`

`plotDotPlot`*Visualizes fedup enrichment and depletion results using ggplot.*

Description

This function supports any combination of numeric x-y variables to plot from fedup results. The list outputted by `runFedup` must first be converted to a data.frame before plotting (see examples for sample use).

Usage

```
plotDotPlot(  
  df,  
  xVar,  
  yVar,  
  xLab = xVar,  
  yLab = NULL,  
  pTitle = NULL,  
  fillVar = NULL,  
  fillCol = NULL,  
  fillLab = fillVar,  
  sizeVar = NULL,  
  sizeLab = sizeVar  
)
```

Arguments

df	(data.frame) table with fedup results generated via runFedup
xVar	(char) x-axis variable (must be a column value in df)
yVar	(char) y-axis variable (must be a column value in df)
xLab	(char) x-axis label (default xVar value)
yLab	(char) y-axis label (default NULL)
pTitle	(char) plot title (default NULL)
fillVar	(char) point fill variable (default NULL)
fillCol	(char) point fill colours (default NULL)
fillLab	(char) point fill label (default fillVar value)
sizeVar	(char) point size variable (default NULL)
sizeLab	(char) point size label (default sizeVar value)

Value

Object returned from ggplot with the enrichment dot plot.

Examples

```
# Load example data
data(geneDouble)
data(pathwaysGMT)
# Load external libraries
suppressMessages(library(dplyr))
suppressMessages(library(tidyr))
# Run fedup
fedupRes <- runFedup(geneDouble, pathwaysGMT)
# Prepare dataframe from fedup results
fedupPlot <- fedupRes %>%
  bind_rows(.id = "set") %>%
  separate(col = "set", into = c("set", "sign"), sep = "_") %>%
  subset(qvalue < 0.01) %>%
  mutate(log10qvalue = -log10(qvalue)) %>%
  mutate(pathway = gsub("\\%.*", "", pathway)) %>%
  as.data.frame()
# Plot
p <- plotDotPlot(
  df = fedupPlot,
  xVar = "log10qvalue",
  yVar = "pathway",
  xLab = "-log10(qvalue)",
  fillVar = "sign",
  fillLab = "Genetic interaction",
  fillCol = c("#0077f1", "#fcde24"),
  sizeVar = "fold_enrichment",
  sizeLab = "Fold enrichment"
)
```

plotFemap	<i>Draws a network representation of overlaps among pathway enrichment results using EnrichmentMap (EM) in Cytoscape.</i>
-----------	---

Description

Draws a network representation of overlaps among pathway enrichment results using EnrichmentMap (EM) in Cytoscape.

Usage

```
plotFemap(
  gmtFile,
  resultsFolder,
  pvalue = 1,
  qvalue = 1,
  formSim = "COMBINED",
  edgeSim = 0.375,
  combSim = 0.5,
  chartData = "NES_VALUE",
  clustAlg = "MCL",
  clustWords = 3,
  hideNodeLabels = FALSE,
  netName = "generic",
  netFile = "png"
)
```

Arguments

gmtFile	(char) absolute path to GMT file (generated via writePathways)
resultsFolder	(char) absolute path to folder with fedup results (generated via writeFemap)
pvalue	(numeric) pvalue cutoff (value between 0 and 1; default 1)
qvalue	(numeric) qvalue cutoff (value between 0 and 1; default 1)
formSim	(character) formula to calculate similarity score (one of OVERLAP, JACCARD, COMBINED; default COMBINED)
edgeSim	(numeric) edge similarity score cutoff (value between 0 and 1; default 0.375)
combSim	(numeric) when coefficients=COMBINED this parameter is used to determine what percentage to use for JACCARD and OVERLAP when combining their value (value between 0 to 1; default 0.5)
chartData	(char) node chart data (one of NES_VALUE, P_VALUE, FDR_VALUE, PHENOTYPES, DATA_SET, EXPRESSION_SET, or NONE; default NES_VALUE)
clustAlg	(character) clusterMaker algorithm (one of AFFINITY_PROPAGATION, CLUSTER_FIZZIFIER, GLAY, CONNECTED_COMPONENTS, MCL, SCPS; default MCL)
clustWords	(integer) maximum words to include in autoAnnotate cluster label (default 3)
hideNodeLabels	(logical) if TRUE hides the node label in the EM; cluster labels generated via AutoAnnotate remain visible
netName	(char) name for EM in Cytoscape (default generic)
netFile	(char) name of output image (supports png, pdf, svg, jpeg image formats)

Value

File name of image to which the network is exported and an open session of Cytoscape (side effect of plotting EM). NULL if Cytoscape is not running locally.

Examples

```
# Load example data
data(geneDouble)
data(pathwaysGMT)
# Run fedup
fedupRes <- runFedup(geneDouble, pathwaysGMT)
# Write out results to temp folder
resultsFolder <- tempdir()
writeFemap(fedupRes, resultsFolder)
# Write out gmt formatted pathway annotations to temp file
gmtFile <- tempfile("pathwaysGMT", fileext = ".gmt")
writePathways(pathwaysGMT, gmtFile)
# Plot enrichment map
netFile <- tempfile("fedup_EM", fileext = ".png")
plotFemap(
  gmtFile = gmtFile,
  resultsFolder = resultsFolder,
  qvalue = 0.05,
  hideNodeLabels = TRUE,
  netName = "fedup_EM",
  netFile = netFile
)
```

```
prepInput
```

Prepares input gene list for [runFedup](#).

Description

This function takes any number of test genes and a common background set of genes and properly formats them for to pass to [runFedup](#) gene argument.

Usage

```
prepInput(setName, ...)
```

Arguments

setName	(char) character vector naming gene vectors passed to ... (must include "background" (case sensitive)).
...	(char) n vectors with at least one background set of genes and any number of test genes.

Value

List of length n with gene vectors corresponding to those passed to ...

Examples

```
# Raw gene data file
genesFile <- system.file("extdata",
  "NIHMS1587165-supplement-1587165_Sup_Tab_2.txt", package = "fedup")
genes <- read.delim(genesFile, h = TRUE, as.is = TRUE)
# Prepare gene vectors
b <- unique(genes[, "gene"])
set1 <- unique(genes[which(genes$FASN_merge < -0.4), "gene"])
set2 <- unique(genes[which(genes$FASN_merge > 0.4), "gene"])
setName <- c("background", "negative", "positive")
# Generate input list with background genes and two test set of genes
geneDouble <- prepInput(setName, b, set1, set2)
```

readPathways	<i>Returns a list of pathways from various file formats.</i>
--------------	--

Description

This function supports custom pathway annotations to use for fedup pathway enrichment analysis. Current file formats supported are gmt, txt, and xlsx.

Usage

```
readPathways(
  pathwayFile,
  header = FALSE,
  pathCol = NULL,
  geneCol = NULL,
  minGene = 1L,
  maxGene = Inf
)
```

Arguments

pathwayFile	(char) path to file with pathway annotations
header	(logical) whether pathwayFile has a header (default FALSE)
pathCol	(char or int) column name or number with pathway identifiers (for use with non-GMT input files (eg "Pathway.ID" or 2; default NULL))
geneCol	(char or int) column name or number with gene identifiers (for use with non-GMT input files (eg "Gene.ID" or 5; default NULL))
minGene	(integer) minimum number of genes to be considered in a pathway (default 1)
maxGene	(integer) maximum number of genes to be considered in a pathway (default Inf)

Value

A list of vectors with pathway annotations.

Examples

```
# Generate pathway list from GMT annotation file
pathways <- readPathways(
  system.file("extdata", "Human_Reactome_November_17_2020_symbol.gmt",
    package = "fedup"
  ),
  minGene = 10, maxGene = 500
)
# Generate pathway list from XLSX annotation file
pathways <- readPathways(
  system.file("extdata", "SAFE_terms.xlsx", package = "fedup"),
  header = TRUE, pathCol = "Enriched.GO.names", geneCol = "Gene.ID"
)
```

runFedup	<i>Runs pathway enrichment and depletion analysis using a Fisher's exact test.</i>
----------	--

Description

This function takes a list of test genes and a common background set to calculate enrichment and depletion for a list of pathways. The method allows for fast and efficient testing of multiple gene sets of interest.

Usage

```
runFedup(genes, pathways)
```

Arguments

genes	(list) named list of vectors with background genes and n test genes.
pathways	(list) named list of vectors with pathway annotations.

Value

List of length n with table(s) of pathway enrichment and depletion results. Rows represent tested pathways. Columns represent:

- pathway – name of the pathway, corresponds to names(pathways);
- size – size of the pathway;
- real_frac – fraction of test gene members in pathway;
- expected_frac – fraction of background gene members in pathway;
- fold_enrichment – fold enrichment measure, evaluates as real_frac / expected_frac;
- status – indicator that pathway is enriched or depleted for test gene members;
- real_gene – vector of test gene members annotated to pathways;
- pvalue – enrichment p-value calculated via Fisher's exact test;
- qvalue – BH-adjusted p-value

Examples

```
# Load pathway annotations
data(pathwaysGMT)
# Run fedup with a single test set
data(geneSingle)
fedupRes <- runFedup(geneSingle, pathwaysGMT)
# Run fedup with two test sets
data(geneDouble)
fedupRes <- runFedup(geneDouble, pathwaysGMT)
# Run fedup with multiple test sets
data(geneMulti)
fedupRes <- runFedup(geneMulti, pathwaysGMT)
```

writeFemap	<i>Writes an enrichment dataset file for use in Cytoscape EnrichmentMap.</i>
------------	--

Description

Writes an enrichment dataset file for use in Cytoscape EnrichmentMap.

Usage

```
writeFemap(results, resultsFolder)
```

Arguments

results (list) list with output results from [runFedup](#)
resultsFolder (char) name of folder to store result file(s)

Value

Table of pathway enrichment and depletion results formatted as a 'Generic results file'. Rows represent tested pathways. Columns represent:

- pathway – pathway ID (must match pathway IDs in the GMT file provided to [plotFemap](#);
- description – pathway name or description;
- pvalue – enrichment pvalue;
- qvalue – BH-corrected pvalue;
- status – +1 or -1, to identify enriched or depleted pathways (+1 maps to red, -1 maps to blue)

Examples

```
# Load example data
data(geneDouble)
data(pathwaysGMT)
# Run fedup
fedupRes <- runFedup(geneDouble, pathwaysGMT)
# Write out results to temp folder
resultsFolder <- tempdir()
writeFemap(fedupRes, resultsFolder)
```

writePathways	<i>Writes a set of pathways (list of vectors) to a GMT file.</i>
---------------	--

Description

Writes a set of pathways (list of vectors) to a GMT file.

Usage

```
writePathways(pathways, gmtFile)
```

Arguments

pathways	(list) named list of vectors
gmtFile	(char) name of output GMT file

Value

GMT-formatted file. Rows represent pathways. Columns represent:

- pathway ID;
- description;
- a list of tab-delimited genes

Examples

```
data(pathwaysXLSX)  
writePathways(pathwaysXLSX, tempfile("pathwaysXLSX", fileext = ".gmt"))
```

Index

* datasets

- geneDouble, 2
- geneMulti, 3
- geneSingle, 3
- pathwaysGMT, 4
- pathwaysTXT, 4
- pathwaysXLSX, 5

- geneDouble, 2
- geneMulti, 3
- geneSingle, 3

- pathwaysGMT, 4
- pathwaysTXT, 4
- pathwaysXLSX, 5
- plotDotPlot, 5
- plotFemap, 7, 11
- prepInput, 8

- readPathways, 9
- runFedup, 5, 6, 8, 10, 11

- writeFemap, 7, 11
- writePathways, 7, 12